. Page 1 of 7

MATERIAL SAFETY DATA SHEET



AMOCO MULTI-PURPOSE GEAR LUBRICANT SAE 80W-90

MSDS No. 01570000 ANSI/ENGLISH

1.0 CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: AMOCO MULTI-PURPOSE GEAR LUBRICANT SAE 80W-90

MANUFACTURER/SUPPLIER:

EMERGENCY HEALTH INFORMATION: 1 (800) 447-8735

Amoco Oil Company 200 East Randolph Drive Chicago, Illinois 60601 U.S.A.

EMERGENCY SPILL INFORMATION: 1 (800) 424-9300 CHEMTREC (USA)

OTHER PRODUCT SAFETY INFORMATION: (312) 856-3907

2.0 COMPOSITION/INFORMATION ON INGREDIENTS

		Range % by Wt.
Hydrotreated solvent dewaxed paraffinic petroleum		L
Solvent refined light paraffinic distillate	64741-89-5	15-40

(See Section 8.0, "Exposure Controls/Personal Protection", for exposure guidelines)

3.0 HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW: This product has been evaluated and does not require any hazard warning on the label under OSHA criteria.

POTENTIAL HEALTH EFFECTS:

EYE CONTACT: No significant health hazards identified.

SKIN CONTACT: Prolonged or repeated contact may produce some skin irritation.

INHALATION: No significant health hazards identified.

INGESTION: No significant health hazards identified.

HMIS CODE: (Health:0) (Flammability:1) (Reactivity:0)

NFPA CODE: (Health:0) (Flammability:1) (Reactivity:0)

4.0 FIRST AID MEASURES

EYE: Flush eyes with plenty of water.

SKIN: Wash exposed skin with soap and water. Get medical attention if irritation develops.

INHALATION: If adverse effects occur, remove to uncontaminated area. Get medical attention.

INGESTION: If a large amount is swallowed, get medical attention.

5.0 FIRE FIGHTING MEASURES

FLASHPOINT: 329°F(165°C) (minimum) (Cleveland open cup)

UEL: Not determined.

LEL: Not determined.

AUTOIGNITION TEMPERATURE: Not determined.

FLAMMABILITY CLASSIFICATION: Not Flammable.

EXTINGUISHING MEDIA: Agents approved for Class B hazards (e.g., dry chemical, carbon dioxide, foam, steam) or water fog.

UNUSUAL FIRE AND EXPLOSION HAZARDS: None identified.

FIRE-FIGHTING EQUIPMENT: Firefighters should wear full bunker gear, including a positive pressure self-contained breathing apparatus.

HAZARDOUS COMBUSTION PRODUCTS: Incomplete burning can produce carbon

monoxide and/or carbon dioxide and other harmful products.

6.0 ACCIDENTAL RELEASE MEASURES

Remove mechanically or contain on an absorbent material such as dry sand or earth. Keep out of sewers and waterways.

7.0 HANDLING AND STORAGE

HANDLING: No special requirements.

STORAGE: No special requirements.

8.0 EXPOSURE CONTROLS / PERSONAL PROTECTION

EYE: None required; however, use of eye protection is good industrial practice.

SKIN: Wear protective clothing and gloves if prolonged or repeated contact is likely.

INHALATION: None required; however, use of adequate ventilation is good industrial practice.

ENGINEERING CONTROLS: Control airborne concentrations below the exposure guidelines.

EXPOSURE GUIDELINES:

Component	CAS#	Exposure Limits
Hydrotreated solvent dewaxed paraffinic petroleum	64742-57- 0	OSHA PEL: 5 mg/m³ (oil mist) (1989(1971) ACGIH TLV-TWA: 5 mg/m³ (oil mist) ACGIH TLV-STEL: 10 mg/m³ (oil mist)
Solvent refined light paraffinic distillate	64741-89- 5	OSHA PEL: 5 mg/m³ (oil mist) (1989)(1971) ACGIH TLV-TWA: 5 mg/m³ (oil mist) ACGIH TLV-STEL: 10 mg/m³ (oil mist)

9.0 CHEMICAL AND PHYSICAL PROPERTIES

APPEARANCE AND ODOR: Oily liquid. Orange.

pH: Not determined.

VAPOR PRESSURE: Not determined.

VAPOR DENSITY: Not determined.

BOILING POINT: Not determined.

MELTING POINT: Not determined.

SOLUBILITY IN WATER: Negligible, below 0.1%.

SPECIFIC GRAVITY (WATER=1): 0.89

VISCOSITY: 13.5-16.5cSt at 100°C ASTM D445

POUR POINT: -10°F (-23°C) (maximum)

VISCOSITY INDEX: 100 Minimum.

10.0 STABILITY AND REACTIVITY

STABILITY: Stable.

CONDITIONS TO AVOID: None identified.

MATERIALS TO AVOID: Avoid chlorine, fluorine, and other strong oxidizers.

HAZARDOUS DECOMPOSITION: None identified.

HAZARDOUS POLYMERIZATION: Will not occur.

11.0 TOXICOLOGICAL INFORMATION

ACUTE TOXICITY DATA:

EYE IRRITATION: Testing not conducted. See Other Toxicity Data.

SKIN IRRITATION: Testing not conducted. See Other Toxicity Data.

DERMAL LD50: Testing not conducted. See Other Toxicity Data.

ORAL LD50: Testing not conducted. See Other Toxicity Data.

INHALATION LC50: Testing not conducted. See Other Toxicity Data.

OTHER TOXICITY DATA: Specific toxicity tests have not been conducted on this product. Our hazard evaluation is based on information from similar products, the ingredients, technical literature, and/or professional experience.

No component of this product present at levels greater than 0.1% is identified as a carcinogen by the U.S. National Toxicology Program, the U.S. Occupational Safety and Health Act, or the International Agency on Research on Cancer (IARC).

12.0 ECOLOGICAL INFORMATION

Ecological testing has not been conducted on this product by Amoco.

13.0 DISPOSAL INFORMATION

Disposal must be in accordance with applicable federal, state, or local regulations. Enclosed-controlled incineration is recommended unless directed otherwise by applicable ordinances.

14.0 TRANSPORTATION INFORMATION

U.S. DEPT OF TRANSPORTATION

Shipping Name Not Regulated

INTERNATIONAL INFORMATION:

Sea (IMO/IMDG)

Shipping Name Not Regulated

Air (ICAO/IATA)

Shipping Name Not Regulated

European Road/Rail (ADR/RID)

Shipping Name Not Regulated

Canadian Transportation of Dangerous Goods

Shipping Name Not Regulated

15.0 REGULATORY INFORMATION

CERCLA SECTIONS 102a/103 HAZARDOUS SUBSTANCES (40 CFR Part 302.4): This product is not reportable under 40 CFR Part 302.4.

SARA TITLE III SECTION 302 EXTREMELY HAZARDOUS SUBSTANCES (40 CFR Part 355): This product is not regulated under Section 302 of SARA and 40 CFR Part 355.

SARA TITLE III SECTIONS 311/312 HAZARDOUS CATEGORIZATION (40 CFR Part 370): This product is not regulated under SARA Title III Section 311/312.

SARA TITLE III SECTION 313 (40 CFR Part 372): This product is not regulated under Section 313 of SARA and 40 CFR Part 372.

U.S. INVENTORY (TSCA): Listed on inventory.

This product contains n-methyl pyrrolidone (CAS 872-50-4) which is currently undergoing review and testing under TSCA Section 4. Notification to the U.S. EPA Office of Toxic Substances is required prior to export of this material from the United States.

This product contains 2-ethylhexanol (CAS 104-76-7) which is currently undergoing review and testing under TSCA Section 4. Notification to the U.S. EPA Office of Toxic Substances is required prior to export of this material from the United States.

OSHA HAZARD COMMUNICATION STANDARD: Contains a component listed by OSHA. Contains a component listed by ACGIH.

WHMIS Controlled Product Classification: Not a Controlled Product under Canada's Workplace Hazardous Material Information System.

EC INVENTORY (EINECS/ELINCS): In compliance.

JAPAN INVENTORY (MITI): Listed on inventory.

AUSTRALIA INVENTORY (AICS): Listed on inventory.

KOREA INVENTORY (ECL): Listed on inventory.

CANADA INVENTORY (DSL): All of the components of this product are listed on the DSL.

PHILIPPINE INVENTORY (PICCS): Not determined.

FOOD CONTACT STATUS

USDA:

H2 Status: This product is acceptable to the USDA for use as a lubricant in official meat and poultry establishments provided there is no possibility of the lubricant or lubricated part contacting edible products.

16.0 OTHER INFORMATION

Prepared by:

Environment, Health and Safety Department

Issued: November 03, 1997

Supersedes: August 19, 1996

This Material Safety Data Sheet conforms to the requirements of ANSI Z400.1.

This material safety data sheet and the information it contains is offered to you in good faith as accurate. We have reviewed any information contained in this data sheet which we received from sources outside our company. We believe that information to be correct but cannot guarantee its accuracy or completeness. Health and safety precautions in this data sheet may not be adequate for all individuals and/or situations. It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. No statement made in this data sheet shall be construed as a permission or recommendation for the use of any product in a manner that might infringe existing patents. No warranty is made, either express or implied.