


10/27/16

| | | |
|--|--|---------------------------|
|  | | Page: 1 |
| SAFETY DATA SHEET | | Revision Date: 09/28/2016 |
| | | Print Date: 10/3/2016 |
| | | SDS Number: R0091437 |
| NAPA® PREM PERF GEAR OIL SAE 80W-90 GEAR OIL | | Version: 1.4 |
| NP75213 | | |

29 CFR 1910.1200 (OSHA HazCom 2012)

Napa Premium
Performance Gear
Oil

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name : NAPA® PREM PERF GEAR OIL SAE 80W-90 GEAR OIL

Relevant identified uses of the substance or mixture and uses advised against


| | |
|---|--|
| Details of the supplier of the safety data sheet Valvoline LLC 3499 Blazer Parkway Lexington, KY 40509 United States of America (USA) 1-800-TEAMVAL | Emergency telephone number 1-800-VALVOLINE Regulatory Information Number 1-800-TEAMVAL Product Information 1-800-TEAMVAL |
|---|--|

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Skin sensitization : Category 1

GHS label elements

Hazard pictograms : 

Signal Word : Warning


Hazard Statements : May cause an allergic skin reaction.

Precautionary Statements : **Prevention:**
 Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.
 Contaminated work clothing must not be allowed out of the workplace.
 Wear protective gloves.

Response:
 IF ON SKIN: Wash with plenty of soap and water.
 If skin irritation or rash occurs: Get medical advice/ attention.
 Wash contaminated clothing before reuse.

Disposal:
 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

| | |
|--|---------------------------|
|  | Page: 2 |
| | Revision Date: 09/28/2016 |
| SAFETY DATA SHEET | Print Date: 10/3/2016 |
| | SDS Number: R0091437 |
| NAPA® PREM PERF GEAR OIL SAE 80W-90 GEAR OIL | Version: 1.4 |
| NP75213 | |

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture
 Chemical nature : Defatter

Hazardous components


| Chemical name | CAS-No. | Classification | Concentration (%) |
|--|------------|--|-------------------|
| RESIDUAL OILS (PETROLEUM), SOLVENT-DEWAXED | 64742-62-7 | This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012). | 21.105 |
| DISTILLATES (PETROLEUM), HYDROTREATED LIGHT | 64742-47-8 | Asp. Tox. 1; H304 | 1.393 |
| AMINES, C12-14-TERT-ALKYL | 68955-53-3 | Flam. Liq. 4; H227 Acute Tox. 4; H302 Acute Tox. 2; H330 Acute Tox. 3; H311 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 | 0.343 |

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.
 Show this safety data sheet to the doctor in attendance.
 Do not leave the victim unattended.

If inhaled : If breathed in, move person into fresh air.
 If unconscious, place in recovery position and seek medical advice.
 If symptoms persist, call a physician.

In case of skin contact : Remove contaminated clothing. If irritation develops, get medical attention.

| | | |
|---|--|---------------------------|
|  | | Page: 3 |
| SAFETY DATA SHEET | | Revision Date: 09/28/2016 |
| | | Print Date: 10/3/2016 |
| | | SDS Number: R0091437 |
| NAPA® PREM PERF GEAR OIL SAE 80W-90 GEAR OIL NP75213 | | Version: 1.4 |

If on skin, rinse well with water.
 First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.
 Wash contaminated clothing before re-use.

In case of eye contact : Flush eyes with water as a precaution.
 Remove contact lenses.
 Protect unharmed eye.
 If eye irritation persists, consult a specialist.

If swallowed : Do not give milk or alcoholic beverages.
 Never give anything by mouth to an unconscious person.
 If symptoms persist, call a physician.


Most important symptoms and effects, both acute and delayed :
 Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities.
 Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:
 stomach or intestinal upset (nausea, vomiting, diarrhea)
 irritation (nose, throat, airways)
 Headache
 Dizziness
 May cause an allergic skin reaction.

Notes to physician : No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
 Water spray
 Foam
 Carbon dioxide (CO2)
 Dry chemical

Unsuitable extinguishing media : High volume water jet

| | | |
|---|--|---------------------------|
|  | | Page: 4 |
| SAFETY DATA SHEET | | Revision Date: 09/28/2016 |
| | | Print Date: 10/3/2016 |
| | | SDS Number: R0091437 |
| NAPA® PREM PERF GEAR OIL SAE 80W-90 GEAR OIL | | Version: 1.4 |
| NP75213 | | |


- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : carbon dioxide and carbon monoxide
Hydrocarbons
- Specific extinguishing methods :
- Product is compatible with standard fire-fighting agents.
- Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.
- Other information : Comply with all applicable federal, state, and local regulations.

SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Do not breathe vapours/dust.
Do not smoke.
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Container hazardous when empty.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
Smoking, eating and drinking should be prohibited in the application area.
For personal protection see section 8.

| | | |
|--|--|---------------------------|
|  | | Page: 5 |
| SAFETY DATA SHEET | | Revision Date: 09/28/2016 |
| | | Print Date: 10/3/2016 |
| | | SDS Number: R0091437 |
| NAPA® PREM PERF GEAR OIL SAE 80W-90 GEAR OIL | | Version: 1.4 |
| NP75213 | | |

Dispose of rinse water in accordance with local and national regulations.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

| Components | CAS-No. | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis |
|--|------------|----------------------------------|---|-----------|
| DISTILLATES (PETROLEUM), HYDROTREATED LIGHT | 64742-47-8 | TWA | 5 mg/m3 Mist | OSHA Z-1 |
| | | TWA | 200 mg/m3 (total hydrocarbon vapor) | ACGIH |
| | | TWA | 5 mg/m3 Mist | OSHA P0 |
| | | TWA | 5 mg/m3 Mist | NIOSH REL |
| | | ST | 10 mg/m3 Mist | NIOSH REL |
| | | PEL | 5 mg/m3 particulate | CAL PEL |

Hazardous components without workplace control parameters

| Components | CAS-No. |
|---------------------------|------------|
| AMINES, C12-14-TERT-ALKYL | 68955-53-3 |

Engineering measures : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment


Respiratory protection : Respiratory protection is not required under normal conditions of use.

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection


: Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

| | | |
|--|--|---------------------------|
|  | | Page: 6 |
| SAFETY DATA SHEET | | Revision Date: 09/28/2016 |
| | | Print Date: 10/3/2016 |
| | | SDS Number: R0091437 |
| NAPA® PREM PERF GEAR OIL SAE 80W-90 GEAR OIL NP75213 | | Version: 1.4 |

- Skin and body protection : Wear as appropriate:
Impervious clothing
Safety shoes
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Discard gloves that show tears, pinholes, or signs of wear.
Wear resistant gloves (consult your safety equipment supplier).
- Hygiene measures : Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Physical state : liquid
- Colour : amber
- Odour : No data available
- Odour Threshold : No data available
- pH : No data available
- Melting point/freezing point : No data available
- Boiling point/boiling range : > 424.9 °F / 218.3 °C
(1013.333 hPa)
- Flash point : > 222 °C
Method: Cleveland open cup
- Evaporation rate : > 1
Ethyl Ether
- Flammability (solid, gas) : No data available
- Upper explosion limit : No data available
- Lower explosion limit : No data available
- Vapour pressure : < 0.1000000 mmHg
- Relative vapour density : > 1AIR=1
- Relative density : 0.89 (60.00 °F)
- Density : 0.8916 g/cm3 (15.56 °C)
- Solubility(ies)

| | | |
|---|--|---------------------------|
|  | | Page: 7 |
| SAFETY DATA SHEET | | Revision Date: 09/28/2016 |
| | | Print Date: 10/3/2016 |
| | | SDS Number: R0091437 |
| NAPA® PREM PERF GEAR OIL SAE 80W-90 GEAR OIL NP75213 | | Version: 1.4 |

Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Thermal decomposition : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : 146 mm²/s (40 °C)

Oxidizing properties : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous reactions : Product will not undergo hazardous polymerization.

Incompatible materials : Strong oxidizing agents

Hazardous decomposition products : Aldehydes
carbon dioxide and carbon monoxide
Carbon monoxide

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Inhalation
Skin contact
Eye Contact
Ingestion

Acute toxicity


Not classified based on available information.

Components:

RESIDUAL OILS (PETROLEUM), SOLVENT-DEWAXED:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.58 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

| | | |
|---|--|---------------------------|
|  | | Page: 8 |
| SAFETY DATA SHEET | | Revision Date: 09/28/2016 |
| | | Print Date: 10/3/2016 |
| | | SDS Number: R0091437 |
| NAPA® PREM PERF GEAR OIL SAE 80W-90 GEAR OIL NP75213 | | Version: 1.4 |

Assessment: Not classified as acutely toxic by inhalation under GHS.

Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg
Remarks: No mortality observed at this dose.

LD50 (Rabbit): > 2,000 mg/kg
Assessment: Not classified as acutely toxic by dermal absorption under GHS.

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 3,160 mg/kg
Assessment: No adverse effect has been observed in acute dermal toxicity tests.

AMINES, C12-14-TERT-ALKYL:

Acute oral toxicity : LD50 (Rat): 612 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat, female): 1.19 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rat): 251 mg/kg
Method: OECD Test Guideline 402

Skin corrosion/irritation

Not classified based on available information.

Product:

Remarks: May cause skin irritation in susceptible persons.

Components:

RESIDUAL OILS (PETROLEUM), SOLVENT-DEWAXED:

Species: Rabbit

Result: No skin irritation

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT:

Result: Slight, transient irritation

AMINES, C12-14-TERT-ALKYL:

Species: Rabbit


Result: Corrosive after 3 minutes to 1 hour of exposure

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

| | | |
|--|--|---------------------------|
|  | | Page: 9 |
| | | Revision Date: 09/28/2016 |
| SAFETY DATA SHEET | | Print Date: 10/3/2016 |
| | | SDS Number: R0091437 |
| NAPA® PREM PERF GEAR OIL SAE 80W-90 GEAR OIL | | Version: 1.4 |
| NP75213 | | |

Remarks: Unlikely to cause eye irritation or injury.

Components:

RESIDUAL OILS (PETROLEUM), SOLVENT-DEWAXED:

Species: Rabbit

Result: No eye irritation

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT:

Result: Slight, transient irritation

AMINES, C12-14-TERT-ALKYL:

Species: Rabbit

Result: Corrosive

Respiratory or skin sensitisation

Skin sensitisation: May cause an allergic skin reaction.

Respiratory sensitisation: Not classified based on available information.

Components:

RESIDUAL OILS (PETROLEUM), SOLVENT-DEWAXED:

Test Type: Buehler Test

Species: Guinea pig

Assessment: Does not cause skin sensitisation.

AMINES, C12-14-TERT-ALKYL:

Test Type: Buehler Test

Species: Guinea pig

Assessment: The product is a skin sensitiser, sub-category 1A.

Germ cell mutagenicity

Not classified based on available information.

Components:

AMINES, C12-14-TERT-ALKYL:

Genotoxicity in vitro

: Test Type: Ames test
 Test species: Salmonella typhimurium
 Metabolic activation: with and without metabolic activation
 Method: OECD Test Guideline 471
 Result: negative

Genotoxicity in vivo

: Test Type: Micronucleus test
 Test species: Mouse
 Cell type: Bone marrow
 Method: OECD Test Guideline 474
 Result: negative

Carcinogenicity

Not classified based on available information.


Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

| | |
|--|---------------------------|
|  | Page: 10 |
| | Revision Date: 09/28/2016 |
| SAFETY DATA SHEET | Print Date: 10/3/2016 |
| NAPA® PREM PERF GEAR OIL SAE 80W-90 GEAR OIL | SDS Number: R0091437 |
| NP75213 | Version: 1.4 |

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Product:

No aspiration toxicity classification

Components:

RESIDUAL OILS (PETROLEUM), SOLVENT-DEWAXED:

No aspiration toxicity classification

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : Acute aquatic toxicity Category 3; Harmful to aquatic life.

Chronic aquatic toxicity : Chronic aquatic toxicity Category 3; Harmful to aquatic life with long lasting effects.

Components:


RESIDUAL OILS (PETROLEUM), SOLVENT-DEWAXED:

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l
 Exposure time: 96 h
 Test Type: static test
 Test substance: WAF
 Method: OECD Test Guideline 203
 Remarks: No toxicity at the limit of solubility

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 10,000 mg/l
 Exposure time: 48 h
 Test Type: static test
 Test substance: WAF
 Method: OECD Test Guideline 202

Toxicity to algae : NOEL (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l
 End point: Growth inhibition
 Exposure time: 72 h
 Test Type: static test
 Test substance: WAF
 Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOELR (Oncorhynchus mykiss (rainbow trout)): Calculated >= 1,000 mg/l

| | | |
|--|--|---------------------------|
|  | | Page: 11 |
| | | Revision Date: 09/28/2016 |
| SAFETY DATA SHEET | | Print Date: 10/3/2016 |
| NAPA® PREM PERF GEAR OIL SAE 80W-90 GEAR OIL | | SDS Number: R0091437 |
| NP75213 | | Version: 1.4 |

Exposure time: 14 d

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEL (Daphnia (water flea)): 10 mg/l
 Exposure time: 21 d
 Test substance: WAF
 Method: OECD Test Guideline 211

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT:
 Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2 - 5 mg/l
 Exposure time: 96 h
 Test Type: semi-static test
 Test substance: WAF
 Method: OECD Test Guideline 203
 Remarks: Information given is based on data obtained from similar substances.

Toxicity to daphnia and other aquatic invertebrates : EL50 (Water flea (Daphnia magna)): 1.4 mg/l
 Exposure time: 48 h
 Test Type: static test
 Test substance: WAF
 Method: OECD Test Guideline 202
 Remarks: Information given is based on data obtained from similar substances.


Toxicity to algae : EL50 (Pseudokirchneriella subcapitata (green algae)): > 1 - 3 mg/l
 Exposure time: 72 h
 Test Type: static test
 Test substance: WAF
 Method: OECD Test Guideline 201
 Remarks: Information given is based on data obtained from similar substances.

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEL (Water flea (Daphnia magna)): 0.48 mg/l
 Exposure time: 21 d
 Test Type: semi-static test
 Test substance: WAF
 Method: OECD Test Guideline 211
 Remarks: Information given is based on data obtained from similar substances.

AMINES, C12-14-TERT-ALKYL:
 Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 1.3 mg/l
 Exposure time: 96 h
 Test Type: static test
 Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Water flea (Daphnia magna)): 2.5 mg/l
 Exposure time: 48 h
 Test Type: static test

Toxicity to algae : ErC50 (Pseudokirchneriella subcapitata (microalgae)): 0.44 mg/l

| | |
|--|---------------------------|
|  | Page: 12 |
| | Revision Date: 09/28/2016 |
| SAFETY DATA SHEET | Print Date: 10/3/2016 |
| NAPA® PREM PERF GEAR OIL SAE 80W-90 GEAR OIL | SDS Number: R0091437 |
| NP75213 | Version: 1.4 |

End point: Growth inhibition
 Exposure time: 72 h
 Test Type: static test
 Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (microalgae)): 0.05 mg/l
 End point: Growth inhibition
 Exposure time: 72 h
 Test Type: static test
 Method: OECD Test Guideline 201

M-Factor (Acute aquatic toxicity) : 1

Toxicity to fish (Chronic toxicity) : NOEC (Oncorhynchus mykiss (rainbow trout)): 0.078 mg/l
 Exposure time: 96 d
 Test Type: flow-through test
 Method: OECD Test Guideline 210

M-Factor (Chronic aquatic toxicity) : 1

Persistence and degradability

Components:

RESIDUAL OILS (PETROLEUM), SOLVENT-DEWAXED:
 Biodegradability : Result: Not readily biodegradable.
 Biodegradation: 2 - 4 %
 Exposure time: 28 d
 Method: OECD Test Guideline 301B

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT:
 Biodegradability : Result: Inherently biodegradable
 Biodegradation: 58.6 %
 Exposure time: 28 d
 Method: OECD Test Guideline 301F

Remarks: Expected to be biodegradable

AMINES, C12-14-TERT-ALKYL:
 Biodegradability : Result: Not readily biodegradable.
 Biodegradation: 22 %
 Exposure time: 28 d
 Method: OECD Test Guideline 301D


No data available

Bioaccumulative potential

Components:

AMINES, C12-14-TERT-ALKYL:
 Partition coefficient: n-octanol/water : log Pow: 2.9

No data available

| | | |
|--|--|---------------------------|
|  | | Page: 13 |
| | | Revision Date: 09/28/2016 |
| SAFETY DATA SHEET | | Print Date: 10/3/2016 |
| NAPA® PREM PERF GEAR OIL SAE 80W-90 GEAR OIL | | SDS Number: R0091437 |
| NP75213 | | Version: 1.4 |

Mobility in soil

Components:

No data available

Other adverse effects

No data available

Product:

Additional ecological information

: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Harmful to aquatic life with long lasting effects.

Components:

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

General advice

: The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Dispose of in accordance with all applicable local, state and federal regulations.

Contaminated packaging

: Empty remaining contents.
Dispose of as unused product.
Empty containers should be taken to an approved waste handling site for recycling or disposal.
Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

REGULATION

| ID NUMBER | PROPER SHIPPING NAME | *HAZARD CLASS | SUBSIDIARY HAZARDS | PACKING GROUP | MARINE POLLUTANT / LTD. QTY. |
|-----------|----------------------|---------------|--------------------|---------------|------------------------------|
| | | | | | |

U.S. DOT - ROAD


| |
|---------------------|
| Not dangerous goods |
|---------------------|

CFR RAIL C

| |
|---------------------|
| Not dangerous goods |
|---------------------|

U.S. DOT - INLAND WATERWAYS

| |
|---------------------|
| Not dangerous goods |
|---------------------|

| | |
|---|---------------------------|
|  | Page: 14 |
| | Revision Date: 09/28/2016 |
| SAFETY DATA SHEET | Print Date: 10/3/2016 |
| NAPA® PREM PERF GEAR OIL SAE 80W-90 GEAR OIL | SDS Number: R0091437 |
| NP75213 | Version: 1.4 |

TDG_ROAD_C

| |
|---------------------|
| Not dangerous goods |
|---------------------|

TDG_RAIL_C

| |
|---------------------|
| Not dangerous goods |
|---------------------|

TDG_INWT_C

| |
|---------------------|
| Not dangerous goods |
|---------------------|

INTERNATIONAL MARITIME DANGEROUS GOODS

| |
|---------------------|
| Not dangerous goods |
|---------------------|

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

| |
|---------------------|
| Not dangerous goods |
|---------------------|

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

| |
|---------------------|
| Not dangerous goods |
|---------------------|

MX_DG

| |
|---------------------|
| Not dangerous goods |
|---------------------|

*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

| | |
|------------------|----|
| Marine pollutant | no |
|------------------|----|

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.


SECTION 15. REGULATORY INFORMATION

SARA 311/312 Hazards : Acute Health Hazard

SARA 313 This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

California Prop 65 This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

The components of this product are reported in the following inventories:

| | | |
|---|--|---------------------------|
|  | | Page: 15 |
| SAFETY DATA SHEET | | Revision Date: 09/28/2016 |
| | | Print Date: 10/3/2016 |
| | | SDS Number: R0091437 |
| NAPA® PREM PERF GEAR OIL SAE 80W-90 GEAR OIL | | Version: 1.4 |
| NP75213 | | |

- TSCA : On TSCA Inventory
- DSL : All components of this product are on the Canadian DSL
- AICS : On the inventory, or in compliance with the inventory
- ENCS : On the inventory, or in compliance with the inventory
- KECI : On the inventory, or in compliance with the inventory
- PICCS : On the inventory, or in compliance with the inventory
- IECSC : On the inventory, or in compliance with the inventory


Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information


Revision Date: 09/28/2016

| | | | | | | | |
|--|--|---------------|----------|---------------------|----------|------------------------|----------|
| <p>NFPA:</p> <div style="text-align: center;"> <p>Flammability</p>  <p>Health Instability</p> <p>Special hazard.</p> </div> | <p>HMIS III:</p> <table border="1" style="width: 100%;"> <tr> <td style="background-color: black; color: white;">HEALTH</td> <td style="text-align: center;">2</td> </tr> <tr> <td style="background-color: black; color: white;">FLAMMABILITY</td> <td style="text-align: center;">1</td> </tr> <tr> <td style="background-color: black; color: white;">PHYSICAL HAZARD</td> <td style="text-align: center;">0</td> </tr> </table> <p>0 = not significant, 1 = Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic</p> | HEALTH | 2 | FLAMMABILITY | 1 | PHYSICAL HAZARD | 0 |
| HEALTH | 2 | | | | | | |
| FLAMMABILITY | 1 | | | | | | |
| PHYSICAL HAZARD | 0 | | | | | | |

NFPA Flammable and Combustible Liquids Classification
Combustible Liquid Class III B

Full text of H-Statements

- H227 Combustible liquid.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H311 Toxic in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H317 May cause an allergic skin reaction.

| | |
|--|---------------------------|
|  | Page: 16 |
| | Revision Date: 09/28/2016 |
| SAFETY DATA SHEET | Print Date: 10/3/2016 |
| | SDS Number: R0091437 |
| NAPA® PREM PERF GEAR OIL SAE 80W-90 GEAR OIL | Version: 1.4 |
| NP75213 | |


H318 Causes serious eye damage.
H330 Fatal if inhaled.

Sources of key data used to compile the Safety Data Sheet
Valvoline internal data including own and sponsored test reports
The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists
BEI : Biological Exposure Index
CAS : Chemical Abstracts Service (Division of the American Chemical Society).
CMR : Carcinogenic, Mutagenic or Toxic for Reproduction
FG : Food grade
GHS : Globally Harmonized System of Classification and Labeling of Chemicals.
H-statement : Hazard Statement
IATA : International Air Transport Association.
IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO : International Civil Aviation Organization
ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"
IMDG : International Maritime Code for Dangerous Goods
ISO : International Organization for Standardization
logPow : octanol-water partition coefficient
LCxx : Lethal Concentration, for xx percent of test population
LDxx : Lethal Dose, for xx percent of test population.
ICxx : Inhibitory Concentration for xx of a substance
Ecxx : Effective Concentration of xx
N.O.S.: Not Otherwise Specified
OECD : Organization for Economic Co-operation and Development
OEL : Occupational Exposure Limit
P-Statement : Precautionary Statement
PBT : Persistent , Bioaccumulative and Toxic
PPE : Personal Protective Equipment
STEL : Short-term exposure limit
STOT : Specific Target Organ Toxicity
TLV : Threshold Limit Value
TWA : Time-weighted average
vPvB : Very Persistent and Very Bioaccumulative
WEL : Workplace Exposure Level

| | | |
|--|--|---------------------------|
|  | | Page: 17 |
| | | Revision Date: 09/28/2016 |
| SAFETY DATA SHEET | | Print Date: 10/3/2016 |
| | | SDS Number: R0091437 |
| NAPA® PREM PERF GEAR OIL SAE 80W-90 GEAR OIL | | Version: 1.4 |
| NP75213 | | |

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act
 DOT : Department of Transportation
 FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act
 HMIRC : Hazardous Materials Information Review Commission
 HMIS : Hazardous Materials Identification System
 NFPA : National Fire Protection Association
 NIOSH : National Institute for Occupational Safety and Health
 OSHA : Occupational Safety and Health Administration
 PMRA : Health Canada Pest Management Regulatory Agency
 RTK : Right to Know
 WHMIS : Workplace Hazardous Materials Information System