


| | |
|---|---------------------------|
|  | Page: 1 |
| | Revision Date: 05/22/2017 |
| SAFETY DATA SHEET | Print Date: 6/2/2017 |
| Zerex™ HD NITRITE FREE EXTENDED LIFE RTU Antifreeze Coolant | SDS Number: 000000248245 |
| 846437 | Version: 1.3 |

Antifreeze Coolant Diesel
Ready Heavy Duty Nitrite
Free Extended Life Formula
ZEREX

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name : Zerex™ HD NITRITE FREE EXTENDED LIFE RTU Antifreeze Coolant

Relevant identified uses of the substance or mixture and uses advised against

Recommended use : Coolant and antifreeze.

| | |
|---|---|
| Details of the supplier of the safety data sheet Valvoline LLC 100 Valvoline Way Lexington, KY 40509 United States of America (USA) 1-800-TEAMVAL | Emergency telephone number 1-800-VALVOLINE (1-800-825-8654) Regulatory Information Number 1-800-TEAMVAL Product Information 1-800-TEAMVAL |
|---|---|



SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Acute toxicity (Oral) : Category 4

Specific target organ systemic toxicity - repeated exposure (Oral) : Category 2 (Kidney, Liver)


GHS label elements

Hazard pictograms :  

Signal Word : Warning

Hazard Statements : Harmful if swallowed.
May cause damage to organs (Kidney, Liver) through prolonged or repeated exposure if swallowed.

Precautionary Statements : **Prevention:**
Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.
Wash skin thoroughly after handling.

| | | |
|---|--|---------------------------|
|  | | Page: 2 |
| SAFETY DATA SHEET | | Revision Date: 05/22/2017 |
| | | Print Date: 6/2/2017 |
| | | SDS Number: 000000248245 |
| Zerex™ HD NITRITE FREE EXTENDED LIFE RTU Antifreeze Coolant | | Version: 1.3 |
| 846437 | | |

Do not eat, drink or smoke when using this product.

Response:

IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.

Get medical advice/ attention if you feel unwell.

Disposal:

Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS


Substance / Mixture : Mixture

Hazardous components

| Chemical name | CAS-No. | Classification | Concentration (%) |
|-------------------|----------|---------------------------------------|-------------------|
| ETHYLENE GLYCOL | 107-21-1 | Acute Tox. 4; H302 STOT RE 2; H373 | 46.5365 |
| DIETHYLENE GLYCOL | 111-46-6 | Acute Tox. 4; H302 STOT RE 2; H373 | 2.326 |

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : If breathed in, move person into fresh air.
If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.
- In case of eye contact : Flush eyes with water as a precaution.
Remove contact lenses.
Protect unharmed eye.

| | | |
|---|--|---------------------------|
|  | | Page: 3 |
| SAFETY DATA SHEET | | Revision Date: 05/22/2017 |
| | | Print Date: 6/2/2017 |
| | | SDS Number: 000000248245 |
| Zerex™ HD NITRITE FREE EXTENDED LIFE RTU Antifreeze Coolant 846437 | | Version: 1.3 |

If eye irritation persists, consult a specialist.

If swallowed

- : Obtain medical attention.
 Rinse mouth with water.
 Do not give milk or alcoholic beverages.
 Never give anything by mouth to an unconscious person.
 If symptoms persist, call a physician.

Most important symptoms and effects, both acute and delayed


- : Effects of acute ethylene glycol poisoning appear in three fairly distinct stages. The initial stage occurs shortly after exposure, lasts 6-12 hours, and is characterized by central nervous system effects (transient exhilaration, nausea, vomiting, and in severe cases, coma, convulsions, and possible death). The second stage lasts from 12-36 hours after exposure and is initiated by the onset of coma. This phase is characterized by tachypnea, tachycardia, mild hypotension, cyanosis, and in severe cases, pulmonary edema, bronchopneumonia, cardiac enlargement, and congestive failure. The final stage occurs 24-72 post-exposure and is characterized by renal failure, ranging from a mild increase in blood urea nitrogen and creatinine followed by recovery, to complete anuria with acute tubular necrosis that can lead to death. Oxaluria is found in most cases. The most significant laboratory finding in ethylene glycol intoxication is severe metabolic acidosis.

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:

- stomach or intestinal upset (nausea, vomiting, diarrhea)
- irritation (nose, throat, airways)
- Cough
- pain in the abdomen and lower back
- cyanosis (causes blue coloring of the skin and nails from lack of oxygen)
- lung edema (fluid buildup in the lung tissue)
- acute kidney failure (sudden slowing or stopping of urine production)
- Convulsions
- Harmful if swallowed.

Notes to physician

- : This product contains ethylene glycol. Ethanol decreases the metabolism of ethylene glycol to toxic metabolites. Ethanol should be administered as soon as possible in cases of severe poisoning since the elimination half-life of ethylene glycol is 3 hours. If medical care will be delayed several hours, give the patient three to four 1-ounce oral "shots" of 86-proof or higher whiskey before or during transport to the hospital. Fomepizole (4-methylpyrazole) is an effective antagonist of alcohol dehydrogenase, and as such, may be

| | | |
|--|--|---------------------------|
|  | | Page: 4 |
| SAFETY DATA SHEET | | Revision Date: 05/22/2017 |
| | | Print Date: 6/2/2017 |
| Zerex™ HD NITRITE FREE EXTENDED LIFE RTU Antifreeze Coolant | | SDS Number: 000000248245 |
| 846437 | | Version: 1.3 |

used as an antidote in the treatment of ethylene glycol poisoning. Hemodialysis effectively removes ethylene glycol and its metabolites from the body.


SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Water spray
Foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : Alcohols
Aldehydes
carbon dioxide and carbon monoxide
ethers
toxic fumes
Sodium oxides
Hydrocarbons
- Specific extinguishing methods :

Product is compatible with standard fire-fighting agents.
- Further information : Standard procedure for chemical fires.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform

| | | |
|---|--|---------------------------|
|  | | Page: 5 |
| SAFETY DATA SHEET | | Revision Date: 05/22/2017 |
| | | Print Date: 6/2/2017 |
| | | SDS Number: 000000248245 |
| Zerex™ HD NITRITE FREE EXTENDED LIFE RTU Antifreeze Coolant 846437 | | Version: 1.3 |

respective authorities.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

Other information : Comply with all applicable federal, state, and local regulations.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Do not breathe vapours/dust.
Do not smoke.
Container hazardous when empty.
Smoking, eating and drinking should be prohibited in the application area.
For personal protection see section 8.
Dispose of rinse water in accordance with local and national regulations.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters


| Components | CAS-No. | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis |
|-------------------|----------|----------------------------------|---|---------|
| ETHYLENE GLYCOL | 107-21-1 | C | 100 mg/m3 Aerosol only | ACGIH |
| | | C | 50 ppm 125 mg/m3 | OSHA P0 |
| | | C | 40 ppm 100 mg/m3 Vapour | CAL PEL |
| DIETHYLENE GLYCOL | 111-46-6 | TWA | 10 mg/m3 | US WEEL |

Engineering measures : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Hand protection

Remarks : The suitability for a specific workplace should be discussed


| | | |
|---|--|---------------------------|
|  | | Page: 6 |
| SAFETY DATA SHEET | | Revision Date: 05/22/2017 |
| | | Print Date: 6/2/2017 |
| | | SDS Number: 000000248245 |
| Zerex™ HD NITRITE FREE EXTENDED LIFE RTU Antifreeze Coolant | | Version: 1.3 |
| 846437 | | |

with the producers of the protective gloves.

- Eye protection : Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.
- Skin and body protection : Wear as appropriate:
 Impervious clothing
 Safety shoes
 Choose body protection according to the amount and concentration of the dangerous substance at the work place.
 Wear resistant gloves (consult your safety equipment supplier).
- Hygiene measures : Wash hands before breaks and at the end of workday.
 When using do not eat or drink.
 When using do not smoke.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Physical state : liquid
- Odour : No data available
- Odour Threshold : No data available
- pH : 9.0
- Melting point/freezing point : No data available
- Boiling point/boiling range : No data available
- Flash point : > 250 °F / > 121 °C
- Evaporation rate : No data available
- Flammability (solid, gas) : No data available
- Upper explosion limit : No data available
- Lower explosion limit : No data available
- Vapour pressure : No data available
- Relative vapour density : No data available
- Relative density : No data available

| | | |
|---|--|---------------------------|
|  | | Page: 7 |
| SAFETY DATA SHEET | | Revision Date: 05/22/2017 |
| | | Print Date: 6/2/2017 |
| | | SDS Number: 000000248245 |
| Zerex™ HD NITRITE FREE EXTENDED LIFE RTU Antifreeze Coolant 846437 | | Version: 1.3 |

Density : 1.076 g/cm³ (15.6 °C)

Solubility(ies)
Water solubility : soluble

Solubility in other solvents : No data available

Partition coefficient: n-
octanol/water : No data available

Thermal decomposition : No data available

Viscosity
Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Oxidizing properties : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.


Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous
reactions : Product will not undergo hazardous polymerization.

Conditions to avoid : excessive heat

Incompatible materials : Acids
Aldehydes
Alkali metals
Alkaline earth metals
Bases
strong alkalis
Strong oxidizing agents
Sulphur compounds

Hazardous decomposition
products : Alcohols
Aldehydes
carbon dioxide and carbon monoxide
ethers
Hydrocarbons
Organic acids
ketones

| | |
|---|---------------------------|
|  | Page: 8 |
| | SAFETY DATA SHEET |
| | Revision Date: 05/22/2017 |
| | Print Date: 6/2/2017 |
| | SDS Number: 000000248245 |
| | Version: 1.3 |
| Zerex™ HD NITRITE FREE EXTENDED LIFE RTU Antifreeze Coolant 846437 | |

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Inhalation
Skin contact
Eye Contact
Ingestion

Acute toxicity
Harmful if swallowed.

Product:

Acute oral toxicity :

Remarks: Ingestion of medications contaminated with diethylene glycol has caused kidney failure and death in humans. Products containing diethylene glycol should be considered toxic by ingestion.

Acute dermal toxicity :

Remarks: Skin absorption of this material (or a component) may be increased through injured skin.

Components:

ETHYLENE GLYCOL:

Acute oral toxicity :

LD0 (Human): Estimated 1.56 g/kg

Assessment: The component/mixture is classified as acute oral toxicity, category 4.

Acute inhalation toxicity :

LC50 (Rat): 10.9 mg/l
Exposure time: 1 h
Test atmosphere: dust/mist
Assessment: No adverse effect has been observed in acute inhalation toxicity tests.

Acute dermal toxicity :

LD50 (Rabbit): 9,530 mg/kg

DIETHYLENE GLYCOL:

Acute oral toxicity :


LD50 (Human): Expected 1,120 mg/kg
Target Organs: Kidney

Acute inhalation toxicity :

LC50 (Rat): > 4.6 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: No adverse effect has been observed in acute inhalation toxicity tests.

Acute dermal toxicity :

LD50 (Rabbit): 13,300 mg/kg

| | |
|---|---------------------------|
|  | Page: 9 |
| | Revision Date: 05/22/2017 |
| SAFETY DATA SHEET | Print Date: 6/2/2017 |
| Zerex™ HD NITRITE FREE EXTENDED LIFE RTU Antifreeze Coolant | SDS Number: 000000248245 |
| 846437 | Version: 1.3 |

Skin corrosion/irritation

Not classified based on available information.

Components:

ETHYLENE GLYCOL:

Species: Rabbit

Result: No skin irritation

DIETHYLENE GLYCOL:

Species: Human

Result: Slight, transient irritation

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks: Unlikely to cause eye irritation or injury.

Components:

ETHYLENE GLYCOL:

Result: Slight, transient irritation

DIETHYLENE GLYCOL:

Species: Rabbit

Result: Slight, transient irritation

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Components:

ETHYLENE GLYCOL:

Test Type: Maximisation Test

Species: Guinea pig

Assessment: Does not cause skin sensitisation.

DIETHYLENE GLYCOL:

Test Type: Maximisation Test

Species: Guinea pig

Method: Directive 67/548/EEC, Annex V, B.6.

Result: Did not cause sensitisation on laboratory animals.

Germ cell mutagenicity

Not classified based on available information.

Components:

ETHYLENE GLYCOL:

Genotoxicity in vitro


: Test Type: Ames test

Test species: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Result: negative

DIETHYLENE GLYCOL:

| | |
|---|---------------------------|
|  | Page: 10 |
| | SAFETY DATA SHEET |
| | Revision Date: 05/22/2017 |
| | Print Date: 6/2/2017 |
| | SDS Number: 000000248245 |
| Zerex™ HD NITRITE FREE EXTENDED LIFE RTU Antifreeze Coolant 846437 | Version: 1.3 |

Genotoxicity in vitro : Test Type: Ames test
 Metabolic activation: with and without metabolic activation
 Method: OECD Test Guideline 471
 Result: negative
 GLP: yes

: Test species: Chinese hamster ovary cells
 Metabolic activation: with and without metabolic activation
 Method: OECD Test Guideline 479
 Result: negative
 GLP: yes

Genotoxicity in vivo : Test Type: In vivo micronucleus test
 Test species: Mouse
 Method: OECD Test Guideline 474
 Result: negative
 GLP: yes

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Components:

ETHYLENE GLYCOL:

Exposure routes: Ingestion

Target Organs: Kidney, Liver

Assessment: May cause damage to organs through prolonged or repeated exposure.

DIETHYLENE GLYCOL:

Exposure routes: Ingestion

Target Organs: Kidney

Assessment: May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Not classified based on available information.

Experience with human exposure

Components:

DIETHYLENE GLYCOL:

Liver

Further information


Product:

Remarks: No data available

Carcinogenicity:

IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed

| | | |
|---|--|---------------------------|
|  | | Page: 11 |
| SAFETY DATA SHEET | | Revision Date: 05/22/2017 |
| | | Print Date: 6/2/2017 |
| | | SDS Number: 000000248245 |
| Zerex™ HD NITRITE FREE EXTENDED LIFE RTU Antifreeze Coolant | | Version: 1.3 |
| 846437 | | |

human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

Components:

ETHYLENE GLYCOL:

Toxicity to fish : LC50 (Lepomis macrochirus (Bluegill sunfish)): 27,540 mg/l
Exposure time: 96 h
Test Type: static test

LC50 (Pimephales promelas (fathead minnow)): 8,050 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia magna (Water flea)): > 10,000 mg/l
Exposure time: 48 h
Test Type: static test


Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): 6,500 - 13,000 mg/l
End point: Growth inhibition
Exposure time: 7 Days

Toxicity to fish (Chronic toxicity) : NOEC (Pimephales promelas (fathead minnow)): 32,000 mg/l
Exposure time: 7 d

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 24,000 mg/l
Exposure time: 7 d

DIETHYLENE GLYCOL:

Toxicity to fish : LC50 (Fathead minnow (Pimephales promelas)): 75,210 mg/l
Exposure time: 96 h
Test Type: flow-through test

| | |
|---|---------------------------|
|  | Page: 12 |
| | SAFETY DATA SHEET |
| | Revision Date: 05/22/2017 |
| | Print Date: 6/2/2017 |
| | SDS Number: 000000248245 |
| Zerex™ HD NITRITE FREE EXTENDED LIFE RTU Antifreeze Coolant 846437 | Version: 1.3 |

Toxicity to daphnia and other aquatic invertebrates : LC50 (Water flea (Daphnia magna)): > 10,000 mg/l
 Exposure time: 24 h
 Test Type: static test
 Method: DIN 38412

Persistence and degradability

Components:

ETHYLENE GLYCOL:

Biodegradability : Result: Readily biodegradable.
 Biodegradation: 90 - 100 %
 Exposure time: 10 d
 Method: OECD Test Guideline 301

DIETHYLENE GLYCOL:

Biodegradability : Result: Readily biodegradable.
 Biodegradation: 70 - 80 %
 Exposure time: 28 d
 Method: OECD Test Guideline 301B

No data available

Bioaccumulative potential

Components:

ETHYLENE GLYCOL:

Bioaccumulation : Species: Crayfish (Procambarus)
 Bioconcentration factor (BCF): 0.27
 Exposure time: 61 d
 Concentration: 1000 mg/l
 Method: Flow through

Partition coefficient: n-octanol/water : log Pow: -1.36

DIETHYLENE GLYCOL:

Bioaccumulation : Species: Leuciscus idus (Golden orfe)
 Bioconcentration factor (BCF): 100

Partition coefficient: n-octanol/water : log Pow: -1.47

No data available

Mobility in soil

Components:


No data available

Other adverse effects

No data available

Product:

Additional ecological information : No data available

| | |
|---|---------------------------|
|  | Page: 13 |
| | SAFETY DATA SHEET |
| | Revision Date: 05/22/2017 |
| | Print Date: 6/2/2017 |
| | SDS Number: 000000248245 |
| | Version: 1.3 |
| Zerex™ HD NITRITE FREE EXTENDED LIFE RTU Antifreeze Coolant 846437 | |

Components:

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

- General advice : Do not dispose of waste into sewer.
 Do not contaminate ponds, waterways or ditches with chemical or used container.
 Send to a licensed waste management company.
- Dispose of in accordance with all applicable local, state and federal regulations.
- Contaminated packaging : Empty remaining contents.
 Dispose of as unused product.
 Empty containers should be taken to an approved waste handling site for recycling or disposal.
 Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

REGULATION

| ID NUMBER | PROPER SHIPPING NAME | *HAZARD CLASS | SUBSIDIARY HAZARDS | PACKING GROUP | MARINE POLLUTANT / LTD. QTY. |
|-----------|----------------------|---------------|--------------------|---------------|------------------------------|
| | | | | | |

U.S. DOT - ROAD

| |
|---------------------|
| Not dangerous goods |
|---------------------|

CFR_RAIL_C

| |
|---------------------|
| Not dangerous goods |
|---------------------|

U.S. DOT - INLAND WATERWAYS


| |
|---------------------|
| Not dangerous goods |
|---------------------|

TDG_ROAD_C

| |
|---------------------|
| Not dangerous goods |
|---------------------|

TDG_RAIL_C

| |
|---------------------|
| Not dangerous goods |
|---------------------|

| | |
|---|---------------------------|
|  | Page: 14 |
| | SAFETY DATA SHEET |
| | Revision Date: 05/22/2017 |
| | Print Date: 6/2/2017 |
| | SDS Number: 000000248245 |
| Zerex™ HD NITRITE FREE EXTENDED LIFE RTU Antifreeze Coolant | Version: 1.3 |
| 846437 | |

TDG_INWT_C

| |
|---------------------|
| Not dangerous goods |
|---------------------|

INTERNATIONAL MARITIME DANGEROUS GOODS

| |
|---------------------|
| Not dangerous goods |
|---------------------|

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

| |
|---------------------|
| Not dangerous goods |
|---------------------|

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

| |
|---------------------|
| Not dangerous goods |
|---------------------|

MX_DG

| |
|---------------------|
| Not dangerous goods |
|---------------------|

*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

| | |
|------------------|----|
| Marine pollutant | no |
|------------------|----|

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

**EPCRA - Emergency Planning and Community Right-to-Know Act
CERCLA Reportable Quantity**

| Components | CAS-No. | Component RQ (lbs) | Calculated product RQ (lbs) |
|-----------------|----------|--------------------|-----------------------------|
| ETHYLENE GLYCOL | 107-21-1 | 5000 | 10744 |


SARA 304 Extremely Hazardous Substances Reportable Quantity
This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Chronic Health Hazard
Acute Health Hazard

SARA 313

| | | |
|-----------------|----------|---------|
| ETHYLENE GLYCOL | 107-21-1 | 46.53 % |
|-----------------|----------|---------|

California Prop 65 WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive

| | | |
|---|--|---------------------------|
|  | | Page: 15 |
| SAFETY DATA SHEET | | Revision Date: 05/22/2017 |
| | | Print Date: 6/2/2017 |
| | | SDS Number: 000000248245 |
| Zerex™ HD NITRITE FREE EXTENDED LIFE RTU Antifreeze Coolant 846437 | | Version: 1.3 |

harm.
ETHYLENE GLYCOL 107-21-1

The components of this product are reported in the following inventories:

- DSL : This product contains one or several components that are not on the Canadian DSL and have annual quantity limits.
- AICS : On the inventory, or in compliance with the inventory
- ENCS : On the inventory, or in compliance with the inventory
- KECI : On the inventory, or in compliance with the inventory
- PICCS : On the inventory, or in compliance with the inventory
- IECSC : On the inventory, or in compliance with the inventory
- TSCA : On TSCA Inventory


Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

SECTION 16. OTHER INFORMATION


Further information

Revision Date: 05/22/2017

| | | | | | | | |
|--|---|--------|----|--------------|---|-----------------|---|
| <p>NFPA:</p> <div style="text-align: center;"> <p>Flammability</p>  <p>Health Instability</p> <p>Special hazard.</p> </div> | <p>HMIS III:</p> <table border="1" style="width: 100%;"> <tr> <td style="background-color: black; color: white;">HEALTH</td> <td style="text-align: center;">1*</td> </tr> <tr> <td style="background-color: black; color: white;">FLAMMABILITY</td> <td style="text-align: center;">1</td> </tr> <tr> <td style="background-color: black; color: white;">PHYSICAL HAZARD</td> <td style="text-align: center;">0</td> </tr> </table> <p>0 = not significant, 1 = Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic</p> | HEALTH | 1* | FLAMMABILITY | 1 | PHYSICAL HAZARD | 0 |
| HEALTH | 1* | | | | | | |
| FLAMMABILITY | 1 | | | | | | |
| PHYSICAL HAZARD | 0 | | | | | | |

NFPA Flammable and Combustible Liquids Classification
Combustible Liquid Class III B

Full text of H-Statements

| | | |
|---|--|---------------------------|
|  | | Page: 16 |
| SAFETY DATA SHEET | | Revision Date: 05/22/2017 |
| | | Print Date: 6/2/2017 |
| | | SDS Number: 000000248245 |
| Zerex™ HD NITRITE FREE EXTENDED LIFE RTU Antifreeze Coolant | | Version: 1.3 |
| 846437 | | |

H302 Harmful if swallowed.
H373 May cause damage to organs through prolonged or repeated exposure if swallowed.


Sources of key data used to compile the Safety Data Sheet
Valvoline internal data including own and sponsored test reports
The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists
BEI : Biological Exposure Index
CAS : Chemical Abstracts Service (Division of the American Chemical Society).
CMR : Carcinogenic, Mutagenic or Toxic for Reproduction
FG : Food grade
GHS : Globally Harmonized System of Classification and Labeling of Chemicals.
H-statement : Hazard Statement
IATA : International Air Transport Association.
IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization
ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"
IMDG : International Maritime Code for Dangerous Goods
ISO : International Organization for Standardization
logPow : octanol-water partition coefficient
LCxx : Lethal Concentration, for xx percent of test population
LDxx : Lethal Dose, for xx percent of test population.
ICxx : Inhibitory Concentration for xx of a substance
Ecxx : Effective Concentration of xx
N.O.S.: Not Otherwise Specified
OECD : Organization for Economic Co-operation and Development
OEL : Occupational Exposure Limit
P-Statement : Precautionary Statement
PBT : Persistent , Bioaccumulative and Toxic
PPE : Personal Protective Equipment
STEL : Short-term exposure limit
STOT : Specific Target Organ Toxicity
TLV : Threshold Limit Value

| | | |
|---|--|---------------------------|
|  | | Page: 17 |
| SAFETY DATA SHEET | | Revision Date: 05/22/2017 |
| | | Print Date: 6/2/2017 |
| | | SDS Number: 000000248245 |
| Zerex™ HD NITRITE FREE EXTENDED LIFE RTU Antifreeze Coolant | | Version: 1.3 |
| 846437 | | |

TWA : Time-weighted average
vPvB : Very Persistent and Very Bioaccumulative
WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act
DOT : Department of Transportation
FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act
HMIRC : Hazardous Materials Information Review Commission
HMIS : Hazardous Materials Identification System
NFPA : National Fire Protection Association
NIOSH : National Institute for Occupational Safety and Health
OSHA : Occupational Safety and Health Administration
PMRA : Health Canada Pest Management Regulatory Agency
RTK : Right to Know
WHMIS : Workplace Hazardous Materials Information System