

SAFETY DATA SHEET

Revision Date 10-Apr-2015

Version 1

1. IDENTIFICATION

Product identifier

Product Name

Gumout Jet Spray Carb and Choke Cleaner

Other means of identification

Product Code

Document

Synonyms

600951

SKU: 800002230, 800002231, 800002241

None

Gumout Carb-1-Choke

CLEANER Jet SPRAY

Recommended use of the chemical and restrictions on use

Recommended Use

Carburetor Cleaner Consumer Use

Uses advised against

All other applications

Details of the supplier of the safety data sheet

Supplier Address

Manufacturer Address

Distributor

ITW Global Brands 6925 Portwest Dr., Suite 100

Houston, TX 77024

Company Phone Number

1-855-888-1988

24 Hour Emergency Phone Number (CHEMTREC) 1-800-424-9300 or 1-703-527-3887 (U.S.)

(RMPDC) 1-877-504-9352 (U.S.)

E-mail address

SDS@itwgb.com

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

NOTE: This product is a consumer product and is labeled in accordance with the US Consumer Product Safety Commission regulations which take precedence over OSHA Hazard Communication labeling. The actual container label will not include the label elements below. The labeling below applies to industrial/professional products.

Serious eye damage/eye irritation	Category 2
Reproductive toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Flammable aerosols	Category 1
Gases under pressure	Compressed gas

Label elements

Emergency Overview

Danger

Causes serious eye irritation

Suspected of damaging fertility or the unborn child

May cause drowsiness or dizziness

May cause damage to organs through prolonged or repeated exposure

Extremely flammable aerosol

Contains gas under pressure; may explode if heated



Appearance Colorless

Physical state Liquid Flammable Aerosol

Odor Alcohol

Precautionary Statements - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Wash face, hands and any exposed skin thoroughly after handling

Wear eye/face protection

Do not breathe dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area

Do not puncture or incinerate container

Contents under pressure and can explode when exposed to heat or open flame

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

IF SWALLOWED: Rinse mouth. DO NO induce vomiting

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Precautionary Statements - Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

Do not expose to temperatures exceeding 122 °F (50 °C)

Keep away from heat, sparks, flames and other ignition sources

Keep out of reach of children

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

- Causes mild skin irritation
- May be harmful if inhaled or swallowed
- Harmful to aquatic life with long lasting effects

3. COMPOSITION/INFORMATION ON INGREDIENTS

substance(s)

Chemical Name	CAS No	Weight-%	Trade Secret
ACETONE	67-64-1	60 - 100	*
TOLUENE	108-88-3	5 - 10	*
CARBON DIOXIDE	124-38-9	5 - 10	*

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

General advice Get medical advice/attention if you feel unwell.

Eye contact IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. If eye irritation persists: Get medical

advice/attention.

Skin contact IF ON SKIN:. Wash skin with soap and water. If skin irritation persists, call a physician.

Wash contaminated clothing before reuse.

Inhalation IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing. If symptoms persist, call a physician.

Ingestion IF SWALLOWED:. Do NOT induce vomiting. Never give anything by mouth to an

unconscious person. Call a physician.

Self-protection of the first aider Use personal protective equipment as required. Avoid contact with skin, eyes or clothing.

Most important symptoms and effects, both acute and delayed

Symptoms See section 2 for more information.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Dry chemical, CO2, sand, earth, water spray or regular foam

Unsuitable extinguishing media

None.

Specific hazards arising from the chemical

Extremely flammable. Contents under pressure and can explode when exposed to heat or flames. Vapors may cause flash fire.

Explosion data

Sensitivity to Mechanical Impact

None

Sensitivity to Static Discharge

May be ignited by heat, sparks or flames.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure adequate ventilation, especially in confined areas. Avoid contact with skin, eyes and

inhalation of vapors. Use personal protective equipment as required. Remove all sources of

ignition.

Environmental precautions

Environmental precautions Do not flush into surface water or sanitary sewer system. See Section 12 for additional

ecological Information.

Methods and material for containment and cleaning up

Methods for containment

Prevent further leakage or spillage if safe to do so.

Methods for cleaning up

Ensure adequate ventilation. Soak up with inert absorbent material. Sweep up and shovel

into suitable containers for disposal.

Prevention of secondary hazards

Clean contaminated objects and areas thoroughly observing environmental regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling

Handle in accordance with good industrial hygiene and safety practice. Avoid breathing vapors or mists. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Wash contaminated clothing before reuse. Use personal protective equipment as required.

Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep containers tightly closed in a cool, well-ventilated place. Keep away from sunlight, ignition sources and other sources of heat. Do not expose to temperatures exceeding 50 °C/122 °F. Keep out of the reach of children.

Incompatible materials

Strong oxidizing agents

8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

	Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
	ACETONE	STEL: 750 ppm	TWA: 1000 ppm	IDLH: 2500 ppm
	67-64-1	TWA: 500 ppm	TVVA: 2400 mg/m ³	TWA: 250 ppm
			(vacated) TWA: 750 ppm	TWA: 590 mg/m ³
			(vacated) TWA: 1800 mg/m ³	
			(vacated) STEL: 2400 mg/m³ The	
		la di la companya di	acetone STEL does not apply to the	
			cellulose acetate fiber industry. It is	
1			in effect for all other sectors	
			(vacated) STEL: 1000 ppm	
	TOLUENE	TWA: 20 ppm	TWA: 200 ppm	IDLH: 500 ppm
	108-88-3		(vacated) TWA: 100 ppm	TWA: 100 ppm
			(vacated) TWA: 375 mg/m ³	TWA: 375 mg/m ³
			(vacated) STEL: 150 ppm	STEL: 150 ppm
1 -	•		(vacated) STEL: 560 mg/m ³	STEL: 560 mg/m ³
			Ceiling: 300 ppm	
	CARBON DIOXIDE	STEL: 30000 ppm	TWA: 5000 ppm	IDLH: 40000 ppm
	124-38-9	TWA: 5000 ppm	TWA: 9000 mg/m ³	TWA: 5000 ppm
			(vacated) TWA: 10000 ppm	TWA: 9000 mg/m ³
] .			(vacated) TWA: 18000 mg/m³	STEL: 30000 ppm
1			(vacated) STEL: 30000 ppm	STEL: 54000 mg/m ³
			(vacated) STEL: 54000 mg/m³	

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Appropriate engineering controls

Engineering Controls

Showers

Eyewash stations Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear safety glasses with side shields (or goggles).

Skin and body protection

Wear protective gloves and protective clothing.

Respiratory protection

Use NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as

appropriate.

General Hygiene Considerations

Handle in accordance with good industrial hygiene and safety practice. Regular cleaning of

Remarks • Method

Tag Closed Cup

equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state

Liquid; Flammable Aerosol

Appearance Odor

Colorless

Alcohol

Odor threshold

No information available

Property

Values No information available

Melting point / freezing point Boiling point / boiling range

No information available

Flash point

56 °C / 133 °F -20 °C / -4 °F

Evaporation rate

No information available

Flammability (solid, gas) Flammability Limit in Air No information available

Upper flammability limit:

2.6 12.8 185

Lower flammability limit: Vapor pressure

No information available

Vapor density Relative density

0.798 Miscible in water

Water solubility Solubility in other solvents

No information available No information available

Partition coefficient Autoignition temperature 465 °C / 869 °F

Decomposition temperature Kinematic viscosity **Dynamic viscosity Explosive properties**

Oxidizing properties

No information available No information available No information available No information available No information available

Other Information

Softening point Molecular weight VOC Content (%)

No information available No information available

9.8%

Density **Bulk density** 0.797 g/cm3 No information available

10. STABILITY AND REACTIVITY

Reactivity

Stable under normal use

Chemical stability

Stable under recommended storage conditions

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Keep away from all heat sources, open flames and other sources of ignition.

Incompatible materials

Strong oxidizing agents

Hazardous Decomposition Products

Carbon oxides

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation May cause irritation of respiratory tract. May cause central nervous system depression with

nausea, headache, dizziness, vomiting, and incoordination. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Harmful by

inhalation.

Eye contact Contact with eyes may cause irritation. May cause redness and tearing of the eyes.

Skin contact May cause skin irritation and/or dermatitis.

Ingestion Ingestion may cause irritation to mucous membranes. Potential for aspiration if swallowed.

Aspiration may cause pulmonary edema and pneumonitis. May be fatal if swallowed.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50	
ACETONE 67-64-1	= 5800 mg/kg (Rat)	-	= 50100 mg/m³(Rat)8 h	
TOLUENE 108-88-3	= 2600 mg/kg (Rat)	= 12000 mg/kg (Rabbit)	= 12.5 mg/L (Rat)4 h	

Information on toxicological effects

Symptoms

No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.
Germ cell mutagenicity No information available.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
TOLUENE		Group 3	•	-
108-88-3				

IARC (International Agency for Research on Cancer)

Not classifiable as a human carcinogen

Chronic toxicity May cause adverse liver effects.

Target Organ Effects Central nervous system, Central Vascular System (CVS), Eyes, kidney, Liver, Respiratory

system, Skin.

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 5526 mg/kg
ATEmix (dermal) 122449 mg/kg
ATEmix (inhalation-dust/mist) 62 mg/l

12 EGOLOGICAL INFORMATION

Ecotoxicity

Chemical Name	Algae/aquatic plants	Fish	Crustacea
ACETONE		4.74 - 6.33: 96 h Oncorhynchus	10294 - 17704: 48 h Daphnia
67-64-1		mykiss mL/L LC50 6210 - 8120: 96	magna mg/L EC50 Static 12600 -
		h Pimephales promelas mg/L LC50	12700: 48 h Daphnia magna mg/L
		static 8300: 96 h Lepomis	EC50
		macrochirus mg/L LC50	

TOLUENE	433: 96 h Pseudokirchneriella	15.22 - 19.05: 96 h Pimephales	5.46 - 9.83: 48 h Daphnia magna
108-88-3	subcapitata mg/L EC50 12.5: 72 h	promelas mg/L LC50 flow-through	mg/L EC50 Static 11.5: 48 h
	Pseudokirchneriella subcapitata	12.6: 96 h Pimephales promelas	Daphnia magna mg/L EC50
4	mg/L EC50 static	mg/L LC50 static 5.89 - 7.81: 96 h	
		Oncorhynchus mykiss mg/L LC50	
		flow-through 14.1 - 17.16: 96 h	
		Oncorhynchus mykiss mg/L LC50	
		static 5.8: 96 h Oncorhynchus	
		mykiss mg/L LC50 semi-static 11.0 -	
		15.0: 96 h Lepomis macrochirus	
		mg/L LC50 static 54: 96 h Oryzias	
	÷.	latipes mg/L LC50 static 28.2: 96 h	
		Poecilia reticulata mg/L LC50	
		semi-static 50.87 - 70.34: 96 h	
		Poecilia reticulata mg/L LC50 static	

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Mobility

Disperses in water.

Chemical Name	<u> </u>	Partition coeff	icient	
ACETONE 67-64-1		-0.24		
TOLUENE 108-88-3		2.65		

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes

Recover or recycle if possible. Disposal should be in accordance with applicable regional,

national and local laws and regulations.

Contaminated packaging

Do not reuse container.

US EPA Waste Number

U002 U220

Chemical Name	RCRA	1 1	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
ACETONE 67-64-1	-		Included in waste stream: F039	-	U002
TOLUENE 108-88-3	U220		Included in waste streams: F005, F024, F025, F039,	-	U220
			K015, K036, K037, K149, K151		

Chemical Name	RCRA - Halogenated Organic Compounds	RCRA - P Series Wastes	RCRA - F Series Wastes	RCRA - K Series Wastes
TOLUENE 108-88-3			Toxic waste waste number F025 Waste description: Condensed light ends, spent filters and filter aids, and spent desiccant wastes from the production of certain chlorinated aliphatic hydrocarbons, by free radical catalyzed processes. These chlorinated aliphatic	

	1.0	and the second of the second o	<u> The same of the </u>
		hydrocarbons are those	
		having carbon chain lengths	
		ranging from one to and	
		including five, with varying	
		 amounts and positions of	
		chlorine substitution.	

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
ACETONE 67-64-1	Ignitable
TOLUENE	Toxic
108-88-3	lgnitable

14. TRANSPORT INFORMATION

DOT

UN/ID no

UN 1950

Proper shipping name:

Aerosols, Consumer Commodity, Limited Quantity (LQ)

2.1

IATA

UN/ID no

Hazard Class

UN 1950

Proper shipping name:

Aerosols, Consumer commodity, Limited Quantity (LQ)

Hazard Class

2.1

IMDG

UN/ID no

UN 1950

Proper shipping name:

Aerosols, Consumer Commodity, Limited Quantity (LQ)

Hazard Class

2.1

15 REGULATORY INFORMATION

International Inventories

TSCA Complies Complies **DSL/NDSL EINECS/ELINCS** Complies Not determined **ENCS** Not determined **IECSC** Not determined KECL **PICCS** Not determined Not determined **AICS**

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
TOLUENE - 108-88-3	1.0

SARA 311/312 Hazard Categories

No Acute health hazard **Chronic Health Hazard** No Fire hazard No Sudden release of pressure hazard No Reactive Hazard No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name CWA - Reportab Quantities		CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances	
TOLUENE	1000 lb	X	X	X	
108-88-3					

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
ACETONE	5000 lb	· -	RQ 5000 lb final RQ
67-64-1			RQ 2270 kg final RQ
TOLUENE	1 lb	-	RQ 1 lb final RQ
108-88-3			RQ 0.454 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

Г	Chemical Name		California Proposition 65	
	TOLUENE - 108-88-3		Developmental	
			Female Reproductive	

U.S. State Right-to-Know Regulations

Chemical Name	· · · · · · · · · · · · · · · · · · ·	Ne	w Jersey	Massachusetts	Pennsylvania
ACETONE 67-64-1			X	X	X
TOLUENE 108-88-3	1.		X	X	X
CARBON DIOXIDE 124-38-9			X	X	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

WHMIS Hazard Class

Non-controlled

Instability 0 Flammability 3 NFPA_ Health hazards 2

Health hazards 2 Physical hazards 1 Personal protection B Flammability 3 HMIS_

NFPA (National Fire Protection Association) HMIS (Hazardous Material Information System)

Revision Date

10-Apr-2015

Revision Note

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet