Product Name: ADVANCE AUTO PARTS MULTI-PURPOSE LUBRICANT MPL

Advance Auto parts multi purpose Lubricant mpl

MSDS No.: A10005

See signs and symptoms below

Signs and Symptoms:

10/10/2017

108-67-8 Mesitylene 1.0 - 5.0 N/A N/A 64742-52-5 Naphthenic Petroleum Distillate 30.0 - 60.0 5 mg/m3 5 mg/m3	I. Basic Inf	formation:							
City, ST Zip: INDIAN TRAIL, NC 28079 Emergency Contact: Rocky Mountain Poision Control Center Emergency Telephone Number: 303-623-5716 Contact: Robert Geer Information Telephone Number: 704-688-3430 Last Update: 10/25/2006 Chemical State:	Manufacturer	: RADIATOR SPECIALTY COMPANY				NF	PA A		
Carly St 2pt in INDIAN I RAIL, NC 28079 Emergency Contact: Rocky Mountain Poision Control Center Emergency Telephone Number: 303-623-5716 Contact: Robert Geer Information Telephone Number: 704-688-3430 Last Update: 10/25/2006 Chemical State:	Address: 600	RADIATOR ROAD				. 4.1		at de-	
Emergency Contact: Rocky Mountain Poision Control Center Emergency Telephone Number: 303-623-5716 Contact: Robert Geer Information Telephone Number: 704-688-3430 Last Update: 10/25/2006 Chemical State:	City, ST Zip:	INDIAN TRAIL, NC 28079				He			
Contact: Robert Geer	Emergency C	ontact: Rocky Mountain Poision Control	Center						
Contact: Robert Geer Information Telephone Number: 704-688-3430	Emergency Te	elephone Number: 303-623-5716					Special	y	
Chemical State:	Contact: Rob	ert Geer					C KOOLGI		
Chemical Type: Pure Mixture C Pers. Protection	Information To	elephone Number: 704-688-3430	Tara II.ai.,				Health		
Pure Mixture C Pers. Protection	Last Update:	10/25/2006							
Pure Mixture C Pers. Protection	Chemical Stat	te: X Liquid Gas	Solid			0	Reactivity	,]	
Trade Secret	- 11		••••••••••••••••••••••••••••••••••••••			С	Pers. Pro	tection	
Trade Secret							, —	•	
Trade Secret	II. Ingredie	ents:					W. 11.		
CAS No. Chemical Name			o gran and some developing the fi		o epiparat (1998)	se djir otiskiji)		and the state of t	e a unite de la
CAS No. Chemical Name % Range NTP SUB Z 313 OSHA ACGIH TLV Limits			E	HS IA	RC	SARA			
25-63-6	CACN-	Chamias I Nam							
111-76-2 2-Butoxy-1-Ethanol 1.0 - 5.0 X 50 ppm 25 ppm 3052-41-3 Aliphatic Hydrocarbon - Non 30.0 - 60.0 100 ppm 100 ppm NJ, Pa. Exempt. 124-38-9 Carbon dioxide 1.0 - 5.0 N/AV 5000 ppm 108-67-8 Mesitylene 1.0 - 5.0 N/A				NTP	SUB Z	<u> </u>			Limits
Aliphatic Hydrocarbon - Non 30.0 - 60.0 100 ppm 100 ppm NJ, Pa. Exempt. 124-38-9 Carbon dioxide 1.0 - 5.0 N/AV 5000 ppm 108-67-8 Mesitylene 1.0 - 5.0 N/A		The state of the s							
Exempt. 124-38-9 Carbon dioxide						X			NI D-
1.0 - 5.0	UUUZ-4 1-3		0.00 - 00.0				тоо ррт	100 ppm	NJ, Pa. H
Sarata S	124-38-9	Carbon dioxide					N/AV .	5000 ppm	
1330-20-7 Xylene (mixed isomers)	108-67-8	Mesitylene	1.0 - 5.0				N/A	N/A	
Hazardous Identification: Hazardous Identification:	64742-52-5						-		
Hazard Category: X Acute Chronic X Fire X Pressure Reactive Hazardous Identification Information: Danger: Flammable. Harmful or fatal if swallowed. Eye and skin irritant. Contents under pressure. Level 3 Aerosol IV. First Aid Measures: Route(s) of Entry: Absorption, Inhalation, and Ingestion.	1330-20-7	Xylene (mixed isomers)	1.0 - 5.0	<u>.: </u>		Х	100 ppm (T	100 ppm (TPA & NJ
Acute Chronic X Fire X Pressure Reactive Reactive Reactive Azzardous Identification Information: Danger: Flammable. Harmful or fatal if swallowed. Eye and skin irritant. Contents under pressure. Level 3 Aerosol IV. First Aid Measures: Route(s) of Entry: Absorption, Inhalation, and Ingestion.	The rest of the state of the state of					de d		1	
Hazardous Identification Information: Danger: Flammable. Harmful or fatal if swallowed. Eye and skin irritant. Contents under pressure. Level 3 Aerosol IV. First Aid Measures: Route(s) of Entry: Absorption, Inhalation, and Ingestion.	Hazard Catego	ory:							
Danger: Flammable. Harmful or fatal if swallowed. Eye and skin irritant. Contents under pressure. Level 3 Aerosol IV. First Aid Measures: Route(s) of Entry: Absorption, Inhalation, and Ingestion.	X Acute	Chronic	X Fire			X Pres	sure		Reactive
IV. First Aid Measures: Route(s) of Entry: Absorption, Inhalation, and Ingestion.	Danger: Fl	lammable. Harmful or fatal if swallow	ed. Eye and skin	irritant. Co	intents un	der pre	ssure.		
Route(s) of Entry: Absorption, Inhalation, and Ingestion.			en de samen de versament en ma			grayean	Topisew Adelects	ing the second state	An ALSMARK
Absorption, Inhalation, and Ingestion.	IV. Tirst Al	u vieasures:		Ye Nayo					
	Route(s) of En	itry:							
	Absorption,	, Inhalation, and Ingestion.							

Product Name: ADVANCE AUTO PARTS MULTI-PURPOSE LUBRICANT MPL (UPC: 762164500757) (AAP SKU: 7070070)

MSDS No.: A10005

Eye Contact: Irritant. Prolonged contact may cause conjunctivitis. Skin Contact: Irritant. Defatting of tissue, dermatitis may occur.

Inhalation: Irritant to mucous membranes. Repeated exposure may cause narcosis, dizziness, respiratory or lung irritation.

Ingestion: HARMFUL OR FATAL IF SWALLOWED. May cause burns to mouth, throat & stomach.

Medical Conditions Generally Aggravated by Exposure:

None Known

Emergency and First Aid Procedures:

Eve Contact: Flush eyes with clean water for 15 minutes while lifting eyelids. Get prompt medical attention.

Skin Contact: Wash with soap and water thoroughly. If adverse effects persist, get prompt medical attention. Launder contaminated clothing before reuse.

Inhalation: Remove to fresh air. If breathing becomes difficult give oxygen and get prompt medical attention. If breathing stops, give artificial respiration and get prompt medical attention.

Ingestion: DO NOT INDUCE VOMITING! Call Poison Control Center, physician, or hospital emergency room immediately. Aspiration of vomitus into the lungs can cause pneumonitis, which can be fatal.

Other Health Warnings:

Vomiting and subsequent aspiration into the lungs may lead to chemical pneumonia and pulmonary edema which is a potentially fatal condition.

V. Fire Fighting Measures:

Flash Point: 132F

Lower Explosive Limit: 0.7%

Upper Explosive Limit: 5%

F.P. Method: TCC

Fire Extinguishing Media: Water Fog, Foam, Carbon Dioxide, Dry Chemical

Special Fire Fighting Procedures:

Wear self-contained positive pressure breathing apparatus and protective clothes. Cool containers with a water fog. Do not use forced water stream as this could cause the fire to spread. Use equipment or shielding to protect personnel against venting, rupturing, or bursting containers.

Unusual Fire and Explosion:

Contents under pressure. At elevated temperatures, container may vent, rupture, or burst violently.

VI. Accidental Release Measures:

Steps to be Taken in Case Material is Released or Spilled:

Eliminate all ignition sources. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Dike or contain spill and absorb with inert materials (sand, sawdust, absorbent sweeping compounds, rags, etc). Place contaminated material into an approved chemical waste container. Where possible, vacuum spilled liquid using an explosion proof vacuum to recover material. Prevent run-off to sewers, streams, or other bodies of water. If run-off occurs, notify proper authorities as required that a spill has occured.

VII. Handling and Storage:

Precautions to be Taken:

Product Name: ADVANCE AUTO PARTS MULTI-PURPOSE LUBRICANT MPL (UPC: 762164500757) (AAP SKU: 7070070)

MSDS No.: A10005

Use with adequate ventilation and proper protective equipment.

Do not use or store near fire, sparks, or open flame. Do not puncture or incinerate container. Exposure to temperatures above 120° may cause container to vent, rupture, or burst.

Other Precautions:

Do not used in confined area without proper ventilation. Contact lenses may cause further damage in case of splash into eye. KEEP AWAY FROM CHILDREN AND ANIMALS! Danger: Flammable.

VIII. Exposure Controls/Personal Protection:

Ventilation Requirements:

Use with adequate ventilation. If TLV is exceeded, wear NIOSH approved respirator.

Personal Protective Equipment:

See Section 2 for applicable exposure limits. For prolonged exposure wear protective safety glasses, gloves, and apron.

IX. Physical and Chemical Properties:

Boiling Point: 320 F

Melting Point: N/A

Evaporation Rate (Butyl Acetate = 1): N/A

Vapor Pressure (mm Hg.): N/A

Specific Gravity (H20 = 1): 0.80500

Vapor Density (AIR = 1): N/A

Solubility In Water: Insoluble

Appearance and Odor: Clear light yellow with sweet vanilla odor

Other Information: VOC Content: 44.0 % (Carb and OTC Compliant)

X. Stability and Reactivity:

Stability:

Product is stable

Incompatibility (Materials to Avoid):

Avoid contact with strong oxidizers

Decomposition/By Products:

Normal products of combustion, smoke, carbon dioxide, carbon monoxide, and sulfur trioxides.

Hazardous Polymerization:

Will not occur

XI. Toxicological Information:

N/D

XII. Ecological Information:

N/D

Product Name: ADVANCE AUTO PARTS MULTI-PURPOSE LUBRICANT MPL (UPC: 762164500757) (AAP SKU: 7070070)

MSDS No.: A10005

XIII. Disposal Considerations:

DISPOSAL: This container may be recycled in aerosol recycling centers when empty. Before offering for recycling, empty the can by using the product according to the label. DO NOT PUNCTURE! If recycling is not available, wrap the container and discard in the trash. Dispose of unused product in accordance with all local, state government and federal laws and regulations.

XIV. Transport Information:

DOT Hazard Class: ORM-D

Shipping Name: Consumer Commodity

The DOT description is provided to assist in the proper shipping classification of this product and may not be suitable for international and air shipping purposes.

ICAO/IATA (US)

Shipping Name: Aerosols

Class: 2.1

UN number: UN1950

International:

ICAO/IATA

Shipping Name: Aerosols

Class: 2.1

UN number: UN1950

IMDG

Shipping Name: Aerosols

Class: 2.1

UN number: UN1950

XV. Regulatory Information:

See Section 2 for SARA Reportable Chemicals.

USA TSCA: All components of this material are either exempt or listed on the US TSCA Inventory.

Warning: This product contains a chemical(s) known to the State of California to cause cancer or birth defects or other reproductive harm.

XVI. Other Information:

Do not used in confined area without proper ventilation. Contact lenses may cause further damage in case of splash into eye. KEEP AWAY FROM CHILDREN AND ANIMALS!

While Radiator Specialty Company believes this data is accurate as of the revision date, we make no warranty with respect to the data and we expressly disclaim all liability for reliance thereon. The data is offered soley for information, investigation, and verification. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this MSDS. The user is repsonsible for full compliance.

Product Name: ADVANCE AUTO PARTS BRAKE PARTS CLEANER (UPC: 762164530037) (SKU: 7040071)

MSDS No.: A5000

I. Basic Information:				
Manufacturer: RADIATOR SPECIALTY COMPANY			NFPA	anda an Talifa an tara. Na kana an
Address: 600 RADIATOR ROAD				
City, ST Zip: INDIAN TRAIL, NC 28079			Health	Reactivity 0
Emergency Contact: Rocky Mountain Poision Contro	ol Center			
Emergency Telephone Number: 303-623-5716			Specja	
Contact: Robert Geer				
Information Telephone Number: 704-688-3430		•	[52] [Baa(Ba	
Last Update: 10/23/2006 Chemical State: X Liquid Gas	☐ Solid		0 Reactiv	ide (a la
Chemical Type: X Pure Mixture	. <u>—</u> 		H Pers. P	rotection
II. Ingredients:			, and the second	
Trade Secret CAS No. Chemical Name	EHS % Range	IARC	SARA 313 OSHA Z PEL	ACGIH Other TLV Limits
124-38-9 Carbon dioxide	1-3	.: **	N/AV	5000 ppm
127-18-4 Tetrachloroethylene	90-100	X X	X 25 ppm	25 ppm
III. Hazardous Identification:				
Hazard Category:				
X Acute X Chronic	Fire		X Pressure	Reactive
Hazardous Identification Information: Danger: Harmful or Fatal if Swallowed. Vapor	harmful. Eye and Sk	n Irritant. Conter	nts Under Pressure	
Level 1 Aerosol				- 11
IV. First Aid Measures:				
Route(s) of Entry:				

Health Hazards (Acute and Chronic):

Affects of overexposure are:

Acute: Liquid splashed on eyes and skin can result in discomfort, pain and irritation. Inhalation can cause irritation of the respiratory tract, dizziness, nausea, headache, loss of coordination and equilibrium, unconsciousness and even death in confined or poorly ventilated areas. Ingestion may result in irritation of the mouth and GI tract.

Prolonged exposure above the OSHA permissible exposure limit may complicate existing liver and kidney diseases.

Signs and Symptoms:

Eye Contace: Irritant. Prolonged contact may cause conjunctivitis. Skin Contact: Irritant. Defatting of tissue, dermatitis may occur.

Inhalation: Irritant to mucous membranes. Repeated exposure may cause narcosis...

Ingestion: HARMFUL OR FATAL IF SWALLOWED. May cause burns to mouth, throat & stomach.

MSDS - Material Safety Data Sheet Product Name: ADVANCE AUTO PARTS BRAKE PARTS CLEANER (UPC: 762164530037) (SKU: 7040071)

MSDS No.: A5000

Medical Conditions Generally Aggravated by Exposure:

May complicate existing liver and kidney diseases.

Emergency and First Aid Procedures:

Eye Contact: Flush eyes with clean water for 15 minutes while lifting eyelids. Get prompt medical attention.

Skin Contact: Wash with soap and water thoroughly. If adverse effects persist, get prompt medical attention. Launder contaminated clothing before reuse.

Inhalation: Remove to fresh air. If breathing becomes difficult give oxygen and get prompt medical attention. If breathing stops, give artificial respiration and get prompt medical attention.

Ingestion: DO NOT INDUCE VOMITING! Call Poison Control Center, physician, or hospital emergency room immediately. Aspiration of vomitus into the lungs can cause pneumonitis, which can be fatal. Do not administer adrenaline or other sympathommietic drugs to persons overexposed to Perchloroethylene.

Other Health Warnings:

Vomiting and subsequent aspiration into the lungs may lead to chemical pneumonia and pulmonary edema which is a potentially fatal condition.

V. Fire Fighting Measures:

Flash Point: None

Lower Explosive Limit:

Upper Explosive Limit:

F.P. Method: N/A

Fire Extinguishing Media: Water Fog, Foam, Carbon Dioxide, Dry Chemical

Special Fire Fighting Procedures:

Wear self-contained positive pressure breathing apparatus and protective clothes. Cool containers with a water fog. Use shield to protect from venting, rupturing, and venting containers.

Unusual Fire and Explosion:

Contents under pressure. May explode when heated. Vapors of this product may present a future health hazard in poorly ventilated areas. May liberate corrosive hydrochloric acid or toxic phosgene fumes.

VI. Accidental Release Measures:

Steps to be Taken in Case Material is Released or Spilled:

Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Dike or contain spill and absorb with inert materials (sand, sawdust, absorbent sweeping compounds, rags, etc). Shovel up and place contaminated material into an approved chemical waste container. Prevent run-off to sewers, streams, or other bodies of water. If run-off occurs, notify proper authorities as required that a spill has occured.

VII. Handling and Storage:

Precautions to be Taken:

Handling: Use with adequate ventilation and proper protective equipment.

Do not use or store near fire, sparks, or flame. Do not puncture or incinerate container. Exposure to temperatures above 120° may cause container to vent, rupture, or burst.

Other Precautions:

Vapors are heavier that air and will collect in low areas. This material or its vapors when in contact with flames, hot glowing surfaces or electric arcs can decompose to form hydrogen chloride gas and possible traces of phosgene. Avoid contamination with water supplies.

MSDS - Material Safety Data Sheet Product Name: ADVANCE AUTO PARTS BRAKE PARTS CLEANER (UPC: 762164530037) (SKU: 7040071)

MSDS No.: A5000

VIII. Exposure Controls/Personal Protection:

Ventilation Requirements:

See Section 2 for applicable exposure limits. Maintain adequate ventilation.

Avoid breathing vapors. In restricted areas, use respirator with approved chemical filters designed to remove vapor. In confined areas, use approved air line type respirator or hood. A self-contained breathing apparatus is required for vapor concentrations above TLV limit

Personal Protective Equipment:

See Section 2 for applicable exposure limits. For prolonged exposure wear protective safety glasses, gloves, and apron.

IX. Physical and Chemical Properties:

Boiling Point: 250°F

Melting Point: N/A

Evaporation Rate (Butyl Acetate = 1): 1.66

Vapor Pressure (mm Hg.): 13

Specific Gravity (H20 = 1): 1.61000

Vapor Density (AIR = 1): 5.7

Solubility In Water: Insoluble

Appearance and Odor: Colorless volatile liquid with ether-like odor

Other Information: VOC Content: 0% (Carb and OTC Compliant)

X. Stability and Reactivity:

Stability:

Stable

Incompatibility (Materials to Avoid):

Water, alkalies, powdered metals (esp. zinc) aluminum and amines. Sparks, flames, electric arcs, and or hot metal surfaces.

Decomposition/By Products:

In the presence of water: hydrochloric acid. Ignition sources and hot metals surfaces: phosgene and chlorine. Flames, welding, and high temperatures induce decomposition.

Hazardous Polymerization:

Will not occur.

XI. Toxicological Information:

ACUTE INHALATION LC50: (rats) 5040 ppm for 8 hours. Moderately toxic. ACUTE DERMAL LD50: (rabbit) > 3228 mg/kg. Slight to very low toxicity SKIN IRRITATION: Mildly irritating.

EYE IRRITATION: Mildly irritating.

ACUTE ORAL LD50: (rats) 2629 mg/kg. Moderalely toxic.

XII. Ecological Information:

Toxic to aquatic life

XIII. Disposal Considerations:

Product Name: ADVANCE AUTO PARTS BRAKE PARTS CLEANER (UPC: 762164530037) (SKU: 7040071)

MSDS No.: A5000

DISPOSAL: This container may be recycled in aerosol recycling centers when empty. Before offering for recycling, empty the can by using the product according to the label. DO NOT PUNCTURE! If recycling is not available, wrap the container and discard in the trash. Dispose of unused product in accordance with all local, state government and federal laws and regulations.

XIV. Transport Information:

DOT Hazard Class: ORM-D

Shipping Name: Consumer Commodity

The DOT description is provided to assist in the proper shipping classification of this product and may not be suitable for international and air shipping purposes.

ICAO/IATA (US)

Shipping Name: Aerosols

Class: 2.1

UN number: UN1950

International:

ICAO/IATA

Shipping Name: Aerosols

Class: 2.1

UN number: UN1950

IMDG

Shipping Name: Aerosols

Class: 2.1

UN number: UN1950

XV. Regulatory Information:

USA TSCA: All chemicals used are listed on the TSCA Inventory.

CERCLA RQ: 1000 lbs

SARA 302: Not listed as a Extremely Hazardous Substance

SARA 311/312 HAZARD CLASS: Acute, Chronic

SARA 313 REPORTABLE: See Section 2 for SARA Reportable Chemicals.

PROPOSITION 65 WARNING: This product product contains a chemical known to the State of California to cause Cancer.

NEW JERSEY RIGHT-TO-KNOW: Tetrachloroethylene

XVI. Other Information:

Do not used in confined area without proper ventilation. Contact lenses may cause further damage in case of splash into eye. KEEP AWAY FROM CHILDREN.

While Advance Auto Parts believes this data is accurate as of the revision date, we make no warranty with respect to the data and we expressly disclaim all liability for reliance thereon. The data is offered soley for information, investigation, and verification. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this MSDS. The user is repsonsible for full compliance.