



SAFETY DATA SHEET

Grease Boat Trailer
-E- MARINE Sta-Lube
multi-purpose

1. Identification

Product identifier Marine Boat Trailer and 4x4 Wheel Bearing Grease

Other means of identification

Product code SL3120, SL3121, SL3125, SL3127, SL3184

Recommended use Bearing grease

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufactured or sold by:

Company name CRC Industries, Inc.
Address 885 Louis Dr.
Warminster, PA 18974 US

Telephone

General Information 215-674-4300

Technical Assistance 800-521-3168

Customer Service 800-272-4620

24-Hour Emergency (CHEMTREC) 800-424-9300 (US)
703-527-3887 (International)

Website www.crcindustries.com

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Serious eye damage/eye irritation Category 2A
Sensitization, skin Category 1

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Warning

Hazard statement May cause an allergic skin reaction. Causes serious eye irritation.

Precautionary statement

Prevention

Avoid breathing vapors. Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves. Wear eye/face protection.

Response

If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical attention. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. Wash contaminated clothing before reuse.

Storage

Store away from incompatible materials.

Disposal

Dispose of contents/container in accordance with local/regional/national regulations.

Hazard(s) not otherwise classified (HNOC) None known.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Distillates (petroleum), hydrotreated heavy naphthenic		64742-52-5	60 - 70

Chemical name	Common name and synonyms	CAS number	%
Distillates (petroleum), solvent-dewaxed heavy paraffinic		64742-65-0	20 - 30
White mineral oil		8042-47-5	5 - 10
Benzoic Acid		65-85-0	1 - 3
Calcium bis(dinonylnaphthalenesulphonate)		57855-77-3	1 - 3
Distillates (petroleum), Hydrotreated Light Naphthenic		64742-53-6	1 - 3

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Move to fresh air. Provide oxygen or artificial respiration if needed. Call a physician if symptoms develop or persist.
Skin contact	Immediately flush with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Never give anything by mouth to a victim who is unconscious or is having convulsions. Do not induce vomiting without advice from poison control center. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause an allergic skin reaction. Dermatitis. Rash.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Unsuitable extinguishing media	None known.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
General fire hazards	No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	<p>The product is immiscible with water and will spread on the water surface.</p> <p>Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.</p> <p>Small Spills: Sweep up or vacuum up spillage and collect in suitable container for disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.</p> <p>Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.</p>

Environmental precautions Avoid discharge into drains, water courses or onto the ground. Contact local authorities in case of spillage to drain/aquatic environment.

7. Handling and storage

Precautions for safe handling Provide adequate ventilation. Avoid breathing vapor. Avoid contact with eyes, skin, and clothing. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. For product usage instructions, please see the product label.

Conditions for safe storage, including any incompatibilities Store in a cool, dry place out of direct sunlight. Keep container tightly closed. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	PEL	5 mg/m ³	Mist.
		2000 mg/m ³ 500 ppm	
Distillates (petroleum), Hydrotreated Light Naphthenic (CAS 64742-53-6)	PEL	5 mg/m ³	Mist.
		2000 mg/m ³ 500 ppm	
Distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0)	PEL	5 mg/m ³	Mist.
		2000 mg/m ³ 500 ppm	
White mineral oil (CAS 8042-47-5)	PEL	5 mg/m ³	Mist.

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	TWA	5 mg/m ³	Inhalable fraction.
Distillates (petroleum), Hydrotreated Light Naphthenic (CAS 64742-53-6)	TWA	5 mg/m ³	Inhalable fraction.
Distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0)	TWA	5 mg/m ³	Inhalable fraction.
White mineral oil (CAS 8042-47-5)	TWA	5 mg/m ³	Inhalable fraction.

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	Ceiling	1800 mg/m ³	
	STEL	10 mg/m ³	Mist.
	TWA	5 mg/m ³	Mist.
Distillates (petroleum), Hydrotreated Light Naphthenic (CAS 64742-53-6)	Ceiling	1800 mg/m ³	
	STEL	10 mg/m ³	Mist.

US. NIOSH: Pocket Guide to Chemical Hazards Components

Components	Type	Value	Form
Distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0)	Ceiling	1800 mg/m3	
	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
White mineral oil (CAS 8042-47-5)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Wear safety glasses with side shields (or goggles).

Skin protection**Hand protection**

Wear protective gloves such as: Latex. Rubber.

Other

Wear appropriate chemical resistant clothing.

Respiratory protection

If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to determine actual employee exposure levels.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties**Appearance****Physical state**

Solid.

Form

Grease.

Color

Blue.

Odor

Mild petroleum.

Odor threshold

Not available.

pH

Not available.

Melting point/freezing point

Not available.

Initial boiling point and boiling range

450 °F (232.2 °C) estimated

Flash point

> 450 °F (> 232.2 °C) Cleveland Open Cup

Evaporation rate

Slow.

Flammability (solid, gas)

Not available.

Upper/lower flammability or explosive limits**Flammability limit - lower (%)**

Not available.

Flammability limit - upper (%)

Not available.

Vapor pressure

Not available.

Vapor density

Not available.

Relative density

0.9

Solubility (water)

Insoluble.

Partition coefficient (n-octanol/water)

Not available.

Material name: Marine Boat Trailer and 4x4 Wheel Bearing Grease

SL3120, SL3121, SL3125, SL3127, SL3184 Version #: 02 Revision date: 08-20-2015 Issue date: 07-30-2015

SDS US

4 / 8

Auto-ignition temperature	500 °F (260 °C) estimated
Decomposition temperature	Not available.
Viscosity (kinematic)	> 21 mm ² /s (104 °F (40 °C))
Percent volatile	Not available.

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	Carbon oxides. Sulfur oxides. Metal oxides.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Prolonged inhalation may be harmful.
Skin contact	May cause an allergic skin reaction.
Eye contact	Causes serious eye irritation.
Ingestion	Can cause stomach ache and vomiting.
Symptoms related to the physical, chemical and toxicological characteristics	Prolonged or excessive inhalation may cause respiratory tract irritation. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause an allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

Acute toxicity	May cause an allergic skin reaction. Expected to be a low hazard for usual industrial or commercial handling by trained personnel.
----------------	--

Product	Species	Test Results
Marine Boat Trailer and 4x4 Wheel Bearing Grease		
Acute		
Dermal		
LD50	Rabbit	2604 mg/kg estimated
Inhalation		
LC50	Rat	100 mg/l, 4 hours estimated
Oral		
LD50	Rat	115472.9 mg/kg Acute Toxicity Estimate

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.
Serious eye damage/eye irritation	Causes serious eye irritation.
Respiratory sensitization	Not a respiratory sensitizer.
Skin sensitization	May cause an allergic skin reaction.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity	Based on available data, the classification criteria are not met.

IARC Monographs. Overall Evaluation of Carcinogenicity

White mineral oil (CAS 8042-47-5)

3 Not classifiable as to carcinogenicity to humans.

US. National Toxicology Program (NTP) Report on Carcinogens

Not available.

Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.
Specific target organ toxicity - single exposure	Not classified.

Specific target organ toxicity - repeated exposure Not classified.
Aspiration hazard Not an aspiration hazard.
Chronic effects Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Product	Species		Test Results
Marine Boat Trailer and 4x4 Wheel Bearing Grease			
Aquatic			
Crustacea	EC50	Daphnia	1638.796 mg/l, 48 hours estimated
Fish	LC50	Fish	5604.2324 mg/l, 96 hours estimated

Components	Species		Test Results
Benzoic Acid (CAS 65-85-0)			
Aquatic			
Fish	LC50	Western mosquitofish (<i>Gambusia affinis</i>)	180 mg/l, 96 hours
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)			
Aquatic			
Crustacea	EC50	Water flea (<i>Daphnia magna</i>)	1000 mg/l, 48 hours
Fish	LC50	Rainbow trout, donaldson trout (<i>Oncorhynchus mykiss</i>)	5000 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability Not readily biodegradable.

Bioaccumulative potential No data available.

Partition coefficient n-octanol / water (log Kow)

Benzoic Acid 1.87

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal of waste from residues / unused products This product is not a RCRA hazardous waste (See 40 CFR Part 261.20 – 261.33). Empty containers may be recycled. Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose in accordance with all applicable regulations.

Hazardous waste code Not regulated.

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

SARA 304 Emergency release notification

Not regulated.

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

Not listed.

CERCLA Hazardous Substance List (40 CFR 302.4)

Benzoic Acid (CAS 65-85-0) Listed.

CERCLA Hazardous Substances: Reportable quantity

Benzoic Acid (CAS 65-85-0) 5000 LBS

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

Food and Drug Administration (FDA) Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 311/312 Immediate Hazard - Yes
Hazard categories Delayed Hazard - No
Fire Hazard - No
Pressure Hazard - No
Reactivity Hazard - No

SARA 302 Extremely hazardous substance No

US state regulations

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)
Distillates (petroleum), Hydrotreated Light Naphthenic (CAS 64742-53-6)
Distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0)

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. New Jersey Worker and Community Right-to-Know Act

Benzoic Acid (CAS 65-85-0)
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)
Distillates (petroleum), Hydrotreated Light Naphthenic (CAS 64742-53-6)
Distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0)
White mineral oil (CAS 8042-47-5)

US. Massachusetts RTK - Substance List

Benzoic Acid (CAS 65-85-0)
Distillates (petroleum), Hydrotreated Light Naphthenic (CAS 64742-53-6)
White mineral oil (CAS 8042-47-5)

US. Pennsylvania Worker and Community Right-to-Know Law

Benzoic Acid (CAS 65-85-0)
White mineral oil (CAS 8042-47-5)

US. Rhode Island RTK

Benzoic Acid (CAS 65-85-0)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Naphthalene (CAS 91-20-3) Listed: April 19, 2002

Volatile organic compounds (VOC) regulations

EPA

VOC content (40 CFR 51.100(s)) Not determined

Consumer products (40 CFR 59, Subpt. C) Not regulated

State

Consumer products Not regulated

VOC content (CA) 0 %

VOC content (OTC) 0 %

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes


*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 07-30-2015
Revision date 08-20-2015
Prepared by Allison Cho
Version # 02
Further information Not available.
HMIS® ratings Health: 1
Flammability: 1
Physical hazard: 0
Personal protection: B
NFPA ratings Health: 1
Flammability: 1
Instability: 0

NFPA ratings



Disclaimer

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries.