

SAFETY DATA SHEET

GUNK Engine Degreaser

DRIGINAL Step 1 CLEAR

1. Identification **Product identifier**

Gunk Engine Degreaser - Original

By: RSC

Other means of identification

SDS number

EB1CA

Part No.

EB1CA

Tariff code

3814.00.5090

Recommended use

Engine Degreaser

Recommended restrictions

None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name

RSC Chemical Solutions

Address

600 Radiator Road Indian Trail, NC 28079

United States

Telephone

Customer Service:

(704) 821-7643

Technical:

(704) 684-1811

Website E-mail

www.rscbrands.com

Not available.

Emergency Telephone:

(303) 623-5716

Emergency Contact:

RMPDC (877-740-5015)

2. Hazard(s) identification

Emergency phone number

Physical hazards

Flammable aerosols

Category 2

Health hazards

Germ cell mutagenicity

Category 1B

Carcinogenicity

Category 2

Specific target organ toxicity, single exposure

Category 3 narcotic effects

Environmental hazards

Hazardous to the aquatic environment, acute hazard

Category 2

Hazardous to the aquatic environment, long-term hazard

Category 2

OSHA defined hazards

Not classified.

Label elements



Signal word

Danger

Hazard statement

Flammable aerosol. May cause drowsiness or dizziness. May cause genetic defects. Suspected of causing cancer. Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

Precautionary statement

Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing mist or vapor. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.

Response

If inhaled: Remove person to fresh air and keep comfortable for breathing. If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Collect spillage.

Material name: Gunk Engine Degreaser - Original EB1CA Version #: 01 Issue date: 05-20-2015

SDS US

Storage

Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from

sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information

22.41% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 22% of the mixture consists of component(s) of unknown long-term hazards to the

Dispose of contents/container in accordance with local/regional/national/international regulations.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Petroleum Distillate Aliphatic		68476-34-6	70 - < 80
Solvent Naphtha (petroleum), Light Arom.		64742-95-6	5 - < 10
1,2,4-Trimethylbenzene		95-63-6	1 - < 3
Carbon Dioxide		124-38-9	1-<3
Trimethylbenzene		25551-13-7	1-<3
BENZENE,1-METHYLETHYL-		98-82-8	< 0.3
NAPHTHALENE		91-20-3	< 0.2
Other components below reportable level	s		10 - < 20

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

Skin contact

Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact

Rinse with water. Get medical attention if irritation develops and persists.

Ingestion

In the unlikely event of swallowing contact a physician or poison control center.

Most important symptoms/effects, acute and delayed

May cause drowsiness and dizziness. Headache. Nausea, vomiting.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

General information

IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing

media

Alcohol resistant foam. Dry powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Special protective equipment

and precautions for firefighters

Fire fighting equipment/instructions Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.

General fire hazards

Flammable aerosol.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Refer to attached safety data sheets and/or instructions for use. Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Use water spray to reduce vapors or divert vapor cloud drift. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Prevent product from entering drains. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Inform appropriate managerial or supervisory personnel of all environmental releases.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid breathing mist or vapor. Avoid prolonged exposure. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Level 3 Aerosol.

This material can accumulate static charge which may cause spark and become an ignition source. Keep out of the reach of children. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air C Components	Туре	Value	
BENZENE,1-METHYLETHY L- (CAS 98-82-8)	PEL	245 mg/m3	
		50 ppm	
Carbon Dioxide (CAS 124-38-9)	PEL	9000 mg/m3	
		5000 ppm	
NAPHTHALENE (CAS 91-20-3)	PEL	50 mg/m3	
		10 ppm	
US. ACGIH Threshold Limit Values			
Components	Туре	Value	Form
,2,4-Trimethylbenzene CAS 95-63-6)	TWA	25 ppm	
BENZENE,1-METHYLETHY (CAS 98-82-8)	TWA	50 ppm	
Carbon Dioxide (CAS 124-38-9)	STEL	30000 ppm	
·	TWA	5000 ppm	
NAPHTHALENE (CAS 91-20-3)	TWA	10 ppm	
Petroleum Distillate Aliphatic (CAS 68476-34-6)	TWA	100 mg/m3	Inhalable fraction and

Material name: Gunk Engine Degreaser - Original EB1CA Version #: 01 Issue date: 05-20-2015

Components	Туре		Value	Form
Trimethylbenzene (CAS 25551-13-7)	TWA		25 ppm	
US. NIOSH: Pocket Guide to	Chemical Hazards			
Components	Туре		Value	
1,2,4-Trimethylbenzene (CAS 95-63-6)	TWA		125 mg/m3	
			25 ppm	
BENZENE,1-METHYLETHY L- (CAS 98-82-8)	TWA		245 mg/m3	
0 1 2 11 (010			50 ppm	
Carbon Dioxide (CAS 124-38-9)	STEL		54000 mg/m3	
,			30000 ppm	
	TWA		9000 mg/m3	
			5000 ppm	
NAPHTHALENE (CAS 91-20-3)	STEL		75 mg/m3	•
01 20-0)			15 ppm	
	TWA		50 mg/m3	
			10 ppm	
logical limit values	No biological exposure lim	its noted for the ingred	lient(s).	
oosure guidelines				
US - California OELs: Skin d	lesignation			
BENZENE,1-METHYLET US - Minnesota Haz Subs: S		Can be absorbed	I through the skin.	
BENZENE,1-METHYLET		Skin designation	applies.	
US - Tennessee OELs: Skin	•		appoo.	
BENZENE,1-METHYLET US ACGIH Threshold Limit \		Can be absorbed	through the skin.	
NAPHTHALENE (CAS 91	-	Can be absorbed	I through the skin.	
Petroleum Distillate Alipha US NIOSH Pocket Guide to 0	atic (CAS 68476-34-6)	Can be absorbed	I through the skin.	
BENZENE,1-METHYLET		-	I through the skin.	
US. OSHA Table Z-1 Limits f	•			
BENZENE,1-METHYLET	HYL- (CAS 98-82-8)	Can be absorbed	through the skin.	
propriate engineering strols	Good general ventilation (t should be matched to cond or other engineering control exposure limits have not be	litions. If applicable, us ols to maintain airborne	se process enclosure e levels below recom	es, local exhaust ventilation Inmended exposure limits.
vidual protection measures, Eye/face protection	such as personal protective Chemical respirator with or		and full facepiece.	
Skin protection	•			
Hand protection	Wear appropriate chemical supplier.	resistant gloves. Suit	able gloves can be r	ecommended by the glove
Other	Use of an impervious apror	n is recommended.		
Respiratory protection	Chemical respirator with organic vapor cartridge and full facepiece.			
Thermal hazards	Wear appropriate thermal p		•	
neral hygiene siderations	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.			
Physical and chemical p	- '			
earance	Liquid.			
	Liquiu.			

Material name: Gunk Engine Degreaser - Original EB1CA Version #: 01 Issue date: 05-20-2015

Liquid.

Aerosol.

Physical state

Form

Color

Red

Odor

Petroleum

Odor threshold

Not available.

Hq

Not available.

Melting point/freezing point

Not available.

Initial boiling point and boiling

Not available.

range

Flash point

165.0 °F (73.9 °C) Tag Closed Cup

Evaporation rate

Not available.

Flammability (solid, gas)

Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

(%)

Flammability limit - upper

Not available.

(%)

Explosive limit - lower (%)

Not available.

Explosive limit - upper (%)

Not available.

Vapor pressure

Not available.

Vapor density

Not available.

Relative density

Not available.

Solubility(ies)

Solubility (water)

Not available.

Partition coefficient

Not available.

(n-octanol/water)

Auto-ignition temperature

500 °F (260 °C) estimated

Decomposition temperature

Not available.

Viscosity

Not available.

Other information

Density

7.37 lbs/gal estimated

Explosive properties

Not explosive.

Flame extension

0 in No

Flammability (flash back) Flammability class

Combustible II estimated

Heat of combustion (NFPA

30B)

38.9 kJ/g

Oxidizing properties Percent volatile

0.14 % estimated

Specific gravity

0.88 estimated

Not oxidizing.

VOC (Weight %)

8.9 % estimated

10. Stability and reactivity

Reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability

Material is stable under normal conditions.

Possibility of hazardous

reactions

Hazardous polymerization does not occur.

Conditions to avoid

Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials

Strong oxidizing agents.

Hazardous decomposition

No hazardous decomposition products are known.

products

11. Toxicological information

Information on likely routes of exposure

Inhalation

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be

harmful.

Skin contact

No adverse effects due to skin contact are expected.

Eye contact

Direct contact with eyes may cause temporary irritation.

Ingestion

Expected to be a low ingestion hazard.

Symptoms related to the

Headache. May cause drowsiness and dizziness. Nausea, vomiting.

physical, chemical and toxicological characteristics

Information on toxicological effects

Acute toxicity

Narcotic effects.

Components

Species

Test Results

1,2,4-Trimethylbenzene (CAS 95-63-6)

Acute

Dermal

LD50

Rabbit

> 3160 mg/kg

Inhalation

LC50

Rat

> 2000 ppm, 48 Hours

Oral

LD50

Rat

6 g/kg

BENZENE,1-METHYLETHYL- (CAS 98-82-8)

Acute

Inhalation

LC50

Mouse

2000 ppm, 7 Hours

24.7 mg/l, 2 Hours

Rat

8000 ppm, 4 Hours

Oral

LD50

Rat

1400 mg/kg

NAPHTHALENE (CAS 91-20-3)

Acute

Dermal

LD50

Rabbit

> 2 g/kg

Rat

> 20 g/kg

Oral

LD50

Guinea pig

1200 mg/kg

Rat

490 mg/kg

Trimethylbenzene (CAS 25551-13-7)

<u>Acute</u>

Oral

LD50

Rat

8970 mg/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Serious eye damage/eye Prolonged skin contact may cause temporary irritation. Direct contact with eyes may cause temporary irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization

Not a respiratory sensitizer.

Skin sensitization

This product is not expected to cause skin sensitization.

Germ cell mutagenicity

May cause genetic defects.

Carcinogenicity

Suspected of causing cancer.

Material name: Gunk Engine Degreaser - Original EB1CA Version #: 01 Issue date: 05-20-2015

IARC Monographs. Overall Evaluation of Carcinogenicity

BENZENE,1-METHYLETHYL- (CAS 98-82-8)

NAPHTHALENE (CAS 91-20-3)

2B Possibly carcinogenic to humans. 2B Possibly carcinogenic to humans.

Petroleum Distillate Aliphatic (CAS 68476-34-6)

3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

NAPHTHALENE (CAS 91-20-3)

Reasonably Anticipated to be a Human Carcinogen.

Reproductive toxicity

This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

May cause drowsiness and dizziness.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard

Not an aspiration hazard.

Chronic effects

Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity

Toxic to aquatic life with long lasting effects.

Species

Components 1,2,4-Trimethylbenzene (CAS 95-63-6)

Aquatic

Fish

LC50

Fathead minnow (Pimephales promelas) 7.19 - 8.28 mg/l, 96 hours

BENZENE,1-METHYLETHYL- (CAS 98-82-8)

Aquatic

Crustacea

EC50

Brine shrimp (Artemia sp.)

3.55 - 11.29 mg/l, 48 hours

Fish

LC50

Rainbow trout, donaldson trout

2.7 mg/l, 96 hours

Test Results

(Oncorhynchus mykiss)

NAPHTHALENE (CAS 91-20-3)

Aquatic

Crustacea

EC50

Water flea (Daphnia magna)

1.09 - 3.4 mg/l, 48 hours

Fish

LC50

Pink salmon (Oncorhynchus gorbuscha) 1.11 - 1.68 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability

No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

BENZENE, 1-METHYLETHYL-

3.66

NAPHTHALENE

3.3

Mobility in soil

No data available.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

14. Transport information

DOT

UN number

Not available.

UN proper shipping name Transport hazard class(es)

Consumer Commodity, MARINE POLLUTANT

Class

ORM-D

Subsidiary risk

Label(s)

Packing group

Not applicable.

Environmental hazards

Marine pollutant Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions Packaging exceptions T75, TP5

Packaging non bulk

306

Packaging bulk

304 314, 315

IATA

UN number

UN1950

UN proper shipping name

Aerosol, flammable

Transport hazard class(es)

Class

2

Subsidiary risk

Packing group

Not applicable.

Environmental hazards

Yes

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

Forbidden.

aircraft

Cargo aircraft only

Forbidden.

IMDG

UN number

UN1950 Aerosols

UN proper shipping name Transport hazard class(es)

Class

2

Subsidiary risk

Packing group

Not applicable.

Environmental hazards

Marine pollutant

Yes

EmS

F-D, S-U

Transport in bulk according to Annex II of MARPOL 73/78 and

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Not established.

the IBC Code

IATA; IMDG



Marine pollutant



15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

BENZENE,1-METHYLETHYL- (CAS 98-82-8)

NAPHTHALENE (CAS 91-20-3)

Listed. Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate Hazard - Yes Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

No

chemical

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.	
1,2,4-Trimethylbenzene	95-63-6	1-<3	_
NAPHTHALENE	91-20-3	< 0.2	

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

BENZENE,1-METHYLETHYL- (CAS 98-82-8)

NAPHTHALENE (CAS 91-20-3)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100) Not listed.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

1,2,4-Trimethylbenzene (CAS 95-63-6)

BENZENE,1-METHYLETHYL- (CAS 98-82-8)

NAPHTHALENE (CAS 91-20-3)

Petroleum Distillate Aliphatic (CAS 68476-34-6)

Solvent Naphtha (petroleum), Light Arom. (CAS 64742-95-6)

Trimethylbenzene (CAS 25551-13-7)

US. Massachusetts RTK - Substance List

1,2,4-Trimethylbenzene (CAS 95-63-6)

BENZENE, 1-METHYLETHYL- (CAS 98-82-8)

Carbon Dioxide (CAS 124-38-9)

NAPHTHALENE (CAS 91-20-3)

Trimethylbenzene (CAS 25551-13-7)

US. New Jersey Worker and Community Right-to-Know Act

1,2,4-Trimethylbenzene (CAS 95-63-6)

BENZENE, 1-METHYLETHYL- (CAS 98-82-8)

Carbon Dioxide (CAS 124-38-9) NAPHTHALENE (CAS 91-20-3)

Petroleum Distillate Aliphatic (CAS 68476-34-6)

Trimethylbenzene (CAS 25551-13-7)

US. Pennsylvania Worker and Community Right-to-Know Law

1,2,4-Trimethylbenzene (CAS 95-63-6)

BENZENE,1-METHYLETHYL- (CAS 98-82-8)

Carbon Dioxide (CAS 124-38-9) NAPHTHALENE (CAS 91-20-3)

Petroleum Distillate Aliphatic (CAS 68476-34-6)

Trimethylbenzene (CAS 25551-13-7)

US. Rhode Island RTK

1,2,4-Trimethylbenzene (CAS 95-63-6)

BENZENE,1-METHYLETHYL- (CAS 98-82-8)

NAPHTHALENE (CAS 91-20-3)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

BENZENE,1-METHYLETHYL- (CAS 98-82-8)

Listed: April 6, 2010

NAPHTHALENE (CAS 91-20-3)

Listed: April 19, 2002

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date

05-20-2015

Version #

01

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

Material name: Gunk Engine Degreaser - Original EB1CA Version #: 01 Issue date: 05-20-2015