

## SAFETY DATA SHEET

Revision Date 05-May-2017

Version 2

#### 1. IDENTIFICATION

Product identifier

**Product Name** 

Wynn's Air Intake Cleaner

Air Intake Cleaner

Wynnis

Other means of identification

**Product Code Synonyms** 

WN A6601

None

Recommended use of the chemical and restrictions on use

Recommended Use

See directions provided with product

Uses advised against

All other applications

Details of the supplier of the safety data sheet

**Supplier Address ITW Professional Automotive Products**  **Manufacturer Address** 

Manufactured and Distributed by:

3606 Craftsman Blvd. Lakeland, FL 33803

**Distributor** 

May Also Be Distributed by:

**ITW Professional Automotive Products** 

1-35 Brownridge Road

Halton Hills, ON, Canada L7G OC6

**Company Phone Number** 

24 Hour Emergency Phone Number Chem-Tel: 800-255-3924

863-665-3338

International Emergency: 00+1+813-248-0585

Contract Number: MIS0003583

E-mail address

EHS@itwproap.com

#### 2. HAZARDS IDENTIFICATION

#### Classification

**OSHA Regulatory Status** 

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

#### NOTE:

Acute toxicity - Inhalation (Gases)	Category 4
Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Aspiration toxicity	Category 1
Flammable liquids	Category 1

#### Label elements

	Emergency Overview	
Danger		
	·	
Harmful if inhaled		

Causes skin irritation
Causes serious eye irritation
May cause drowsiness or dizziness
May cause damage to organs through prolonged or repeated exposure
May be fatal if swallowed and enters airways
Extremely flammable liquid and vapor



Appearance Clear

Physical state Liquid

Odor Solvent

## **Precautionary Statements - Prevention**

Use only outdoors or in a well-ventilated area

Wash face, hands and any exposed skin thoroughly after handling

Wear protective gloves/protective clothing/eye protection/face protection

Do not breathe dust/fume/gas/mist/vapors/spray

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting/equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Keep cool

#### **Precautionary Statements - Response**

Get medical advice/attention if you feel unwell

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

If skin irritation occurs: Get medical advice/attention

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

Wash contaminated clothing before reuse

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or doctor/physician if you feel unwell

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Do NOT induce vomiting

In case of fire: Use CO2, dry chemical, or foam for extinction

## **Precautionary Statements - Storage**

Store locked up

Store in a well-ventilated place. Keep container tightly closed

#### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

#### Hazards not otherwise classified (HNOC)

Not applicable

#### Other Information

- May be harmful if swallowed
- May be harmful in contact with skin
- Toxic to aquatic life with long lasting effects
- Harmful to aquatic life

Unknown acute toxicity

1.61 % of the mixture consists of ingredient(s) of unknown toxicity

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### Substance(s)

Chemical Name	CAS No	Weight-%	Trade Secret
Xylene	1330-20-7	10 - 30	*
Solvent naphtha (petroleum), light aromatic	64742-95-6	10 - 30	*
Acetone	67-64-1	7 - 13	*
Ethylbenzene	100-41-4	7 - 13	*
1,2,4-Trimethylbenzene	95-63-6	7 - 13	*
1,3,5-Trimethylbenzene	108-67-8	1 - 5	*
Cumene	98-82-8	1 - 5	*

## 4. FIRST AID MEASURES

#### Description of first aid measures

General advice

Get medical advice/attention if you feel unwell.

Eye contact

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. If eye irritation persists: Get medical

advice/attention.

Skin contact

IF ON SKIN:. Wash skin with soap and water. If skin irritation persists, call a physician.

Wash contaminated clothing before reuse.

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing. If symptoms persist, call a physician.

Ingestion

IF SWALLOWED:. Do NOT induce vomiting. Never give anything by mouth to an

unconscious person. Call a physician.

Self-protection of the first aider

Ensure that medical personnel are aware of the material(s) involved and take precautions to

protect themselves.

## Most important symptoms and effects, both acute and delayed

**Symptoms** 

See section 2 for more information.

## Indication of any immediate medical attention and special treatment needed

Note to physicians

Treat symptomatically.

## 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Carbon dioxide (CO2), Dry chemical, Foam

Unsuitable extinguishing media

Do not use a solid water stream as it may scatter and spread fire.

#### Specific hazards arising from the chemical

Flammable.

**Explosion data** 

Sensitivity to Mechanical Impact

None.

Sensitivity to Static Discharge

None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full

protective gear.

### **6. ACCIDENTAL RELEASE MEASURES**

## Personal precautions, protective equipment and emergency procedures

Personal precautions

Remove all sources of ignition. Use personal protective equipment as required.

Environmental precautions

**Environmental precautions** 

See Section 12 for additional ecological information. Do not flush into surface water or

sanitary sewer system.

## Methods and material for containment and cleaning up

Methods for containment

Prevent further leakage or spillage if safe to do so.

Methods for cleaning up

Soak up with inert absorbent material.

Prevention of secondary hazards

Clean contaminated objects and areas thoroughly observing environmental regulations.

#### 7. HANDLING AND STORAGE

#### Precautions for safe handling

Advice on safe handling

Handle in accordance with good industrial hygiene and safety practice. Avoid breathing vapors or mists. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Wash contaminated clothing before reuse. Use personal protective equipment as required.

## Conditions for safe storage, including any incompatibilities

**Storage Conditions** 

Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric

motors and static electricity).

Incompatible materials

Strong oxidizing agents

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## Control parameters

**Exposure Guidelines** 

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Xylene	STEL: 150 ppm	TWA: 100 ppm	<u>-</u>
1330-20-7	TWA: 100 ppm	TWA: 435 mg/m <sup>3</sup>	
		(vacated) TWA: 100 ppm	
		(vacated) TWA: 435 mg/m³	•
		(vacated) STEL: 150 ppm	
	7	(vacated) STEL: 655 mg/m³	
Acetone	STEL: 500 ppm	TWA: 1000 ppm	IDLH: 2500 ppm
67-64-1	TWA: 250 ppm	TWA: 2400 mg/m <sup>3</sup>	TWA: 250 ppm
		(vacated) TWA: 750 ppm	TWA: 590 mg/m <sup>3</sup>
	•	(vacated) TWA: 1800 mg/m³	
	•	(vacated) STEL: 2400 mg/m³ The	
		acetone STEL does not apply to the	
		cellulose acetate fiber industry. It is	
		in effect for all other sectors	
		(vacated) STEL: 1000 ppm	
Ethylbenzene	TWA: 20 ppm	TWA: 100 ppm	IDLH: 800 ppm
100-41-4		TWA: 435 mg/m <sup>3</sup>	TWA: 100 ppm
		(vacated) TWA: 100 ppm	TWA: 435 mg/m <sup>3</sup>
		(vacated) TWA: 435 mg/m³	STEL: 125 ppm
		(vacated) STEL: 125 ppm	STEL: 545 mg/m <sup>3</sup>
		(vacated) STEL: 545 mg/m³	
1,2,4-Trimethylbenzene		- '	TWA: 25 ppm

95-63-6			TWA: 125 mg/m <sup>3</sup>
1,3,5-Trimethylbenzene 108-67-8	-	-	TWA: 25 ppm TWA: 125 mg/m <sup>3</sup>
Cumene 98-82-8	TWA: 50 ppm	TWA: 50 ppm TWA: 245 mg/m³ (vacated) TWA: 50 ppm (vacated) TWA: 245 mg/m³ (vacated) S* S*	IDLH: 900 ppm TWA: 50 ppm TWA: 245 mg/m³

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

Appropriate engineering controls

**Engineering Controls** 

Showers

Eyewash stations Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear safety glasses with side shields (or goggles).

Skin and body protection

Wear protective natural rubber, nitrile rubber, Neoprene™ or PVC gloves.

Respiratory protection Use NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as

**General Hygiene Considerations** 

appropriate.

Handle in accordance with good industrial hygiene and safety practice. Regular cleaning of equipment, work area and clothing is recommended.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

## Information on basic physical and chemical properties

Physical state Appearance

Liquid Clear Solvent

Odor Color

amber

Odor threshold

No information available

**Property** 

<u>Values</u>

Remarks • Method

Нq Melting point / freezing point

Boiling point / boiling range Flash point

**Evaporation rate** Flammability (solid, gas)

Flammability Limit in Air

Upper flammability limit: Lower flammability limit: Vapor pressure

Vapor density Relative density Water solubility

Solubility in other solvents Partition coefficient Autoignition temperature

Decomposition temperature Kinematic viscosity Dynamic viscosity **Explosive properties** 

No information available No information available > 35 °C / 95 °F

3 °C / 37 °F

No information available No information available

No information available No information available No information available No information available

0.87

Insoluble in water

No information available No information available No information available No information available

2 mm2/s

No information available No information available

**Oxidizing properties** 

No information available

**Other Information** 

Softening point Molecular weight VOC Content (%) Density No information available No information available No information available No information available No information available

## 10. STABILITY AND REACTIVITY

#### Reactivity

**Bulk density** 

No data available

#### Chemical stability

Stable under recommended storage conditions

#### Possibility of Hazardous Reactions

None under normal processing.

#### Conditions to avoid

Excessive heat.

#### Incompatible materials

Strong oxidizing agents

## **Hazardous Decomposition Products**

Carbon oxides

## 11. TOXICOLOGICAL INFORMATION

## Information on likely routes of exposure

Inhalation

May cause irritation of respiratory tract.

Eye contact

Contact with eyes may cause irritation. May cause redness and tearing of the eyes.

Skin contact

May cause skin irritation and/or dermatitis.

Ingestion

Ingestion may cause irritation to mucous membranes.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Xylene 1330-20-7	= 3500 mg/kg ( Rat )	> 4350 mg/kg (Rabbit) > 1700 mg/kg (Rabbit)	= 29.08 mg/L (Rat)4 h = 5000 ppm (Rat)4 h
Solvent naphtha (petroleum), light aromatic 64742-95-6	= 8400 mg/kg(Rat)	> 2000 mg/kg (Rabbit)	= 3400 ppm (Rat) 4 h
Acetone 67-64-1	= 5800 mg/kg ( Rat )	-	= 50100 mg/m³(Rat)8 h
Ethylbenzene 100-41-4	= 3500 mg/kg (Rat)	= 15400 mg/kg(Rabbit)	= 17.2 mg/L (Rat)4 h
1,2,4-Trimethylbenzene 95-63-6	= 3280 mg/kg ( Rat )	> 3160 mg/kg ( Rabbit )	= 18 g/m³(Rat)4 h
1,3,5-Trimethylbenzene 108-67-8	= 5000 mg/kg (Rat)	-	= 24 g/m³(Rat)4 h
Cumene 98-82-8	= 1400 mg/kg ( Rat )	= 12300 μL/kg (Rabbit)	> 3577 ppm (Rat) 6 h = 39000 mg/m³ (Rat) 4 h

#### Information on toxicological effects

**Symptoms** 

No information available.

## Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization

No information available.

Germ cell mutagenicity

No information available.

Carcinogenicity The table below indicates whether each agency has listed any ingradient as a corrigorous

21	The table be	now indicates whether eac	n agency has listed any ingre	cuent as a carcinogen.
Chemical Name	ACGIH	IARC	NTP	OSHA
Xylene 1330-20-7	-	Group 3	-	-
Ethylbenzene 100-41-4	A3	Group 2B	-	X
Cumene 98-82-8	-	Group 2B	Reasonably Anticipated	Х

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Not classifiable as a human carcinogen

Group 1 - Carcinogenic to Humans

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Chronic toxicity

May cause adverse effects on the bone marrow and blood-forming system.

**Target Organ Effects** Central nervous system, Eyes, Respiratory system, Skin, Blood.

The following values are calculated based on chapter 3.1 of the GHS document . ATEmix (oral)

4373 mg/kg

ATEmix (dermal)

2447 mg/kg

ATEmix (inhalation-gas)

6211 mg/l

ATEmix (inhalation-dust/mist)

3 mg/l

ATEmix (inhalation-vapor)

340473.1 mg/l

### 12. ECOLOGICAL INFORMATION

#### **Ecotoxicity**

14.71 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

#### Persistence and degradability

No information available.

#### **Bioaccumulation**

No information available.

#### Mobility

No information available.

Chemical Name	Partition coefficient
Xylene 1330-20-7	2.77 - 3.15
Acetone 67-64-1	-0.24
Ethylbenzene 100-41-4	3.118
1,2,4-Trimethylbenzene 95-63-6	3.63
Cumene 98-82-8	3.7

#### Other adverse effects

No information available

#### 13. DISPOSAL CONSIDERATIONS

#### Waste treatment methods

Disposal of wastes

This material, as supplied, is a hazardous waste according to federal regulations (40 CFR

261).

Contaminated packaging

Do not reuse container.

**US EPA Waste Number** 

U002 U239 D001

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status		
Xylene	Toxic		
1330-20-7	Ignitable		
Acetone 67-64-1	Ignitable		
Ethylbenzene	Toxic		
100-41-4	Ignitable		
Cumene	Toxic		
98-82-8	Ignitable		

#### 14. TRANSPORT INFORMATION

#### NOTE:

DOT

UN/ID no

UN1993

Proper shipping name:

Flammable liquids, n.o.s, (Contains Acetone and Xylene), Limited Quantity (LQ)

**Hazard Class Packing Group** 

II

<u>IATA</u>

UN/ID no

UN/ID no

UN1993

Proper shipping name:

Flammable liquid, n.o.s, (Contains Acetone and Xylene)

**Hazard Class** 

11

**Packing Group** 

**IMDG** 

UN1993

II

Proper shipping name:

Flammable liquids, n.o.s, (Contains Acetone and Xylene), Limited Quantity (LQ)

**Hazard Class** 

**Packing Group** 

## 15. REGULATORY INFORMATION

**International Inventories** 

**TSCA** Complies **DSL/NDSL** Complies **EINECS/ELINCS** Complies **ENCS** Complies **IECSC** Complies **KECL** Complies **PICCS** Complies AICS Complies

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

## US Federal Regulations

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
Xylene - 1330-20-7	1.0
1,2,4-Trimethylbenzene - 95-63-6	1.0
Ethylbenzene - 100-41-4	0.1
Isopropanol - 67-63-0	1.0
Cumene - 98-82-8	1.0

#### SARA 311/312 Hazard Categories

Acute health hazard	No
Chronic Health Hazard	No
Fire hazard	Yes
Sudden release of pressure hazard	No.
Reactive Hazard	No

#### **CWA (Clean Water Act)**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Xylene 1330-20-7	100 lb	-	-	X
Ethylbenzene 100-41-4	1000 lb	Х	×	X

#### CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ) RQ 100 lb final RQ		
Xylene	100 lb	-			
1330-20-7			RQ 45.4 kg final RQ		
Acetone 67-64-1	5000 lb	-	RQ 5000 lb final RQ		
Ethylbenzene	1000 lb		RQ 2270 kg final RQ RQ 1000 lb final RQ		
100-41-4			RQ 454 kg final RQ		
Cumene 98-82-8	5000 lb	~	RQ 5000 lb final RQ		
IS State Demulations		· · · · · · · · · · · · · · · · · · ·	RQ 2270 kg final RQ		

#### US State Regulations

## **California Proposition 65**

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65		
Ethylbenzene - 100-41-4	Carcinogen		
Cumene - 98-82-8	Carcinogen		

## U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania		
Xylene 1330-20-7	X	Х	X		
Acetone 67-64-1	X	X	Х		
1,2,4-Trimethylbenzene 95-63-6	X	Х	Х		
Isopropanol 67-63-0	X	X	Х		
1,3,5-Trimethylbenzene	-	<u> </u>			

108-67-8			 T			
Diethylbenzene 25340-17-4	Х	-			<del></del>	
Cumene 98-82-8	X	Х	<del>                                     </del>	X		

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

**WHMIS Hazard Class** 

D2A - Very toxic materials, B2 - Flammable liquid

# 16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA HMIS Health hazards 2 Health hazards 2 Flammability 4 Flammability 4 Instability 0

Instai

Physical hazards 0

Personal protection B

NFPA (National Fire Protection Association) HMIS (Hazardous Material Information System)

**Revision Date** 

05-May-2017

**Disclaimer** 

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**