

7/24/17

SAFETY DATA SHEET – POULAN PRO SYNTHETIC 2 STROKE

Poulan High Performance
40 to 1 Two cycle Engine
Oil

Spectrum
CORPORATION



1. IDENTIFICATION

1.1. PRODUCT IDENTIFIER USED ON LABEL:

Finished Product Item Number	Customer Item Number	LABEL DESCRIPTION ACTUAL	BRAND
SM5729PO	952030224	POULAN EASY-MIX 40:1 SYNTHETIC 2-STROKE ENGINE OIL	POULAN
SM5710PW	584955301	POULAN PRO WEED EATER 40:1 FULL SYNTHETIC	POULAN
SM5702PP	585236901	POULAN PRO WEED EATER 50:1 FULL SYNTHETIC	POULAN
SM5720PO	587312101	POULAN PRO WEED EATER 40:1 FULL SYNTHETIC	POULAN
SM5722PO	587312102	POULAN PRO WEED EATER 40:1 FULL SYNTHETIC	POULAN
SM5721PO	585666301/585826802	POULAN PRO WEED EATER 50:1 FULL SYNTHETIC	POULAN
SM5731PO	585063601/585826803	POULAN PRO WEED EATER 40:1 FULL SYNTHETIC	POULAN
SM57TOTE	952030236	POULAN FULL SYNTHETIC	POULAN

1.2. RECOMMENDED USE OF THE CHEMICAL AND RESTRICTIONS ON USE;

- 1.2.1. PETROLEUM LUBRICATING OIL
- 1.2.2. NO OTHER USES RECOMMENDED

1.3. NAME, ADDRESS, AND TELEPHONE NUMBER OF THE CHEMICAL MANUFACTURER, IMPORTER, OR OTHER RESPONSIBLE PARTY:

1.3.1.

Spectrum Lubricants Corporation

500 Industrial Park Drive
Selmer, TN 38375-3276
United States of America

Product Information

MSDS Requests: (800) 264-6457 or +17316454972
Technical Information: (800) 264-6457 or +17316454972
General Information: vswedley@spectrumcorporation.com

1.4. EMERGENCY PHONE NUMBER:

1.4.1.

SAFETY DATA SHEET – POULAN PRO SYNTHETIC 2 STROKE

Emergency Response

North America: CHEMTREC (800) 424-9300 after 5:00pm CST Or +17035273887

Health Emergency

USA: (800) 264-6457 or +17316454972

2. HAZARD(S) IDENTIFICATION

2.1. CLASSIFICATION OF THE CHEMICAL IN ACCORDANCE WITH PARAGRAPH (d) of §1910.1200:

- 2.1.1. Acute Inhalation Category 4
- 2.1.2. Eye Irritant Category 2
- 2.1.3. Skin Corrosion/Irritation Category 2
- 2.1.4. Aquatic Environment Category 4

2.2. Signal Word:

- 2.2.1. Warning

2.3. Symbol:



2.4. Hazard Statements:

- 2.4.1. Harmful if Inhaled
- 2.4.2. Causes serious eye irritation
- 2.4.3. Causes skin irritation
- 2.4.4. May cause long lasting harmful effects to aquatic life.

2.5. Precautionary Statements:

2.5.1. Prevention:

- 2.5.1.1. Avoid breathing dust/fume/gas/mist/vapors/spray.
- 2.5.1.2. Use only outdoors or in a well-ventilated area.
- 2.5.1.3. Wear eye/face protection
- 2.5.1.4. Wear protective gloves
- 2.5.1.5. Avoid release to the environment.

2.5.2. Response:

- 2.5.2.1. If inhaled: Remove person to fresh air and keep comfortable for breathing.
- 2.5.2.2. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists get medical advice/attention.
- 2.5.2.3. If on skin: wash with plenty of water, if irritation or rash occurs get medical advice/attention. Take off contaminated clothing and wash it before reuse.
- 2.5.2.4. Call a poison center/doctor if you feel unwell.

3. Composition/ information on ingredients

SAFETY DATA SHEET – POULAN PRO SYNTHETIC 2 STROKE

3.1. The chemical name and concentration (exact percentage) or concentration ranges of all ingredients which are classified as health hazards in accordance with paragraph (d) of §1910.1200

3.1.1.

COMPONENTS	CAS Number	EU Number	Concentration (%)	Hazard Statements (see Section 16)
Distillates (petroleum), hydrotreated light	64742-47-8	265-149-8	10-30	H226, H304, H315,
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	72623-87-1	276-738-4	30-50	
Polyolefin Phenol	Not available	Not available	3-6	H315, H319
Polymerized fatty acid 2-ethylhexyl ester	68424-40-8	Not available	10-30	H413
Polyisobutylene	9003-27-4	Not available	10-30	H413

4. FIRST AID MEASURES

4.1.

Skin:	Wash skin with soap and warm water. Wash clothing before re-use.
Eye:	If splashed into eyes flush eyes with clear water for several minutes.
Inhalation:	Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell
Ingestion:	If ingested, do not induce vomiting. Call a physician.

5. FIRE FIGHTING MEASURES

5.1. **Flash Point:** 210°F (99°C)

5.2. **Protective Equipment/Fire Fighting Instructions:**

5.2.1. For fires involving this material, do not enter any enclosed or confined fire space without proper protective equipment, including self-contained breathing apparatus.

5.3. **Extinguishing Media:**

5.3.1. Use water fog, foam, dry chemical or carbon dioxide (CO₂) to extinguish flames.

5.4. **Special Firefighting Procedures:**

5.4.1. Cool exposed containers with water spray.

5.5. **Unusual Fire and Explosion Hazards:**

5.5.1. Pressure increase in over heated closed containers. Cool containers with water spray.

6. ACCIDENTAL RELEASE MEASURES

SAFETY DATA SHEET – POULAN PRO SYNTHETIC 2 STROKE

6.1. Spill Procedures:

6.1.1. Remove ignition sources. Recover Liquid. Add absorbent to spill area. Ventilate confined spaces. Advise authorities if product enters sewers, etc.

6.2. Waste Disposal:

6.2.1. Assure conformity with applicable disposal regulations. Dispose of absorbed material at approved waste site

6.3. Precautionary Measures:

6.3.1. Do not get in eyes, on skin, or on clothing. Do not taste or swallow. Wash thoroughly after handling.

6.3.2. Avoid contaminating soil or releasing this material into sewage and drainage systems and bodies of water.

7. HANDLING AND STORAGE

7.1. HANDLING

7.1.1. Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum re-conditioner or disposed of properly.

7.2. STORAGE

7.2.1. Keep container closed when not in use. Do not store with strong oxidizing agents. Do not store at elevated temperatures.

8. EXPOSURE CONTROLS/ PERSONAL PROTECTION

8.1. Component Exposure Limits:

8.1.1. SYNTHETIC ENGINE OIL 5mg/m³ (oil mist) ACGIH TLV OSHA PEL

COMPONENTS	ACGIH TLV	OSHA PEL
Distillates (petroleum), hydrotreated light	5mg/m ³ (oil mist) TWA	5mg/m ³ (oil mist) TWA
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	5mg/m ³ (oil mist) TWA	5mg/m ³ (oil mist) TWA
Polyolefin Phenol	5mg/m ³ (oil mist) TWA	5mg/m ³ (oil mist) TWA
Polymerized fatty acid 2-ethylhexyl ester	5mg/m ³ (oil mist) TWA	5mg/m ³ (oil mist) TWA
Polysisobutylene	5mg/m ³ (oil mist) TWA	5mg/m ³ (oil mist) TWA

SAFETY DATA SHEET – POULAN PRO SYNTHETIC 2 STROKE

8.2. Engineering Controls:

8.2.1. Ventilate as needed to comply with exposure limit

8.3. Eye Protection:

8.3.1. Use goggles/face shield to avoid eye contact

8.4. Glove Protection:

8.4.1. Use impervious gloves to avoid repeated/prolonged skin contact.

8.5. Work/Hygienic Practices:

8.5.1. If clothing becomes contaminated, change to fresh clean clothing. Do not wear until thoroughly laundered.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Appearance/Odor:	Dark green/blue colored liquid with mild hydrocarbon odor.	9.2. Odor Threshold:	No data available
9.3. pH:	No data available	9.4. Boiling Point:	Wide range
9.5. Melting Point:	No data available	9.6. Solubility (H ₂ O):	Negligible
9.7. Specific Gravity:	0.865 @ 15.6°C	9.8. Density:	7.2 lbs/gal
9.9. Octanol/H ₂ O Coeff.:	No data available	9.10. Evaporation Rate (BUAC=1):	<1
9.11. Molecular Weight:	No data available	9.12. Decomposition Temp:	No data available
9.13. Auto Ignition:	No data available	9.14. Lower Flammability Limit:	No data available
9.15. Flash Point:	210°F (99°C)	9.16. Upper Flammability Limit:	No data available
9.17. Vapor Density (Air=1):	>1	9.18. Vapor Pressure:	<1mmHg @ 20°C
9.19. VOC:	173g/L	9.20. Flammability Class:	Not classified
9.21. Viscosity @ 40°C	42cSt (42 mm ² /s)	9.22. Viscosity @ 100°C	7.5cSt (7.5 mm ² /s)

10. STABILITY AND REACTIVITY

10.1. Reactivity:

10.1.1. Material does not pose a significant reactivity hazard.

SAFETY DATA SHEET – POULAN PRO SYNTHETIC 2 STROKE

10.2. Chemical Stability:

10.2.1. Stable

10.3. Incompatibility/Conditions to avoid:

10.3.1. Avoid strong oxidants

10.4. Possibility of Hazardous Reactions:

10.4.1. Will not undergo hazardous polymerization.

10.5. Hazardous Decomposition Products:

10.5.1. Partial burning produces fumes, smoke and carbon monoxide

11. TOXICOLOGY INFORMATION

11.1. Likely Routes of Exposure:

11.1.1. Ingestion, Inhalation, Eye contact, Skin contact.

11.2. Acute Effects:

11.2.1. Inhalation: Harmful if inhaled. May cause respiratory irritation.

11.2.2. Eye Contact: Causes serious eye irritation.

11.2.3. Skin Contact: Causes Skin irritation.

11.2.4. Ingestion: Expected to be low ingestion hazard.

11.3. Component Data/ Analysis

COMPONENTS	Oral (LD50) (Rat)	Inhalation (LC50) (Rat)	Dermal (LD50) (Rabbit)
Residual oils (petroleum), solvent-refined	>5000 mg/kg	2.18 mg/l (4hr)	>5000 mg/kg
Distillates (petroleum), hydrotreated light	>5000 mg/kg	2.18 mg/l (4hr)	>5000 mg/kg
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	>5000 mg/kg	2.18 mg/l (4hr)	>5000 mg/kg
Polyolefin Phenol	No data	No data	No data
Polymerized fatty acid 2-ethylhexyl ester	>5000 mg/kg		
Polyisobutylene	>5000 mg/kg	5.53 mg/l (4hr)	>2000 mg/kg

11.4. Sensitization:

11.4.1. None known.

11.5. Carcinogenicity:

11.5.1. None greater than 0.1%.

11.6. Mutagenicity:

11.6.1. None known.

11.7. Reproductive Toxicity:

11.7.1. None known.

11.8. Teratogenicity:

11.8.1. None known.

12. ECOLOGICAL INFORMATION

12.1. Ecotoxicity

SAFETY DATA SHEET – POULAN PRO SYNTHETIC 2 STROKE

12.1.1. An environmental fate analysis is not available for this specific product. Plants and animals may experience harmful or fatal effects when coated with petroleum products. Petroleum-based (mineral) lubricating oils normally will float on water. In stagnant or slow-flowing waterways, an oil layer can cover a large surface area. As a result, this oil layer might limit or eliminate natural atmospheric oxygen transport into the water. With time, if not removed, oxygen depletion in the waterway may be sufficient to cause a fish kill or create an anaerobic environment.

12.2. Environmental Fate

12.2.1. Analysis for ecological effects has not been conducted on this product. However, if spilled, this product and any contaminated soil or water may be harmful to human, animal, and aquatic life. Also, the coating action associated with petroleum and petroleum products can be harmful or fatal to aquatic life and waterfowl.

13. DISPOSAL CONSIDERATIONS

13.1. Waste Disposal:

13.1.1. Assure conformity with applicable disposal regulations. Dispose of absorbed material at approved waste site.

14. TRANSPORTATION INFORMATION

The shipping description below may not represent requirements for all modes of transportation, shipping methods or locations outside of the United States.

14.1. ROAD AND RAIL

14.1.1. DOT: NOT REGULATED

14.2. VESSEL

14.2.1. IMDG: NOT REGULATED

14.3. AIR

14.3.1. IATA: NOT REGULATED

15. REGULATORY INFORMATION

15.1. TSCA Inventory

15.1.1. This product and/or its components are listed on the Toxic Substances Control Act (TSCA) inventory.

15.2. SARA 302/304 Emergency Planning and Notification

15.2.1. No components were identified.

15.3. SARA 311/312 Hazard Identification

15.3.1. Acute (Immediate) Health Hazard

15.4. SARA 313 Toxic Chemical Notification and Release Reporting

15.4.1. : No components were identified.

15.5. CERCLA

15.5.1. No components were identified.

15.6. Clean Water Act (CWA)

15.6.1. This material is classified as an oil under Section 311 of the Clean Water Act (CWA) and the Oil Pollution Act of 1990 (OPA). Discharges or spills which produce a visible sheen on waters of the United States, their

SAFETY DATA SHEET – POULAN PRO SYNTHETIC 2 STROKE

adjoining shorelines, or into conduits leading to surface waters must be reported to the EPA's National Response Center at (800) 424-8802.

15.7. California Proposition 65:

15.7.1. The product contains chemicals known to the state of California to cause cancer, birth defects, or any other reproductive harm.

15.8. New Jersey Right-to-Know Label

15.8.1. Petroleum Oil

15.9. WHMIS HAZARD SYMBOL AND CLASSIFICATION

15.9.1. NOT CLASSIFIED

16. OTHER INFORMATION

16.1.

HAZARD RANKINGS			
HMIS		NFPA	
HEALTH HAZARD	1	HEALTH HAZARD	1
FIRE HAZARD	1	FIRE HAZARD	1
PHYSICAL HAZARD	0	INSTABILITY/REACTIVITY	0
Personal Protection	B		

Components Hazard Statements	
H226	Flammable liquid and vapor.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H413	May cause long lasting harmful effects to aquatic life.

16.2. **Date of preparation:** 12/9/2013

16.3. **Revised:** 03/18/2015

16.4. MANUFACTURER DISCLAIMER:

16.4.1. *The data presented herein is based upon tests and information, which we believe to be reliable.*

However, users should make their own investigations to determine the suitability of the information for their particular purpose.