Tulip Dimensional Fabric Paint



MATERIAL SAFETY DATA SHEET

1. COMPANY AND PRODUCT IDENTIFICATION

DUNCAN ENTERPRISES

5673 East Shields Avenue Fresno, CA 93727

559-291-4444

559-291-9444 (Fax)

EMERGENCY TELEPHONE NUMBERS

Health Emergency:

559-291-4444 7:00 am - 3:30 pm

Pacific Standard Time

Spill and Off-Hour

Health Emergencies:

800-424-9300

U.S. and Canada

703-527-3887

Outside U.S. and

Canada (Collect)

Product Name:

65000, FLG, FLGL, FLIS, FLP, FLS, FLGL, FLIP, FLM, GP, IP and SP

SERIES TULIP SLICKS, PEARLS, GLITTERS, CRYSTALS, PUFFS,

MATTES, GLOWS, METALLICS, GELLIES, EXTENDER

Product Description: Dimensional Fabric Paint

2. COMPOSITION / INFORMATION ON INGREDIENTS

The ingredients in this formulation are a trade secret. All ingredients in the formula are non-hazardous, unless specified in Sections 3 and 15.

3. HAZARDS IDENTIFICATION

HMIS Hazard Ratings for Product

Health:

1

0 = Minimal

Flammability:

0

1 = Slight 2 = Moderate

Reactivity: Personal Protection: 0

See Section 8

3 = Serious

4 = Severe

* = Chronic Effects

No Hazardous Ingredients

4. FIRST AID MEASURES

Eye Contact:

Flush eyes with large amounts of water until irritation subsides. Consult a physician

if irritation persists.

Skin Contact: Wash affected skin areas thoroughly with soap and water. Consult a physician if

irritation persists.

Inhalation:

Move subject to fresh air.

Ingestion:

If swallowed, give two glasses of water to drink. Consult a physician. Never give

anything by mouth to an unconscious person.

5. FIRE FIGHTING MEASURES

Autoignition Temperature:

Unknown

Flash Point:

Not Applicable

Upper Explosive Limit (%):

Not Applicable Not Applicable

Lower Explosive Limit (%): Extinguisher Media:

CO2. Dry Chemical, Foam - Use extinguishing

media appropriate for surrounding fire

Special Firefighting Procedures:

Not Applicable

Page 1 of 5

5. FIRE FIGHTING MEASURES (Continued)

Fire & Explosion Hazards:

Not Applicable

NFPA Flammability Hazard Class:

0 = Insignificant

6. ACCIDENTAL RELEASE MEASURES

Spill or Leak Procedures:

Spills should be taken up with suitable absorbent material and placed in containers. Spill areas can be washed with water; collect wash water for approved disposal. Do not flush to storm sewer or waterway.

For safety and environmental precautions, please review entire Material Safety Data Sheet for necessary

7. HANDLING AND STORAGE

Storage Temperature:

40° - 100°F

Handling / Storage:

information.

Protect from freezing; keep container sealed when not in use

Ventilation Requirements:

8. EXPOSURE CONTROL AND PERSONAL PROTECTION

Conditions Under Which Personal

Protective Equipment Required:

Normal work conditions, maintenance / repair.

Eye Protection Requirements:

Glove Requirements:

Wear safety glasses with side shields. Gloves are not normally required for foreseeable

conditions of use.

Clothing Requirements:

Protective clothing is normally not necessary for

foreseeable conditions of use.

Change / Removal of Clothing:

None required

Wash Requirements:

None

Respirator Requirements:

None required under normal handling conditions.

General Ventilation Requirements:

9. PHYSICAL AND CHEMICAL PROPERTIES

Pure Material or Mixture:

Mixture

Physical Form:

Viscous liquid

Appearance / Physical Description:

Colored viscous liquid; slight odor

Odor Threshold:

Not Available

pH:

8.0 - 8.5

Boiling Point:

> 212°F

Melting / Freezing Point:

< 32°F

Solubility in Water:

Miscible

Not Applicable

Partition Coefficient (n-octanol/water):

0.84 - 1.08

Specific Gravity (Water = 1):

7.0 - 9.0 lb / gal

50 - 60% / wt

Bulk Density: Volatiles:

Evaporation Rate (Water = 1):

17.5 mm Hg @ 20°C (68°F)

Vapor Pressure:

Vapor Density (Air = 1):

Volatile Organic Compounds:

0.62

Autoignition Temperature:

150 g/l Unknown

Flash Point:

Not Applicable

Not Applicable Page 2 of 5

Oxidizing Properties:

10. STABILITY AND REACTIVITY

Stability:

Stable

Incompatibilities:

Materials that react with water.

NFPA Reactivity Hazard Class:

0 = Insignificant

Hazardous Decomposition Products:

Carbon Monoxide, Carbon Dioxide

Hazardous Polymerization:

Will not occur.

11. TOXICOLOGICAL INFORMATION

Short - Term Effects of Exposure

Route of Entry

Acute Effects - Eye:

Slight, transient

Acute Effects - Skin Contact: No hazard in normal industrial use. Acute Effects - Inhalation:

No hazard in normal industrial use.

Acute Effects – Ingestion:

No hazard in normal industrial use.

Long - Term Effects of Exposure

Effect of Chronic Exposure:

This product should be considered non - hazardous and has no known

Target Organs:

chronic effects. Not applicable

Carcinogenicity

None

12. ECOLOGICAL INFORMATION

No Applicable Data

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods:

Waste disposal should be in accordance with existing Federal, State,

and Local environmental regulations.

Empty Container Warnings:

Empty containers may contain product residue; follow MSDS and label

warnings even after they have been emptied.

14. TRANSPORT INFORMATION

U.S. Department of Transportation Information

DOT Shipping Name:

Paints or Stains 149980 Sub. 2

DOT Hazard Class:

Non-hazardous

DOT Reportable Quantity:

None

United Nations Information

U.N. Number: None

U.N. Class:

None

15. REGULATORY INFORMATION

TSCA:

All components are on the TSCA Inventory

FDA:

21CFR175.105

SARA/Title III:

This product contains no substances at or above the reported threshold under

Section 313, based on available data.



Products bearing the Nontoxic Product Seal are certified in a program of toxicological evaluation by a nationally recognized toxicologist to contain no materials in sufficient quantities to be toxic or injurious to humans or to cause acute or chronic health problems. These products are certified to be labeled in accordance with the voluntary chronic hazard labeling standard ASTM D-4236. In addition, there is no physical hazard as defined within 29 CFR Part 1910.1200(c).

16. OTHER INFORMATION

Table of Abbreviations

American Conference of Governmental Industrial Hygienists **ACGIH**

American National Standards Institute ANSI American Society for Testing Materials **ASTM**

Degrees Centigrade °C Chemical Abstract Service

CAS Comprehensive Environmental Response, Compensation and Liability Act **CERCLA**

Code of Federal Regulations CFR Controlled Products Regulations **CPR** Department of Transportation DOT **Environmental Protection Agency EPA**

Degrees Fahrenheit OF

Food & Drug Administration FDA

Grams per liter q/1

Mercury Hg

Hazardous Materials Identification System HMIS International Agency for Research on Cancer IARC

Lethal Dose LD

Milligram per kilogram mg / kg

Millimeter mm

Material Safety Data Sheet **MSDS**

Mine Safety and Health Administration **MSHA**

Not Applicable N/A

National Fire Protection Association **NFPA**

National Institute for Occupational Safety and Health NIOSH

National Toxicology Program NTP

Occupational Safety and Health Administration **OSHA**

Parts per million ppm

Superfund Amendment and Reauthorization Act SARA

Short-Term Exposure Limit STEL Toxic Substances Control Act **TSCA** Time - Weighted Average TWA

United Nations U.N.

Workplace Hazardous Materials Information System WHMIS

Greater Than Less Than <

16. OTHER INFORMATION (Continued)

Creation Date: Revision Date: 01/97 05/09/02 Frank Peters

Technical Contact:

R&D Chemist Duncan Enterprises 5673 East Shields Avenue

Fresno, CA 93727 559-291-4444 559-291-9444 (Fax)

<u>Disclaimer</u>

The information given and the recommendations made herein apply to our product(s) alone and not combined with any other product(s). Such are based on our research and on data from other reliable sources and are believed to be accurate. No guarantee of accuracy is made. It is the purchaser's responsibility before using any product to verify this data under their own operating conditions and to determine whether the product is suitable for their purposes.