## Tulip Dimensional SLick Paints

# LOVETOCREATE®

### **Safety Data Sheet**



#### 1. COMPANY AND PRODUCT IDENTIFICATION

**iLoveToCreate** 

A Duncan Enterprises Company 5673 East Shields Avenue Fresno. CA 93727 559-291-4444 559-291-9444 (Fax)

**EMERGENCY TELEPHONE NUMBERS** 

**Health Emergencies:** 

559-291-4444 7:00 am - 3:30 pm Pacific Std. Time

Spill and Off-Hour Health Emergencies:

800-424-9300 U.S. and Canada

703-527-3887 Outside U.S. and Canada (Collect)

**Product Name:** 

**TULIP 3D FASHION PAINT** 

**Product Description:** 

Dimensional Fabric Paint

#### 2. HAZARDS IDENTIFICATION

HMIS Hazard Ratings for Product		Rating Scale: 0 = Minimal 1 = Slight
Personal Protection	See Section 8	3 = Serious 4 = Severe * = Chronic Effects

#### 3. COMPOSITION / INGREDIENT INFORMATION

The ingredients in this formulation are a trade secret. All ingredients in the formula are nonhazardous, unless specified in Sections 2 and 15.

#### 4. FIRST AID MEASURES

Eye Contact:

Flush eyes with large amounts of water until irritation subsides. Consult a

physician if irritation persists.

Skin

Wash affected skin areas thoroughly with soap and water. Consult a physician if

Contact:

irritation persists.

Inhalation:

Move subject to fresh air.

Ingestion:

If swallowed, give two glasses of water to drink. Consult a physician. Never give

anything by mouth to an unconscious person.

#### 5. FIRE FIGHTING MEASURES

**Autoignition Temperature:** 

Unknown

Flash Point:

Not Applicable

Upper Explosive Limit (%):

Not Applicable

Lower Explosive Limit (%):

Not Applicable

**Extinguisher Media:** 

CO2, Dry Chemical, Foam - Use extinguishing

media appropriate for surrounding fire

**Special Firefighting Procedures:** 

Not Applicable

Fire & Explosion Hazards:

Not Applicable 0 = Insignificant

NFPA Flammability Hazard Class:

#### 6. ACCIDENTAL RELEASE MEASURES

Spills should be taken up with suitable absorbent material and placed in Spill or Leak containers. Spill areas can be washed with water, collect wash water for

Procedures: approved disposal. Do not flush to storm sewer or waterway.

For safety and environmental precautions, please review entire Safety Data Sheet for necessary information.

#### 7. HANDLING AND STORAGE

Storage Temperature: 40° - 100°F

Protect from freezing; keep container sealed when not in use. Handling / Storage:

Ventilation Requirements: General

#### 8. EXPOSURE CONTROL AND PERSONAL PROTECTION

**Conditions Under Which Personal** 

Normal work conditions, maintenance / repair. **Protective Equipment Required:** Wear safety glasses with side shields.

**Eye Protection Requirements:** 

Gloves not normally required for foreseeable conditions of **Glove Requirements:** 

Protective clothing is normally not necessary for **Clothing Requirements:** 

foreseeable conditions of use.

Change / Removal of Clothing: None required

Wash Requirements:

None

**Respirator Requirements:** None required under normal handling conditions.

**Ventilation Requirements:** General

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Mixture Pure Material or Mixture: Viscous liquid **Physical Form:** 

Colored viscous liquid; slight odor **Appearance / Physical Description:** 

**Boiling Point:** > 212°F **Melting / Freezing Point:** < 32°F

**Odor Threshold:** Not Applicable Solubility in Water: Miscible

Not Applicable Partition Coefficient (n-octanol/water): 0.84 - 1.08Specific Gravity (Water = 1): 7.0 - 9.0 lb/gal **Bulk Density:** 

>50% / wt Volatiles:

Vapor Pressure: 17.5 mm Hg @ 20°C (68°F)

Evaporation Rate (Water = 1): 0.62

Vapor Density (Air = 1): Volatile Organic Compounds: 150 a / 1 Unknown Autoignition Temperature: Not Applicable Flash Point:

Not Applicable **Oxidizing Properties:** 

#### 10. STABILITY AND REACTIVITY

Stability:

Stable

Incompatibilities:

Materials that react with water

**NFPA Reactivity Hazard Class:** 

0 = Insignificant

**Hazardous Decomposition Products:** 

Carbon monoxide, carbon dioxide

**Hazardous Polymerization:** 

Will not occur

#### 11. TOXICOLOGICAL INFORMATION

#### Acute (Short-Term) Effects of Exposure

Route of Entry

Acute Effects - Eye:

Slight, transient

Acute Effects - Skin Contact: Acute Effects – Inhalation:

No hazard in normal industrial use No hazard in normal industrial use

Acute Effects – Ingestion:

No hazard in normal industrial use

Chronic (Long-Term) Effects of Exposure

**Effect of Chronic** 

This product should be considered non - hazardous and has no known chronic effects.

**Exposure: Target Organs:** 

Not applicable

Carcinogenicity:

None

#### 12. ECOLOGICAL INFORMATION

#### No Applicable Data

#### 13. DISPOSAL CONSIDERATIONS

Waste Disposal

Methods:

Waste disposal should be in accordance with existing Federal, State, and Local environmental regulations.

**Empty Container** Warnings:

Empty containers may contain product residue; follow SDS and label

warnings even after they have been emptied.

#### 14. TRANSPORT INFORMATION

U.S. Department of Transportation Information

**DOT Shipping Name:** 

Paints or Stains 149980 Sub. 2

**DOT Hazard Class:** 

Non-hazardous

**DOT Reportable Quantity:** 

None

**United Nations Information** 

U.N. Number: U.N. Class:

None None

#### 15. REGULATORY INFORMATION

TSCA: All components are on the TSCA Inventory

**FDA:** 21CFR175.105

SARA/Title III: This product contains no substances at or above the reported threshold under

Section 313, based on available data.

CONFORMS TO
NONTOXIC
ASTM D-4236

Products bearing the Nontoxic Product Seal are certified in a program of toxicological evaluation by a nationally recognized toxicologist to contain no materials in sufficient quantities to be toxic or injurious to humans or to cause acute or chronic health problems. These products are certified to be labeled in accordance with the voluntary chronic hazard labeling standard ASTM D-4236. In addition, there is no physical hazard as defined within 29 CFR Part

1910.1200(c).

#### **16. OTHER INFORMATION**

	Table of Abbreviations		
ACGIH	American Conference of Governmental Industrial Hygienists		
ANSI	American National Standards Institute		
ASTM	American Society for Testing Materials		
°C	Degrees Centigrade		
CAS	Chemical Abstract Service		
CERCLA	Comprehensive Environmental Response, Compensation and Liability Act		
CFR	Code of Federal Regulations		
CPR	Controlled Products Regulations		
DOT	Department of Transportation		
EPA	Environmental Protection Agency		
°F	Degrees Fahrenheit		
FDA	Food & Drug Administration		
g/I	Grams per liter		
DOT	Department of Transportation		
EPA	Environmental Protection Agency		
°F	Degrees Fahrenheit		
FDA	Food & Drug Administration		
g/I	Grams per liter		
Hg	Mercury		
HMIS	Hazardous Materials Identification System		
IARC	International Agency for Research on Cancer		
LD	Lethal Dose		
mg / kg	Milligram per kilogram		
mm	Millimeter		
MSHA	Mine Safety and Health Administration		
N/A	Not Applicable		
NFPA	National Fire Protection Association		
NIOSH	National Institute for Occupational Safety and Health		
NTP	National Toxicology Program		
OSHA	Occupational Safety and Health Administration		
ppm	Parts per million		
SARA	Superfund Amendment and Reauthorization Act		
SDS	Safety Data Sheet		
STEL	Short-Term Exposure Limit		

#### 16. OTHER INFORMATION (Continued)

Table of Abbreviations (Continued)			
TSCA	Toxic Substances Control Act		
TWA	Time - Weighted Average		
U.N.	United Nations		
WHMIS	Workplace Hazardous Materials Information System		
>	Greater Than		
<	Less Than		

Creation Date: 01/15/09
Revision Date: 03/13/15
Technical Contact: Frank Peters
Research & Development Manager
iLoveToCreate
A Duncan Enterprises Company
5673 East Shields Avenue
Fresno, CA 93727
559-291-4444

559-291-4444 559-291-9444 (Fax)

#### **Disclaimer**

The information given and the recommendations made herein apply to our product(s) alone and not combined with any other product(s). Such are based on our research and on data from other reliable sources and are believed to be accurate. No guarantee of accuracy is made. It is the purchaser's responsibility before using any product to verify this data under their own operating conditions and to determine whether the product is suitable for their purposes.