SAFETY DATA SHEET

1. Identification

Recommended use

Product identifier CRC Technician Grade Wire Wire Dryer

Other means of identification

Product code 05104

Wire drver

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufactured or sold by:

Company name

CRC Industries. Inc. 885 Louis Dr. -

Address

Warminster, PA 18974 US

Telephone

General Information

215-674-4300 800-521-3168

Technical **Assistance**

800-272-4620

Customer Service 24-Hour Emergency

800-424-9300 (US)

(CHEMTREC)

703-527-3887 (International)

Website

www.crcindustries.com

2. Hazard(s) identification

Physical hazards Flammable aerosols Category 1

> Gases under pressure Compressed gas

Health hazards Skin corrosion/irritation Category 2

> Specific target organ toxicity, single exposure Category 3 narcotic effects

Aspiration hazard

Category 1

Dryer Dries Wet Ignition

System 05104

Environmental hazards

OSHA defined hazards

Not classified.

Not classified.

Label elements



Signal word

Danger

Hazard statement

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways. Causes skin irritation. May cause drowsiness or dizziness.

Precautionary statement

Prevention

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Do not apply while equipment is energized. Pressurized container: Do not pierce or burn, even after use. Extinguish all flames, pilot lights and heaters. Vapors will accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Avoid breathing mist or vapor. Wash thoroughly after handling. Wear protective gloves.

Response

If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If inhaled: Remove person to fresh air and keep comfortable for

breathing. Call a poison center/doctor if you feel unwell.

Storage Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to

temperatures exceeding 50°C/122°F. Exposure to high temperature may cause can to burst.

Material name: Wire Dryer

SDS US 05104 Version #: 01 Issue date: 05-21-2015

Disposal

Hazard(s) not otherwise classified (HNOC)

Dispose of contents/container in accordance with local/regional/national regulations.

None known.

3. Composition/information on ingredients

lixtures				
Chemical name	Common name and synonyms	CAS number	%	
Distillates (petroleum), hydrotreated light		64742-47-8	60 - 70	
Distillates (petroleum), solvent-refined heavy paraffinic		64741-88-4	10 - 20	
Carbon dioxide		124-38-9	3 - 5	
n-Butyl stearate		123-95-5	3 - 5	
Fatty Acids, C18-unsatd., Dimers		61788-89-4	1 - 3	
Petrolatum		8009-03-8	1 - 3	
Sorbitan monooleate		68910-94-1	1 - 3	
Sorbitan oleate		1338-43-8	1 - 3	
Vanilla fragrances		Proprietary	< 0.3	

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

sh air and keep at rest in a position comfortable for breathing. Call a POISON
hysician if you feel unwell.
ed clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical sh contaminated clothing before reuse.
t medical attention if irritation develops and persists.
pison control center immediately. Rinse mouth. Do not induce vomiting. If phead low so that stomach content doesn't get into the lungs.
ss and dizziness. Headache. Nausea, vomiting. Aspiration may cause and pneumonitis. Diarrhea. Skin irritation. May cause redness and pain.
portive measures and treat symptomatically. Keep victim under observation. elayed.
personnel are aware of the material(s) involved, and take precautions to
m. Water fog. Dry chemical powder. Dry chemicals. Carbon dioxide (CO2).
as an extinguisher, as this will spread the fire.
sure. Pressurized container may rupture when exposed to heat or flame. zardous to health may be formed.
standard protective equipment including flame retardant coat, helmet with ubber boots, and in enclosed spaces, SCBA.
eak if safe to do so. Move containers from fire area if you can do so without exposed to heat with water spray and remove container, if no risk is involved. e cooled with water to prevent vapor pressure build up.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many vapors are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop the flow of material, if this is without risk. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. Avoid breathing mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged or repeated contact with skin. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices. For product usage instructions, please see the product label.

Conditions for safe storage, including any incompatibilities

Level 3 Aerosol.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

upational exposure limits			
U.S OSHA			
Components	Туре	Value	Form
Fatty Acids, C18-unsatd., Dimers (CAS 61788-89-4)	TWA	5 mg/m3	Respirable
US. OSHA Table Z-1 Limits for Air Co	ontaminants (29 CFR 1910.1000)		_
Components	Туре	Value	Form
Carbon dioxide (CAS 124-38-9)	PEL	9000 mg/m3	
		5000 ppm	
Distillates (petroleum), solvent-refined heavy paraffinic (CAS 64741-88-4)	PEL	5 mg/m3	Mist.
, , , , , , , , , , , , , , , , , , , ,		2000 mg/m3	
		500 ppm	
Petrolatum (CAS 8009-03-8)	PEL	5 mg/m3	Mist.
ACGIH			
Components	Туре	Value	Form
Fatty Acids, C18-unsatd., Dimers (CAS 61788-89-4)	STEL	10 mg/m3	Respirable
,	TWA	5 mg/m3	Respirable
US. ACGIH Threshold Limit Values			
Components	Туре	Value	Form
Carbon dioxide (CAS 124-38-9)	STEL	30000 ppm	
•	TWA	5000 ppm	

Material name: Wire Dryer

Components	Туре	Value	Form
Distillates (petroleum), solvent-refined heavy paraffinic (CAS 64741-88-4)	TWA	5 mg/m3	Inhalable fraction.
n-Butyl stearate (CAS 123-95-5)	TWA	10 mg/m3	
Petrolatum (CAS 8009-03-8)	TWA	5 mg/m3	Inhalable fraction.
US. NIOSH: Pocket Guide to	Chemical Hazards		
Components	Туре	Value	Form
Carbon dioxide (CAS 124-38-9)	STEL	54000 mg/m3	
		30000 ppm	
	TWA	9000 mg/m3	
		5000 ppm	
Distillates (petroleum), hydrotreated light (CAS 64742-47-8)	TWA	100 mg/m3	
Distillates (petroleum), solvent-refined heavy paraffinic (CAS 64741-88-4)	Ceiling	1800 mg/m3	
,	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
Petrolatum (CAS 8009-03-8)	STEL	10 mg/m3	Mist.
•	TWA	5 mg/m3	Mist.
ogical limit values	No biological exposure limits noted for	or the ingredient(s).	
ropriate engineering rols	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.		

Eye/face protection

Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection

Wear protective gloves such as: Nitrile. Neoprene.

Other

Wear appropriate chemical resistant clothing.

Respiratory protection

If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to

determine actual employee exposure levels.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work

clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance		
Physical state	Liquid.	
Form	Aerosol.	
Color	Blue green.	
Odor	Vanilla.	
Odor threshold	Not available.	
рН	Not available.	
Molting point/fronzing point	72 4 °E (58 °C	

Melting point/freezing point

-72.4 °F (-58 °C) estimated

Initial boiling point and boiling 212 °F (100 °C) estimated

range

Material name: Wire Dryer

Flash point

187 °F (86.1 °C) Tag Closed Cup

Evaporation rate

Slow.

Flammability (solid, gas)

Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower

0.6 % estimated

(%)

(/0)

Flammability limit - upper (%)

er 5

5.5 % estimated

1811.3 hPa estimated

Vapor pressure

> 1 (air = 1)

Vapor density Relative density

- 1 (all - 1)

Troiding density

0.84 estimated

Solubility (water)

Negligible.

Partition coefficient

Not available.

(n-octanol/water)

456.8 °F (236 °C) estimated

Auto-ignition temperature Decomposition temperature

Not available.

Viscosity (kinematic)

Not available.

Percent volatile

88 % estimated

10. Stability and reactivity

Reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability

Material is stable under normal conditions.

Possibility of hazardous reactions

S

No dangerous reaction known under conditions of normal use.

Conditions to avoid

Heat, flames and sparks. Avoid temperatures exceeding the flash point. Contact with incompatible

materials.

Incompatible materials

Strong oxidizing agents.

Hazardous decomposition

products

Carbon oxides.

11. Toxicological information

Information on likely routes of exposure

Inhalation

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be

harmful.

Skin contact

Causes skin irritation.

Eye contact

Direct contact with eyes may cause temporary irritation.

Ingestion

Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious

chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics

Headache. May cause drowsiness and dizziness. Nausea, vomiting. Diarrhea. Aspiration may cause pulmonary edema and pneumonitis. Skin irritation. May cause redness and pain.

Information on toxicological effects

Acute toxicity

May be fatal if swallowed and enters airways. Narcotic effects.

Product Wire Dryer

Acute

Dermal

Jermai

LD50

Rabbit

Species

2148 mg/kg estimated

Test Results

Inhalation

LC50

Rat

6.3 mg/l, 4 hours estimated

Oral

LD50

Rat

5352 mg/kg estimated

^{*} Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye

Direct contact with eyes may cause temporary irritation.

irritation

Respiratory sensitization

Not a respiratory sensitizer.

Skin sensitization

This product is not expected to cause skin sensitization.

Germ cell mutagenicity

No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity

This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

Reproductive toxicity

This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

May cause drowsiness and dizziness.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard

May be fatal if swallowed and enters airways. If aspirated into lungs during swallowing or vomiting,

may cause chemical pneumonia, pulmonary injury or death.

Chronic effects

Prolonged inhalation may be harmful.

12. Ecological information

cotoxicity	The produpossibility	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.		
Product		Species	Test Results	
Wire Dryer				
Aquatic				
Crustacea	EC50	Daphnia	5297.5435 mg/l, 48 hours estimated	
Acute				
Fish	LC50	Fish	4941.936 ppm, 96 hours estimated	
Components		Species	Test Results	
Distillates (petroleum)	, hydrotreated light	(CAS 64742-47-8)		
Aquatic				
Acute				
Fish	LC50	Bluegill (Lepomis macrochirus)	2.2 mg/l, 96 hours	
Sorbitan oleate (CAS	1338-43-8)			
Aquatic				
Acute				
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	> 1000 mg/l, 96 hours	

^{*} Estimates for product may be based on additional component data not shown.

Persistence and degradability

No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Fatty Acids, C18-unsatd., Dimers

1 - 2.5, logKow

Mobility in soil

No data available.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal of waste from residues / unused products

The dispensed liquid product is not a RCRA hazardous waste (See 40 CFR Part 261.20 - 261.33). Empty container can be recycled. Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose in accordance with all applicable regulations.

Hazardous waste code

Not regulated.

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

Material name: Wire Dryer

14. Transport information

DOT

UN number

UN1950

UN proper shipping name

Transport hazard class(es)

Class Subsidiary risk 2.1

Label(s) Packing group 2.1

Not applicable. Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions

N82 306

Packaging exceptions Packaging non bulk

None

Packaging bulk

None

IATA

UN number

UN1950

UN proper shipping name Transport hazard class(es) Aerosols, flammable, Limited Quantity

Aerosols, flammable, Limited Quantity

Class

Subsidiary risk

2.1

Packing group

Not applicable.

Environmental hazards

No.

ERG Code Special precautions for user

Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

Allowed.

aircraft

Cargo aircraft only

Allowed.

IMDG

UN number

UN1950

UN proper shipping name

AEROSOLS, LIMITED QUANTITY

Transport hazard class(es)

Class

2

Subsidiary risk

Packing group

Not applicable.

Environmental hazards

Marine pollutant

No.

EmS

Not available.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910,1001-1050)

Not listed.

SARA 304 Emergency release notification

Not regulated.

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

CERCLA Hazardous Substances: Reportable quantity

Not listed.

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Material name: Wire Dryer

SDS US

05104 Version #: 01 Issue date: 05-21-2015

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

Food and Drug

Not regulated.

Administration (FDA)

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 311/312 **Hazard categories** Immediate Hazard - Yes Delayed Hazard - No Fire Hazard - Yes

Pressure Hazard - Yes Reactivity Hazard - No

SARA 302 Extremely

No

hazardous substance

US state regulations

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd.

Distillates (petroleum), hydrotreated light (CAS 64742-47-8)

Distillates (petroleum), solvent-refined heavy paraffinic (CAS 64741-88-4)

Petrolatum (CAS 8009-03-8)

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. New Jersey Worker and Community Right-to-Know Act

Carbon dioxide (CAS 124-38-9)

Distillates (petroleum), hydrotreated light (CAS 64742-47-8)

US. Massachusetts RTK - Substance List

Carbon dioxide (CAS 124-38-9)

US. Pennsylvania Worker and Community Right-to-Know Law

Carbon dioxide (CAS 124-38-9)

Distillates (petroleum), hydrotreated light (CAS 64742-47-8)

US. Rhode Island RTK

None.

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

Volatile organic compounds (VOC) regulations

EPA

VOC content (40 CFR

100 %

51.100(s))

Consumer products

Not regulated

(40 CFR 59, Subpt. C)

State

Consumer products

Not regulated

VOC content (CA)

0 %

VOC content (OTC)

0 %

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No

Country(s) or region Inventory name On inventory (yes/no)*

Japan Inventory of Existing and New Chemical Substances (ENCS)

Korea Existing Chemicals List (ECL)

Philippines Philippine Inventory of Chemicals and Chemical Substances No

(PICCS)

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date05-21-2015Prepared byAllison Cho

Version # 01

Further information CRC # 510E
HMIS® ratings Health: 1

Flammability: 3 Physical hazard: 0 Personal protection: B

NFPA ratings Health: 1

Flammability: 3 Instability: 0

NFPA ratings



Disclaimer

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries.

SDS US

Yes