

SAFETY DATA SHEET

Product Name: WITE-OUT® Brand Correction Fluids (Super Smooth, Extra Coverage, and Quick Dry)

Date Prepared: May 27, 2015

Version 9

SECTION 1 - IDENTIFICATION			
Product Name:	WITE-OUT® Brand Correction Fluids (Super Smooth, Extra Coverage, and Quick Dry)		
Synonyms:	Different Products: 1- Quick Dry WQ5- White 2- Quick Dry WQ5- Buff 3- Extra Coverage WE4 4- Super Smooth WS4 5- Cover-It		
Product Use:	Correction fluid		
Manufacturer/ Vendor Information:	Manufactured for/Distributed by: BIC Corporation One BIC Way, Suite 1 Shelton, CT 06484 USA (203) 783-2000 Emergency Telephone Number: (203) 783-2412		
	Supplier Information: BIC Inc. 155 Oakdale Road Downsview, Ontario M3N 1W2 CANADA (416) 742-9173 x288 (Business hours)		
SDS Contact:	Product Safety		
Telephone number:	(203) 783-2124		

	SECTION 2 - HAZARDS IDENTIFICATION	
	er product and is not subject to the requirements of OSHA HCS 2012. None azard identification in accordance with HCS/HazCom 2012, is provided for the ers.	
Classification in accordance with 29 CFR § 1910.1200:	Flammable Liquid – Category 2 Specific Target Organ Toxicity – Single Exposure (STOT-SE) – Category 3 (narcotic effects) Aspiration Hazard – Category 1	
Signal Word:	Danger	
Hazard Statements:	Highly flammable liquid and vapor. May be fatal if swallowed and enters airways. May cause drowsiness of dizziness.	
Symbols:		

WITE-OUT® Brand Correction Fluids

SAFETY DATA SHEET according to the HCS/HazCom 2012 (29 CFR § 1910.1200)

Precautionary	Prevention:			
Statements:	Avoid breathing vapors.			
	Keep away from heat/sparks/open flames/hot surfaces No smoking.			
	Keep container tightly closed.			
	Take precautionary measures against static discharge.			
	Use explosion-proof electrical/ventilating/lighting/equipment.			
	Use only non-sparking tools.			
	Use only outdoors or in a well-ventilated area.			
	Wear protective gloves/eye protection/face protection.			
	Response:			
	Do NOT induce vomiting			
	If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a			
	poison center/doctor if you feel unwell.			
1 1 1	If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with			
	water/shower.			
· ·	If swallowed: Immediately call a poison center/doctor.			
	Starogo			
	Storage: Store in a well-ventilated place. Keep cool.			
	Store locked up.			
	otore locked up.			
	Disposal:			
	Dispose of contents/container in accordance with local / regional / national /			
	international regulations.			
	international rogalizations.			
	9% of the mixture consists of ingredients of unknown acute dermal toxicity			
Any Hazards Not	None			
Otherwise Classified:				
	or more information refer to Section 11 of this SDS			

Preparation:		
CAS No.	Chemical Name	% by Weight
13463-67-7	Titanium dioxide	30-60%
64741-66-8	Naphtha (petroleum), light alkylate	Products 1-2: 7-13% Products 3-4: 15-40%
64742-49-0	Naphtha, petroleum, hydrotreated light	Products 1-3: 15-40% Product 4: 7-13%

SAFETY DATA SHEET according to the HCS/HazCom 2012 (29 CFR § 1910.1200)

	SECTION 4 - FIRST-AID MEASURES
ger	ickly and gently blot or brush away chemical. Flush contaminated eye(s) with lukewarm, ntly flowing water for 5 minutes or until the chemical is removed. If irritation occurs, ain medical advice.
che	ritation does occur, flush with lukewarm gently flowing water for 5 minutes or until emical is removed. Remove contaminated clothing, shoes, and leather goods (e.g. tchbands) as the product is highly flammable. If irritation occurs, obtain medical advice.
hea	reathing has stopped, trained personnel should begin artificial respiration (AR) or, if the art has stopped, cardiopulmonary resuscitation (CPR) immediately. Immediately asport victim to an emergency care facility.
Ingestion: DO hav	NOT INDUCE VOMITING. Aspiration hazard if swallowed. If vomiting occurs naturally, we victim lean forward to reduce risk of aspiration. Transport victim to an emergency care lity if necessary
Most Important Syi	mptoms and Effects, Both Acute and Delayed
Symptoms/Injuries after Inhalation:	Deliberately concentrating and inhaling this product can lead to Central Nervous System (CNS) effects, unconsciousness and/or death. Product may be irritating if inhaled accidentally.
Symptoms/Injuries after Skin Contact:	Short-term exposure is expected to cause only slight irritation, if any.
Symptoms/Injuries after Eye Contact:	Mild eye irritation may occur if product comes in contact with eyes.
Symptoms/Injuries after Ingestion:	Ingestion of this product may cause CNS depression, symptoms of which may include; weakness, dizziness, slurred speech, drowsiness, unconsciousness and in cases of severe overexposure; coma and death. Ingestion of this product may lead to aspiration of the liquid, especially if vomiting occurs. This may result in chemical pneumonitis (inflammation of the lungs) and/or pulmonary edema (an accumulation of fluid in the lungs).
ndication of Any In	nmediate Medical Attention and Special Treatment Needed
Freat symptomatic	ally.

	SECTION 5 - FIRE-FIGHTING MEASURES
Extinguishing Media:	Suitable: CO ₂ , Foam, Dry Chemical Unsuitable: Water stream or jet
Conditions of Flammability:	HIGHLY FLAMMABLE. Can release vapors that form flammable mixtures at or above the flash point.
Special Firefighting Procedures:	Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes.
Hazardous Combustion Products:	Carbon monoxide, carbon dioxide, reactive hydrocarbons, carbonyl compounds, smoke and irritating vapors may be formed on combustion.

SI	ECTION 6 — ACCIDENTAL RELEASE MEASURES
Personal Precautions:	Highly flammable liquid. Ventilate area.
Methods for Containment and Cleaning Up:	Avoid contaminating sewers, streams, rivers and other watercourses with spilled material absorb with inert absorbent material (do not use combustible materials like cloth or paper) and dispose of properly.

	SECTION 7 – HANDLING AND STORAGE
Handling	
Precautions for Safety	Highly flammable liquid. Avoid contact with eyes and skin. Wash thoroughly after
	handling this product if in contact with skin. Avoid contact with heat, and sources of
	ignition.

according to the HCS/HazCom 2012 (29 CFR § 1910.1200)

Storage	Store in cool, dry, well-ventilated area. Store away from incompatible and reactive
	materials (See Section 10). Keep container tightly closed. Store away from heat and
	sources of ignition.

SECTION	l 8 – EXPO	SURE CONTRO	OLS/ PERSONAL PROTECTION
Control parameters			
Chemical Name		CAS Number	Exposure Limits
Titanium dioxide		13463-67-7	ACGIH: (TLV-TWA) 10 mg/m ³ OSHA: (PEL-TWA) 15 mg/m ³
Naphtha, petroleum, hydrotreated light		64742-49-0	ACGIH: (TLV-TWA) 400 ppm ACGIH: (TLV-STEL) 500 ppm OSHA: (PEL-TWA) 500 ppm (Recommended based on a similar product – Heptane)
The selection of personal prappropriate to your particula			epending upon the conditions of use. Use equipment
Engineering Measures: F	For normal application, special ventilation is not necessary.		
Eye Protection:	Not required	under normal use	e conditions.
Hand Protection:	None necessary under normal use conditions.		
Skin and Body Protection: N	None necessary under normal use conditions.		
Respiratory Protection:	None necessary under normal use conditions.		

ACGIH = American Conference of Governmental Industrial Hygienists

OSHA = Occupational Safety & Health Administration

PEL = Permissible Exposure Limit

TLV = Threshold Limit Values

TWA = Time-Weighted Average

STEL = Short-Term Exposure Limit

SEG	TION 9 - PHYSICAL AND CHEMICAL PROPERTIES
Appearance & Physical State:	Free flowing white liquid
Odor:	Petroleum solvent odor
Odor Threshold:	Not Available
pH:	Not Available
Melting Point:	-22.2 to -13.3°C (-8 to +8°F)
Boiling Point:	95.6-113.9°C (204-237°F)
Flash point:	WQ5: -10°C (14°F) (ASTM D3828-05) WE4: -5°C (23°F) WS4: 0.9°C (33.6°F)
Evaporation Rate:	0.89-1.08 (Butyl Acetate=1)
Flammability (solid/gas):	Highly flammable vapors
Flammable Limits in Air Lower (LFL): Upper (UFL):	1.7% by volume 12.3 % by volume
Vapor Pressure:	26-49 mmHg at 20°C
Vapor Density:	3.4-4.0 (estimated) (air =1)
Density/Specific Gravity:	1.25 (Water =1)
Solubility in Water:	0.1g/L at 20°C

SAFETY DATA SHEET according to the HCS/HazCom 2012 (29 CFR § 1910.1200)

Octanol/ Water Partition Coefficient	Not Available		
Auto-ignition Temperature:	~246.1°C (based on petroleum solvent - approximate)		
Decomposition Temperature:	Not Available		
Viscosity:	Not Available		

Reactivity:	SECTION 10 – STABILITY AND REACTIVITY This product is stable under the normal conditions of use.	
Chemical Stability:	Stable	
Possibility of Hazardous Reactions:	Not expected to undergo hazardous polymerization.	
Conditions to avoid:	Avoid heat sources, sparks or flames and static discharge.	
Incompatible Materials:	Avoid strong oxidizing or reducing agents, strong acids and strong bases.	
Hazardous Decomposition Products:	Not expected to undergo decomposition.	

The state of the s	Annual and Annual Administration of the Control of	COLOGICAL INFORMA	
Routes of Entry:	Skin contact, Inhalation, Eye contact, Skin Absorption, Ingestion		
Acute Toxicity Product data: Route & Species	Value		
Oral; rat, LD ₅₀ Inhalation; rat LC ₅₀ Dermal, ATE	>15 g/kg 90-169.4 mg/L/1H >5 g/kg		
ATE = acute toxicity estimate Ingredient data: Chemical		Double & Charica	
	CAS#	Route & Species	<u>Value</u>
Titanium dioxide	13463-67-7	Dermal; rabbit, LD ₅₀	>10 000 mg/kg
Naphtha (petroleum), light alkylate	64741-66-8	Dermal; rabbit, LD ₅₀	>2000 mg/kg
Naphtha petroleum, hydrotreated light	64742-49-0	Dermal; rabbit, LD ₅₀	>3160 mg/kg
Eye Irritation:	Not expected to be a tolerance test.	n eye irritant based on the	e results of an <i>in vitro</i> ocular
Skin Irritation:	Not expected to be a primary skin irritant based on the results of an <i>in-vivo</i> human skin patch test.		
ngestion Effects:	Ingestion of this prod include; weakness, d and in cases of seven product may lead to a may result in chemica pulmonary edema (a	uct may cause CNS deprizziness, slurred speech, re overexposure; coma ar aspiration of the liquid, es al pneumonitis (inflammat n accumulation of fluid in	pecially if vomiting occurs. This ion of the lungs) and/or the lungs).
nhalation Effects:	Deliberately concentrating and inhaling this product can lead to CNS effects, unconsciousness and/or death.		

WITE-OUT® Brand Correction Fluids

SAFETY DATA SHEET

according to the HCS/HazCom 2012 (29 CFR § 1910.1200)

Skin Sensitization:	Contact with this product is not expected to cause skin sensitization, based upon the available data and the known hazards of the components.		
Respiratory Tract Sensitization:	Contact with this product is not expected to cause respiratory tract sensitization, based upon the available data and the known hazards of the components.		
Chronic Toxicity			
Carcinogenicity:	Based on the known hazards of the components, the product is not expected to pose a carcinogenicity risk.		
Mutagenicity:	This product is not known to contain any components at >= 0.1% that have been shown to cause mutagenicity. Therefore, based upon the available data and the known hazards of the components, this product is not expected to be a mutagen.		
Reproductive Toxicity:	This product is not known to contain any components at >= 0.1% that have been shown to cause reproductive toxicity. Therefore, based upon the available data and the known hazards of the components, this product is not expected to be a reproductive toxin.		
Teratogenicity/Embryotoxicity:			
Other Chronic Effects:	Repeated and chronic product abuse such as deliberately concentrating and inhaling this product can result in adverse effects to the CNS such as drowsiness, dizziness and potentially serious long-term health effects.		

	SECTION 12 - ECOLOGICAL INI	IFORMATION
Ecotoxicity:	Not Available	
Persistence/ Degradability:	Not Available	
Bioaccumulation:	Not Available	
Mobility:	Not Available	
Other Adverse Effects:	Not Available	

	SECTION 13 - DISPOSAL CONSIDERATIONS
Waste Disposal Method:	In accordance with local, provincial/territorial or federal guidelines and regulations

SAFETY DATA SHEET according to the HCS/HazCom 2012 (29 CFR § 1910.1200)

	SECTION 14 - TRANSPORT INFORMA	ATION		
	Shipping name	UN Number	Hazard Class	PG
DOT (US)	For domestic transport by road, rail and cargo:			
	Proper Shipping Name: Coating solution	1139	3	II .
	Product packaged in containers less than 5 liters can be shipped as Limited quantity or Consumer Commodity			
IMDG	For International transport by cargo vessel, road, rail: Proper shipping name: Coating Solution NOTE: Shipped as Limited Quantity	1139	3	
IATA	For international transport by Air: Proper Shipping Name: Consumer Commodity	ID8000	9	: - 1, 1

DOT = Department of Transport

IMDG = International Maritime Dangerous Goods

IATA = International Air Transport Association

SECTION 15 - REGULATORY INFORMATION

OSHA Classification: (OSHA Hazard Communication Standard (29 CFR §1910.1200))

This product has been classified in accordance with the hazard criteria of OSHA's HCS/HazCom 2012 and the SDS contains all the information required by the 29 CFR § 1910.1200

Hazard Ratings

	NPCA/HMIS	NFPA 704
Health:	1	1
Flammability:	3	3. ·
Reactivity:	0	0.

All the ingredients in the product are listed on the TSCA inventory. This product requires no labeling as per the State of California's Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65). None of the ingredients in this product are Class I or Class II ozone depletors. None of the ingredients in this product are listed as an Extremely Hazardous Substance under the RCRA, SARA 302/313, Clean Air Act, and Clean Water Act.

Regulated under SARA 311/312 Acute: no Chronic: no Fire: no

SECTION 16 – OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Preparation Date: May 27, 2015 Supersedes Date: November 10, 2014

Disclaimer: The information given is based on data currently available to us and is believed to be correct. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. No responsibility is assumed for injury or damage from the use of the products described herein.