

SAFETY DATA SHEET

CRC Battery Cleaner and Acid Indicator Spray

1. Identification

Product identifier

Battery Cleaner with Acid Indicator

Other means of identification

Product code

05023, 05623

Recommended use

Battery cleaner

Recommended restrictions

None known.

Manufacturer/Importer/Supplier/Distributor information

Manufactured or sold by:

Company name

CRC Industries, Inc.

Address

885 Louis Dr.

Telephone

General Information

215-674-4300

Technical

800-521-3168

Assistance

Customer Service

800-272-4620

24-Hour Emergency

800-424-9300 (US)

(CHEMTREC)

703-527-3887 (International)

Warminster, PA 18974 US

Website

www.crcindustries.com

2. Hazard(s) identification

Physical hazards

Gases under pressure

Liquefied gas

Health hazards

Not classified.

Environmental hazards

Not classified.

OSHA defined hazards

Not classified.

Label elements



Signal word

Warning

Hazard statement

Contains gas under pressure; may explode if heated.

Precautionary statement

Prevention

Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 49°C/120°F. Use with adequate ventilation. Open doors and windows or use other means to

ensure a fresh air supply during use and while product is drying.

Response

Wash hands after handling.

Storage

Protect from sunlight. Store in a well-ventilated place. Exposure to high temperature may cause

can to burst.

Disposal

Dispose of contents/container in accordance with local/regional/national regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%	
Water		7732-18-5	80 - 90	
Liquefied Petroleum Gas		68476-86-8	5 - 10	
2-Butoxyethanol		111-76-2	1-3	

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation

Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact

Rinse skin with water/shower. Get medical attention if irritation develops and persists.

Eye contact

Rinse with water. Get medical attention if irritation develops and persists.

Ingestion

Call a POISON CENTER or doctor/physician.

Most important

ant "o oto o outo o o

symptoms/effects, acute and delayed

Direct contact with eyes may cause temporary irritation.

Indication of immediate medical attention and special

Provide general supportive measures and treat symptomatically.

treatment needed
General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire-fighting equipment/instructions
General fire hazards

In case of fire: Stop leak if safe to do so. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up.

Contents under pressure. Pressurized container may rupture when exposed to heat or flame.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. This product is miscible in water. Stop the flow of material, if this is without risk. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS,

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. Do not get in eyes, on skin, or on clothing. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. For product usage instructions, please see the product label.

Conditions for safe storage, including any incompatibilities

Level 1 Aerosol.

Contents under pressure. Do not expose to heat or store at temperatures above 120°F/49°C as can may burst. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Components	nits for Air Conta	Туре			llue
2-Butoxyethanol (CAS		PEL		24	0 mg/m3
111-76-2)					ppm
US. ACGIH Threshold L	imit Values			30	ррш
Components		Туре) . 	Va	lue
2-Butoxyethanol (CAS 111-76-2)		TWA		20	ppm
US. NIOSH: Pocket Guid	le to Chemical Ha				
Components		Туре		Val	lue
2-Butoxyethanol (CAS 111-76-2)		TWA		24	mg/m3
				5 p	pm
Biological limit values					
ACGIH Biological Expos Components	ure Indices Value		Determinant	Specimen	Sampling Time
2-Butoxyethanol (CAS 111-76-2)	200 mg/g		Butoxyacetic acid (BAA), with hydrolysis	Creatinine in urine	*
* - For sampling details, pl	ease see the sourc	ce docui	ment.		
xposure guidelines					
US - California OELs: Sk	in designation				
2-Butoxyethanol (CAS US - Minnesota Haz Subs	111-76-2)		Can be	absorbed throug	h the skin.
2-Butoxyethanol (CAS		n appu			
US - Tennessee OELs: SI	kin designation		SKIN GE	signation applies	•
US - Tennessee OELs: SI 2-Butoxyethanol (CAS	kin designation	arda. Cla	Can he	absorbed throug	
US - Tennessee OELs: SI 2-Butoxyethanol (CAS US NIOSH Pocket Guide 2-Butoxyethanol (CAS	kin designation 111-76-2) to Chemical Haza 111-76-2)		Can be in designation Can be	absorbed throug	h the skin.
US - Tennessee OELs: SI 2-Butoxyethanol (CAS US NIOSH Pocket Guide 2-Butoxyethanol (CAS US. OSHA Table Z-1 Limit	kin designation 111-76-2) to Chemical Haza 111-76-2) ts for Air Contam		Can be tin designation Can be (29 CFR 1910.100	absorbed throug absorbed throug	h the skin. h the skin.
US - Tennessee OELs: SI 2-Butoxyethanol (CAS US NIOSH Pocket Guide 2-Butoxyethanol (CAS US. OSHA Table Z-1 Limit 2-Butoxyethanol (CAS ppropriate engineering	kin designation 111-76-2) to Chemical Haza 111-76-2) ts for Air Contam 111-76-2) Good general should be ma or other engin	inants (ventilated to be described to be desc	Can be cin designation Can be (29 CFR 1910.100 Can be tion (typically 10 ai conditions. If app	absorbed throug absorbed throug absorbed throug r changes per ho licable, use proce	h the skin. h the skin. h the skin. ur) should be used. Ventilation rates ess enclosures, local exhaust ventilation, helow recommended exposure limits. If
US - Tennessee OELs: SI 2-Butoxyethanol (CAS US NIOSH Pocket Guide 2-Butoxyethanol (CAS US. OSHA Table Z-1 Limi 2-Butoxyethanol (CAS ppropriate engineering ontrols	kin designation 111-76-2) to Chemical Haza 111-76-2) ts for Air Contam 111-76-2) Good general should be mai or other engin exposure limit	inants (ventilated to be deering of the sering of the ser	Can be cin designation Can be (29 CFR 1910.100 Can be tion (typically 10 a conditions. If app controls to maintai not been establish	absorbed throug absorbed throug (0) absorbed throug ir changes per ho licable, use proce n airborne levels ted, maintain airb	h the skin. h the skin. h the skin. ur) should be used. Ventilation rates
US - Tennessee OELs: SI 2-Butoxyethanol (CAS US NIOSH Pocket Guide 2-Butoxyethanol (CAS US. OSHA Table Z-1 Limi 2-Butoxyethanol (CAS ppropriate engineering ontrols	tin designation 111-76-2) to Chemical Haza 111-76-2) ts for Air Contam 111-76-2) Good general should be mai or other engin exposure limit	inants (ventilated to the decring of the decring o	Can be cin designation Can be (29 CFR 1910.100 Can be tion (typically 10 a conditions. If app controls to maintai not been establish	absorbed throug absorbed throug (0) absorbed throug ir changes per ho licable, use proce n airborne levels ed, maintain airb	h the skin. h the skin. h the skin. ur) should be used. Ventilation rates ess enclosures, local exhaust ventilation, helow recommended exposure limits. If
US - Tennessee OELs: SI 2-Butoxyethanol (CAS US NIOSH Pocket Guide of 2-Butoxyethanol (CAS US. OSHA Table Z-1 Limit 2-Butoxyethanol (CAS ppropriate engineering controls dividual protection measure Eye/face protection Skin protection	tin designation 111-76-2) to Chemical Haza 111-76-2) ts for Air Contam 111-76-2) Good general should be mai or other engin exposure limit	inants (ventilated to the decring of the decring o	Can be cin designation Can be (29 CFR 1910.100 Can be tion (typically 10 ai conditions. If app controls to maintai not been establish	absorbed throug absorbed throug (0) absorbed throug ir changes per ho licable, use proce n airborne levels ed, maintain airb	h the skin. h the skin. h the skin. ur) should be used. Ventilation rates ess enclosures, local exhaust ventilation, helow recommended exposure limits. If
US - Tennessee OELs: SI 2-Butoxyethanol (CAS US NIOSH Pocket Guide of 2-Butoxyethanol (CAS US. OSHA Table Z-1 Limit 2-Butoxyethanol (CAS ppropriate engineering controls dividual protection measure Eye/face protection Skin protection Hand protection	tin designation 111-76-2) to Chemical Haza 111-76-2) ts for Air Contam 111-76-2) Good general should be mai or other engin exposure limit s, such as perso Wear safety g	ventilat tched to eering o s have nal prof lasses v	Can be cin designation Can be (29 CFR 1910.100) Can be tion (typically 10 aid to conditions. If appropriate to maintain not been establish tective equipment with side shields (des such as: Nitrile.	absorbed throug absorbed throug (0) absorbed throug ir changes per ho licable, use proce n airborne levels ed, maintain airb	h the skin. h the skin. h the skin. ur) should be used. Ventilation rates ess enclosures, local exhaust ventilation, helow recommended exposure limits. If
US - Tennessee OELs: SI 2-Butoxyethanol (CAS US NIOSH Pocket Guide of 2-Butoxyethanol (CAS US. OSHA Table Z-1 Limit 2-Butoxyethanol (CAS uppropriate engineering ontrols adividual protection measure Eye/face protection Skin protection Hand protection Other	tin designation 111-76-2) to Chemical Haza 111-76-2) ts for Air Contam 111-76-2) Good general should be may or other enginexposure limit ts, such as perso Wear safety g Wear protective Wear suitable	ventilate to the total to the total to the total proof to the total tota	Can be cin designation Can be (29 CFR 1910.100 Can be tion (typically 10 at conditions. If appropriate to maintain not been establish tective equipment with side shields (des such as: Nitrile. ive clothing.	absorbed throug absorbed throug (0) absorbed throug ir changes per ho licable, use proce n airborne levels ed, maintain airb or goggles).	h the skin. h the skin. h the skin. ur) should be used. Ventilation rates ess enclosures, local exhaust ventilation, below recommended exposure limits. If orne levels to an acceptable level.
US - Tennessee OELs: SI 2-Butoxyethanol (CAS US NIOSH Pocket Guide of 2-Butoxyethanol (CAS US. OSHA Table Z-1 Limit 2-Butoxyethanol (CAS uppropriate engineering ontrols adividual protection measure Eye/face protection Skin protection Hand protection	kin designation 111-76-2) to Chemical Haza 111-76-2) ts for Air Contam 111-76-2) Good general should be may or other engin exposure limit es, such as person Wear safety g Wear protectiv Wear suitable If engineering NIOSH-approv breathing appa	ventilate to the total to the total to the total to the total tota	Can be cin designation Can be (29 CFR 1910.100) Can be tion (typically 10 at conditions. If appropriate to maintain not been establish tective equipment with side shields (constructions) Es such as: Nitrile. It ive clothing. Es are not feasible condige respirator with	absorbed throug absorbed throug (0) absorbed throug r changes per ho licable, use procen airborne levels led, maintain airbort goggles).	h the skin. h the skin. h the skin. ur) should be used. Ventilation rates ess enclosures, local exhaust ventilation, helow recommended exposure limits. If
US - Tennessee OELs: SI 2-Butoxyethanol (CAS US NIOSH Pocket Guide of 2-Butoxyethanol (CAS US. OSHA Table Z-1 Limits 2-Butoxyethanol (CAS Appropriate engineering controls adividual protection measure Eye/face protection Skin protection Hand protection Other	tin designation 111-76-2) to Chemical Haza 111-76-2) ts for Air Contam 111-76-2) Good general should be mai or other engin exposure limit es, such as perso Wear safety g Wear protectiv Wear suitable If engineering NIOSH-approv breathing appa	ventilation to the control of the co	Can be cin designation Can be (29 CFR 1910.100) Can be tion (typically 10 at a conditions. If appropriate to maintain not been establish tective equipment with side shields (of the same as such as: Nitrile. The confined spaces	absorbed throug absorbed throug (0) absorbed throug ir changes per holicable, use procen airborne levels ed, maintain airbor goggles).	h the skin. h the skin. h the skin. ur) should be used. Ventilation rates ess enclosures, local exhaust ventilation, below recommended exposure limits. If orne levels to an acceptable level. eeds the applicable exposure limits, use for cartridge. Use a self-contained cies. Air monitoring is needed to

Material name: Battery Cleaner with Acid Indicator 05023, 05623 Version #: 01 Issue date: 07-24-2015

Liquid.

Physical state

Form

Aerosol.

Color

Clear.

Odor

Odorless. Not available.

Odor threshold

8.5

Melting point/freezing point

-103 °F (-75 °C) estimated

Ha

Initial boiling point and boiling

212 °F (100 °C) estimated

range

Flash point

None (Tag Closed Cup)

Evaporation rate

Slow.

Flammability (solid, gas) Upper/lower flammability or explosive limits

Not available.

Flammability limit - lower

1.3 % estimated

Flammability limit - upper

(%)

10.6 % estimated

265.9 hPa estimated

Vapor pressure

> 1 (air = 1)

Vapor density

Relative density

1.01

Solubility (water)

Soluble.

Partition coefficient

(n-octanol/water)

Not available.

Auto-ignition temperature

446 °F (230 °C) estimated

Decomposition temperature

Not available.

Viscosity (kinematic)

Not available.

Percent volatile

94.3 % estimated

10. Stability and reactivity

Reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability

Material is stable under normal conditions.

Possibility of hazardous reactions

Conditions to avoid

No dangerous reaction known under conditions of normal use. Heat, flames and sparks. Contact with incompatible materials.

Incompatible materials

Strong oxidizing agents.

Hazardous decomposition

Carbon oxides.

products

11. Toxicological information

Information on likely routes of exposure

Inhalation

Prolonged inhalation may be harmful.

Skin contact

2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and

prolonged. These effects have not been observed in humans.

Eye contact

Direct contact with eyes may cause temporary irritation.

Ingestion

May cause discomfort if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity

Not available.

Product	Species Test Results			
Battery Cleaner with Acid Indicator				
<u>Acute</u>	•			
Dermal				
LD50	Rabbit	15187 mg/kg estimated		
Inhalation		₩.		
LC50	Rat	83 mg/l, 4 hours estimated		
Oral		3 7 7 7 8 9 9 9 9 9 9 9 9 9 9		

^{*} Estimates for product may be based on additional component data not shown.

Rat

Skin corrosion/irritation

LD50

Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye

irritation

Direct contact with eyes may cause temporary irritation.

Respiratory sensitization

Not a respiratory sensitizer.

Skin sensitization

This product is not expected to cause skin sensitization.

Germ cell mutagenicity

No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity

This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

2-Butoxyethanol (CAS 111-76-2)

3 Not classifiable as to carcinogenicity to humans.

21294 mg/kg estimated

US. National Toxicology Program (NTP) Report on Carcinogens

Not available.

Reproductive toxicity

This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard

Not an aspiration hazard.

Chronic effects

May be harmful if absorbed through skin.

2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans.

12. Ecological information

cotoxicity	The prod possibility	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.			
Product		Species	Test Results		
Battery Cleaner with A	cid Indicator				
Aquatic					
Acute					
Crustacea	EC50	Daphnia	54385.9648 mg/l, 48 hours estimated		
Fish	LC50	Fish	5472.7153 mg/l, 96 hours estimated		
Components		Species	Test Results		
2-Butoxyethanol (CAS	111-76-2)				
Aquatic					
Acute					
Crustacea	EC50	Water flea (Daphnia magna)	1550 mg/l, 48 hours		
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	>= 1000 mg/l, 96 hours		

^{*} Estimates for product may be based on additional component data not shown.

Persistence and degradability

No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

2-Butoxyethanol

0.81, log Pow

Mobility in soil

No data available.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal of waste from residues / unused products

The dispensed liquid product is not a RCRA hazardous waste (See 40 CFR Part 261.20 - 261.33). Consult authorities before disposal. Contents under pressure. Do not puncture, incinerate or crush.

Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in

accordance with local/regional/national regulations.

Hazardous waste code

Contaminated packaging

Not regulated.

Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Do not re-use empty containers.

14. Transport information

DOT

UN number

UN1950

UN proper shipping name Transport hazard class(es)

Aerosols, non-flammable, limited quantity

Class

2.2

Subsidiary risk

2.2

Label(s) Packing group

Not applicable.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions

Not available.

Packaging exceptions

306 None

Packaging non bulk Packaging bulk

None

IATA

UN number

UN1950

UN proper shipping name Transport hazard class(es)

Aerosols, non-flammable, limited quantity

Class

Subsidiary risk

2.2

Not applicable.

Packing group **Environmental hazards**

No.

ERG Code

Special precautions for user

10L

Other information

Read safety instructions, SDS and emergency procedures before handling.

Passenger and cargo

aircraft

Allowed.

Cargo aircraft only

Allowed.

IMDG

UN number

UN1950

UN proper shipping name Transport hazard class(es)

AEROSOLS, LIMITED QUANTITY

Class

2

Subsidiary risk

Packing group

Not applicable.

Environmental hazards

Marine pollutant

No.

EmS

Not available.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Material name: Battery Cleaner with Acid Indicator 05023, 05623 Version #: 01 Issue date: 07-24-2015 TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

SARA 304 Emergency release notification

Not regulated.

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

2-Butoxyethanol (CAS 111-76-2)

CERCLA Hazardous Substance List (40 CFR 302.4)

2-Butoxyethanol (CAS 111-76-2)

Listed.

CERCLA Hazardous Substances: Reportable quantity

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

Food and Drug

Not regulated.

Administration (FDA)

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 311/312

Immediate Hazard - No. Delayed Hazard - No

Hazard categories

Fire Hazard - No Pressure Hazard - Yes Reactivity Hazard - No

SARA 302 Extremely hazardous substance No

US state regulations

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Liquefied Petroleum Gas (CAS 68476-86-8)

2-Butoxyethanol (CAS 111-76-2)

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

US. New Jersey Worker and Community Right-to-Know Act

2-Butoxyethanol (CAS 111-76-2)

US. Massachusetts RTK - Substance List

2-Butoxyethanol (CAS 111-76-2)

US. Pennsylvania Worker and Community Right-to-Know Law

2-Butoxyethanol (CAS 111-76-2)

US. Rhode Island RTK

2-Butoxyethanol (CAS 111-76-2)

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

Volatile organic compounds (VOC) regulations

EPA

VOC content (40 CFR

7.9 %

51.100(s))

Consumer products (40 CFR 59, Subpt. C)

Not regulated

State

Consumer products

Not regulated

VOC content (CA)

7.9 %

Material name: Battery Cleaner with Acid Indicator

05023, 05623 Version #: 01 Issue date: 07-24-2015

SDS US

International inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes
*A !!!/!! !!! (I () !!		100

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 07-24-2015

Prepared by Allison Cho

Version # 01

Further information

CRC # 530C

HMIS® ratings Health: 1 Flammability: 0

Physical hazard: 0 Personal protection: B

NFPA ratings

Health: 1

Flammability: 0 Instability: 0

NFPA ratings



Disclaimer

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries.