ASHLAND.	Page: 1
SAFETY DATA SHEET	Revision Date: 05/22/2015
	Print Date: 5/27/2015
	SDS Number: R0178048
NAPA® PREM PERF HD SAE 30 MOTOR OIL	Version: 1.0
NP75110	

10/27/16

29 CFR 1910.1200 (OSHA HazCom 2012)

Napa SAE 30 Heavy Duty motor oil

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

75-110

Product identifier

Trade name

: NAPA® PREM PERF HD SAE 30

MOTOR OIL

Recommended use of the chemical and restrictions on use

Details of the supplier of the safety data sheet
Ashland
P.O. Box 2219
Columbus, OH 43216
United States of America

Emergency telephone number
1-800-ASHLAND (1-800-274-5263)

Regulatory Information Number
1-800-325-3751

Product Information
614-790-3333

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

GHS Label element

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture

: Mixture

Chemical nature

: Defatter

Hazardous components

Chemical Name	CAS-No.	Classification	Concentration (%)
Benzenesulfonic acid, C10-60- alkyl derivs., sodium salts	90194-32-4	Eye Irrit. 2A; H319	6.24

ASHLAND	Page: 2
SAFETY DATA SHEET	Revision Date: 05/22/2015
	Print Date: 5/27/2015
	SDS Number: R0178048
NAPA® PREM PERF HD SAE 30 MOTOR OIL	Version: 1.0
NP75110	

SECTION 4. FIRST AID MEASURES

General advice

: No hazards which require special first aid measures.

If inhaled

: If breathed in, move person into fresh air.

If unconscious place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact

: First aid is not normally required. However, it is

recommended that exposed areas be cleaned by washing

with soap and water.

In case of eye contact

: Remove contact lenses.

Protect unharmed eye.

If swallowed

: Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

Most important symptoms and effects, both acute and

delayed

: No symptoms known or expected.

Notes to physician

: No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media

: Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Water spray

Foam

Carbon dioxide (CO2)

Dry chemical

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses

Hazardous combustion

products

carbon dioxide and carbon monoxide

Hydrocarbons

Specific extinguishing

methods

.

Product is compatible with standard fire-fighting agents.

Further information

: Standard procedure for chemical fires.

Special protective equipment

: In the event of fire, wear self-contained breathing apparatus.

ASHLAND.	Page: 3
SAFETY DATA SHEET	Revision Date: 05/22/2015
	Print Date: 5/27/2015
	SDS Number: R0178048
NAPA® PREM PERF HD SAE 30 MOTOR OIL	Version: 1.0
NP75110	

for firefighters

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions. protective equipment and emergency procedures

: Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

Environmental precautions

: Prevent further leakage or spillage if safe to do so.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

Other information

: Comply with all applicable federal, state, and local regulations.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling

: Smoking, eating and drinking should be prohibited in the

application area.

For personal protection see section 8.

Conditions for safe storage

: Electrical installations / working materials must comply with

the technological safety standards.

Materials to avoid

: No materials to be especially mentioned.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Engineering measures

: General room ventilation should be adequate for normal conditions of use. However, if unusual operating conditions exist, provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known,

suspected or apparent adverse effects.

Personal protective equipment

Respiratory protection

: No personal respiratory protective equipment normally

required.

Eye protection

: Not required under normal conditions of use. Wear splashproof safety goggles if material could be misted or splashed

into eyes.

ASHLAND	Page: 4
SAFETY DATA SHEET	Revision Date: 05/22/2015
	Print Date: 5/27/2015
	SDS Number: R0178048
NAPA® PREM PERF HD SAE 30 MOTOR OIL NP75110	Version: 1.0

Skin and body protection

: Wear as appropriate:

Safety shoes

Wear resistant gloves (consult your safety equipment

supplier).

Hygiene measures

: General industrial hygiene practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state

: liquid

Odour

: No data available

Odour Threshold

: No data available

Hq

: No data available

Melting point/freezing point

: No data available

Boiling point/boiling range

: No data available

Flash point

: > 390 °F / > 199 °C

Method: Cleveland open cup

Evaporation rate

: No data available

Flammability (solid, gas)

: No data available

Upper explosion limit

: 6 %(V)

Calculated Explosive Limit

Lower explosion limit

Relative vapour density

1 %(V)

Vapour pressure

Calculated Explosive Limit

: 0.0133333 hPa (21.11 °C)

Calculated Vapor Pressure

: No data available

Relative density

: No data available

Density

: 0.8785 g/cm3 (15.6 °C)

Solubility(ies)

Water solubility

: insoluble

Solubility in other solvents

: No data available

Partition coefficient: n-

octanol/water

: No data available

Thermal decomposition

: No data available

Viscosity

ASHLAND	Page: 5
SAFETY DATA SHEET	Revision Date: 05/22/2015
	Print Date: 5/27/2015
	SDS Number: R0178048
NAPA® PREM PERF HD SAE 30 MOTOR OIL	Version: 1.0
NP75110	

Viscosity, dynamic

: No data available

Viscosity, kinematic

: 80 mm2/s (40 °C)

Oxidizing properties

: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity

: No decomposition if stored and applied as directed.

Chemical stability

: Stable under recommended storage conditions.

Possibility of hazardous

reactions

: Product will not undergo hazardous polymerization.

Incompatible materials

: Strong oxidizing agents

Hazardous decomposition

products

No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of : Inhalation

exposure

Inhalation Skin contact Eye Contact

Ingestion

Acute toxicity

Not classified based on available information.

Skin corrosion/irritation

Not classified based on available information.

Product:

Result: Repeated exposure may cause skin dryness or cracking.

Components:

Benzenesulfonic acid, C10-60-alkyl derivs., sodium salts:

Result: Not irritating to skin

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks: Unlikely to cause eye irritation or injury.

Components:

Benzenesulfonic acid, C10-60-alkyl derivs., sodium salts:

Result: Irritating to eyes

ASHLAND.		Page: 6
SAFETY DATA SHEET		Revision Date: 05/22/2015
		Print Date: 5/27/2015
	-	SDS Number: R0178048
NAPA® PREM PERF HD SAE 30 MOTOR OIL		Version: 1.0
NP75110		

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Product:

No aspiration toxicity classification

Further information

Product:

Remarks: No data available

Carcinogenicity:

IARC

No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by OSHA.

NTP

No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Revision Date: 05/22/2015
Print Date: 5/27/2015
SDS Number: R0178048
Version: 1.0

Additional ecological information

: No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

General advice

: Dispose of in accordance with all applicable local, state and

federal regulations.

Contaminated packaging

: Empty remaining contents.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD	SUBSIDIARY	PACKING	MARINE
		CLASS	HAZARDS	GROUP	POLLUTANT /
					LTD. QTY.

U.S. DOT - ROAD

100	Not dangerous goods		
			•

U.S. DOT - RAIL

Not dangerous goods		* 4
		· · ·

U.S. DOT - INLAND WATERWAYS

Not dangerous goods

TRANSPORT CANADA - ROAD

Not dangerous goods

TRANSPORT CANADA - RAIL

Not dangerous goods

TRANSPORT CANADA - INLAND WATERWAYS

Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods

ASHLAND.	Page: 8
SAFETY DATA SHEET	Revision Date: 05/22/2015
	Print Date: 5/27/2015
	SDS Number: R0178048
NAPA® PREM PERF HD SAE 30 MOTOR OIL	Version: 1.0
NP75110	

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

MEXICAN REGULATION FOR THE LAND TRANSPORT OF HAZARDOUS MATERIALS AND WASTES

Not dangerous goods

*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

	-i	
Marine pollutant	no	
Manne politicant	1 1	
1 and the second of the second	1 1	1
1	1 1	

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

SARA 311/312 Hazards

: No SARA Hazards

SARA 313

Component(s)SARA 313

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Pennsylvania Right To Know

HEAVY PARAFFINIC DISTILLATE 64742-54-7 90.00 - 100.00 % Benzenesulfonic acid, C10-60-alkyl derivs., 90194-32-4 5.00 - 10.00 %

sodium salts

New Jersey Right To Know

HEAVY PARAFFINIC DISTILLATE 64742-54-7 90.00 - 100.00 % Benzenesulfonic acid, C10-60-alkyl derivs., 90194-32-4 5.00 - 10.00 % sodium salts

POLYOLEFIN AMIDE ALKENEAMINE Not Assigned 1.00 - 5.00 %

LUBRICANT ADDITIVE Not Assigned 1.00 - 5.00 %

California Prop 65

Proposition 65 warnings are not required for this product

based on the results of a risk assessment.

The components of this product are reported in the following inventories:

TSCA On TSCA Inventory

ASHLAND	Page: 9
SAFETY DATA SHEET	Revision Date: 05/22/2015
	Print Date: 5/27/2015
	SDS Number: R0178048
NAPA® PREM PERF HD SAE 30 MOTOR OIL	Version: 1.0
NP75110	

DSL

: All components of this product are on the Canadian DSL.

AUSTR

: On the inventory, or in compliance with the inventory

NZIOC

: Not in compliance with the inventory

KECL

: On the inventory, or in compliance with the inventory

PICCS

: On the inventory, or in compliance with the inventory

IECSC

: Low volume exemption


Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information

Revision Date: 05/22/2015



NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIB

Full text of H-Statements referred to under sections 2 and 3.

H319

Causes serious eye irritation.

Sources of key data used to compile the Safety Data Sheet
Ashland internal data including own and sponsored test reports
The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

ASHLAND.	Page: 10
SAFETY DATA SHEET	Revision Date: 05/22/2015
	Print Date: 5/27/2015
	SDS Number: R0178048
NAPA® PREM PERF HD SAE 30 MOTOR OIL	Version: 1.0
NP75110	

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet:

ACGIH: American Conference of Industrial Hygienists

BEI : Biological Exposure Index

CAS: Chemical Abstracts Service (Division of the American Chemical Society).

CMR: Carcinogenic, Mutagenic or Toxic for Reproduction

FG: Food grade

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization

ICAO-TI (ICAO): Technical Instructions by the "International Civil Aviation Organization"

IMDG: International Maritime Code for Dangerous Goods

ISO: International Organization for Standardization

logPow: octanol-water partition coefficient

LCxx: Lethal Concentration, for xx percent of test population

LDxx : Lethal Dose, for xx percent of test population. ICxx : Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx N.O.S.: Not Otherwise Specified

OECD : Organization for Economic Co-operation and Development

OEL: Occupational Exposure Limit
P-Statement: Precautionary Statement
PBT: Persistent, Bioaccumulative and Toxic
PPE: Personal Protective Equipment

STEL : Short-term exposure limit STOT : Specific Target Organ Toxicity

TLV: Threshold Limit Value TWA: Time-weighted average

vPvB: Very Persistent and Very Bioaccumulative

WEL: Workplace Exposure Level

CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act

DOT: Department of Transportation

FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act HMIRC : Hazardous Materials Information Review Commission

HMIS: Hazardous Materials Identification System NFPA: National Fire Protection Association

NIOSH: National Institute for Occupational Safety and Health OSHA: Occupational Safety and Health Administration

PMRA: Health Canada Pest Management Regulatory Agency

RTK: Right to Know

WHMIS: Workplace Hazardous Materials Information System