5/6/2015



Safety Data Sheet Spartan Chemical Company, Inc.

Revision Date: 12-Dec-2014

:: PRODUCT AND COMPANY IDENTIFICATION

Product Identifier

Product Name: Product Number:

XTRACTION II 3096

Xtraction 2 Soil

Recommended Use:

Recommended Use: Uses Advised Against:

Carpet cleaner
For Industrial and Institutional Use Only

Extraction carpet cleaver

Manufacturer/Supplier:

Spartan Chemical Company, Inc.

1110 Spartan Drive Maumee, Ohio 43537 USA 800-537-8990 (Business hours) www.spartanchemical.com

24 Hour Emergency Phone Numbers:

Medical Emergency/Information: 888-314-6171

Transportation/Spill/Leak: CHEMTREC 800-424-9300

2#HAYARIÐSIDENTIÐ CATION

GHS Classification

Skin Corrosion/Irritation:

Category 1

Serious Eye Damage/Eye Irritation: Category 1

GHS Label Elements

Signal Word:

Symbols:

Danger



Hazard Statements:

Precautionary Statements:

Causes severe skin burns and serious eye damage.

Prevention:

Do not breathe mist, vapors or spray.

Wash hands and any exposed skin thoroughly after handling.

Wear protective gloves. Wear eye / face protection. Wear protective clothing.

Response:

IMMEDIATELY CALL A POISON CENTER OR PHYSICIAN.

-Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

-Skin

IF ON SKIN (or hair). Take off immediately all contaminated clothing. Rinse skin with water

or shower. Wash contaminated clothing before reuse.

-Inhalation:

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing.

-Ingestion:

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

-Specific Treatment:

See Safety Data Sheet Section 4: "FIRST AID MEASURES" for additional information.

Storage:

Store locked up.

Disposal:

Dispose of contents and container in accordance with local, state and federal regulations.

Hazards Not Otherwise Classified: Not Applicable

Revision Date: 12-Dec-2014 3096 - XTRACTION II

Other Information:

- · May be harmful if swallowed.
- Inhalation of vapors or mist may cause respiratory irritation.

· Keep out of reach of children.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No		Weight-%	
water	7732-18-5		60-100	
alcohol ethoxylate	68439-46-3		1-5	
sodium carbonate	497-19-8		1-5	
2-butoxyethanol	111-76-2		1-5	
tetrasodium ethylenediaminetetraacetate	64-02-8		1-5	
sodium alkylnaphthalenesulfonate	PROPRIETARY		1-5	

Specific chemical identity and/or exact percentage of composition has been withheld as a trade secret.

- - - 2 FIRSTAID MEASURES

Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and -Eye Contact:

> easy to do. Continue rinsing. IMMEDIATELY CALL A POISON CENTER OR PHYSICIAN. Take off immediately all contaminated clothing and shoes. Rinse with water or shower for

at least 15 minutes. IMMEDIATELY CALL A POISON CENTER OR PHYSICIAN. Wash

contaminated clothing before reuse. Discard or destroy contaminated shoes.

Remove victim to fresh air and keep at rest in a position comfortable for breathing. -Inhalation:

IMMEDIATELY CALL A POISON CENTER OR PHYSICIAN.

Rinse mouth. Do NOT induce vomiting, IMMEDIATELY CALL A POISON CENTER OR -Ingestion:

PHYSICIAN. Never give anything by mouth to an unconscious person.

Note to Physicians: Treat symptomatically.

ERECHING MEASURES

Suitable Extinguishing Media: Product does not support combustion. Use extinguishing agent suitable for type of

> surrounding fire Dried product is capable of burning. Combustion products are toxic.

Specific Hazards Arising from the

Chemical:

Hazardous Combustion Products: May include Carbon monoxide Carbon dioxide and other toxic gases or vapors.

Protective Equipment and

-Skin Contact:

Wear MSHA/NIOSH approved self-contained breathing apparatus (SCBA) and full protective gear. Cool fire-exposed containers with water spray.

Precautions for Firefighters:

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions: **Environmental Precautions:** Methods for Clean-Up:

Avoid contact with skin, eyes or clothing. Use personal protective equipment as required.

Do not rinse spill onto the ground, into storm sewers or bodies of water.

Prevent further leakage or spillage if safe to do so. Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see Section 13).

TATAL HANDLING AND STORAGE

Handle in accordance with good industrial hygiene and safety practice. Wash thoroughly Advice on Safe Handling:

after handling.

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep out of the reach **Storage Conditions:**

of children. Keep from freezing.

3096 - XTRACTION II Revision Date: 12-Dec-2014

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits:

Che	mical Name		ACGIH TLV	OSHA PEL	NIOSH	
2-b	utoxyethanol		TWA: 20 ppm	TWA: 50 ppm	IDLH: 700 ppm	
	111-76-2			TWA: 240 mg/m³	TWA: 5 ppm	
· · · · ·		. :		(vacated) TWA: 25 ppm	TWA: 24 mg/m ³	.]
				(vacated) TWA: 120 mg/m ³		
				(vacated) S*		
				S*		

Engineering Controls: Provide good general ventilation.

If work practices generate dust, fumes, gas, vapors or mists which expose workers to chemicals above the occupational exposure limits, local exhaust ventilation or other

engineering controls should be considered.

Personal Protective Equipment

Eye/Face Protection:

Wear splash goggles.

Skin and Body Protection: Wear rubber or other cher

Respiratory Protection:

Wear rubber or other chemical-resistant gloves. Not required with expected use.

If occupational exposure limits are exceeded or respiratory irritation occurs, use of a

NIOSH/MSHA approved respirator suitable for the use-conditions and chemicals in Section

3 should be considered.

General Hygiene Considerations:

Wash hands and any exposed skin thoroughly after handling.

See 29 CFR 1910 132-138 for further guidance.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance/Physical State:	Liquid
Color:	Light green
Odor:	Floral fragrance
pH:	11.3-11.8
Melting Point / Freezing Point:	No information available
Boiling Point / Boiling Range:	100 °C / 212 °F
Flash Point:	> 100 °C / > 212 °F ASTM D56
Evaporation Rate:	< 1 (Butyl acetate = 1)
Flammability (solid, gas)	No information available.
Upper Flammability Limit:	No information available.
Lower Flammability Limit:	No information available.
Vapor Pressure:	No information available.
Vapor Density:	No information available.
Specific Gravity:	1.049
Solubility(ies):	Soluble in water
Partition Coefficient:	No information available.
Autoignition Temperature:	No information available.
Decomposition Temperature:	No information available
Viscosity:	No information available.

BEENOESTATEILITEVAANDELEAGRIVIDA

Reactivity: This material is considered to be non-reactive under normal conditions of use.

Chemical Stability: Stable under normal conditions.

Possibility of Hazardous Reactions: Not expected to occur with normal handling and storage.

Conditions to Avoid: Extremes of temperature and direct sunlight. Incompatible Materials: Strong oxidizing agents. Strong acids.

Hazardous Decomposition

May include carbon monoxide, carbon dioxide (CO2) and other toxic gases or vapors.

Products:

EXETOXICOLOGICAL INFORMATION

3096 - XTRACTION II Revision Date: 12-Dec-2014

Likely Routes of Exposure:

Eyes, Skin, Ingestion, Inhalation.

Symptoms of Exposure: -Eye Contact:

Pain, redness, swelling of the conjunctiva and tissue damage. Eye contact may cause

permanent damage.

-Skin Contact:

Pain, redness, blistering and possible chemical burn.

-Inhalation:

Nasal discomfort and coughing.

-Ingestion:

Pain, nausea, vomiting and diarrhea.

immediate, Delayed, Chronic Effects

Product Information:

Data not available or insufficient for classification.

Chronic Toxicity:

May cause adverse effects on the bone marrow and blood-forming system. May cause

adverse liver effects.

Target Organ Effects:

Blood. Central nervous system. -Eyes. hematopoietic system. kidney. Liver. Respiratory

System. -Skin.

Numerical Measures of Toxicity

The following acute toxicity estimates (ATE) are calculated based on the GHS document.

ATEmix (oral):

9234 mg/kg

ATEmix (dermal):

30069 mg/kg

ATEmix (inhalation-dust/mist): ATEmix (inhalation-vapor):

34.4 mg/l 108.5 mg/l

Component Acute Toxicity Information

Chemical Name	Oral LD50	Dermal LD50	Inhaiation LC50
water 7732-18-5	> 90 mL/kg (Rat)	Not Available	Not Available
alcohol ethoxylate 68439-46-3	= 1378 mg/kg(Rat)	> 2 g/kg(Rabbit)	Not Available
sodium carbonate 497-19-8	= 4090 mg/kg (Rat)	Not Available	Not Available
2-butoxyethanol 111-76-2	= 470 mg/kg (Rat)	= 2270 mg/kg(Rat)= 220 mg/kg(Rabbit)	= 2.21 mg/L (Rat) 4 h = 450 ppm (Rat) 4 h
tetrasodium ethylenediaminetetraacetate 64-02-8	= 10 g/kg (Rat)	Not Available	Not Available

Carcinogenicity: No components present at 0.1% or greater are listed as to being carcinogens by ACGIH, IARC, NTP or OSHA.

Ecotoxicity

Chemical Name	Algae/Aquatic Plants	Fish	Toxicity to Microorganisms	Crustacea
sodium carbonate	242: 120 h Nitzschia mg/L	300: 96 h Lepomis	Not Available	265: 48 h Daphnia magna
497-19-8	EC50	macrochirus mg/L LC50		mg/L EC50
· · · · · · · · · · · · · · · · · · ·	et e	static 310 - 1220: 96 h		
		Pimephales promelas mg/L		
		LC50 static		<u> </u>
2-butoxyethanol	Not Available	1490: 96 h Lepomis	Not Available	1698 - 1940: 24 h Daphnia
111-76-2		macrochirus mg/L LC50		magna mg/L EC50 1000: 48
		static 2950: 96 h Lepomis		h Daphnia magna mg/L
		macrochirus mg/L LC50		EC50
tetrasodium	1.01: 72 h Desmodesmus	41: 96 h Lepomis	Not Available	610: 24 h Daphnia magna
ethylenediaminetetraacetate	subspicatus mg/L EC50	macrochirus mg/L LC50		mg/L:EC50
64-02-8		static 59.8: 96 h Pimephales		
<u> </u>		promelas mg/L LC50 static	<u> </u>	

Persistence and Degradability:

No information available.

Bioaccumulation:

No information available.

Other Adverse Effects:

No information available.

43: DISPOSAL CONSIDERATIONS

3096 - XTRACTION II

Disposal of Wastes:

Dispose of in accordance with federal, state and local regulations.

Contaminated Packaging:

Dispose of in accordance with federal, state and local regulations.

THE RANGEOR HINEORNATION PROPERTY

DOT:

UN/ID No:

UN1760

Proper Shipping Name:

Corrosive liquids, n.o.s., (contains sodium hydroxide)

Hazard Class:

- 8

Packing Group:

- iii

15 REGULATIORY INFORMATION

TSCA Status: (Toxic Substance Control Act Section 8(b) Inventory)

All chemical substances in this product are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

SARA 313

This product contains the following listed substances:

2-butoxyethanol

CAS No 111-76-2 applies to R-(OCH2CH2)n-OR', where n = 1, 2, or 3, R=Alkyl C7 or less, or R = Phenyl or Alkyl substituted phenyl, R' = H or Alkyl C7 or less, or OR' consisting of Carboxylic acid ester, Sulfate, Phosphate, Nitrate, or Sulfonate, Chemical Category N230

SARA 311/312 Hazard Categories

Acute Health Hazard: Chronic Health Hazard: Yes Yes

Fire Hazard:

No

Sudden release of pressure hazard: Reactive Hazard:

No No

California Proposition 65

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65
formaldehyde - 50-00-0	Carcinogen
methanol - 67-56-1	Developmental
acetaldehyde - 75-07-0	Carcinogen
naphthalene - 91-20-3	Carcinogen

WARNING: This product contains a chemical known to the State of California to cause cancer.

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

16 OT HERINFORWATION

NFPA

Health Hazards: 3

Flammability: 0

Instability: 0

Special: N/A

Revision Date: 12-Dec-2014

<u>HMIS</u>

Health Hazards: 3*

Flammability: 0

Physical Hazards: 0

Revision Date:

12-Dec-2014

Reasons for Revision:

No information available.

<u>Disclaimer:</u>

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet