# **Poulan**°

# **SAFETY DATA SHEET**

Stroke 2 Engine oil Poulan Weedeater smokeless

1. Identification

**Product identifier** 

Poulan Weedeater 40:1 2-Stroke Oil

Other means of identification

Product code

585826801, 952030132, 952030133, 952030260, 952030165, 530030194, 585826804,

952030127, 952030128, 585826805, 952030207, 585826807, 581561701, 952031138, (Not all

part numbers are available in all markets.)

Recommended use

2-stroke engines

**Recommended restrictions** 

None known.

Manufacturer/Importer/Supplier/Distributor information

Supplier

Husqvarna Group

**Address** 

9335 Harris Corners Parkway

Charlotte, NC 28269

USA

Telephone number

800-487-5951

**Emergency telephone** 

+1-760-476-3961 (Access code 333721)

number

2. Hazard(s) identification

Physical hazards

Not classified.

**Health hazards** 

Sensitization, skin

Category 1

**OSHA** defined hazards

Not classified.

Label elements



Signal word

Warning

**Hazard statement** 

May cause an allergic skin reaction.

**Precautionary statement** 

Prevention

Avoid breathing mist or vapor. Contaminated work clothing must not be allowed out of the

workplace. Wear protective gloves.

Response

If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

Storage

Store away from incompatible materials.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information

None.

## 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	CAS number	%	
Solvent-dewaxed heavy paraffinic distillates (petroleum)	64742-65-0	65 - 80	
Residual oils (petroleum), solvent-refined	64742-01-4	15 - 25	

Poulan Weedeater 40:1 2-Stroke Oil

SDS US

930487 Version #: 01 Revision date: - Issue date: 25-September-2015

64742-47-8	5 - 10
101-96-2	0.1 - 0.5
•	

#### **Composition comments**

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

#### 4. First-aid measures

Inhalation

Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact

Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions.

Eye contact

Rinse with water. Get medical attention if irritation develops and persists.

Ingestion

Rinse mouth. Do not induce vomiting without advice from poison control center. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Get medical attention if

symptoms occur.

Most important symptoms/effects, acute and delayed

May cause an allergic skin reaction. Dermatitis. Rash.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

## 5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Powder. Alcohol resistant foam. Dry chemicals. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions Cool containers exposed to heat with water spray and remove container, if no risk is involved.

Specific methods General fire hazards Use standard firefighting procedures and consider the hazards of other involved materials.

Material will burn in a fire.

## 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Large Spills: Stop the flow of material, if this is without risk, Use water spray to reduce vapors or divert vapor cloud drift. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

# **Environmental precautions**

7. Handling and storage Precautions for safe handling

Avoid breathing mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged or repeated contact with skin. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Keep away from heat and sources of ignition. Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

Poulan Weedeater 40:1 2-Stroke Oil

## 8. Exposure controls/personal protection

#### Occupational exposure limits

## US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	Form	
Solvent-dewaxed heavy paraffinic distillates (petroleum) (CAS 64742-65-0)	PEL	5 mg/m3	Mist.	
•		2000 mg/m3		

#### **US. ACGIH Threshold Limit Values**

Components	Туре	Value	Form
Residual oils (petroleum), solvent-refined (CAS 64742-01-4)	TWA	5 mg/m3	Inhalable fraction.

#### US. NIOSH: Pocket Guide to Chemical Hazards

Components	Туре	Value Form
Distillates (petroleum), hydrotreated light (CAS 64742-47-8)	TWA	100 mg/m3
Solvent-dewaxed heavy paraffinic distillates (petroleum) (CAS 64742-65-0)	Ceiling	1800 mg/m3
,	STEL	10 mg/m3 Mist.

#### **Biological limit values**

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

500 ppm

#### Individual protection measures, such as personal protective equipment

Wear safety glasses with side shields (or goggles). Eye/face protection

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove

supplier.

Other

Wear appropriate chemical resistant clothing.

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the

workplace.

## 9. Physical and chemical properties

#### **Appearance**

Physical state Liquid. **Form** Liquid Color Blue Odor Mild hydrocarbon.

Odor threshold Not available.

pΗ Not available. Melting point/freezing point Not available.

Initial boiling point and boiling Wide range.

range

Flash point

205.0 °F (96.1 °C)

Poulan Weedeater 40:1 2-Stroke Oil

SDS US

930487 Version #: 01 Revision date: -Issue date: 25-September-2015 **Evaporation rate** 

< 1 (BUAC=1)

Flammability (solid, gas)

Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

(%)

Flammability limit - upper

Not available.

(%)

Explosive limit - lower (%)

Not available.

Explosive limit - upper (%)

Not available.

Vapor pressure

< 1 mm Hg (68 °F (20 °C))

Vapor density

> 1 (Air=1)

Relative density

0.877 (60.08 °F (15.6 °C))

Solubility(ies)

Solubility (water)

Negligible.

Partition coefficient

Not available.

(n-octanol/water)

\*

Auto-ignition temperature
Decomposition temperature

Not available. Not available.

Viscosity

Not available.

Other information

Density

7.30 lbs/gal

**Explosive properties** 

Not explosive.

Flammability class

Not classified.

Kinematic viscosity

8.54 mm<sup>2</sup>/s (212 °F (100 °C))

59.24 mm<sup>2</sup>/s (104 °F (40 °C))

Oxidizing properties

Not oxidizing.

VOC (Weight %)

79

# 10. Stability and reactivity

Reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability

Material is stable under normal conditions.

Possibility of hazardous

No dangerous reaction known under conditions of normal use.

reactions

Conditions to avoid Contact with incompatible materials.

Incompatible materials

Strong oxidizing agents.

Hazardous decomposition

products

Carbon oxides.

## 11. Toxicological information

#### Information on likely routes of exposure

Inhalation

Prolonged inhalation may be harmful.

Skin contact

May cause an allergic skin reaction.

Eye contact

Direct contact with eyes may cause temporary irritation.

Ingestion

May cause irritation of the gastrointestinal tract.

Symptoms related to the physical, chemical and toxicological characteristics

May cause an allergic skin reaction. Dermatitis. Rash.

## Information on toxicological effects

**Acute toxicity** 

Not expected to be acutely toxic.

Skin corrosion/irritation

Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye

Direct contact with eyes may cause temporary irritation.

irritation

Poulan Weedeater 40:1 2-Stroke Oil

SDS US

930487 Version #: 01 Revision date: -

Issue date: 25-September-2015

Respiratory or skin sensitization

Respiratory sensitization

Not a respiratory sensitizer.

Skin sensitization

May cause an allergic skin reaction.

Germ cell mutagenicity

No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity

This product is not classified as a carcinogen.

IARC Monographs. Overall Evaluation of Carcinogenicity

NTP Report on Carcinogens

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity

This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

Not classified.

single exposure

Specific target organ toxicity repeated exposure

Not classified.

Aspiration hazard

Not an aspiration hazard.

**Chronic effects** 

Prolonged inhalation may be harmful.

12. Ecological information

**Ecotoxicity** 

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability

Bioaccumulative potential

The product is insoluble in water.

Mobility in soil Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations

Hazardous waste code-

Dispose in accordance with all applicable regulations.

No data is available on the degradability of this product.

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

## 14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

**IMDG** 

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and

Not established.

Issue date: 25-September-2015

the IBC Code

930487

## 15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Poulan Weedeater 40:1 2-Stroke Oil Version #: 01

Revision date: -

SDS US

5/7

## TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

## OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

## CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

# Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate Hazard - Yes Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

#### SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

Yes

chemical

#### SARA 313 (TRI reporting)

Not regulated.

#### Other federal regulations

## Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

#### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

#### US state regulations

#### US. Massachusetts RTK - Substance List

Distillates (petroleum), hydrotreated light (CAS 64742-47-8)

N,N'-di-sec-butyl-p-phenylenediamine (CAS 101-96-2)

Solvent-dewaxed heavy paraffinic distillates (petroleum) (CAS 64742-65-0)

## US. New Jersey Worker and Community Right-to-Know Act

Distillates (petroleum), hydrotreated light (CAS 64742-47-8)

Solvent-dewaxed heavy paraffinic distillates (petroleum) (CAS 64742-65-0)

#### US. Pennsylvania Worker and Community Right-to-Know Law

Distillates (petroleum), hydrotreated light (CAS 64742-47-8)

N,N'-di-sec-butyl-p-phenylenediamine (CAS 101-96-2)

## US. Rhode Island RTK

Not regulated.

## **US. California Proposition 65**

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

#### International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes

Country(s) or region

Inventory name

On inventory (yes/no)\*

United States & Puerto Rico

Toxic Substances Control Act (TSCA) Inventory

Yes

\*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

# 16. Other information, including date of preparation or last revision

Issue date

25-September-2015

Revision date

\_

Version #

01

HMIS® ratings

Health: 1

Flammability: 1 Physical hazard: 0

NFPA ratings



**Disclaimer** 

Husqvarna Group cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.