



# SAFETY DATA SHEET

"World's Best" Glass Cleaner

Ammonia Free Its

Streakless Spray

By: Sprayway Inc.

## 1. Identification

Product number 1000000075  
 Product identifier **SW050 GLASS CLEANER**  
 Company information Sprayway, Inc.  
 1000 INTEGRAM DR  
 Pacific, MO 63069 United States  
 Company phone 1-630-628-3000  
 Emergency telephone US 1-866-836-8855  
 Emergency telephone outside US 1-952-852-4646  
 Version # 01  
 Recommended use cleaner  
 Recommended restrictions None known.

## 2. Hazard(s) identification

Physical hazards Gases under pressure Liquefied gas  
 Health hazards Not classified.  
 OSHA defined hazards Not classified.  
 Label elements



Signal word Warning  
 Hazard statement Contains gas under pressure; may explode if heated.  
 Precautionary statement  
 Prevention Observe good industrial hygiene practices.  
 Response If exposed or concerned: Get medical advice/attention.  
 Storage Protect from sunlight. Store in a well-ventilated place.  
 Disposal Dispose of waste and residues in accordance with local authority requirements.  
 Hazard(s) not otherwise classified (HNOC) None known.  
 Supplemental information None.

## 3. Composition/information on ingredients

### Mixtures

| Chemical name                            | Common name and synonyms | CAS number | %        |
|------------------------------------------|--------------------------|------------|----------|
| 2-Butoxyethanol                          |                          | 111-76-2   | 2.5 - 10 |
| Ethyl Alcohol                            |                          | 64-17-5    | 2.5 - 10 |
| Butane                                   |                          | 106-97-8   | 1 - 2.5  |
| Propane                                  |                          | 74-98-6    | 1 - 2.5  |
| Other components below reportable levels |                          |            | 90 - 100 |

\*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

## 4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.  
 Skin contact No adverse effects due to skin contact are expected.

|                                                                               |                                                                                                                  |
|-------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------|
| <b>Eye contact</b>                                                            | No specific first aid measures noted.                                                                            |
| <b>Ingestion</b>                                                              | Not likely, due to the form of the product.                                                                      |
| <b>Most important symptoms/effects, acute and delayed</b>                     | Direct contact with eyes may cause temporary irritation.                                                         |
| <b>Indication of immediate medical attention and special treatment needed</b> | Provide general supportive measures and treat symptomatically.                                                   |
| <b>General information</b>                                                    | Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. |

## 5. Fire-fighting measures

|                                                                      |                                                                                                                                                                                                                                                                                                                                                                                         |
|----------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Suitable extinguishing media</b>                                  | Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).                                                                                                                                                                                                                                                                                                                             |
| <b>Unsuitable extinguishing media</b>                                | None known.                                                                                                                                                                                                                                                                                                                                                                             |
| <b>Specific hazards arising from the chemical</b>                    | During fire, gases hazardous to health may be formed.                                                                                                                                                                                                                                                                                                                                   |
| <b>Special protective equipment and precautions for firefighters</b> | Self-contained breathing apparatus and full protective clothing must be worn in case of fire.                                                                                                                                                                                                                                                                                           |
| <b>Fire fighting equipment/instructions</b>                          | In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out. |
| <b>Specific methods</b>                                              | Cool containers exposed to flames with water until well after the fire is out.                                                                                                                                                                                                                                                                                                          |
| <b>General fire hazards</b>                                          | Contents under pressure. Pressurized container may explode when exposed to heat or flame.                                                                                                                                                                                                                                                                                               |

## 6. Accidental release measures

|                                                                            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|----------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Personal precautions, protective equipment and emergency procedures</b> | Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS. |
| <b>Methods and materials for containment and cleaning up</b>               | Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. For waste disposal, see section 13 of the SDS.                                                                                                                                                                                                                        |
| <b>Environmental precautions</b>                                           | Avoid discharge into drains, water courses or onto the ground.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |

## 7. Handling and storage

|                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|---------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Precautions for safe handling</b>                                | Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Ground and bond containers when transferring material. Close valve after each use and when empty. Protect cylinders from physical damage; do not drag, roll, slide, or drop. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Suck back of water into the container must be prevented. Do not allow backfeed into the container. Purge air from system before introducing gas. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt. Do not re-use empty containers. Do not get in eyes, on skin, or on clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. |
| <b>Conditions for safe storage, including any incompatibilities</b> | Level 1 Aerosol.<br>Contents under pressure. Do not expose to heat or store at temperatures above 120°F/49°C as can may burst. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Cylinders should be stored upright, with valve protection cap in place, and firmly secured to prevent falling or being knocked over. Stored containers should be periodically checked for general condition and leakage. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |

## 8. Exposure controls/personal protection

### Occupational exposure limits

#### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

| Components                     | Type | Value                  |
|--------------------------------|------|------------------------|
| 2-Butoxyethanol (CAS 111-76-2) | PEL  | 240 mg/m3<br>50 ppm    |
| Ethyl Alcohol (CAS 64-17-5)    | PEL  | 1900 mg/m3<br>1000 ppm |
| Propane (CAS 74-98-6)          | PEL  | 1800 mg/m3<br>1000 ppm |

#### US. ACGIH Threshold Limit Values

| Components                     | Type | Value    |
|--------------------------------|------|----------|
| 2-Butoxyethanol (CAS 111-76-2) | TWA  | 20 ppm   |
| Butane (CAS 106-97-8)          | STEL | 1000 ppm |
| Ethyl Alcohol (CAS 64-17-5)    | STEL | 1000 ppm |

#### US. NIOSH: Pocket Guide to Chemical Hazards

| Components                     | Type | Value                  |
|--------------------------------|------|------------------------|
| 2-Butoxyethanol (CAS 111-76-2) | TWA  | 24 mg/m3<br>5 ppm      |
| Butane (CAS 106-97-8)          | TWA  | 1900 mg/m3<br>800 ppm  |
| Ethyl Alcohol (CAS 64-17-5)    | TWA  | 1900 mg/m3<br>1000 ppm |
| Propane (CAS 74-98-6)          | TWA  | 1800 mg/m3<br>1000 ppm |

### Biological limit values

#### ACGIH Biological Exposure Indices

| Components                     | Value    | Determinant                              | Specimen            | Sampling Time |
|--------------------------------|----------|------------------------------------------|---------------------|---------------|
| 2-Butoxyethanol (CAS 111-76-2) | 200 mg/g | Butoxyacetic acid (BAA), with hydrolysis | Creatinine in urine | *             |

\* - For sampling details, please see the source document.

### Exposure guidelines

#### US - California OELs: Skin designation

2-Butoxyethanol (CAS 111-76-2) Can be absorbed through the skin.

#### US - Minnesota Haz Subs: Skin designation applies

2-Butoxyethanol (CAS 111-76-2) Skin designation applies.

#### US - Tennessee OELs: Skin designation

2-Butoxyethanol (CAS 111-76-2) Can be absorbed through the skin.

#### US NIOSH Pocket Guide to Chemical Hazards: Skin designation

2-Butoxyethanol (CAS 111-76-2) Can be absorbed through the skin.

#### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

2-Butoxyethanol (CAS 111-76-2) Can be absorbed through the skin.

### Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

### Individual protection measures, such as personal protective equipment

**Eye/face protection** Wear safety glasses with side shields (or goggles).

#### Skin protection

**Hand protection** Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.

**Other** Wear suitable protective clothing.

|                                       |                                                                                                                                                                                                                                                |
|---------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Respiratory protection</b>         | If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.                                                                                                                        |
| <b>Thermal hazards</b>                | Wear appropriate thermal protective clothing, when necessary.                                                                                                                                                                                  |
| <b>General hygiene considerations</b> | When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. |

## 9. Physical and chemical properties

### Appearance

|                                                |                                            |
|------------------------------------------------|--------------------------------------------|
| <b>Physical state</b>                          | Gas.                                       |
| <b>Form</b>                                    | Aerosol. Liquefied gas.                    |
| <b>Color</b>                                   | Not available.                             |
| <b>Odor</b>                                    | Not available.                             |
| <b>Odor threshold</b>                          | Not available.                             |
| <b>pH</b>                                      | 9.1 - 10.1 estimated                       |
| <b>Melting point/freezing point</b>            | Not available.                             |
| <b>Initial boiling point and boiling range</b> | 212 °F (100 °C) estimated                  |
| <b>Flash point</b>                             | -156.0 °F (-104.4 °C) Propellant estimated |
| <b>Evaporation rate</b>                        | Not available.                             |
| <b>Flammability (solid, gas)</b>               | Not available.                             |

### Upper/lower flammability or explosive limits

|                                                |                              |
|------------------------------------------------|------------------------------|
| <b>Flammability limit - lower (%)</b>          | Not available.               |
| <b>Flammability limit - upper (%)</b>          | Not available.               |
| <b>Explosive limit - lower (%)</b>             | Not available.               |
| <b>Explosive limit - upper (%)</b>             | Not available.               |
| <b>Vapor pressure</b>                          | 80 - 100 psig @70F estimated |
| <b>Vapor density</b>                           | Not available.               |
| <b>Relative density</b>                        | Not available.               |
| <b>Solubility(ies)</b>                         |                              |
| <b>Solubility (water)</b>                      | Not available.               |
| <b>Partition coefficient (n-octanol/water)</b> | Not available.               |
| <b>Auto-ignition temperature</b>               | Not available.               |
| <b>Decomposition temperature</b>               | Not available.               |
| <b>Viscosity</b>                               | Not available.               |

### Other information

#### Aerosol spray enclosed space

|                                        |                          |
|----------------------------------------|--------------------------|
| <b>Deflagration density</b>            | > 2.52 g/cm3 Tested      |
| <b>Aerosol spray ignition distance</b> | < 15 cm Tested estimated |
| <b>Explosive properties</b>            | Not explosive.           |
| <b>Oxidizing properties</b>            | Not oxidizing.           |
| <b>Specific gravity</b>                | 0.977 - 0.997            |
| <b>VOC (Weight %)</b>                  | 9.5 % estimated          |

## 10. Stability and reactivity

|                                           |                                                                                               |
|-------------------------------------------|-----------------------------------------------------------------------------------------------|
| <b>Reactivity</b>                         | The product is stable and non-reactive under normal conditions of use, storage and transport. |
| <b>Chemical stability</b>                 | Material is stable under normal conditions.                                                   |
| <b>Possibility of hazardous reactions</b> | Hazardous polymerization does not occur.                                                      |

|                                         |                                                                                          |
|-----------------------------------------|------------------------------------------------------------------------------------------|
| <b>Conditions to avoid</b>              | Heat. Avoid temperatures exceeding the flash point. Contact with incompatible materials. |
| <b>Incompatible materials</b>           | Strong oxidizing agents.                                                                 |
| <b>Hazardous decomposition products</b> | No hazardous decomposition products are known.                                           |

## 11. Toxicological information

### Information on likely routes of exposure

|                     |                                                                                                                                                          |
|---------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Inhalation</b>   | Prolonged inhalation may be harmful.                                                                                                                     |
| <b>Skin contact</b> | 2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans. |
| <b>Eye contact</b>  | Direct contact with eyes may cause temporary irritation.                                                                                                 |
| <b>Ingestion</b>    | Expected to be a low ingestion hazard.                                                                                                                   |

**Symptoms related to the physical, chemical and toxicological characteristics**  
Direct contact with eyes may cause temporary irritation.

### Information on toxicological effects

#### Acute toxicity

| Components                     | Species    | Test Results            |
|--------------------------------|------------|-------------------------|
| 2-Butoxyethanol (CAS 111-76-2) |            |                         |
| <b>Acute</b>                   |            |                         |
| <b>Dermal</b>                  |            |                         |
| LD50                           | Guinea pig | 7.3 ml/kg, 4 Days       |
|                                |            | 0.23 ml/kg, 24 Hours    |
|                                | Rabbit     | 435 mg/kg, 24 Hours     |
|                                |            | 0.68 ml/kg, 24 Hours    |
|                                |            | 0.63 ml/kg              |
| <b>Inhalation</b>              | Rat        | > 2000 mg/kg, 24 Hours  |
|                                |            |                         |
|                                | Rabbit     | 400 ppm, 7 Hours        |
|                                | Rat        | 450 ppm, 4 Hours        |
|                                |            |                         |
| <b>Oral</b>                    |            |                         |
| LD100                          | Rabbit     | 695 mg/kg               |
| LD50                           | Dog        | > 695 mg/kg             |
|                                | Guinea pig | 1414 mg/kg              |
|                                | Mouse      | 1519 mg/kg              |
|                                | Rat        | 1746 mg/kg              |
| Butane (CAS 106-97-8)          |            |                         |
| <b>Acute</b>                   |            |                         |
| <b>Inhalation</b>              |            |                         |
| LC50                           | Mouse      | 1237 mg/l, 120 Minutes  |
|                                |            | 52 %, 120 Minutes       |
|                                | Rat        | 1355 mg/l               |
| Ethyl Alcohol (CAS 64-17-5)    |            |                         |
| <b>Acute</b>                   |            |                         |
| <b>Inhalation</b>              |            |                         |
| LC50                           | Cat        | 85.41 mg/l, 4.5 Hours   |
|                                |            | 43.68 mg/l, 6 Hours     |
|                                | Mouse      | > 60000 ppm             |
|                                |            | 79.43 mg/l, 134 Minutes |
|                                | Rat        | > 115.9 mg/l, 4 Hours   |

| Components            | Species | Test Results           |
|-----------------------|---------|------------------------|
|                       |         | 51.3 mg/l, 6 Hours     |
| <b>Oral</b>           |         |                        |
| LD50                  | Monkey  | 6000 mg/kg             |
|                       | Mouse   | 10500 ml/kg            |
|                       | Pig     | > 5000 mg/kg           |
|                       | Rat     | 10470 mg/kg            |
|                       |         | 7800 ml/kg             |
| Propane (CAS 74-98-6) |         |                        |
| <b>Acute</b>          |         |                        |
| <b>Inhalation</b>     |         |                        |
| LC50                  | Mouse   | 1237 mg/l, 120 Minutes |
|                       |         | 52 %, 120 Minutes      |
|                       | Rat     | 1355 mg/l              |
|                       |         | 658 mg/l/4h            |

\* Estimates for product may be based on additional component data not shown.

**Skin corrosion/irritation** Prolonged skin contact may cause temporary irritation.

**Serious eye damage/eye irritation** Direct contact with eyes may cause temporary irritation.

#### Respiratory or skin sensitization

**Respiratory sensitization** Not a respiratory sensitizer.

**Skin sensitization** This product is not expected to cause skin sensitization.

**Germ cell mutagenicity** No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

**Carcinogenicity** This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

#### IARC Monographs. Overall Evaluation of Carcinogenicity

2-Butoxyethanol (CAS 111-76-2)

3 Not classifiable as to carcinogenicity to humans.

#### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

#### US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

**Reproductive toxicity** This product is not expected to cause reproductive or developmental effects.

**Specific target organ toxicity - single exposure** Not classified.

**Specific target organ toxicity - repeated exposure** Not classified.

**Aspiration hazard** Not likely, due to the form of the product.

**Chronic effects** May be harmful if absorbed through skin. Prolonged inhalation may be harmful.

2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans.

## 12. Ecological information

**Ecotoxicity** The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

| Product             | Species      | Test Results                        |
|---------------------|--------------|-------------------------------------|
| SW050 GLASS CLEANER |              |                                     |
| <b>Aquatic</b>      |              |                                     |
| Crustacea           | EC50 Daphnia | 13838.1602 mg/l, 48 hours estimated |

| Components                     | Species | Test Results                                                         |
|--------------------------------|---------|----------------------------------------------------------------------|
| 2-Butoxyethanol (CAS 111-76-2) |         |                                                                      |
| <b>Aquatic</b>                 |         |                                                                      |
| Fish                           | LC50    | Inland silverside ( <i>Menidia beryllina</i> ) 1250 mg/l, 96 hours   |
| Ethyl Alcohol (CAS 64-17-5)    |         |                                                                      |
| <b>Aquatic</b>                 |         |                                                                      |
| Crustacea                      | EC50    | Water flea ( <i>Daphnia magna</i> ) 7700 - 11200 mg/l, 48 hours      |
| Fish                           | LC50    | Fathead minnow ( <i>Pimephales promelas</i> ) > 100.1 mg/l, 96 hours |

\* Estimates for product may be based on additional component data not shown.

**Persistence and degradability** No data is available on the degradability of this product.

#### Bioaccumulative potential

##### Partition coefficient n-octanol / water (log Kow)

|                 |       |
|-----------------|-------|
| 2-Butoxyethanol | 0.83  |
| Butane          | 2.89  |
| Ethyl Alcohol   | -0.31 |
| Propane         | 2.36  |

**Mobility in soil** No data available.

**Other adverse effects** No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

### 13. Disposal considerations

|                                              |                                                                                                                                                                                                                                                         |
|----------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Disposal instructions</b>                 | Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations. |
| <b>Local disposal regulations</b>            | Dispose in accordance with all applicable regulations.                                                                                                                                                                                                  |
| <b>Hazardous waste code</b>                  | The waste code should be assigned in discussion between the user, the producer and the waste disposal company.                                                                                                                                          |
| <b>Waste from residues / unused products</b> | Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).                                        |
| <b>Contaminated packaging</b>                | Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.              |

### 14. Transport information

#### DOT

|                              |                 |
|------------------------------|-----------------|
| UN number                    | UN1950          |
| UN proper shipping name      | Aerosols        |
| Transport hazard class(es)   |                 |
| Class                        | 2.2             |
| Subsidiary risk              | -               |
| Label(s)                     | 2.2             |
| Packing group                | Not applicable. |
| Special precautions for user | Not available.  |
| Packaging exceptions         | 306             |
| Packaging non bulk           | None            |
| Packaging bulk               | None            |

#### IATA

|                              |                                                                         |
|------------------------------|-------------------------------------------------------------------------|
| UN number                    | UN1950                                                                  |
| UN proper shipping name      | Aerosols, non-flammable                                                 |
| Transport hazard class(es)   |                                                                         |
| Class                        | 2.2                                                                     |
| Subsidiary risk              | -                                                                       |
| Label(s)                     | 2.2                                                                     |
| Packing group                | Not applicable.                                                         |
| Environmental hazards        | No.                                                                     |
| ERG Code                     | 2L                                                                      |
| Special precautions for user | Read safety instructions, SDS and emergency procedures before handling. |

**Other information**

**Passenger and cargo aircraft** Allowed with restrictions.

**Cargo aircraft only** Allowed with restrictions.

**Packaging Exceptions** LTD QTY

**IMDG**

**UN number** UN1950

**UN proper shipping name** AEROSOLS

**Transport hazard class(es)**

**Class** 2.2

**Subsidiary risk** -

**Label(s)** 2.2

**Packing group** Not applicable.

**Environmental hazards**

**Marine pollutant** No.

**EmS** Not available.

**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.

**Packaging Exceptions** LTD QTY

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not applicable.

**DOT****IATA; IMDG****General information**

Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers: Ensure that containers are firmly secured. Ensure cylinder valve is closed and not leaking. Ensure valve outlet cap nut or plug (where provided) is correctly fitted. Ensure valve protection device (where provided) is correctly fitted. Ensure adequate ventilation. Ensure compliance with applicable regulations.

**15. Regulatory information**

**US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)**

Not listed.

**SARA 304 Emergency release notification**

Not regulated.



**OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)**

Not regulated.

**Superfund Amendments and Reauthorization Act of 1986 (SARA)**

**Hazard categories**  
Immediate Hazard - No  
Delayed Hazard - No  
Fire Hazard - No  
Pressure Hazard - Yes  
Reactivity Hazard - No

**SARA 302 Extremely hazardous substance**

Not listed.

**SARA 311/312 Hazardous chemical** No

**SARA 313 (TRI reporting)**

| Chemical name   | CAS number | % by wt. |
|-----------------|------------|----------|
| 2-Butoxyethanol | 111-76-2   | 2.5 - 10 |

**Other federal regulations****Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Not regulated.

**Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)**

Butane (CAS 106-97-8)  
Propane (CAS 74-98-6)

**Safe Drinking Water Act (SDWA)** Not regulated.

**US state regulations****US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)**

Not listed.

**US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))**

2-Butoxyethanol (CAS 111-76-2)  
Butane (CAS 106-97-8)

**US. Massachusetts RTK - Substance List**

2-Butoxyethanol (CAS 111-76-2)  
Butane (CAS 106-97-8)  
Ethyl Alcohol (CAS 64-17-5)  
Propane (CAS 74-98-6)

**US. New Jersey Worker and Community Right-to-Know Act**

2-Butoxyethanol (CAS 111-76-2)  
Butane (CAS 106-97-8)  
Ethyl Alcohol (CAS 64-17-5)  
Propane (CAS 74-98-6)

**US. Pennsylvania Worker and Community Right-to-Know Law**

2-Butoxyethanol (CAS 111-76-2)  
Butane (CAS 106-97-8)  
Ethyl Alcohol (CAS 64-17-5)  
Propane (CAS 74-98-6)

**US. Rhode Island RTK**

Butane (CAS 106-97-8)  
Propane (CAS 74-98-6)

**US. California Proposition 65**

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

**International Inventories**

| Country(s) or region | Inventory name                                             | On inventory (yes/no)* |
|----------------------|------------------------------------------------------------|------------------------|
| Australia            | Australian Inventory of Chemical Substances (AICS)         | Yes                    |
| Canada               | Domestic Substances List (DSL)                             | Yes                    |
| Canada               | Non-Domestic Substances List (NDSL)                        | No                     |
| China                | Inventory of Existing Chemical Substances in China (IECSC) | Yes                    |

| Country(s) or region        | Inventory name                                                         | On inventory (yes/no)* |
|-----------------------------|------------------------------------------------------------------------|------------------------|
| Europe                      | European Inventory of Existing Commercial Chemical Substances (EINECS) | Yes                    |
| Europe                      | European List of Notified Chemical Substances (ELINCS)                 | No                     |
| Japan                       | Inventory of Existing and New Chemical Substances (ENCS)               | No                     |
| Korea                       | Existing Chemicals List (ECL)                                          | No                     |
| New Zealand                 | New Zealand Inventory                                                  | No                     |
| Philippines                 | Philippine Inventory of Chemicals and Chemical Substances (PICCS)      | No                     |
| United States & Puerto Rico | Toxic Substances Control Act (TSCA) Inventory                          | Yes                    |

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information, including date of preparation or last revision

**Issue date** 03-09-2018

**Version #** 01

**Disclaimer** The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**Revision information** Product and Company Identification: Alternate Trade Names