

# SAFETY DATA SHEET

Issuing Date 03-Apr-2007

Revision Date 07-Mar-2015

**Revision Number 0** 

# 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

**GHS** product identifier

Mag-E-Aluminum Polish

**Product Name** 

Product Code(s)

Mothers Mag & Aluminum Polish

perfect for ALL Metals

Shines and protects

Other means of identification

05100, 05101, 05102, 05104, 35100, 55100

By: mothers

**Synonyms** 

None

### Recommended use of the chemical and restrictions on use

Recommended Use

Metal polish

Uses advised against

No information available

## Supplier's details

Supplier Address MOTHERS POLISHES WAXES CLEANERS

5456 Industrial Drive Huntington Beach, CA 92649

TEL: 714-891-3364 FAX: 714-893-1827

### **Emergency telephone number**

**Emergency Telephone** 

Number

Chemtrec Phone: 1-800-424-9300 (within the U.S.) or +1 703-527-3887 (outside the U.S.)

## 2. HAZARDS IDENTIFICATION

#### Classification

This chemical is considered hazardous according to the OSHA Hazard Communication Standard 2012 (29 CFR 1910.1200)

Aspiration Toxicity	Category 1
Flammable liquids	Category 4

## GHS Label elements, including precautionary statements

# **Emergency Overview**

Signal Word

Danger

Hazard Statements

May be fatal if swallowed and enters airways

Combustible liquid.



Appearance White

Physical State Solid.

Odor Pine

#### **Precautionary Statements**

#### Prevention

- · Keep away from heat/sparks/open flames/hot surfaces No smoking.
- Wear protective gloves/protective clothing/eye protection/face protection.

#### **General Advice**

None

#### Ingestion

- IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
- Do NOT induce vomiting.

#### Fire

• In case of fire: Use CO2, dry chemical, or foam for extinction.

#### Storage

- · Store locked up.
- · Store in a well-ventilated place. Keep cool.

#### Disposal

· Dispose of contents/container to an approved waste disposal plant.

#### **Hazard Not Otherwise Classified (HNOC)**

Not applicable

# Other information

36.04743% of the mixture consists of ingredient(s) of unknown toxicity.

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %	Trade secret
Petroleum distillates, hydrotreated light	64742-47-8	25-50	*
Aluminum oxide	1344-28-1	25-50	*
Solvent naphtha (petroleum), medium aliphatic	64742-88-7	<10	*
Triethanolamine	102-71-6	<10	*
Tall oil fatty acids	61790-12-3	<10	*
Hexylene glycol	107-41-5	<10	*

<sup>\*</sup>The exact percentage (concentration) of composition has been withheld as a trade secret.

## 4. FIRST AID MEASURES

Description of necessary first-aid measures

Eye Contact Rinse immed

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If

symptoms persist, call a physician.

Skin Contact Wash off immediately with soap and plenty of water. If symptoms persist, call a physician.

Inhalation Move to fresh air. If breathing is difficult, give oxygen. If symptoms persist, call a physician.

Ingestion

Drink plenty of water. Rinse mouth. Do NOT induce vomiting. Never give anything by mouth

to an unconscious person. Consult a physician if necessary

**Protection of First-aiders** 

For personal protection see Section 8

Most important symptoms/effects, acute and delayed

Most Important Symptoms/Effects Aspiration into lungs can produce severe lung damage

Indication of immediate medical attention and special treatment needed, if necessary

**Notes to Physician** 

Treat symptomatically.

## 5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Carbon dioxide (CO<sub>2</sub>). Foam. Dry powder. Dry chemical.

Unsuitable Extinguishing Media Do not use a solid water stream as it may scatter and spread fire.

#### **Specific Hazards Arising from the Chemical**

Combustible liquid. Vapors may travel to source of ignition and flash back. Thermal decomposition can lead to release of irritating gases and vapors.

**Explosion Data** 

Sensitivity to Mechanical Impact Sensitivity to Static Discharge None. Yes.

**Protective Equipment and Precautions for Firefighters** 

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

### **6. ACCIDENTAL RELEASE MEASURES**

#### Personal precautions, protective equipment and emergency procedures

**Personal Precautions** 

Avoid contact with the skin and the eyes. Use personal protective equipment. Remove all sources of ignition.

Environmental Precautions

**Environmental Precautions** 

Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.

See Section 12 for additional Ecological Information.

#### Methods and materials for containment and cleaning up

**Methods for Containment** 

Prevent further leakage or spillage if safe to do so.

Methods for Cleaning Up

Dam up. Soak up with inert absorbent material. Clean contaminated surface thoroughly.

Keep in suitable and closed containers for disposal.

## 7. HANDLING AND STORAGE

#### Precautions for safe handling

Handling

Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin and eyes. Ensure adequate ventilation. Remove all sources of ignition.

## Conditions for safe storage, including any incompatibilities

Storage

Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of children.

**Incompatible Products** 

None known based on information supplied.

# 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

#### Control parameters

#### **Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Petroleum distillates, hydrotreated light 64742-47-8	TWA: 5 mg/m³ STEL: 10 mg/m³ (as oll mist)	TWA: 5 mg/m³ (as oil mist)	-
Aluminum oxide 1344-28-1	TWA: 1 mg/m³ respirable fraction	TWA: 15 mg/m³ total dust TWA: 5 mg/m³ respirable fraction (vacated) TWA: 10 mg/m³ total dust (vacated) TWA: 5 mg/m³ respirable fraction	<u>-</u>
Triethanolamine 102-71-6	TWA: 5 mg/m³	-	-
Tall oil fatty acids 61790-12-3	5 mg/m³ (resp) 10 mg/m³ STEL (resp)	5 mg/m³ (resp)	-
Hexylene glycol 107-41-5	Ceiling: 25 ppm	(vacated) Ceiling: 25 ppm (vacated) Ceiling: 125 mg/m³	Ceiling: 25 ppm Ceiling: 125 mg/m <sup>3</sup>

Immediately Dangerous to Life or Health.

**Other Exposure Guidelines** 

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

#### Appropriate engineering controls

**Engineering Measures** 

Showers

Eyewash stations Ventilation systems

### Individual protection measures, such as personal protective equipment

**Eye/Face Protection** 

Safety glasses with side-shields.

Skin and Body Protection

Protective gloves.

**Respiratory Protection** 

No protective equipment is needed under normal use conditions. If exposure limits are

exceeded or irritation is experienced, ventilation and evacuation may be required.

**Hygiene Measures** 

When using, do not eat, drink or smoke. Provide regular cleaning of equipment, work area

None known

White

information available

and clothing.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

Physical State Odor	Solid. Pine	Appearance Odor Threshold	Whi No
Property	<u>Values</u>	Remarks/ - I	<u>Method</u>
pH	No data available	None known	
Melting Point/Range	55 °C	None known	
Boiling Point/Boiling Range	No data available	None known	
Flash Point	90`°C / 194 °F	None known	
Evaporation rate	No data available	None known	
Flammability (solid, gas)	No data available	None known	
Flammability Limits in Air			
upper flammability limit	No data available		
lower flammability limit	No data available		

No data available

Vapor Pressure

Vapor Density	No data available	None known
Specific Gravity	No data available	None known
Water Solubility	No data available	None known
Solubility in other solvents	No data available	None known
Partition coefficient: n-octanol/v	vaterNo data available	None known
Autoignition Temperature	No data available	None known
Decomposition Temperature	No data available	None known
Viscosity	No data available	None known

Flammable Properties

Combustible material: may burn but does not ignite readily.

Explosive Properties Oxidizing Properties

No data available No data available

Other information

**VOC Content (%)** 

<30

# 10. STABILITY AND REACTIVITY

#### Reactivity

No data available.

#### **Chemical stability**

Stable under normal conditions.

## Possibility of hazardous reactions

None under normal processing.

### **Hazardous Polymerization**

Hazardous polymerization does not occur.

#### Conditions to avoid

Heat, flames and sparks.

## **Incompatible materials**

None known based on information supplied.

## **Hazardous decomposition products**

None under normal use. Thermal decomposition can lead to release of irritating gases and vapors.

## 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

**Product Information** 

Inhalation Eye Contact No known effect.

Skin Contact Ingestion Contact with eyes may cause irritation.

Prolonged or repeated contact may dry skin and cause irritation. Causes mild skin irritation Ingestion may cause irritation to mucous membranes. Ingestion may cause gastrointestinal

irritation, nausea, vomiting and diarrhea. Potential for aspiration if swallowed.

# **Component Information**

Chemical Name LD50 Oral LD50 Dermal LC50 Inhalation			***	
	Chemical Name	LD50 Oral	LD50 Dermal	LUSU Innalation

Petroleum distillates, hydrotreated light	> 5000 mg/kg(Rat)	> 2000 mg/kg(Rabbit)	> 5.2 mg/L (Rat)4 h
Aluminum oxide	> 5000 mg/kg (Rat)	-	-
Solvent naphtha (petroleum), medium aliphatic	> 5000 mg/kg(Rat)	= 3000 mg/kg(Rabbit)	> 5.28 mg/L (Rat)4 h
Triethanolamine	= 4190 mg/kg (Rat)	> 2000 mg/kg(Rabbit)> 16 mL/kg (Rat)	-
Tall oil fatty acids	= 7600 mg/kg (Rat)		-
Hexylene glycol	= 3692 mg/kg (Rat)	12,3000 mg/kg ( Rabbit )	> 310 mg/m³ (Rat) 1 h

### Symptoms related to the physical, chemical and toxicological characteristics

**Symptoms** 

No information available.

# Delayed and immediate effects and also chronic effects from short and long term exposure

Sensitization

No information available.

Mutagenic Effects

No information available.

Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Triethanolamine		Group 3		

IARC: (International Agency for Research on Cancer)

Group 3 - Not Classifiable as to its Carcinogenicity to Humans

**Reproductive Toxicity** 

No information available.

STOT - single exposure

No information available.

STOT - repeated exposure

No information available.

Chronic Toxicity

Avoid repeated exposure. Repeated contact may cause allergic reactions in very

susceptible persons. Intentional misuse by deliberately concentrating and inhaling contents

may be harmful or fatal

Target Organ Effects

Respiratory system. Eyes. Skin. Central nervous system (CNS).

Aspiration Hazard

May be fatal if swallowed and enters airways

Numerical measures of toxicity - Product

Acute Toxicity 36.04743% of the mixture consists of ingredient(s) of unknown toxicity.

The following values are calculated based on chapter 3.1 of the GHS document:

LD50 Oral

14428 mg/kg; Acute toxicity estimate

LD50 Dermal

25219 mg/kg; Acute toxicity estimate

Inhalation

mg/L

dust/mist

57.1 mg/L; Acute toxicity estimate mg/L

### 12. ECOLOGICAL INFORMATION

#### **Ecotoxicity**

The environmental impact of this product has not been fully investigated.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Petroleum distillates, hydrotreated light 64742-47-8		LC50 96 h: = 45 mg/L flow-through (Pimephales promelas) LC50 96 h: = 2.2 mg/L static (Lepomis macrochirus) LC50 96 h: = 2.4 mg/L static (Oncorhynchus mykiss)		LC50 96 h: = 4720 mg/L (Den-dronereides heteropoda)
Aluminum oxide 1344-28-1		LC50 96 h: > 100 mg/L semistatic (Salmo trutta)		LC50 48 h: > 100 mg/L (daphnia magna)
Solvent naphtha (petroleum), medium aliphatic 64742-88-7	EC50 96 h: = 450 mg/L (Pseudokirchneriella subcapitata)	LC50 96 h: = 800 mg/L static (Pimephales promelas)		EC50 48 h: > 100 mg/L (Daphnia magna)

Triethanolamine 102-71-6	EC50 72 h: = 216 mg/L (Desmodesmus subspicatus) EC50 96 h: = 169 mg/L (Desmodesmus subspicatus)	LC50 96 h: 10600 - 13000 mg/L flow-through (Pimephales promelas) LC50 96 h: > 1000 mg/L static (Pimephales promelas) LC50 96 h: 450 - 1000 mg/L static (Lepomis macrochirus)	EC50 > 10000 mg/L 30 min	EC50 24 h: = 1386 mg/L (Daphnia magna)
Tall oil fatty acids 61790-12-3	EC50 72 h: >= 1000 mg/L (Pseudokirchneriella subcapitata)		,	
Hexylene glycol 107-41-5		LC50 96 h: 10500 - 11000 mg/L flow-through (Pimephales promelas) LC50 96 h: = 10000 mg/L static (Lepomis macrochirus) LC50 96 h: = 8690 mg/L flow-through (Pimephales promelas) LC50 96 h: = 10700 mg/L static (Pimephales promelas)	EC50 = 3038 mg/L 5 min	EC50 48 h: 2700 - 3700 mg/L (Daphnia magna)

Persistence and Degradability

No information available.

Bioaccumulation

No information available.

Chemical Name	Log Pow
Triethanolamine	-2.53
Tall oil fatty acids	5.98
Hexylene glycol	0.13986

# Other Adverse Effects

No information available.

# 13. DISPOSAL CONSIDERATIONS

**Waste Disposal Methods** 

Dispose of in accordance with federal, state, and local regulations

**Contaminated Packaging** 

Do not re-use empty containers.

California Hazardous Waste Codes 331

# 14. TRANSPORT INFORMATION

<u>DOT</u>

Not regulated

<u>TDG</u>

Not regulated

<u>MEX</u>

Not regulated

<u>ICAO</u>

Not regulated

<u>IATA</u>

IMDG/IMO

Not regulated

Not regulated

<u>RID</u>

Not regulated

<u>ADR</u>

Not regulated

ADN

Not regulated

# 15. REGULATORY INFORMATION

**International Inventories** 

TSCA EINECS Complies Complies ELINCS

Complies

#### Legend

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

## **U.S. Federal Regulations**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

## SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	No
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

#### **Clean Water Act**

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

#### **CERCLA**

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

## U.S. State Regulations

#### California Proposition 65

This product does not contain any Proposition 65 chemicals.

### U.S. State Right-to-Know Regulations

"X" designates that the ingredients are listed on the state right to know list.

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Illinois	Rhode Island
Aluminum oxide	X	Х	Х		Х
Solvent naphtha (petroleum), medium aliphatic	X				
Triethanolamine	Х	X	Х		Х
Hexylene glycol	Х	X	Х		Х

## **U.S. EPA Label Information**

EPA Pesticide Registration Number Not applicable

		16. OTHER INFORM	ATION	
NFPA	Health Hazard 2	Flammability 2	Instability 0	Physical and Chemical Hazards N/A
<u>HMIS</u>	Health Hazard 2	Flammability 2	Physical Hazard 0	Personal Protection B

**Prepared By** 

Product Stewardship 23 British American Blvd. Latham, NY 12110 1-800-572-6501

Issuing Date 03-Apr-2007
Revision Date 07-Mar-2015
Revision Note Update to Format.

#### General Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

**End of Safety Data Sheet**