

## **SAFETY DATA SHEET**

Marine Grease Multi-Purpose Boat Trailer - E-Marine

1. Identification

BY: CRC

**Product identifier** 

Marine Boat Trailer and 4x4 Wheel Bearing Grease

Other means of identification

Product code

SL3120, SL3121, SL3125, SL3127, SL3184

Recommended use

Bearing grease

**Recommended restrictions** 

None known.

Manufacturer/Importer/Supplier/Distributor information

Manufactured or sold by:

Company name

CRC Industries, Inc.

Address

885 Louis Dr.

Warminster, PA 18974 US

Telephone

**General Information** 

215-674-4300

Technical

800-521-3168

Assistance

**Customer Service** 

800-272-4620

24-Hour Emergency

800-424-9300 (US)

(CHEMTREC)

703-527-3887 (International)

Website

www.crcindustries.com

#### 2. Hazard(s) identification

Physical hazards

Not classified.

Health hazards

Serious eye damage/eye irritation

Category 2A Category 1

Sensitization, skin

**Environmental hazards** 

OSHA defined hazards

Not classified. Not classified.

Label elements



Signal word

Warning

**Hazard statement** 

May cause an allergic skin reaction. Causes serious eye irritation.

Precautionary statement

Prevention

Avoid breathing vapors. Wash thoroughly after handling. Contaminated work clothing must not be

allowed out of the workplace. Wear protective gloves. Wear eye/face protection.

Response

If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical attention. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. Wash contaminated

clothing before reuse.

Storage

Store away from incompatible materials.

Disposal

Dispose of contents/container in accordance with local/regional/national regulations.

Hazard(s) not otherwise classified (HNOC)

heavy naphthenic

None known.

#### 3. Composition/information on ingredients

Mixtures			
Chemical name	Common name and synonyms	CAS number	%
Distillates (petroleum), hydrotreated	· · · · · · · · · · · · · · · · · · ·	64742-52-5	60 - 70

Chemical name	Common name and synonyms	CAS number	%	
Distillates (petroleum), solvent-dewaxed heavy paraffinic		64742-65-0	20 - 30	
White mineral oil		8042-47-5	5 - 10	
Benzoic Acid		65-85-0	1 - 3	
Calcium bis(dinonylnaphthalenesulphonate)		57855-77-3	1 - 3	
Distillates (petroleum), Hydrotreated Light Naphthenic		64742-53-6	1 - 3	

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

#### 4. First-aid measures

Inhalation	Move to fresh air. Provide oxygen or artificial respiration if needed. Call a physician if symptoms develop or persist.
Skin contact	Immediately flush with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Never give anything by mouth to a victim who is unconscious or is having convulsions. Do not induce vomiting without advice from poison control center. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause an allergic skin reaction. Dermatitis. Rash.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

## 5. Fire-fighting measures

	·
Suitable extinguishing media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Unsuitable extinguishing media	None known.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
General fire hazards	No unusual fire or explosion hazards noted.

## 6. Accidental release measures

Personal precautions,
protective equipment and
emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

# Methods and materials for containment and cleaning up

The product is immiscible with water and will spread on the water surface.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.

Small Spills: Sweep up or vacuum up spillage and collect in suitable container for disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

### 7. Handling and storage

Precautions for safe handling

Provide adequate ventilation. Avoid breathing vapor. Avoid contact with eyes, skin, and clothing. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. For product usage instructions, please see the product label.

Conditions for safe storage, including any incompatibilities

Store in a cool, dry place out of direct sunlight. Keep container tightly closed. Store away from incompatible materials (see Section 10 of the SDS).

#### 8. Exposure controls/personal protection

Components         Type         Value         Form           Distillates (petroleum), hydrotreated beavy naphthenic (CAS 64742-52-5)         PEL         5 mg/m3         Mist.           Distillates (petroleum), Hydrotreated Light Naphthenic (CAS 64742-53-6)         PEL         5 mg/m3         Mist.           Distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0)         PEL         5 mg/m3         Mist.           White mineral oil (CAS 64742-65-0)         PEL         5 mg/m3         Mist.           US. ACGIH Threshold Limit Values Components         Type         Value         Form           Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-65-0)         TWA         5 mg/m3         Inhalable fraction.           Distillates (petroleum), hydrotreated Light Naphthenic (CAS 64742-65-0)         TWA         5 mg/m3         Inhalable fraction.           Distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0)         TWA         5 mg/m3         Inhalable fraction.           White mineral oil (CAS 64742-65-0)         TWA         5 mg/m3         Inhalable fraction.           UNIS mineral oil (CAS 64742-65-0)         TWA         5 mg/m3         Inhalable fraction.           White mineral oil (CAS 64742-65-0)         TWA         5 mg/m3         Inhalable fraction.           UNIS NIOSH: Pocket Guide to Chemical Hazards Compon	upational exposure limits US. OSHA Table Z-1 Limits for Air	Contaminants (29 CFR 1910.1000)		
hydrotreated heavy   hydrotreated heavy   hydrotreated Light   hydrotreated heavy paraffinic (CAS 64742-65-0)   hydrotreated Light			Value	Form
Distillates (petroleum),	hydrotreated heavy naphthenic (CAS	PEL	5 mg/m3	Mist.
Distillates (petroleum),   PEL   5 mg/m3   Mist.     Hydrotreated Light   Naphthemic (CAS   64742-53-6)     Distillates (petroleum),   PEL   5 mg/m3   Mist.     Distillates (Petroleum),   Mist.   5 mg/m3   Mist.     Distillates (Petroleum),   TWA   5 mg/m3   Inhalable fraction.     Distillates (Petroleum),   TWA   5 mg/m3   Mist.	04742-32-3)		2000 mg/m3	
Distillates (petroleum),			-	
Distillates (petroleum),   PEL   5 mg/m3   Mist.	Distillates (petroleum), Hydrotreated Light Naphthenic (CAS 64742-53-6)	PEL .	• •	Mist.
Distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0)   Solvent-dewaxed heavy had been been been been been been been bee	- / 1		2000 mg/m3	
Distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0)   2000 mg/m3   500 ppm   500				•
White mineral oil (CAS   PEL   5 mg/m3   Mist.	Distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0)	PEL	• •	Mist.
White mineral oil (CAS 8042-47-5)  US. ACGIH Threshold Limit Values Components  Type  Value  Form  Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)  Distillates (petroleum), TWA Naphthenic (CAS 64742-65-0)  US. MICHIGAN TWA Naphthenic (CAS 64742-65-0)  White mineral oil (CAS 64742-65-0)  US. NIOSH: Pocket Guide to Chemical Hazards Components  Type  Value  Form  TWA  5 mg/m3 Inhalable fraction.  1 malable fraction.  1 malabl	paramine (eric eri 12 de e)	•	2000 mg/m3	
White mineral oil (CAS 8042-47-5)  US. ACGIH Threshold Limit Values Components  Type  Value  Form  Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)  Distillates (petroleum), TWA  TWA  5 mg/m3  Inhalable fraction.  1 malable fraction.  2 malable fraction.  3 malable fraction.  5 mg/m3  Inhalable fraction.  1 malable fraction.  1 malable fraction.  1 malable fraction.  1 malable fraction.  2 malable fraction.  3 malable fraction.  5 mg/m3  Inhalable fraction.  1 malable fraction.  1 mala				
Components  Type  Value  Form  Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-65-0)  Distillates (petroleum), TWA  S mg/m3  Inhalable fraction.  TWA  S mg/m3  Inhalable fraction.  Fraction.  TWA  S mg/m3  Inhalable fraction.  TWA  S mg/m3  Inhalable fraction.  Fraction.  TWA  S mg/m3  Inhalable fraction.	White mineral oil (CAS 8042-47-5)	PEL		Mist.
Components  Type  Value  Form  Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-65-0)  Distillates (petroleum), TWA  S mg/m3  Inhalable fraction.  TWA  S mg/m3  Inhalable fraction.  Fraction.  TWA  S mg/m3  Inhalable fraction.  TWA  S mg/m3  Inhalable fraction.  Fraction.  TWA  S mg/m3  Inhalable fraction.	US. ACGIH Threshold Limit Values			
hydrotreated heavy naphthenic (CAS 64742-52-5) Distillates (petroleum), TWA 5 mg/m3 Inhalable fraction. Hydrotreated Light Naphthenic (CAS 64742-53-6) Distillates (petroleum), TWA 5 mg/m3 Inhalable fraction.  Bit illates (petroleum), TWA 5 mg/m3 Inhalable fraction.  Solvent-dewaxed heavy paraffinic (CAS 64742-65-0) White mineral oil (CAS TWA 5 mg/m3 Inhalable fraction.  BUS. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Form  Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)  STEL 10 mg/m3 Mist. TWA 5 mg/m3 Mist.  Distillates (petroleum), Hydrotreated Light Naphthenic (CAS 64742-53-6)	Components		Value	Form
Distillates (petroleum), Hydrotreated Light Naphthenic (CAS 64742-53-6) Distillates (petroleum), TWA 5 mg/m3 Inhalable fraction.  Type Value Form  Distillates (petroleum), Ceiling 1800 mg/m3 Mist.  TWA 5 mg/m3 Mist.  TWA 5 mg/m3 Mist.  TWA 5 mg/m3 Mist.  Distillates (petroleum), Hydrotreated Light Naphthenic (CAS 64742-53-6)	Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	TWA	5 mg/m3	Inhalable fraction.
Distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0)  White mineral oil (CAS TWA 5 mg/m3 Inhalable fraction. 8042-47-5)  US. NIOSH: Pocket Guide to Chemical Hazards  Components Type Value Form  Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)  STEL 10 mg/m3 Mist.  TWA 5 mg/m3 Mist.  Distillates (petroleum), Ceiling 1800 mg/m3  Mist.  TWA 5 mg/m3 Mist.  Distillates (petroleum), Hydrotreated Light Naphthenic (CAS 64742-53-6)	Distillates (petroleum), Hydrotreated Light Naphthenic (CAS	TWA	5 mg/m3	Inhalable fraction.
White mineral oil (CAS TWA 5 mg/m3 Inhalable fraction. 8042-47-5)  US. NIOSH: Pocket Guide to Chemical Hazards  Components Type Value Form  Distillates (petroleum), Ceiling 1800 mg/m3 hydrotreated heavy naphthenic (CAS 64742-52-5)  STEL 10 mg/m3 Mist. TWA 5 mg/m3 Mist.  Distillates (petroleum), Ceiling 1800 mg/m3 Mist.  TWA 5 mg/m3 Mist.  Distillates (petroleum), Ceiling 1800 mg/m3  Hydrotreated Light Naphthenic (CAS 64742-53-6)	Distillates (petroleum), solvent-dewaxed heavy	TWA	5 mg/m3	Inhalable fraction.
Components  Type  Value  Form  Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)  STEL TWA  Distillates (petroleum), Hydrotreated Light Naphthenic (CAS 64742-53-6)	White mineral oil (CAS	TWA	5 mg/m3	Inhalable fraction.
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)  STEL 10 mg/m3 Mist.  TWA 5 mg/m3 Mist.  Distillates (petroleum), Ceiling 1800 mg/m3  Hydrotreated Light Naphthenic (CAS 64742-53-6)	US. NIOSH: Pocket Guide to Chem	ical Hazards		
hydrotreated heavy naphthenic (CAS 64742-52-5)  STEL  TWA  Distillates (petroleum),  Hydrotreated Light Naphthenic (CAS 64742-53-6)  STEL  10 mg/m3  Mist.  5 mg/m3  Mist.  1800 mg/m3	Components	Туре	Value	Form
TWA 5 mg/m3 Mist.  Distillates (petroleum), Ceiling 1800 mg/m3  Hydrotreated Light  Naphthenic (CAS 64742-53-6)	hydrotreated heavy naphthenic (CAS			
Distillates (petroleum), Ceiling 1800 mg/m3 Hydrotreated Light Naphthenic (CAS 64742-53-6)			<del>-</del>	
Hydrotreated Light Naphthenic (CAS 64742-53-6)			_	Mist.
·	Distillates (petroleum), Hydrotreated Light Naphthenic (CAS 64742-53-6)	Ceiling	1800 mg/m3	
	,	STEL	10 mg/m3	Mist.

Components	Туре	Value	Form
Distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0)	Ceiling	1800 mg/m3	
	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
White mineral oil (CAS 8042-47-5)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.

**Biological limit values** 

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection

Wear protective gloves such as: Latex. Rubber.

Other

Wear appropriate chemical resistant clothing.

Respiratory protection

If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to

determine actual employee exposure levels.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

## 9. Physical and chemical properties

#### Appearance

Physical state

Solid.

**Form** 

Grease.

Color

Blue.

Odor

Mild petroleum.

Odor threshold

Not available.

Not available.

Melting point/freezing point

Not available.

Initial boiling point and boiling range

450 °F (232.2 °C) estimated

Flash point

> 450 °F (> 232.2 °C) Cleveland Open Cup

**Evaporation rate** 

Slow.

Flammability (solid, gas)

Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

Flammability limit - upper

Not available.

(%)

Vapor pressure

Not available.

Vapor density

Not available.

Relative density

0.9

Solubility (water)

Insoluble.

Partition coefficient (n-octanol/water)

Not available.

Auto-ignition temperature

500 °F (260 °C) estimated

Decomposition temperature

Not available.

Viscosity (kinematic)

> 21 mm<sup>2</sup>/s (104 °F (40 °C))

Percent volatile

Not available.

## 10. Stability and reactivity

Reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability

Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid

Contact with incompatible materials.

Incompatible materials

Strong oxidizing agents.

Hazardous decomposition products

Carbon oxides. Sulfur oxides. Metal oxides.

## 11. Toxicological information

## Information on likely routes of exposure

Inhalation

Prolonged inhalation may be harmful.

Skin contact

May cause an allergic skin reaction.

Eve contact

Causes serious eye irritation.

Ingestion

Can cause stomach ache and vomiting.

Symptoms related to the physical, chemical and toxicological characteristics Prolonged or excessive inhalation may cause respiratory tract irritation. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause an

allergic skin reaction. Dermatitis. Rash.

#### Information on toxicological effects

Acute toxicity

May cause an allergic skin reaction. Expected to be a low hazard for usual industrial or

commercial handling by trained personnel.

Product

**Species** 

**Test Results** 

Marine Boat Trailer and 4x4 Wheel Bearing Grease

Acute

Dermal

LD50

Rabbit

2604 mg/kg estimated

Inhalation

LC50

Rat

100 mg/l, 4 hours estimated

Oral

LD50

Rat

115472.9 mg/kg Acute Toxicity Estimate

Skin corrosion/irritation

Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory sensitization Skin sensitization

Not a respiratory sensitizer.

May cause an allergic skin reaction.

Germ cell mutagenicity

No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity

Based on available data, the classification criteria are not met.

#### IARC Monographs. Overall Evaluation of Carcinogenicity

White mineral oil (CAS 8042-47-5)

3 Not classifiable as to carcinogenicity to humans.

## US. National Toxicology Program (NTP) Report on Carcinogens

Not available.

Reproductive toxicity

This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Material name: Marine Boat Trailer and 4x4 Wheel Bearing Grease

SDS US

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard

Not an aspiration hazard.

Chronic effects

Prolonged exposure may cause chronic effects.

## 12. Ecological information

**Ecotoxicity** 

**Product** 

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Species Marine Boat Trailer and 4x4 Wheel Bearing Grease

Aquatic

Fish

Components

Crustacea

EC50 LC50

Daphnia

**Species** 

Fish

1638.796 mg/l, 48 hours estimated 5604.2324 mg/l, 96 hours estimated

**Test Results** 

Benzoic Acid (CAS 65-85-0)

Aquatic

Fish

LC50

Western mosquitofish (Gambusia affinis) 180 mg/l, 96 hours

Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)

**Aquatic** 

Crustacea

**EC50** 

Water flea (Daphnia magna)

1000 ma/l. 48 hours

**Test Results** 

Fish

LC50

Rainbow trout, donaldson trout

5000 mg/l, 96 hours

(Oncorhynchus mykiss)

Persistence and degradability

Not readily biodegradable.

Bioaccumulative potential

No data available.

\* Estimates for product may be based on additional component data not shown.

Partition coefficient n-octanol / water (log Kow)

Benzoic Acid

1.87

Mobility in soil

No data available.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

#### 13. Disposal considerations

Disposal of waste from residues / unused products This product is not a RCRA hazardous waste (See 40 CFR Part 261.20 - 261.33). Empty containers may be recycled. Collect and reclaim or dispose in sealed containers at licensed waste

disposal site. Dispose in accordance with all applicable regulations.

Hazardous waste code

Not regulated.

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

#### 14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

**IMDG** 

Not regulated as dangerous goods.

#### 15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Material name: Marine Boat Trailer and 4x4 Wheel Bearing Grease

SDS US

#### SARA 304 Emergency release notification

Not regulated.

## US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

Not listed

#### **CERCLA Hazardous Substance List (40 CFR 302.4)**

Benzoic Acid (CAS 65-85-0)

Listed.

### **CERCLA Hazardous Substances: Reportable quantity**

Benzoic Acid (CAS 65-85-0)

5000 LBS

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

## Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

## Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

Food and Drug

Not regulated.

Administration (FDA)

## Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 311/312

Immediate Hazard - Yes Delayed Hazard - No

Hazard categories

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

No.

## US state regulations

## US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)

Distillates (petroleum), Hydrotreated Light Naphthenic (CAS 64742-53-6)

Distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0)

## US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100) Not listed.

## US. New Jersey Worker and Community Right-to-Know Act

Benzoic Acid (CAS 65-85-0)

Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)

Distillates (petroleum), Hydrotreated Light Naphthenic (CAS 64742-53-6)

Distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0)

White mineral oil (CAS 8042-47-5)

#### US. Massachusetts RTK - Substance List

Benzoic Acid (CAS 65-85-0)

Distillates (petroleum), Hydrotreated Light Naphthenic (CAS 64742-53-6)

White mineral oil (CAS 8042-47-5)

### US. Pennsylvania Worker and Community Right-to-Know Law

Benzoic Acid (CAS 65-85-0)

White mineral oil (CAS 8042-47-5)

#### **US. Rhode Island RTK**

Benzoic Acid (CAS 65-85-0)

#### US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

## US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Naphthalene (CAS 91-20-3)

Listed: April 19, 2002

## Volatile organic compounds (VOC) regulations

**EPA** 

VOC content (40 CFR

Not determined

51.100(s))

Material name: Marine Boat Trailer and 4x4 Wheel Bearing Grease

SDS US

Consumer products (40 CFR 59, Subpt. C)

Not regulated

State

**Consumer products** 

Not regulated

VOC content (CA)

0 %

VOC content (OTC)

0 %

#### International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

<sup>\*</sup>A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information, including date of preparation or last revision

 Issue date
 07-30-2015

 Revision date
 08-20-2015

 Prepared by
 Allison Cho

 Version #
 02

Further information Not available.

HMIS® ratings Health: 1

Flammability: 1 Physical hazard: 0 Personal protection: B

NFPA ratings Health: 1

Flammability: 1 Instability: 0

**NFPA** ratings



#### Disclaimer

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries.