

SAFETY DATA SHEET

DOW CORNING

MOLYKOTE(R) G-0052 FM WHITE EP BEARING GREASE

Version 3.0 Revision Date: 03/19/2016 SDS Number: 888494-00006 Date of last issue: 11/10/2015
Date of first issue: 12/03/2014

SECTION 1. IDENTIFICATION

Product name : MOLYKOTE(R) G-0052 FM WHITE EP BEARING GREASE

Product code : 000000000004051667, 000000000004051667

Manufacturer or supplier's details

Company name of supplier : Dow Corning Corporation

Address : South Saginaw Road
Midland Michigan 48686

Telephone : (989) 496-6000

Emergency telephone : 24 Hour Emergency Telephone : (989) 496-5900
CHEMTREC : (800) 424-9300

White EP Bearing
Grease

Recommended use of the chemical and restrictions on use

Recommended use : Lubricants and lubricant additives

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Not a hazardous substance or mixture.

GHS label elements

Not a hazardous substance or mixture.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Organic grease

Hazardous ingredients

Chemical name	CAS-No.	Concentration (% w/w)
White mineral oil (petroleum)	8042-47-5	>= 70 - < 90
Aluminum hydroxide benzoate stearate	54326-11-3	>= 10 - < 20
Calcium carbonate	471-34-1	>= 5 - < 10
Zinc oxide	1314-13-2	>= 5 - < 10

SECTION 4. FIRST AID MEASURES

If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.

SAFETY DATA SHEET

DOW CORNING

MOLYKOTE(R) G-0052 FM WHITE EP BEARING GREASE

Version 3.0	Revision Date: 03/19/2016	SDS Number: 888494-00006	Date of last issue: 11/10/2015 Date of first issue: 12/03/2014
----------------	------------------------------	-----------------------------	---

- | | |
|---|---|
| In case of skin contact | : Wash with water and soap as a precaution.
Get medical attention if symptoms occur. |
| In case of eye contact | : Flush eyes with water as a precaution.
Get medical attention if irritation develops and persists. |
| If swallowed | : If swallowed, DO NOT induce vomiting.
Get medical attention if symptoms occur.
Rinse mouth thoroughly with water. |
| Most important symptoms and effects, both acute and delayed | : None known. |
| Protection of first-aiders | : No special precautions are necessary for first aid responders. |
| Notes to physician | : Treat symptomatically and supportively. |

SECTION 5. FIRE-FIGHTING MEASURES

- | | |
|--|---|
| Suitable extinguishing media | : Water spray
Alcohol-resistant foam
Carbon dioxide (CO2)
Dry chemical |
| Unsuitable extinguishing media | : None known. |
| Specific hazards during fire fighting | : Exposure to combustion products may be a hazard to health. |
| Hazardous combustion products | : Carbon oxides
Metal oxides |
| Specific extinguishing methods | : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area. |
| Special protective equipment for fire-fighters | : Wear self-contained breathing apparatus for firefighting if necessary.
Use personal protective equipment. |

SECTION 6. ACCIDENTAL RELEASE MEASURES

- | | |
|---|--|
| Personal precautions, protective equipment and emergency procedures | : Follow safe handling advice and personal protective equipment recommendations. |
| Environmental precautions | : Discharge into the environment must be avoided. |

**MOLYKOTE(R) G-0052 FM WHITE EP
BEARING GREASE**Version
3.0Revision Date:
03/19/2016SDS Number:
888494-00006Date of last issue: 11/10/2015
Date of first issue: 12/03/2014

Prevent further leakage or spillage if safe to do so.
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for
containment and cleaning up

: Soak up with inert absorbent material.
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures

: See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation

: Use only with adequate ventilation.

Advice on safe handling

: Handle in accordance with good industrial hygiene and safety practice.
Take care to prevent spills, waste and minimize release to the environment.

Conditions for safe storage

: Keep in properly labeled containers.
Store in accordance with the particular national regulations.

Materials to avoid

: Do not store with the following product types:
Strong oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Ingredients with workplace control parameters**

Ingredients	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
White mineral oil (petroleum)	8042-47-5	TWA (Mist)	5 mg/m ³	OSHA Z-1
		TWA (Inhalable fraction)	5 mg/m ³	ACGIH
		TWA (Mist)	5 mg/m ³	NIOSH REL
		ST (Mist)	10 mg/m ³	NIOSH REL
Aluminum hydroxide benzoate stearate	54326-11-3	TWA	10 mg/m ³	ACGIH
Calcium carbonate	471-34-1	TWA (Res-	5 mg/m ³	NIOSH REL

SAFETY DATA SHEET

DOW CORNING**MOLYKOTE(R) G-0052 FM WHITE EP
BEARING GREASE**Version
3.0Revision Date:
03/19/2016SDS Number:
888494-00006

Date of last issue: 11/10/2015

Date of first issue: 12/03/2014

		pirable)		
		TWA (total)	10 mg/m ³	NIOSH REL
Zinc oxide	1314-13-2	TWA (Respirable fraction)	2 mg/m ³	ACGIH
		STEL (Respirable fraction)	10 mg/m ³	ACGIH
		TWA (Dust)	5 mg/m ³	NIOSH REL
		TWA (Fumes)	5 mg/m ³	NIOSH REL
		ST (Fumes)	10 mg/m ³	NIOSH REL
		C (Dust)	15 mg/m ³	NIOSH REL
		TWA (total dust)	15 mg/m ³	OSHA Z-1
		TWA (respirable fraction)	5 mg/m ³	OSHA Z-1
		TWA (Fumes)	5 mg/m ³	OSHA Z-1

Engineering measures : Ensure adequate ventilation, especially in confined areas.
Minimize workplace exposure concentrations.

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Hand protection

Remarks : Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:
Safety glasses

Skin and body protection : Skin should be washed after contact.

Hygiene measures : Ensure that eye flushing systems and safety showers are located close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.
These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may require added precautions.

**MOLYKOTE(R) G-0052 FM WHITE EP
BEARING GREASE**Version
3.0Revision Date:
03/19/2016SDS Number:
888494-00006Date of last issue: 11/10/2015
Date of first issue: 12/03/2014**II****SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance	: Grease
Color	: white
Odor	: slight
Odor Threshold	: No data available
pH	: Not applicable
Melting point/freezing point	: No data available
Initial boiling point and boiling range	: Not applicable
Flash point	: > 200 °C Method: closed cup
Evaporation rate	: Not applicable
Flammability (solid, gas)	: Not classified as a flammability hazard
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapor pressure	: Not applicable
Relative vapor density	: No data available
Relative density	: 0.89
Solubility(ies) Water solubility	: No data available
Partition coefficient: n-octanol/water	: No data available
Autoignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity Viscosity, dynamic	: Not applicable
Explosive properties	: Not explosive
Oxidizing properties	: The substance or mixture is not classified as oxidizing.
Molecular weight	: No data available

**MOLYKOTE(R) G-0052 FM WHITE EP
BEARING GREASE**

Version 3.0	Revision Date: 03/19/2016	SDS Number: 888494-00006	Date of last issue: 11/10/2015 Date of first issue: 12/03/2014
----------------	------------------------------	-----------------------------	---

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Not classified as a reactivity hazard.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Can react with strong oxidizing agents.
Conditions to avoid	: None known.
Incompatible materials	: Oxidizing agents
Hazardous decomposition products	: No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Ingredients:**White mineral oil (petroleum):**

Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg
Acute inhalation toxicity	: LC50 (Rat): > 5 mg/l Exposure time: 4 h Test atmosphere: dust/mist Assessment: The substance or mixture has no acute inhalation toxicity
Acute dermal toxicity	: LD50 (Rabbit): > 2,000 mg/kg Assessment: The substance or mixture has no acute dermal toxicity

Aluminum hydroxide benzoate stearate:

Acute oral toxicity	: LD50 (Rat): > 2,000 mg/kg Method: OECD Test Guideline 420 Assessment: The substance or mixture has no acute oral toxicity
Acute dermal toxicity	: LD50 (Rat): > 2,000 mg/kg Method: OECD Test Guideline 402 Assessment: The substance or mixture has no acute dermal toxicity

**MOLYKOTE(R) G-0052 FM WHITE EP
BEARING GREASE**Version
3.0Revision Date:
03/19/2016SDS Number:
888494-00006Date of last issue: 11/10/2015
Date of first issue: 12/03/2014**II****Calcium carbonate:**

- Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 420
Assessment: The substance or mixture has no acute oral toxicity
- Acute inhalation toxicity : LC50 (Rat): > 3 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity
- Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

Zinc oxide:

- Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 401
- Acute inhalation toxicity : LC50 (Rat): > 5.7 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity

Skin corrosion/irritation

Not classified based on available information.

Ingredients:**White mineral oil (petroleum):**

Species: Rabbit
Result: No skin irritation

Aluminum hydroxide benzoate stearate:

Method: OECD Test Guideline 439
Result: No skin irritation

Calcium carbonate:

Species: Rabbit
Method: OECD Test Guideline 404
Result: No skin irritation

Zinc oxide:

Species: Rabbit

**MOLYKOTE(R) G-0052 FM WHITE EP
BEARING GREASE**

Version	Revision Date:	SDS Number:	Date of last issue:
3.0	03/19/2016	888494-00006	11/10/2015
			Date of first issue: 12/03/2014

Method: OECD Test Guideline 404
Result: No skin irritation

Serious eye damage/eye irritation

Not classified based on available information..

Ingredients:**White mineral oil (petroleum):**

Species: Rabbit
Result: No eye irritation

Aluminum hydroxide benzoate stearate:

Species: Rabbit
Result: No eye irritation
Method: OECD Test Guideline 405

Calcium carbonate:

Species: Rabbit
Result: No eye irritation
Method: OECD Test Guideline 405

Zinc oxide:

Species: Rabbit
Result: No eye irritation
Method: OECD Test Guideline 405

Respiratory or skin sensitization**Skin sensitization**

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Ingredients:**White mineral oil (petroleum):**

Test Type: Buehler Test
Routes of exposure: Skin contact
Species: Guinea pig
Result: negative

Aluminum hydroxide benzoate stearate:

Test Type: Local lymph node assay (LLNA)
Routes of exposure: Skin contact
Species: Mouse
Method: OECD Test Guideline 429
Result: negative

**MOLYKOTE(R) G-0052 FM WHITE EP
BEARING GREASE**

Version	Revision Date:	SDS Number:	Date of last issue: 11/10/2015
3.0	03/19/2016	888494-00006	Date of first issue: 12/03/2014

Calcium carbonate:

Test Type: Local lymph node assay (LLNA)
Routes of exposure: Skin contact
Species: Mouse
Method: OECD Test Guideline 429
Result: negative

Zinc oxide:

Test Type: Maximization Test
Routes of exposure: Skin contact
Species: Guinea pig
Method: OECD Test Guideline 406
Result: negative

Germ cell mutagenicity

Not classified based on available information.

Ingredients:**White mineral oil (petroleum):**

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo
cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Method: OECD Test Guideline 474
Result: negative
Remarks: Based on data from similar materials

Aluminum hydroxide benzoate stearate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

: Test Type: In vitro mammalian cell gene mutation test
Result: negative

Calcium carbonate:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Result: negative

Zinc oxide:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo
cytogenetic assay)
Species: Rat

**MOLYKOTE(R) G-0052 FM WHITE EP
BEARING GREASE**

Version 3.0	Revision Date: 03/19/2016	SDS Number: 888494-00006	Date of last issue: 11/10/2015 Date of first issue: 12/03/2014
----------------	------------------------------	-----------------------------	---

Application Route: Inhalation
Method: OECD Test Guideline 474
Result: negative

Carcinogenicity

Not classified based on available information.

Ingredients:**White mineral oil (petroleum):**

Species: Rat
Application Route: Ingestion
Exposure time: 24 Months
Result: negative

IARC

No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

Ingredients:**White mineral oil (petroleum):**

Effects on fertility : Test Type: One-generation reproduction toxicity study
Species: Rat
Application Route: Skin contact
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Result: negative

Aluminum hydroxide benzoate stearate:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the

**MOLYKOTE(R) G-0052 FM WHITE EP
BEARING GREASE**

Version 3.0	Revision Date: 03/19/2016	SDS Number: 888494-00006	Date of last issue: 11/10/2015 Date of first issue: 12/03/2014
----------------	------------------------------	-----------------------------	---

reproduction/developmental toxicity screening test

Species: Rat

Application Route: Ingestion

Method: OECD Test Guideline 422

Result: negative

Calcium carbonate:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

Effects on fetal development : Test Type: Reproduction/Developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

Zinc oxide:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 416
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Hamster
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Ingredients:**Zinc oxide:**

Routes of exposure: inhalation (dust/mist/fume)

Assessment: No significant health effects observed in animals at concentrations of 0.2 mg/l/6h/d or less.

**MOLYKOTE(R) G-0052 FM WHITE EP
BEARING GREASE**

Version	Revision Date:	SDS Number:	Date of last issue: 11/10/2015
3.0	03/19/2016	888494-00006	Date of first issue: 12/03/2014

Repeated dose toxicity**Ingredients:****White mineral oil (petroleum):**

Species: Rat
LOAEL: > 160 mg/kg
Application Route: Ingestion
Exposure time: 90 Days

Species: Rat
LOAEL: >= 1 mg/l
Application Route: inhalation (dust/mist/fume)
Exposure time: 4 Weeks
Method: OECD Test Guideline 412

Aluminum hydroxide benzoate stearate:

Species: Rat
NOAEL: > 225 mg/kg
Application Route: Ingestion
Exposure time: 54 Days
Method: OECD Test Guideline 422
Remarks: Based on data from similar materials

Calcium carbonate:

Species: Rat
NOAEL: 1,000 mg/kg
Application Route: Ingestion
Exposure time: 6 Weeks
Method: OECD Test Guideline 422

Zinc oxide:

Species: Rat
NOAEL: 1.5 mg/m³
Application Route: inhalation (dust/mist/fume)
Exposure time: 3 Months
Method: OECD Test Guideline 413

Aspiration toxicity

Not classified based on available information.

Ingredients:**White mineral oil (petroleum):**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

**MOLYKOTE(R) G-0052 FM WHITE EP
BEARING GREASE**Version
3.0Revision Date:
03/19/2016SDS Number:
888494-00006Date of last issue: 11/10/2015
Date of first issue: 12/03/2014**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity****Ingredients:****White mineral oil (petroleum):**

Toxicity to fish	: LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h Method: OECD Test Guideline 202
Toxicity to algae	: NOEC (Pseudokirchneriella subcapitata (green algae)): 100 mg/l Exposure time: 72 h Method: OECD Test Guideline 201
Toxicity to fish (Chronic toxicity)	: NOEC (Oncorhynchus mykiss (rainbow trout)): 1,000 mg/l Exposure time: 28 d
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC (Daphnia magna (Water flea)): 1,000 mg/l Exposure time: 21 d

Aluminum hydroxide benzoate stearate:

Toxicity to fish	: LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h Method: OECD Test Guideline 202
Toxicity to algae	: ErC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l Exposure time: 72 h Method: OECD Test Guideline 201

Calcium carbonate:

Toxicity to fish	: LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h Method: OECD Test Guideline 202
Toxicity to algae	: ErC50 (Desmodesmus subspicatus (green algae)): > 14 mg/l Exposure time: 72 h

**MOLYKOTE(R) G-0052 FM WHITE EP
BEARING GREASE**Version
3.0Revision Date:
03/19/2016SDS Number:
888494-00006Date of last issue: 11/10/2015
Date of first issue: 12/03/2014

Method: OECD Test Guideline 201

Zinc oxide:

- Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 330 - 780 µg/l
Exposure time: 96 h
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 6.9 - 16.2 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
- Toxicity to algae : EC50 (Selenastrum capricornutum (green algae)): 136 µg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
- NOEC (Selenastrum capricornutum (green algae)): 24 µg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
- M-Factor (Acute aquatic toxicity) : 1
- Toxicity to fish (Chronic toxicity) : NOEC (Oncorhynchus mykiss (rainbow trout)): 199 µg/l
Exposure time: 30 d
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 37 µg/l
Exposure time: 21 d
Remarks: Based on data from similar materials
- M-Factor (Chronic aquatic toxicity) : 1
- Toxicity to bacteria : EC50: 5.2 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209
Remarks: Based on data from similar materials

Persistence and degradability**Ingredients:****White mineral oil (petroleum):**

- Biodegradability : Result: Not readily biodegradable.
Biodegradation: 31 %
Exposure time: 28 d

Aluminum hydroxide benzoate stearate:

- Biodegradability : Result: Readily biodegradable.
Biodegradation: 79 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

**MOLYKOTE(R) G-0052 FM WHITE EP
BEARING GREASE**Version
3.0Revision Date:
03/19/2016SDS Number:
888494-00006Date of last issue: 11/10/2015
Date of first issue: 12/03/2014**II****Bioaccumulative potential****Ingredients:****Zinc oxide:**

Bioaccumulation

: Species: Fish
Bioconcentration factor (BCF): 177**Mobility in soil**

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**Resource Conservation and
Recovery Act (RCRA) : This product has been evaluated for RCRA characteristics
and does not meet the criteria of hazardous waste if discarded
in its purchased form.

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste
handling site for recycling or disposal.
If not otherwise specified: Dispose of as unused product.**SECTION 14. TRANSPORT INFORMATION****International Regulation****UNRTDG**UN number : UN 3077
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,
N.O.S.
(Zinc oxide)
Class : 9
Packing group : III
Labels : 9**IATA-DGR**UN/ID No. : UN 3077
Proper shipping name : Environmentally hazardous substance, solid, n.o.s.
(Zinc oxide)
Class : 9
Packing group : III
Labels : Miscellaneous
Packing instruction (cargo
aircraft) : 956
Packing instruction (passen-
ger aircraft) : 956

**MOLYKOTE(R) G-0052 FM WHITE EP
BEARING GREASE**

Version	Revision Date:	SDS Number:	Date of last issue: 11/10/2015
3.0	03/19/2016	888494-00006	Date of first issue: 12/03/2014

IMDG-Code

UN number	: UN 3077
Proper shipping name	: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Zinc oxide)
Class	: 9
Packing group	: III
Labels	: 9
EmS Code	: F-A, S-F
Marine pollutant	: yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation**49 CFR**

UN/ID/NA number	: UN 3077
Proper shipping name	: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S., ENVIRONMENTALLY HAZARDOUS SUBSTANCES, SOLID, N.O.S. (Zinc oxide)
Class	: 9
Packing group	: III
Labels	: CLASS 9
ERG Code	: 171
Marine pollutant	: yes (Zinc oxide)
Remarks	: Above applies only to containers over 119 gallons or 450 li- ters., Shipment by ground under DOT is non-regulated; how- ever it may be shipped per the applicable hazard classification to facilitate multi-modal transport involving ICAO (IATA) or IMO.

SECTION 15. REGULATORY INFORMATION**EPCRA - Emergency Planning and Community Right-to-Know****CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : No SARA Hazards**SARA 302** : No chemicals in this material are subject to the reporting re-
quirements of SARA Title III, Section 302.**SARA 313** : The following components are subject to reporting levels es-
tablished by SARA Title III, Section 313:

Zinc oxide	1314-13-2	5 %
------------	-----------	-----

**MOLYKOTE(R) G-0052 FM WHITE EP
BEARING GREASE**

Version	Revision Date:	SDS Number:	Date of last issue:
3.0	03/19/2016	888494-00006	11/10/2015
			Date of first issue: 12/03/2014

US State Regulations**Pennsylvania Right To Know**

White mineral oil (petroleum)	8042-47-5
Aluminum hydroxide benzoate stearate	54326-11-3
Calcium carbonate	471-34-1
Zinc oxide	1314-13-2

California Prop. 65

This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

California List of Hazardous Substances

White mineral oil (petroleum)	8042-47-5
Zinc oxide	1314-13-2


California Permissible Exposure Limits for Chemical Contaminants

White mineral oil (petroleum)	8042-47-5
Calcium carbonate	471-34-1
Zinc oxide	1314-13-2

The ingredients of this product are reported in the following inventories:

NZIoC	All ingredients listed or exempt.
REACH	All ingredients (pre-)registered or exempt.
TSCA	All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.
AICS	All ingredients listed or exempt.
IECSC	All ingredients listed or exempt.
ENCS/ISHL	All components are listed on ENCS/ISHL or exempted from inventory listing.
KECI	One or more ingredients are not listed or exempt.
PICCS	Consult your local Dow Corning office.
DSL	All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).
TCSI	All ingredients listed or exempt.

SAFETY DATA SHEET

DOW CORNING**MOLYKOTE(R) G-0052 FM WHITE EP
BEARING GREASE**Version
3.0Revision Date:
03/19/2016SDS Number:
888494-00006Date of last issue: 11/10/2015
Date of first issue: 12/03/2014**SECTION 16. OTHER INFORMATION****Further information****NFPA:****HMIS III:**

HEALTH	0
	1
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,
2 = Moderate, 3 = High
4 = Extreme, * = Chronic

Full text of other abbreviations

ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL	: USA. NIOSH Recommended Exposure Limits
OSHA Z-1	: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
ACGIH / TWA	: 8-hour, time-weighted average
ACGIH / STEL	: Short-term exposure limit
NIOSH REL / TWA	: Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	: STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
NIOSH REL / C	: Ceiling value not be exceeded at any time.
OSHA Z-1 / TWA	: 8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration;

**MOLYKOTE(R) G-0052 FM WHITE EP
BEARING GREASE**

Version	Revision Date:	SDS Number:	Date of last issue:
3.0	03/19/2016	888494-00006	11/10/2015
			Date of first issue: 12/03/2014

n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 03/19/2016

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8