Henry.

SAFETY DATA SHEET

Issue Date 24-Apr-2015

Revision Date 10-May-2015

Version 2

Product identifier

Product Name

#16 Roofer's Choice Plastic Roof Cement

Other means of identification

Product Code Synonyms

RC016

None

Roofers Choice #16 Wet-N-Dry Roof Cement

Recommended use of the chemical and restrictions on use

Recommended Use Uses advised against

Sealant.

No information available

Details of the supplier of the safety data sheet

Manufacturer Address

HENRY COMPANY

999 N. Sepulveda Blvd., Suite 800

El Segundo, CA 90245-2716

Company Contact: Technical Services

Telephone Number: 800-486-1278

Web Site: www.henry.com www.ca.henry.com

Emergency telephone number

Emergency Telephone

CHEMTREC: 800-424-9300

CHEMTREC: 703-527-3887

CANUTEC: 613-966-6666

24. AZARDSI DENIHE(GARTON

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Oral	Not classified
Acute toxicity - Dermal	Not classified
Acute toxicity - Inhalation (Gases)	Not classified
Acute toxicity - Inhalation (Vapors)	Not classified
Acute toxicity - Inhalation (Dusts/Mists)	Not classified
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Respiratory sensitization	Not classified
Skin sensitization	Not classified
Germ cell mutagenicity	Not classified
Carcinogenicity	Not classified
Reproductive toxicity	Not classified
Specific target organ toxicity (single exposure)	Not classified
Specific target organ toxicity (repeated exposure)	Not classified
Aspiration toxicity	Not classified
Flammable liquids	Category 3

Label elements

Emergency Overview

Warning

Hazard statements

Causes skin irritation

Causes serious eye irritation

May cause respiratory irritation. May cause drowsiness or dizziness

Flammable liquid and vapor



Appearance paste

Physical state liquid

Odor Petroleum distillates

Precautionary Statements - Prevention

Wear protective gloves/protective clothing/eye protection/face protection Keep away from heat/sparks/open flames/hot surfaces. - No smoking Wash face, hands and any exposed skin thoroughly after handling

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

IF ON SKIN: Wash with plenty of soap and water

If skin irritation occurs: Get medical advice/attention

IF INHALED: Call a POISON CENTER or doctor if you feel unwell

In case of fire: Use Water spray, fog or regular foam for extinction

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

Harmful to aquatic life with long lasting effects

Unknown acute toxicity

29.97% of the mixture consists of ingredient(s) of unknown toxicity

Fig 60 M ROS III (6 KW) ROS RANGO S WATE (6 KW) NO REED EN THE

<u>Substance</u>

Chemical Name	CAS No.	Weight-%	Trade Secret
Petroleum Asphalt	8052-42-4	30-50	*
Water	7732-18-5	20-30	-
Stoddard solvent	8052-41-3	10-20	*
Clays	NA-Mixture	1-5	*
QUARTZ	14808-60-7	<0.1	*

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret.

Description of first aid measures

Eye contact

Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids.

Consult a physician.

Skin contact

Wash skin with soap and water.

Inhalation

Remove to fresh air.

Ingestion

Clean mouth with water and drink afterwards plenty of water.

Most important symptoms and effects, both acute and delayed

Symptoms

Drowsiness.

Indication of any immediate medical attention and special treatment needed

Note to physicians

Treat symptomatically.

88 FIRE FIGHTING MEASURES

Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media CAUTION: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

No information available.

Explosion data

Sensitivity to Mechanical Impact None. Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

WAS GRACIONENTA PRESENCIA METASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions

Ensure adequate ventilation, especially in confined areas.

Environmental precautions

Environmental precautions

See Section 12 for additional ecological information.

Methods and material for containment and cleaning up

Methods for containment

Prevent further leakage or spillage if safe to do so.

Methods for cleaning up

Pick up and transfer to properly labeled containers.

THE PARTY OF THE PARTY OF THE PARTY OF THE

Precautions for safe handling

Advice on safe handling

Handle in accordance with good industrial hygiene and safety practice.

Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep containers tightly closed in a cool, well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static

electricity).

Incompatible materials

Strong oxidizing agents.

(E(0)Z|U;{=\$@0)\b{;{0}\${3\\$|={{0}}\${1\\$|={{0}}\${1\\$|}\$

Control parameters

Exposure Guidelines

This product, as supplied, does not contain any hazardous materials with occupational

exposure limits established by the region specific regulatory bodies

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Petroleum Asphalt 8052-42-4	TWA: 0.5 mg/m³ benzene soluble aerosol fume, inhalable fraction		Ceiling: 5 mg/m³ fume 15 min
Stoddard solvent 8052-41-3	TWA: 100 ppm	TWA: 500 ppm TWA: 2900 mg/m³ (vacated) TWA: 100 ppm (vacated) TWA: 525 mg/m³	IDLH: 20000 mg/m³ Ceiling: 1800 mg/m³ 15 min TWA: 350 mg/m³
QUARTZ 14808-60-7	TWA: 0.025 mg/m³ respirable fraction	(vacated) TWA: 0.1 mg/m³ respirable dust : (30)/(%SiO2 + 2) mg/m³ TWA total dust : (250)/(%SiO2 + 5) mppcf TWA respirable fraction	IDLH: 50 mg/m³ respirable dust TWA: 0.05 mg/m³ respirable dust
		: (10)/(%SiO2 + 2) mg/m³ TWA respirable fraction	

Appropriate engineering controls

Engineering Controls

Showers

Evewash stations Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear safety glasses with side shields (or goggles).

Skin and body protection

Wear protective gloves and protective clothing.

Respiratory protection

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

provided in accordance with current local regulations.

General Hygiene Considerations

Handle in accordance with good industrial hygiene and safety practice.

Information on basic physical and chemical properties

Physical state **Appearance**

liquid paste black

Odor

Petroleum distillates No information available

Color **Property**

Values

Remarks • Method

Odor threshold

Melting point / freezing point

No information available No information available

RC016- #16 ROOFER'S CHOICE WET'N DRY ROOF CEMENT

Revision Date 10-May-2015

Boiling point / boiling range

>= 150 °C Flash point

Evaporation rate

40 °C

Flammability (solid, gas)

No information available No information available

Flammability Limit in Air

9%

Upper flammability limit: Lower flammability limit:

1%

Vapor pressure Vapor density

No information available No information available

Relative density Water solubility 0.9 - 1.3No information available

Solubility in other solvents Partition coefficient

No information available No information available

Autoignition temperature **Decomposition temperature**

No information available No information available

Kinematic viscosity Dynamic viscosity **Explosive properties** >100 mm2/s No information available No information available

Oxidizing properties

No information available

Other Information

Softening point Molecular weight VOC Content (%) Density

No information available No information available No information available No information available No information available

STRACTULING AND REPAGRIMANT

@ 40 °C

Reactivity

Bulk density

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Extremes of temperature and direct sunlight.

Incompatible materials

Strong oxidizing agents.

Hazardous Decomposition Products

None known based on information supplied.

ALTOXICOLOGICALINFORMATION

Information on likely routes of exposure

Product Information

No data available

Inhalation

May cause irritation of respiratory tract. May cause drowsiness or dizziness.

Eye contact

Irritating to eyes.

Skin contact

Irritating to skin.

Ingestion

No data available.

Observator at Nicona			
Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
	Oldi LD00	Detitial FD30	Inhalation LC50

RC016- #16 ROOFER'S CHOICE WET'N DRY ROOF CEMENT

Revision Date 10-May-2015

Petroleum Asphalt 8052-42-4	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	<u>-</u>
QUARTZ 14808-60-7	= 500 mg/kg (Rat)	-	-

Information on toxicological effects

Symptoms

Vapors may cause drowsiness and dizziness.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization

No information available. No information available.

Germ cell mutagenicity Carcinogenicity

No information available.

No information available.

CGIH

Chemical Name	ACGIH	IARC	NTP	OSHA
Petroleum Asphalt 8052-42-4	•	Group 2B	-	X
QUARTZ	A2	Group 1	Vnouve	
14808-60-7		Group	Known	X

Reproductive toxicity

No information available.

STOT - single exposure

No information available.

STOT - repeated exposure

No information available.

Aspiration hazard

No information available.

Numerical measures of toxicity - Product Information

ATEmix (oral)

5,602.00

ATEmix (dermal)

5,602.00

ATEmix (inhalation-gas)

99,999.00

ATEmix (inhalation-dust/mist)

14.01

ATEmix (inhalation-vapor)

99,999.00

Nellterweitel (ENERGE ENERGY (ENERGY (EN

Ecotoxicity

49.4 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

Persistence and degradability

Not readily biodegradable.

Bioaccumulation

No information available.

Chemical Name	Partition coefficient
Petroleum Asphalt	>6
8052-42-4	

Other adverse effects

No information available

Ozone

Not applicable

Waste treatment methods

Disposal of wastes

Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated packaging

Do not reuse container.

TA TRANSHORUNGORNATION

DOT

Not regulated (If shipped in NON BULK packaging by ground transport)

TDG

Not regulated

IATA

UN/ID no.

UN1999

Proper shipping name

Tars, Liquid

Hazard Class

3

Packing Group

III

IMDG

UN/ID no.

UN1999

Proper shipping name

Tars, Liquid

Hazard Class
Packing Group

3 III

Description

May be transported as non-hazardous in accordance with IMDG 2.3.2.5

MANAGEMENT OF THE RESERVE OF THE PROPERTY INFORMATION

All components used in this product are on the TSCA Inventory and the Canadian DSL.

International Inventories

TSCA Complies
DSL/NDSL Complies
EINECS/ELINCS Complies
ENCS Does not comply

IECSCCompliesKECLCompliesPICCSCompliesAICSComplies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances
IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

SARA 311/312 Hazard Categories

Acute health hazard Yes Chronic Health Hazard No Fire hazard No Sudden release of pressure hazard No Reactive Hazard No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

US State Regulations

California Proposition 65

This product contains chemicals known to the state of California to cause birth defects or other reproductive harm

U.S. State Right-to-Know Regulations

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

18.01 HER INFORMATION, NOLLIBING DATE OF PREPARATION OF THE LAST REVISION

NFPA

Health hazards 2

Flammability 2

Instability 0

Physical and Chemical

HMIS

Health hazards 2

Flammability 2

Physical hazards 0

Properties -Personal protection X

Issue Date Revision Date

24-Apr-2015 10-May-2015

Revision Note

No information available

Disclaimer

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet