

SAFETY DATA SHEET

9/21/16

HARRIS STAY SILV

1. Identification

Product identifier

Stay-Silv® White Brazing Flux

White BRAzing FLUX

Other means of identification

SDS number

0134

Recommended use

Metal brazing operations.

Recommended restrictions

None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer/Supplier

Harris Products Group 4501 Quality Place Mason, Ohio 45040 US custservmason@jwharris.com

Telephone number

513-754-2000

Emergency Telephone

1-888-609-1762 (US, Canada, Mexico only)

Numbers

Please quote 333988

2. Hazard(s) identification

Physical hazards

Not classified.

Health hazards

Acute toxicity, oral Acute toxicity, dermal Category 4

Category 4

Acute toxicity, inhalation

Category 4

Reproductive toxicity (the unborn child)

Category 2

OSHA defined hazards

Not classified.

Label elements



Signal word

Warning

Hazard statement

Harmful if swallowed. Harmful in contact with skin. Harmful if inhaled. Suspected of damaging the unborn child by ingestion.

Precautionary statement

Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing vapors. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.

Response

If swallowed: Call a poison center/doctor if you feel unwell. If on skin: Wash with plenty of water. If inhaled: Remove person to fresh air and keep comfortable for breathing. If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Rinse mouth. Take off contaminated clothing and wash before reuse.

Storage

Store locked up.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

None known.

classified (HNOC)

Supplemental information

The reproductive toxicity associated with this product is expected to occur via the ingestion route only.

Hydrogen fluoride, a possible decomposition product, is extremely corrosive and a poison by all routes of entry. Hydrogen fluoride can penetrate the skin and produce burns, which may not be immediately painful or visible; the burns impact the lower layers of skin and bone tissue. Hydrogen fluoride exposures involving 20 percent of the body or more can be fatal through systemic fluoride poisoning.

3. Composition/information on ingredients

Mixtures

| Chemical name | | CAS number | % |
|--------------------------------------|---|------------|-------|
| Potassium difluorodihydroxyborate | | 85392-66-1 | >50 |
| | erine en e | | |
| POTASSIUM FLUORIDE | | 7789-23-3 | 20-30 |

Composition comments

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation

Remove person from contaminated area to fresh air. Apply artificial respiration if needed.

Skin contact

Remove contaminated clothes and rinse skin thoroughly with water for at least 15 minutes. A 2.5 pct calcium gluconate gel applied topically after skin has been thoroughly washed will help reduce severity of symptoms.

Eve contact

Immediately rinse eyes with water. Remove any contact lenses, and continue flushing eyes with running water for at least 15 minutes. Hold eyelids apart to ensure rinsing of the entire surface of the eye and lids with water. Get immediate medical attention.

Ingestion

Do NOT induce vomiting. Immediately rinse mouth and drink a cupful of water. Never give anything by mouth to an unconscious person. Get medical attention immediately. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects, acute and delayed

Contact with this material may cause burns to the eyes. Symptoms include itching, burning, redness, and tearing of eyes. Prolonged or repeated contact with the product may cause irritation of skin. Itching, redness, burning of skin. Edema. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media

Use fire-extinguishing media appropriate for surrounding materials. Water spray, foam, dry powder or carbon dioxide.

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

During fire, hazardous combustion products are released that may include: Hydrogen fluoride. fluorine-, boron- and potassium-containing compounds.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions
Specific methods

General fire hazards

Move containers from fire area if you can do so without risk.

Use standard firefighting procedures and consider the hazards of other involved materials. No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid inhalation of vapors and spray mists. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

2/8

902265 Version #: 01 Revision date: - Issue date: 02-September-2015

Methods and materials for containment and cleaning up

This product is miscible in water.

Large Spills: Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. For waste disposal, see Section 13 of the SDS.

Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not contaminate water.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid inhalation of vapors and spray mists. Avoid contact with eyes, skin, and clothing. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash contaminated clothing before reuse. Observe good industrial hygiene practices. Avoid prolonged exposure. Do not taste or swallow. When using, do not eat, drink or smoke. Wear appropriate personal protective equipment (See Section 8). Wash thoroughly after handling. Avoid release to the environment.

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from food, drink and animal feedingstuffs. Keep out of the reach of children. Store away from incompatible materials (see Section 10 of the SDS). Store in tightly closed original container in a dry, cool and well-ventilated place. Do not store in container made of glass or silicate-based material.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

| Components | Type | | Value | | |
|--|-----------|---------------------------------------|---------------------------------------|----------------------|-----|
| Fluorides (CAS 16984-48-8) | PEL | · · · · · · · · · · · · · · · · · · · | 2.5 mg/m3 | | |
| POTASSIUM FLUORIDE | PEL | | 2.5 mg/m3 | | |
| (CAS 7789-23-3) | | | · · · · · · · · · · · · · · · · · · · | | |
| US. OSHA Table Z-2 (29 CFR 1910.1000) | | | | | |
| Components | Type | | Value | Form | |
| Fluorides (CAS 16984-48-8) | TWA | - | 2.5 mg/m3 | Dust. | |
| POTASSIUM FLUORIDE (CAS 7789-23-3) | TWA | | 2.5 mg/m3 | Dust. | |
| US. ACGIH Threshold Limit Values | | | | | |
| OO. AOON THIOSHOID LIMIT VALUES | | | | | |
| Components | Type | | Value | Form | |
| Fluorides (CAS 16984-48-8) | TWA | | 2.5 mg/m3 | | 1.5 |
| Potassium | STEL | | 6 mg/m3 | Inhalable fraction. | |
| difluorodihydroxyborate | | | | | |
| (CAS 85392-66-1) | TWA | | 2 mg/m3 | Inhalable fraction | |
| POTASSIUM FLUORIDE | TWA | | 2.5 mg/m3 | Illialable Ilaction. | |
| (CAS 7789-23-3) | IVV | | 2.5 mg/m5 | | |
| US. NIOSH: Pocket Guide to Chemical Ha | zards | | | | |
| Components | Type | | Value | | |
| Fluorides (CAS 16984-48-8) | TWA | | 2.5 mg/m3 | | |
| Potassium | TWA | | 2.5 mg/m3 2.5 mg/m3 | | |
| difluorodihydroxyborate | IVVA | | 2.5 mg/m5 | | |
| (CAS 85392-66-1) | | | | | |
| POTASSIUM FLUORIDE | TWA | | 2.5 mg/m3 | | |
| (CAS 7789-23-3) | | | | | |
| ogical limit values | | | | | |
| ACGIH Biological Exposure Indices | | | | | |
| Components Value | Determina | nt Specimen | Sampling | <u></u> | |

Fluoride

Fluoride

Urine

Urine

Fluorides (CAS 16984-48-8)3 mg/l

2 mg/l

ACGIH Biological Exposure Indices

| Components | Value | Determinant | Specimen | Sampling Time | |
|---------------------------------------|--------|-------------|----------|---------------|--|
| POTASSIUM FLUORIDE (CAS 7789-23-3) | 3 mg/l | Fluoride | Urine | * | |
| | 2 mg/l | Fluoride | Urine | * * | |
| * Faragonalina datalla al- | | | | | |

For sampling details, please see the source document.

Exposure guidelines

No exposure standards allocated.

Appropriate engineering controls

Provide adequate ventilation. Observe Occupational Exposure Limits and minimize the risk of inhalation of dust. Shower, hand and eye washing facilities near the workplace are recommended.

Individual protection measures, such as personal protective equipment

White paste.

Eye/face protection

Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection

Wear protective gloves (i.e. latex, nitrile, neoprene).

Other

Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Chemical resistant clothing is recommended.

Respiratory protection

Use a respirator when local exhaust or ventilation is not adequate to keep exposures below the TLV. In a confined space a supplied respirator may be required. Selection and use of respiratory protective equipment should be in accordance with OSHA General Industry Standard 29 CFR

1910.134; or in Canada with CSA Standard Z94.4.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Appearance

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective

equipment to remove contaminants.

9. Physical and chemical properties

| willie paste. |
|--|
| Solid. |
| Paste. |
| White. |
| Odorless. |
| Not available. |
| |
| Not applicable. |
| Not applicable. |
| |
| losive limits |
| losive limits Not available. |
| Not available. |
| Not available. Not available. Not available. |
| Not available. Not available. Not available. Not available. Not available. |
| Not available. Not available. Not available. Not available. Not available. Not available. |
| Not available. |
| Not available. Not available. |
| |

Not available.

Viscosity

Not available.

Other information

Explosive properties

Not explosive.

Oxidizing properties

Not oxidizing.

10. Stability and reactivity

Reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability

Material is stable under normal conditions.

Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid

Contact with incompatible materials.

Incompatible materials

Strong oxidizing agents. Strong acids. Halogenated compounds. Silicate-based materials.

Hazardous decomposition

products

Hydrogen fluoride, fluorine-, boron- and potassium-containing compounds.

11. Toxicological information

Information on likely routes of exposure

Inhalation

Harmful by inhalation. Dust may irritate respiratory system.

Skin contact

Prolonged or repeated contact may dry skin and cause irritation. Harmful in contact with skin. Hydrogen fluoride, a possible decomposition product, is extremely corrosive and a poison by all routes of entry. Hydrogen fluoride can penetrate the skin and produce burns, which may not be immediately painful or visible; the burns impact the lower layers of skin and bone tissue. Hydrogen fluoride exposures involving 20 percent of the body or more can be fatal through

systemic fluoride poisoning.

Eye contact

May cause eye burns. Risk of serious damage to eyes.

Ingestion

Harmful if swallowed. Ingestion may produce burns to the lips, oral cavity, upper airway,

esophagus and possibly the digestive tract.

Symptoms related to the physical, chemical and toxicological characteristics

Contact with this material may cause burns to the eyes. Symptoms include itching, burning, redness, and tearing of eyes. Prolonged or repeated contact with the product may cause irritation of skin. Itching, redness, burning of skin. Edema. Symptoms of overexposure may be headache,

dizziness, tiredness, nausea and vomiting.

Information on toxicological effects

Acute toxicity

Harmful if inhaled. Harmful in contact with skin. Harmful if swallowed. Harmful if inhaled or absorbed through skin. Causes eye burns. Prolonged or repeated contact with the product may cause burns to the skin Dust irritates the respiratory system, and may cause coughing and difficulties in breathing.

Components

Species

Test Results

POTASSIUM FLUORIDE (CAS 7789-23-3)

Acute

Oral

LD50

Rat

245 mg/kg

Skin corrosion/irritation

Prolonged or repeated contact may dry skin and cause irritation.

Serious eye damage/eye

irritation

May cause burns.

Respiratory or skin sensitization

Respiratory sensitization

Knowledge about sensitization hazard is incomplete.

Skin sensitization

Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.

Knowledge about sensitization hazard is incomplete.

Germ cell mutagenicity

No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity

This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

Fluorides (CAS 16984-48-8)

3 Not classifiable as to carcinogenicity to humans.

POTASSIUM FLUORIDE (CAS 7789-23-3)

3 Not classifiable as to carcinogenicity to humans.

NTP Report on Carcinogens

Not listed.

Stay-Silv® White Brazing Flux SDS US

902265 Version #: 01 Revision date: -Issue date: 02-September-2015

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity

Suspected of damaging the unborn child by ingestion. Possible reproductive hazard. Can cause adverse reproductive effects - such as birth defects, miscarriages, or infertility and sterility by

repeated ingestion.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Knowledge about health hazard is incomplete.

Aspiration hazard

Knowledge about health hazard is incomplete.

Chronic effects

Prolonged exposure may cause chronic effects. May cause damage to the kidneys. Exposure to extremely high levels of fluorides can cause abdominal pain, diarrhea, muscular weakness, and convulsions. In extreme cases it can cause loss of consciousness and death. Prolonged overexposure to fluorides may increase fluoride content of bones and teeth, and may result in

fluorosis, with mottling of teeth (in children) and brittleness of bones.

Further information

Symptoms may be delayed.

12. Ecological information

Ecotoxicity

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment. Large amounts of the product may affect the acidity (pH-factor) in water with possible risk of harmful effects to aquatic organisms.

Persistence and degradability

No data is available on the degradability of this product.

Bioaccumulative potential

No data available.

Mobility in soil

No data available.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. This material and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Dispose of contents/container in accordance with

local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not established.

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

CERCLA/SARA Hazardous Substances - Not applicable.

Stay-Silv® White Brazing Flux

SDS US

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate Hazard - Yes Delayed Hazard - Yes Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

Yes

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)
US state regulations

This product does not contain a chemical known to the State of California to cause cancer, birth

defects or other reproductive harm.

US. Massachusetts RTK - Substance List

Not regulated.

US. New Jersey Worker and Community Right-to-Know Act

Fluorides (CAS 16984-48-8)

POTASSIUM FLUORIDE (CAS 7789-23-3)

US. Pennsylvania Worker and Community Right-to-Know Law

Fluorides (CAS 16984-48-8)

POTASSIUM FLUORIDE (CAS 7789-23-3)

US. Rhode Island RTK

Not regulated.

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

International Inventories

| Country(s) or region | Inventory name Or | On inventory (yes/no)* | |
|----------------------|--|------------------------|-----|
| Australia | Australian Inventory of Chemical Substances (AICS) | | Yes |
| Canada | Domestic Substances List (DSL) | | Yes |
| Canada | Non-Domestic Substances List (NDSL) | | No |
| China | Inventory of Existing Chemical Substances in China (IECSC) | | Yes |
| Europe | European Inventory of Existing Commercial Chemical Substances (EINECS) | | Yes |
| Europe | European List of Notified Chemical Substances (ELINCS) | | No |
| Korea | Existing Chemicals List (ECL) | | Yes |
| New Zealand | New Zealand Inventory | | Yes |
| Philippines | Philippine Inventory of Chemicals and Chemical Substances (PICCS) | | Yes |

Stay-Silv® White Brazing Flux

SDS US

Country(s) or region

Inventory name

On inventory (yes/no)*

United States & Puerto Rico

Toxic Substances Control Act (TSCA) Inventory

Vac

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date

02-September-2015

Revision date

Version #

01

Further information

HMIS® is a registered trade and service mark of the NPCA.

NFPA ratings



References

ACGIH

EPA: AQUIRE database

NLM: Hazardous Substances Data Base

US. IARC Monographs on Occupational Exposures to Chemical Agents

HSDB® - Hazardous Substances Data Bank

IARC Monographs. Overall Evaluation of Carcinogenicity National Toxicology Program (NTP) Report on Carcinogens

ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices

Disclaimer

The information in the sheet was written based on the best knowledge and experience currently available. Harris Products Group cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use.