Page: 1/15

#### **Safety Data Sheet**

## according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date: 25.07.2016 Revision: 25.07.2016

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: Buffing Solution (Rubber Cleaner)
- · Article number: 14-100
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture: Cleaner solvent
- · 1.3 Details of the supplier of the Safety Data Sheet
- Manufacturer/Supplier:

31 Incorporated 100 Enterprise Dr.

Newcomerstown, OH 43832 Phone: (740) 498-8324

· 1.4 Emergency telephone number:

ChemTel Inc.

(800)255-3924, +1 (813)248-0585

Napa Tire Repair Rubber Prep Pre Buff Buffing Solutions#7651322

#### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Classifications listed are applicable to the OSHA GHS Hazard Communication Standard (29CFR1910.1200).

The following Hazard Statements are applicable only to the EU regulations and not the US GHS regulation: H361f, H400, H410.

The following Hazard Statements are applicable only according to OSHA regulations within the United States. These Statements are not applicable for the CLP regulation (1272/2008/EC) in the EU: H361.

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Repr. 2 H361f Suspected of damaging fertility.

STOT SE 3 H336 May cause drowsiness or dizziness.

STOT RE 2 H373 May cause damage to the nervous system through prolonged or repeated

exposure. Route of exposure: Inhalation.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

Aquatic Acute 1 H400 Very toxic to aquatic life.

Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.

#### · 2.2 Label elements

#### · Labelling according to Regulation (EC) No 1272/2008

The product is additionally classified and labelled according to the Globally Harmonized System within the United States (GHS).

The product is classified and labelled according to the CLP regulation.

(Cont'd. on page 2)

Page: 2/15

#### Safety Data Sheet

## according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA

Printing date: 25.07.2016 Revision: 25.07.2016

Trade name: Buffing Solution (Rubber Cleaner)

(Cont'd. from page 1)

#### · Hazard pictograms

The following pictogram(s) are only for use within Europe: GHS09.



#### · Signal word Danger

#### · Hazard-determining components of labelling:

n-hexane heptane acetone

#### · Hazard statements

The following Hazard Statements are applicable only to the EU regulations and not the US GHS regulation: H361f, H410.

The following Hazard Statements are applicable only according to OSHA regulations within the United States. These Statements are not applicable for the CLP regulation (1272/2008/EC) in the EU: H361.

H361 Suspected of damaging fertility or the unborn child.

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H361f Suspected of damaging fertility.

H336 May cause drowsiness or dizziness.

H373 May cause damage to the nervous system through prolonged or repeated exposure. Route of exposure: Inhalation.

H304 May be fatal if swallowed and enters airways.

H410 Very toxic to aquatic life with long lasting effects.

#### · Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P260 Do not breathe mist/vapours/spray. Wash thoroughly after handling. P264

P280 Wear protective gloves / eye protection.

P233 Keep container tightly closed.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P370+P378 In case of fire: Use foam, powder, or carbon dioxide for extinction. P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

Get medical advice/attention if you feel unwell. P314 P331

Do NOT induce vomiting. Store in a well-ventilated place. Keep cool. P403+P235

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

#### · Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

(Cont'd. on page 3)

#### **Safety Data Sheet**

#### according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date: 25.07.2016

Trade name: Buffing Solution (Rubber Cleaner)

Revision: 25.07.2016

(Cont'd, from page 2)

### · NFPA ratings (scale 0 - 4)

Health = 2 Fire = 3Reactivity = 0

· HMIS-ratings (scale 0 - 4)

\*2 Health = \*2 Fire = 3REACTIVITY 0 Reactivity = 0

- Indicates a long term health hazard from repeated or prolonged exposures.
- · 2.3 Other hazards There are no other hazards not otherwise classified that have been identified.
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

## **SECTION 3: Composition/information on ingredients**

#### · 3.2 Mixtures

· Components:		
EINECS: 203-777-6	n-hexane Flam. Liq. 2, H225 Repr. 2, H361f; STOT RE 2, H373; Asp. Tox. 1, H304 Aquatic Chronic 2, H411 Skin Irrit. 2, H315; STOT SE 3, H336	25-50%
CAS: 142-82-5 EINECS: 205-563-8 Index number: 601-008-00-2	heptane Flam. Liq. 2, H225 Asp. Tox. 1, H304 Aquatic Acute 1, H400; Aquatic Chronic 1, H410 Skin Irrit. 2, H315; STOT SE 3, H336	25-50%
EINECS: 200-662-2	acetone	10-25%

Additional information: For the wording of the listed Hazard Statements refer to section 16.

#### **SECTION 4: First aid measures**

#### · 4.1 Description of first aid measures

· After inhalation:

Supply fresh air; consult doctor in case of complaints.

Provide oxygen treatment if affected person has difficulty breathing.

In case of irregular breathing or respiratory arrest provide artificial respiration.

In case of unconsciousness place patient stably in side position for transportation.

(Cont'd. on page 4)

Page: 4/15

#### **Safety Data Sheet**

## according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date: 25.07.2016 Revision: 25.07.2016

Trade name: Buffing Solution (Rubber Cleaner)

(Cont'd. from page 3)

#### · After skin contact:

Immediately remove any clothing soiled by the product. Immediately wash with water and soap and rinse thoroughly. If skin irritation continues, consult a doctor.

#### · After eye contact:

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

#### After swallowing:

Rinse out mouth and then drink plenty of water.

A person vomiting while laying on their back should be turned onto their side.

Do not induce vomiting; call for medical help immediately.

#### · 4.2 Most important symptoms and effects, both acute and delayed

Headache

Breathing difficulty

Dizziness

Coughing

Irritant to skin and mucous membranes.

Irritant to eyes.

Gastric or intestinal disorders when ingested.

Nausea

Disorientation

#### · Hazards:

Danger of impaired breathing.

May be harmful in contact with skin.

May be harmful if inhaled.

Repeated exposure may cause skin dryness or cracking.

Vapours may cause drowsiness and dizziness.

Suspected of damaging fertility or the unborn child.

Danger of disturbed cardiac rhythm.

Danger of convulsion.

Possible risk of irreversible effects.

#### $^{\cdot}$ 4.3 Indication of any immediate medical attention and special treatment needed

If swallowed, gastric irrigation with added, activated carbon.

If necessary oxygen respiration treatment.

If swallowed or in case of vomiting, danger of entering the lungs.

Later observation for pneumonia and pulmonary oedema.

Vapours may cause drowsiness and dizziness.

Medical supervision for at least 48 hours.

#### SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water
- 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

(Cont'd. on page 5)

#### **Safety Data Sheet**

## according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date: 25.07.2016 Revision: 25.07.2016

Trade name: Buffing Solution (Rubber Cleaner)

(Cont'd. from page 4)

#### 5.3 Advice for firefighters

· Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

· Additional information:

Eliminate all ignition sources if safe to do so.

Use large quantities of foam as it is partially destroyed by the product.

#### **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

Use respiratory protective device against the effects of fumes/dust/aerosol.

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources.

Protect from heat.

#### · 6.2 Environmental precautions

Do not allow to enter sewers/ surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

#### 6.3 Methods and material for containment and cleaning up

Allow to evaporate.

Absorb with non-combustible liquid-binding material (sand, diatomite, acid binders, universal binders).

Do not flush with water or aqueous cleansing agents

Used rags or other cleaning materials should be soaked with water and placed in a sealed container.

#### 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

#### SECTION 7: Handling and storage

#### · 7.1 Precautions for safe handling

Rags / metal wools / cuttings / shavings and waste papers soaked with product must be placed in a sealed, metal container rated for flammable waste.

Prevent formation of aerosols.

Avoid splashes or spray in enclosed areas.

Use only in well ventilated areas.

#### · Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Flammable gas-air mixtures may form in empty receptacles.

Fumes can combine with air to form an explosive mixture.

(Cont'd. on page 6)

Page: 6/15

#### **Safety Data Sheet**

## according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date: 25.07.2016 Revision: 25.07.2016

Trade name: Buffing Solution (Rubber Cleaner)

(Cont'd. from page 5)

#### · 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by storerooms and receptacles:

Store in a cool location.

Provide ventilation for receptacles.

Avoid storage near extreme heat, ignition sources or open flame.

· Information about storage in one common storage facility:

Store away from foodstuffs.

Store away from oxidising agents.

· Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Keep container tightly sealed.

· 7.3 Specific end use(s) No further relevant information available.

#### SECTION 8: Exposure controls/personal protection

#### · 8.1 Control parameters

	parameters	
· Ingredients v	with limit values that require monitoring at the workplace:	
110-54-3 n-hexane		
IOELV (EU)	Long-term value: 72 mg/m³, 20 ppm	
PEL (USA)	Long-term value: 1800 mg/m³, 500 ppm	
REL (USA)	Long-term value: 180 mg/m³, 50 ppm	
TLV (USA)	Long-term value: 176 mg/m³, 50 ppm Skin; BEI	
EL (Canada)	Long-term value: 20 ppm Skin	
EV (Canada)	Long-term value: 176 mg/m³, 50 ppm	
142-82-5 hep	tane	
IOELV (EU)	Long-term value: 2085 mg/m³, 500 ppm	
PEL (USA)	Long-term value: 2000 mg/m³, 500 ppm	
REL (USA)	Long-term value: 350 mg/m³, 85 ppm Ceiling limit: 1800* mg/m³, 440* ppm *15-min	
TLV (USA)	Short-term value: 2050 mg/m³, 500 ppm Long-term value: 1640 mg/m³, 400 ppm	
EL (Canada)	Short-term value: 500 ppm Long-term value: 400 ppm	
EV (Canada)	Short-term value: 2,045 mg/m³, 500 ppm Long-term value: 1,635 mg/m³, 400 ppm	
67-64-1 acetone		
IOELV (EU)	Long-term value: 1210 mg/m³, 500 ppm	
PEL (USA)	Long-term value: 2400 mg/m³, 1000 ppm	
	(Cont'd. on page 7	

Page: 7/15

#### **Safety Data Sheet**

## according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date: 25.07.2016 Revision: 25.07.2016

Trade name: Buffing Solution (Rubber Cleaner)

REL (USA) Long-term value: 590 mg/m³, 250 ppm

TLV (USA) Short-term value: (1782) NIC-1187 mg/m³, (750) NIC-500 ppm
Long-term value: (1188) NIC-475 mg/m³, (500) NIC-200 ppm
BEI

EL (Canada) Short-term value: 500 ppm
Long-term value: 250 ppm

EV (Canada) Short-term value: 750 ppm
Long-term value: 500 ppm

• **DNELs:** No further relevant information available. • **PNECs:** No further relevant information available.

#### Ingredients with biological limit values:

#### 110-54-3 n-hexane

BEI (USA) 0,4 mg/L

Medium: urine

Time: end of shift at end of workweek

Parameter: 2,5-Hexanedione without hydrolysis

#### 67-64-1 acetone

BEI (USA) 50 mg/L

Medium: urine Time: end of shift

Parameter: Acetone (nonspecific)

#### 8.2 Exposure controls

#### Personal protective equipment:

#### · General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Pregnant women should strictly avoid inhalation or skin contact.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

#### Respiratory protection:

Not required under normal conditions of use.

Use suitable respiratory protective device when high concentrations are present.

Use suitable respiratory protective device when aerosol or mist is formed.

For spills, respiratory protection may be advisable.

NIOSH or EN approved organic vapour respirator equipped with a dust/mist prefilter should be used.

#### Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Cont'd. on page 8)

Page: 8/15

(Cont'd. from page 7)

#### **Safety Data Sheet**

## according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date: 25.07.2016 Revision: 25.07.2016

**Trade name: Buffing Solution (Rubber Cleaner)** 

· Eye protection:



Safety glasses

- · Body protection: Solvent resistant protective clothing
- · Limitation and supervision of exposure into the environment:
- No further relevant information available.
- · Risk management measures: See Section 7 for additional information.

9.1 Information on basic physic	al and chemical properties
Appearance	a. aa
Form:	Liquid
Colour:	White
Odour:	Solvent-like
Odour threshold:	Not determined.
pH-value:	Not determined.
Melting point/Melting range:	Not determined.
Boiling point/Boiling range:	82 °C (180 °F)
Flash point:	-15 °C (5 °F)
Flammability (solid, gaseous):	Not applicable.
Auto/Self-ignition temperature:	215 °C (419 °F)
Decomposition temperature:	Not determined.
Danger of explosion:	Product is not explosive. However, formation of explosive vapour mixtures are possible.
Explosion limits	
Lower:	1,1 Vol %
Upper:	13,0 Vol %
Oxidising properties	Not determined.
Vapour pressure at 20 °C (68 °F):	233 hPa (175 mm Hg)
Density at 20 °C (68 °F):	0,76 g/cm³ (6,342 lbs/gal)
Relative density:	Not determined.
Vapour density:	Not determined.
Evaporation rate:	Not determined.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.

Page: 9/15

#### **Safety Data Sheet**

## according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date: 25.07.2016 Revision: 25.07.2016

Trade name: Buffing Solution (Rubber Cleaner)

(Cont'd. from page 8)

· Viscosity

Dynamic: Kinematic:

Not determined.

9.2 Other information

No further relevant information available.

#### SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: Keep away from heat and direct sunlight.
- · 10.3 Possibility of hazardous reactions

Flammable.

Reacts violently with oxidising agents.

Used empty containers may contain product gases which form explosive mixtures with air.

Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomised.

Toxic fumes may be released if heated above the decomposition point.

10.4 Conditions to avoid

Keep away from heat and direct sunlight.

Keep ignition sources away - Do not smoke.

Store away from oxidising agents.

- · 10.5 Incompatible materials No further relevant information available.
- 10.6 Hazardous decomposition products Carbon monoxide and carbon dioxide

### **SECTION 11: Toxicological information**

- · 11.1 Information on toxicological effects
- · Acute toxicity: Based on available data, the classification criteria are not met.

· LD/LC50	values	relevant	for c	lassification:
-----------	--------	----------	-------	----------------

#### 142-82-5 heptane

Oral LD50 > 5000 mg/kg (rat) (Estimate)
Inhalative LC50/4h 103 mg/l (rat)

- Primary irritant effect
- Skin corrosion/irritation:

Causes skin irritation.

· Serious eye damage/irritation:

Causes serious eye irritation.

- Respiratory or skin sensitisation: Based on available data, the classification criteria are not met.
- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer):

None of the ingredients are listed.

(Cont'd. on page 10)

Page: 10/15

#### **Safety Data Sheet**

## according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date: 25.07.2016 Revision: 25.07.2016

**Trade name: Buffing Solution (Rubber Cleaner)** 

(Cont'd. from page 9)

#### · NTP (National Toxicology Program):

None of the ingredients are listed.

#### · OSHA-Ca (Occupational Safety & Health Administration):

None of the ingredients are listed.

#### Probable routes of exposure:

Ingestion.

Inhalation

Eve contact.

Skin contact.

#### · Acute effects (acute toxicity, irritation and corrosivity):

Vapours have narcotic effect.

May be harmful if swallowed.

May be harmful in contact with skin.

May be harmful if inhaled.

Causes skin and eye irritation.

- · Repeated dose toxicity: Repeated exposure may cause skin dryness or cracking.
- · Germ cell mutagenicity: Based on available data, the classification criteria are not met.
- · Carcinogenicity: Based on available data, the classification criteria are not met.
- Reproductive toxicity:

Suspected of damaging fertility.

STOT-single exposure:

May cause drowsiness or dizziness.

STOT-repeated exposure:

May cause damage to the nervous system through prolonged or repeated exposure. Route of exposure: Inhalation.

· Aspiration hazard:

May be fatal if swallowed and enters airways.

#### SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: Toxic for aquatic organisms
- · 12.2 Persistence and degradability Easily biodegradable
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- Ecotoxical effects:
- Remark:

Very toxic for fish

The product is oxygen-consuming. The declared action may be partly caused by lack of oxygen.

- · Additional ecological information:
- · General notes:

Do not allow product to reach ground water, water course or sewage system.

Due to available data on eliminability/decomposition and bioaccumulation potential prolonged term damage of the environment can not be excluded.

(Cont'd. on page 11)

Page: 11/15

#### **Safety Data Sheet**

## according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date: 25.07.2016 Revision: 25.07.2016

Trade name: Buffing Solution (Rubber Cleaner)

(Cont'd. from page 10)

(Cont'd. on page 12)

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

#### SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Contact waste processors for recycling information.

Can be burned with household garbage after consulting with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations.

The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.

· Uncleaned packaging:

· Label

· Recommendation: Disposal must be made according to official regulations.

14.1 UN-Number DOT, ADR, IMDG, IATA	UN1993
14.2 UN proper shipping name	
DOT	Flammable liquids, n.o.s. (hexanes, heptanes)
ADR	FLAMMABLE LIQUID, N.O.S. (HEXANE
	HEPTANES), ENVIRONMENTALLY HAZARDOUS
IMDG	FLAMMABLE LIQUID, N.O.S. (HEXANE
IATA	HEPTANES, MARINE POLLUTANT
IATA	Flammable liquid, n.o.s. (hexanes, heptanes)
14.3 Transport hazard class(es)	
DOT	
Class	3 Flammable liquids.

3

Page: 12/15

# Safety Data Sheet according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date: 25.07.2016

Revision: 25.07.2016

Trade name: Buffing Solution (Rubber Cleaner)

·	(Cont'd. from page 1
· ADR	
· Class · Label	3 (F1) Flammable liquids.
IMDG	
<b>*</b>	
· Class · Label	3 Flammable liquids. 3
·IATA	
· Class · Label	3 Flammable liquids. 3
· 14.4 Packing group · DOT, ADR, IMDG, IATA	II .
· 14.5 Environmental hazards:	
· Marine pollutant:	Yes Symbol (fish and tree)
14.6 Special precautions for user	Warning: Flammable liquids.
· Danger code (Kemler): · EMS Number:	33 F-E,S-E
14.7 Transport in bulk according to An	· <u></u>
of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
·DOT	Product is additionally classified as a MARINE POLLUTANT based on MARPOL and DOT rules Labeling as a MARINE POLLUTANT is not require for non-bulk single package shipments by moto vehicle, rail car or aircraft. Bulk packaging consist of a maximum capacity of greater than 450L (119 gallons) for a liquid and a maximum net mass greater than 400kg (882 pounds) for a solid.

Page: 13/15

# Safety Data Sheet according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date: 25.07.2016 Revision: 25.07.2016

Trade name: Buffing Solution (Rubber Cleaner)

(Cont'd. from page 12)

SECTION 15: Regulatory information
15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture United States (USA) SARA
· Section 355 (extremely hazardous substances):
None of the ingredients are listed.
· Section 313 (Specific toxic chemical listings):
110-54-3 n-hexane
TSCA (Toxic Substances Control Act):
All ingredients are listed.
· Proposition 65 (California):
· Chemicals known to cause cancer:
None of the ingredients are listed.
· Chemicals known to cause reproductive toxicity for females:
None of the ingredients are listed.
· Chemicals known to cause reproductive toxicity for males:
None of the ingredients are listed.
· Chemicals known to cause developmental toxicity:
None of the ingredients are listed.
Carcinogenic Categories
· EPA (Environmental Protection Agency)
110-54-3 n-hexane
142-82-5 heptane D
67-64-1 acetone I
· IARC (International Agency for Research on Cancer)
None of the ingredients are listed.
NIOSH-Ca (National Institute for Occupational Safety and Health)
None of the ingredients are listed.
· Canadian Domestic Substances List (DSL)
All ingredients are listed.
· Other regulations, limitations and prohibitive regulations
Substances of very high concern (SVHC) according to REACH, Article 57
None of the ingredients are listed.
· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

Page: 14/15

#### **Safety Data Sheet**

## according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date: 25.07.2016 Revision: 25.07.2016

Trade name: Buffing Solution (Rubber Cleaner)

(Cont'd. from page 13)

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H361f Suspected of damaging fertility.

H373 May cause damage to the nervous system through prolonged or repeated exposure. Route of exposure: Inhalation.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

#### · Abbreviations and acronyms:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

LDLo: Lowest Lethal Dose Observed

Flam. Liq. 2: Flammable liquids – Category 2

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Repr. 2: Reproductive toxicity - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

#### Sources

Website, European Chemicals Agency (echa.europa.eu)

Website, US EPA Substance Registry Services (ofmpub.epa.gov/sor internet/registry/substreg/home/overview/home.do)

Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org)

Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: ISBN: 978-0-470-07488-6

Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5.

Safety Data Sheets, Individual Manufacturers

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

(Cont'd. on page 15)

Page: 15/15

Safety Data Sheet according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date: 25.07.2016

Revision: 25.07.2016

**Trade name: Buffing Solution (Rubber Cleaner)** 

(Cont'd. from page 14)

Tampa, Florida USA 33602-2902 Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com