

20704

ID INTERDYNAMICS AUTO AIR CONDITIONING
R-134A UV Leak Detector DYE FOR ALL A/C

Systems

INT
UV134DC**Material Safety Data Sheet**

UVD-1

Date of Preparation: 2/1/04

MSDS No. UVD-1

Section 1 - Chemical Product and Company Identification**Product Name:** UV Leak Finder, 5-Shot.**Part Number(s):** UVD-1**CAS Number:** NOT APPLICABLE TO MIXTURES**Product Class:** Automotive product**Manufacturer:** Interdynamics, Inc. 80 39th Street, 8th Floor, Brooklyn, NY 11232**Information Phone No. (Interdynamics):** 718-499-0608 **Emergency Phone No. (CHEMTREC):** 800-424-9300**Section 2 - Composition/ Information on Ingredients**

Ingredient Name	CAS Number	OSHA TWA	ACGIH TLV
1,1,1,2- Tetrafluoroethane	811-97-2	-	-
Polyol Ester	N/A	Not Listed	Not Listed
Dye	N/A	Not Listed	Not Listed
Ingredients not precisely identified are proprietary or non-hazardous.			

Section 3 - Physical and Chemical Properties**Physical State:** Gas and liquid under pressure.
mm Hg.**Boiling Range:** Gas -26.2 deg. F. @ 760**Appearance/Odor:** Green/Ethereal and Sweetish Odor.**Vapor Density (Air=1):** 3.5**% Volatile:** N/A**Specific Gravity (@C20 °C):** 1.0**Evaporation Rate(Butyl Acetate=1):** >1
deg. F. Liquid: <1**Vapor Pressure:** Gas: 85.8 mm Hg. @ 70**Section 4 - Fire Fighting Measures****Flash Point:** Not Determined**Flash Point Method:** N/A**LEL:** N/A**Extinguishing Media:** Carbon Dioxide, Dry Chemical, Foam, Water Fog, Sand/Earth.**Unusual Fire or Explosion Hazards:** This material may become flammable when mixed with air under pressure and exposed to strong ignition sources. Contact with certain reactive metals may result in formation of explosive or exothermic reactions under specific conditions (e.g., very high temperatures and/or appropriate pressures).**Special Fire-Fighting Procedures:** Firefighters must wear self-contained breathing apparatus with full face-piece operated in pressure demand or positive pressure mode. Use full turnout gear.**Section 5 - Stability and Reactivity****Stability:** Stable**Polymerization:** Will not occur.**Incompatibilities & Conditions to Avoid:** Do not mix with oxygen or air above atmospheric pressure. Any source of high temperature such as lighted cigarettes, flames, hot spots, welding may yield toxic and/or corrosive decomposition products. **Materials to Avoid:** At very high temperatures and/or appropriate pressures, freshly abraded aluminum surfaces may cause strong exothermic reaction; Also avoid, chemically active metals, potassium, calcium, powdered aluminum, magnesium, and zinc. Avoid strong oxidizing agents.

NOV 03 2005

NOV 03 2005

Hazardous Decomposition Products: At high temperatures CO & CO₂; HF & Carbonyl Halides such as Phosgene.

Section 6 - Health Hazard Information

Primary Entry Routes: Eyes, dermal, inhalation and ingestion

Target Organs: Eyes, skin, respiratory system

Signs & Symptoms of Exposure: Irritation to skin and eyes. Dizziness, loss of coordination or lung irritation. Ingestion may cause gastrointestinal discomfort and diarrhea.

Acute Effects: Skin and eye irritation. May cause dizziness and loss of concentration. At high levels, Cardiac Arrhythmia may occur. Possible frostbite.

Chronic Effects: No data available.

Carcinogenicity: This product does not contain components that are listed as a Carcinogen.

Medical Conditions Generally Aggravated by Exposure: May adversely affect use of Catecholamine drugs such as Epinephrine. Prolonged exposure may cause Kidney and Liver damage.

Emergency and First Aid Procedures

Inhalation: Exposure to very high concentration can induce anesthetic effect. Can act as an asphyxiant by limiting oxygen. Cardiac sensitization to circulating epinephrine-like compounds can result in fatal cardiac arrhythmias. Remove to fresh air. Give artificial respiration if not breathing. Give oxygen if breathing labored. If cardiac arrest, apply external cardiac massage. Do not administer adrenaline or similar drugs as cardiac arrhythmias may result. Call physician immediately.

Eye Contact: Liquid splashes or vapor spray may cause freeze burns. Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for 15 minutes. Have eyes examined and treated by medical personnel.

Skin Contact: Liquid form of this material may cause freeze burns (frostbite-like lesions). Thaw affected areas with water, remove contaminated clothing carefully. Wash affected areas of skin thoroughly with plenty of warm water. Obtain medical attention. Prolonged contact with skin may cause red skin irritation or dermatitis. Remove oil from skin by washing well with soap and water. Launder clothing before reuse.

Ingestion: May cause slight irritation if ingested but not toxic. Do not induce vomiting without a Physician's advice.

Section 7 - Spill, Leak, and Disposal Procedures

Keep at temperature not exceeding 113 DEG F. Keep containers dry. Keep away from direct sunlight, or any heat source.

See SEC 09 Special Precautions for industrial hygiene control measures. Clean up any oil spill. Prevent entry into sewers and water ways. Absorb with inert absorbent. Place used rags and absorbent in closed metal containers. It is illegal to purposely vent into the atmosphere.

Steps To Be Taken In Case Material Is Released or Spilled: Evacuate unprotected personnel. Wear protective equipment. Ventilate area. Contain and absorb with non-combustible absorbent. Transfer into suitable containers.

Waste Disposal Method: In accordance with applicable Federal, State and local regulations.

Precautions To Be Taken In Handling and Storage: Wear protective gloves and clothing with an outer layer of Mylar coated Durafab. Wear safety goggles. Use in well ventilated areas. Keep away from strong oxidizing agents.

Other Precautions: Do not puncture container except with an Interdynamics' approved device intended to be used with the particular container. Store in a shaded, cool, dry place. Do not expose to temperatures above 113 deg. F. Connect can to low pressure side of automobile A/C port only. Do not expose to high altitudes or low pressure ambient environment.

Section 8 - Exposure Controls / Personal Protection

Ventilation general mechanical ventilation. Oil mist inhalation should be avoided.

Protective Clothing/Equipment: NIOSH or MSHA respiratory protection must be worn if exposure to high concentrations is possible. Chemical tight goggles, full face-shield in addition if splashing is possible. Oil impervious Protective Gloves with outer layer of Mylar coated Durafab or PVA or Neoprene. Apron, arm covers or full body suit, depending on conditions. Impervious boots in case of prolonged liquid contact.

Safety Stations: Ventilate low-lying areas such as sumps or pits where dense vapors may collect. Use local exhaust to control exposures.

Work/Hygienic Practices: Use in well ventilated areas. Avoid inhaling vapors. Avoid contact with eyes, skin or clothing.

DOT Transportation Data

<u>PART NUMBER(S)</u>	<u>SHIPPING NAME</u>	<u>HAZARD CLASS ID NO.</u>	<u>PACKING GROUP</u>
UVD-1	Consumer Commodity	ORM-D	N/A

Disclaimer: All information appearing herein is based upon data obtained from manufacturers and/or recognized technical sources. While the information is believed to be accurate, we make no representations as to its accuracy or sufficiency. Conditions of use are beyond our control, therefore users are responsible for verifying the data under their own operating conditions to determine whether the product is suitable for their particular purposes and they assume all risks of their use, handling, and disposal of the product. Users also assume all risks in regards to the publications of use of, or reliance upon, information contained herein. This information relates only to the product designated herein, and does not relate to its use in combination with any other material or process.

22