

Section 1: IDENTIFICATION

1.1 PRODUCT IDENTIFIER

ACRY I PRO CERamic

Product Name:

AcrylPro Ceramic Tile Adhesive

Tile Adhesive

Product Code:

Not Available

1.2 RECOMMENDED USE OF CHEMICAL AND RESTRICTIONS ON USE

Product Use:

Ceramic Tile Adhesive

1.3 DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEETS

Name/Address:

Custom Building Products

3490 Piedmont Road, Suite 1300

Atlanta, GA 30329

Telephone Number:

(562)-598-8808

1.4 EMERGENCY TELEPHONE NUMBER

Emergency Telephone

INFOTRAC 1-800-535-5053 (US and Canada)

Number:

INTERNATIONAL + 1-352-323-3500

Section 2: HAZARD(S) IDENTIFICATION

2.1 CLASSIFICATION OF THE CHEMICAL IN ACCORDANCE WITH PARAGRAPH (d) OF 29 CFR

1910.1200 (OSHA HAZCOM2012)

Acute Toxicity - Oral

Category 4

Serious Eye Damage/Eye Irritation

Category 2

Germ Cell Mutagenicity

Category 1B

Carcinogenicity

Category 1A

STOT-RE

Category 2

2.2 LABEL ELEMENTS ACCORDING TO OSHA HAZCOM2012

2.2a SIGNAL WORD:

DANGER!

HAZARD STATEMENTS

Harmful if swallowed

Causes serious eye irritation

May cause genetic defects

May cause cancer

Causes damage to organs through prolonged or repeated exposure



2.2c HAZARD PICTOGRAMS





2.2d PRECAUTIONARY STATEMENTS

	DDEVENTION.	
1.	PREVENTION	Wash hands thoroughly after handling. Do not breathe dust/fume/gas/mist/ vapors/spray. Do not eat, drink or
		smoke when using this product. Use only outdoors or in a
		well-ventilated area. Obtain special instructions before
		use. Do not handle until all safety precautions have been
		read and understood. Wear protective gloves/protective
	·	clothing/eye protection/face protection.
ii.	RESPONSE	If on skin: Wash with plenty of water. Take off
		contaminated clothing and wash it before reuse. If skin
		irritation or rash occurs: Get medical advice/attention.
*		If in eyes: Rinse cautiously with water for several minutes.
		Remove contact lenses, if present and easy to do.
		Continue rinsing. If eye irritation persists: Get medical
		advice/attention. If inhaled: Remove person to fresh air
		and keep comfortable for breathing. If experiencing
		respiratory symptoms: call a poison center/doctor. If
		exposed or concerned: get medical advice/attention
iii.	STORAGE	Store in a well-ventilated place. Keep container tightly closed.
iv.	DISPOSAL	Dispose of contents/containers in accordance with all
		local, state, provincial, and federal regulations.

2.3 ADDITIONAL INFORMATION

2.3a HNOC – HAZARDS NOT OTHERWISE CLASSIFIED Not applicable

2.3b UNKNOWN ACUTE TOXICITY

63% of the mixture consists of ingredient(s) of unknown acute toxicity.

2.3c WHMIS CLASSIFICATION

Class D2B – Skin/Eye Irritant Class D2A – Very toxic Materials

2.3d LABEL ELEMENTS ACCORDING TO WHMIS

WHMIS HAZARD SYMBOLS





Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 MIXTURES

Calcium Carbonate	1317-65-3	30 – 60%
Ethylene Glycol	107-21-1	1 – 5%
Stoddard Solvent	8052-41-3	1 – 5%
Crystalline Silica, Quartz	14808-60-7	1 – 5%

Section 4: FIRST-AID MEASURES

4.1 DESCRIPTION OF THE FIRST-AID MEASURES

Eye Contact: In case of contact, immediately flush eyes with plenty of water for at

least 15 minutes. If easy to do, remove contact lenses, if worn. Get

medical attention immediately.

Skin Contact: In case of contact, immediately flush skin with plenty of water.

Remove contaminated clothing and shoes. Wash clothing before

reuse. Call a physician if irritation develops and persists.

Inhalation: If breathing is difficult, remove victim to fresh air and keep at rest in

a position comfortable for breathing. Get medical advice/attention if

you feel unwell.

Ingestion: If swallowed, do NOT induce vomiting unless directed to do so by

medical personnel. Never give anything by mouth to an

unconscious person. Get medical advice/attention.

4.2 MOST IMPORTANT SYMPTOMS/EFFECTS, ACUTE AND DELAYED

Eye Contact: Causes serious eye irritation. Symptoms may include discomfort or

pain, excess blinking and tear production, with marked redness and

swelling of the conjunctiva.

Skin Contact: May cause skin irritation. Handling can cause dry skin, discomfort,

irritation, and dermatitis.

Inhalation: May cause respiratory tract irritation. Causes damage to organs

through prolonged or repeated exposure. This product contains

crystalline silica. Prolonged or repeated inhalation of respirable



crystalline silica from this product can cause silicosis, a serious

disabling and fatal lung disease.

Ingestion:

May be harmful if swallowed. Ingestion may cause discomfort

and/or distress, nausea or vomiting.

4.3 INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED

Not applicable

Section 5: FIRE-FIGHTING MEASURES

5.1 FLAMMABILITY

Flammability:

Not Flammable by WHMIS/OSHA HAZCOM2012 Criteria

5.2 EXTINGUISHING MEDIA

5.2a. Suitable Extinguishing Media:

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment

5.2b. Unsuitable Extinguishing Media:

CAUTION: Use of water spray when fighting fire may be inefficient

5.3 SPECIFIC HAZARDS ARISING FROM THE CHEMICAL

5.3a. Products of Combustion:

May include, and are not limited to: oxides of carbon

5.3b. Explosion Data

Sensitivity to Mechanical Impact:

Not available.

Sensitivity to Static Discharge:

Not available.

Section 6: ACCIDENTAL RELEASE MEASURES

6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT, AND EMERGENCY PROCEDURES Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to

unnecessary and unprotected personnel.

6.2 METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP

Methods for Containment:

Prevent further leakage or spillage if safe to do so. Do not flush to sewer or allow to enter waterways. Use appropriate Personal

Protective Equipment (PPE).

Page 13 of 13



Methods for Cleaning-Up:

Pick up and transfer to properly labeled containers

Section 7: HANDLING AND STORAGE

7.1 PRECAUTIONS FOR SAFE HANDLING

Handling:

Use in well-ventilated areas. Wear chemical resistant gloves and eye protection. Do not mix with other chemical products, except as indicated by the manufacturers. Do not get in eyes. Do not get on skin or clothing. Do not breathe fumes. Do not take internally.

General Hygiene Advice:

Use good industrial hygiene practices and wear recommended personal protection. Launder contaminated clothing before reuse.

Wash hands before eating, drinking, or smoking.

7.2 CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

Storage:

Keep out of the reach of children. Keep container tightly closed. Store at room temperature and keep containers closed when not in

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 CONTROL PARAMETER Exposure Guidelines

Occupational Exposure Limits		
Chemical Name	OSHA-PEL	ACGIH-TLV
Calcium Carbonate	5 mg/m³ (Resp.) 15 mg/m³ (Total)	5 mg/m³ (Resp.)
Ethylene Glycol	50 ppm	50 ppm
Stoddard Solvent	100 ppm	100 ppm
Crystalline Silica, Quartz	0.1 mg/m³	0.025 mg/m ³

8.2 EXPOSURE CONTROLS

Engineering Controls:

Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.

8.3 INDIVIDUAL PROTECTION MEASURES

8.3a. Personal Protective Equipment:

i. **Eye/Face Protection:** Wear approved eye protection [properly fitted dust- or splash-proof chemical safety goggles/face (face shield)]

Page 13 of 13



ii. Skin Protection:

- 1. Hand Protection: Wear chemical resistant gloves.
- 2. Body Protection: Wear suitable protective clothing
- **iii. Respiratory Protection:** A NIOSH approved dust mask or filtering face piece is recommended in poorly ventilated areas or when permissible exposure limits may be exceeded. Respirators should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134) and ANSI's standard for respiratory protection (Z88.2).
- iv. General Health and Safety Measures: Handle according to established industrial hygiene and safety practices.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance (physical state, color, etc.):	Paste liquid, white
Odor:	Latex
Odor Threshold:	Not available
pH:	9
Melting point/Freezing point:	Not available
Initial boiling point and boiling range:	Not available
Flash point:	Not available
Evaporation rate (Water=1):	Not available
Flammability:	Not flammable
Upper Flammability/Explosive Limit:	Not available
Lower Flammability/Explosive Limit:	Not available
Vapor Pressure	Not available
Vapor Density:	Not available
Relative Density:	Not available
Solubility in Water:	Slightly Soluble
Partition coefficient: n-octanol/water:	Not available
Auto-ignition temperature:	Not available
Decomposition Temperature:	Not available
Viscosity (cps):	Not available
VOC Content:	59 g/L

Section 10: STABILITY AND REACTIVITY

10.1. REACTIVITY

No dangerous reaction known under conditions of normal use.

10.2. CHEMICAL STABILITY

Stable under recommended storage conditions



10.3. POSSIBILITY OF HAZARDOUS REACTION

No dangerous reaction known under conditions of normal use.

10.4. CONDITIONS TO AVOID

Non-available

10.5. INCOMPATIBLE MATERIALS

Non-available

10.6. HAZARDOUS DECOMPOSITION PRODUCTS

Upon decomposition, this product may yield oxides of carbon.

Section 11: TOXICOLOGICAL INFORMATION

11.1. LIKELY ROUTES OF EXPOSURE:

Skin contact, skin absorption, eye contact, inhalation, and ingestion.

11.2. SYMPTOMS RELATED TO PHYSICAL/CHEMICAL/TOXICOLOGICAL CHARACTERISTICS:

Eye Contact: Causes serious eye irritation. Symptoms may include discomfort or

pain, excess blinking and tear production, with marked redness and

swelling of the conjunctiva.

Skin Contact: May causes skin irritation. Handling can cause dry skin, discomfort,

irritation, and dermatitis.

Inhalation: May cause respiratory tract irritation. Causes damage to organs

through prolonged or repeated exposure. This product contains crystalline silica. Prolonged or repeated inhalation of respirable crystalline silica from this product can cause silicosis, a serious

disabling and fatal lung disease.

Ingestion: May be harmful if swallowed. Ingestion may cause discomfort

and/or distress, nausea or vomiting.

Chemical Name	LC50	LD50
Calcium Carbonate	Not available	Not available
Ethylene Glycol	Inhalation > 2.5 mg/L, rat	Oral 4000 mg/kg, rat Dermal 9530 µL/kg, rabbit
Stoddard Solvent	Inhalation: > 5000ppm, rat	Oral: > 5,000 mg/kg, rat
Crystalline Silica, Quartz	Not available	Not available



Chemical Name	Chemical Listed as Carcinogens or Potential Carcinogen (NTP,IARC,OSHA,ACGIH,CP65)
Calcium Carbonate	Not Listed
Ethylene Glycol	G-A4
Stoddard Solvent	Not Listed
Crystalline Silica, Quartz	N-A2, I-1, O-1, ACGIH-A2, CP65

11.3. DELAYED, IMMEDIATE, AND CHRONIC EFFECTS OF SHORT AND LONG-TERM EXPOSURE

Skin Corrosion/Irritation:	May cause skin irritation	
Serious Eye Damage/Irritation:	Causes serious eye irritation	
Respiratory Sensitization:	Not available	
Skin Sensitization:	Not available	
STOT-Single Exposure:	Not available	
Aspiration Hazard:	Not available	
Carcinogenicity:	May cause cancer	
Germ Cell Mutagenicity:	May cause genetic defects	
Reproductive Toxicity:	Not available	
STOT-Repeated Exposure:	Causes damage to organs through prolonged or repeated exposure	
Synergistic/Antagonistic Effects:	Not available	

Section 12: ECOLOGICAL INFORMATION

12.1. ECOTOXICITY

May cause long-term adverse effects to the aquatic environment. Keep from entry into sewers and waterways.

Ecotoxicity		
Chemical Name	EC50/NOEC-48 Hours	LC50/NOEC-96 Hours
Calcium Carbonate	Not available	Not available
Ethylene Glycol	Not available	Not available
Stoddard Solvent	Not available	Not available
Crystalline Silica, Quartz	Not available	Not available

12.2. PERSISTENCE AND DEGRADABILITY

Not available

12.3. BIOACCUMULATIVE POTENTIAL

Not available



12.4. MOBILITY IN SOIL

Not available

12.5. OTHER ADVERSE EFFECTS

Not available

Section 13: DISPOSAL CONSIDERATIONS

13.1. DISPOSAL METHOD

Dispose of contents/containers in accordance with all local, state, provincial, and federal regulations

13.2. OTHER DISPOSAL CONSIDERATIONS

Not available

Section 14: TRANSPORT INFORMATION

UN NUMBER:	UN NUMBER:
Not regulated	Not regulated
UN PROPER SHIPPING NAME:	UN PROPER SHIPPING NAME:
Not regulated	Not regulated
TRANSPORT HAZARD CLASS (ES):	TRANSPORT HAZARD CLASS (ES):
Not regulated	Not regulated
PACKING GROUP (if applicable):	PACKING GROUP (if applicable):
Not regulated	Not regulated

SUMMARY: Product is not regulated under DOT/TDG and other transportation regulations.

14.1. ENVIRONMENTAL HAZARDS

Not available

14.2. TRANSPORT IN BULK ACCORDING TO ANNEX II OF MARPOL 73/78 AND THE IBC CODE Not available

14.3. SPECIAL PRECAUTIONS FOR USER

Do not handle until all safety precautions have been read and understood.

Section 15: REGULATORY INFORMATION



15.1. SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS/LEGISLATIONS SPECIFIC FOR THE CHEMICAL

Canada: This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Controlled Products Regulations.

US: SDS prepared pursuant to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

15.2. US FEDERAL INFORMATION:

Calcium Carbonate	Not Listed	Not Listed	Not Listed	Not Listed
Ethylene Glycol	Not Listed	Not Listed	5,000	313
Stoddard Solvent	Not Listed	Not Listed	Not Listed	Not Listed
Crystalline Silica, Quartz	Not Listed	Not Listed	Not Listed	Not Listed

15.3. US STATE RIGHT TO KNOW LAWS:

California Proposition 65:	WARNING! This product contains a chemical known to the State of California to cause cancer, birth defects or other reproductive harm
Other U.S. States "Right to Know" Lists:	
	Calcium carbonate: CAS#1317-65-3
New Jersey:	Ethylene Glycol: CAS#107-21-1
•	Stoddard Solvent: CAS#8052-41-3
	Silica, quartz: CAS#14808-60-7
Pennsylvania:	Calcium carbonate: CAS#1317-65-3
·	Ethylene Glycol: CAS#107-21-1
	Stoddard Solvent: CAS#8052-41-3
	Silica, quartz: CAS#14808-60-7
Massachusetts:	Calcium carbonate: CAS#1317-65-3
	Ethylene Glycol: CAS#107-21-1
	Stoddard Solvent: CAS#8052-41-3
	Silica, quartz: CAS#14808-60-7
Minnesota:	Calcium carbonate: CAS#1317-65-3
	Ethylene Glycol: CAS#107-21-1
	Stoddard Solvent: CAS#8052-41-3
	Silica, quartz: CAS#14808-60-7
Florida:	Not Available
Michigan:	Not Available


15.4. GLOBAL INVENTORIES




Calcium Carbonate	Yes	DSL(*)
Ethylene Glycol	Yes	DSL
Stoddard Solvent	Yes	DSL
Crystalline Silica, Quartz	Yes	DSL


*Exemption: Natural occurring chemical

15.5. NFPA AND HMIS RATINGS:



Hazard Index	
4	Severe Hazard
3	Serious Hazard
2	Moderate Hazard
1	Slight Hazard







15.6. SOURCE AGENCY CARCINOGEN CLASSIFICATIONS:

CP65	California Proposition 65
OSHA (O)	Occupational Safety and Health Administration
ACGIH (G)	American Conference of Governmental Industrial Hygienists
	A1 – Confirmed human carcinogen
	A2 – Suspected human carcinogen
	A3 – Animal carcinogen
	A4 – Not classifiable as a human carcinogen
	A5 – Not suspected a human carcinogen
IARC (I)	International Agency for Research on Cancer
	 1 – The agent (mixture) is carcinogenic to humans
	 2A – The agent (mixture) is probably carcinogenic to humans; there is limited evidence of carcinogenicity in humans and sufficient evidence of carcinogenicity in experimental animals. 2B – The agent (mixture) is possibly carcinogenic to humans; there is limited evidence of carcinogenicity in humans in the absence of sufficient evidence of carcinogenicity in experimental animals. 3 – The agent (mixture, exposure circumstance) is not classifiable as to its carcinogenicity to humans. 4 – The agent (mixture, exposure circumstance) is probably not
	carcinogenic to humans.
NTP (N)	National Toxicology Program
, ,	1 – Known to be carcinogens
	2 – Reasonably anticipated to be carcinogens

Section 16: OTHER INFORMATION

Date of Preparation:

September 16, 2014

Version:

1.0

Revision Date:

N/A

Disclaimer: We believe the statements, technical information and recommendations contained are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

Prepared by:

Custom Building Products Phone: (562)-968-2980

www.custombuildingproducts.com

End of Safety Data Sheet