

# MATERIAL SAFETY GLitter Bond **DATA SHEET**

3-7-17

### 1. COMPANY AND PRODUCT IDENTIFICATION

**DUNCAN ENTERPRISES** 

5673 East Shields Avenue

Fresno, CA 93727

559-291-4444

559-291-9444 (Fax)

**EMERGENCY TELEPHONE NUMBERS** 

Health Emergency:

559-291-4444 7:00 am - 3:30 pm

Pacific Standard Time

Spill and Off-Hour

Health Emergencies:

800-424-9300

U.S. and Canada Outside U.S. and

703-527-3887

Canada (Collect)

**Product Name:** 

**TULIP FASHION GLITTER BOND** 

Synonym Name(s):

Water-Based Adhesive

### 2. COMPOSITION / INFORMATION ON INGREDIENTS

The ingredients in this formulation are a trade secret. All ingredients in the formula are non-hazardous, unless specified in Sections 3 and 15.

#### 3. HAZARDS IDENTIFICATION

**HMIS Hazard Ratings for Product** 

Health:

0 = Minimal

Flammability:

0

1 = Slight

Reactivity: Personal Protection:

See Section 8

2 = Moderate 3 = Serious

4 = Severe

\* = Chronic Effects

No Hazardous Ingredients

### 4. FIRST AID MEASURES

Eye Contact:

Flush eyes with large amounts of water until irritation subsides. Consult a physician

if irritation persists.

Skin Contact: Wash affected skin areas thoroughly with soap and water. Consult a physician if

irritation persists.

Inhalation:

Move subject to fresh air.

Ingestion:

If swallowed, give two glasses of water to drink. Consult a physician. Never give

anything by mouth to an unconscious person.

#### 5. FIRE FIGHTING MEASURES

**Autoignition Temperature:** 

Unknown

Flash Point:

Not Applicable

**Upper Explosive Limit (%):** 

Not Applicable

Lower Explosive Limit (%):

Not Applicable

Extinguisher Media:

CO2, Dry Chemical, Foam - Use extinguishing

media appropriate for surrounding fire

**Special Firefighting Procedures:** 

Fire & Explosion Hazards:

Not Applicable

NFPA Flammability Hazard Class:

Not Applicable 0 = Insignificant

### Duncan Enterprises Material Safety Data Sheet - Tulip Fashion Glitter Bond

### 6. ACCIDENTAL RELEASE MEASURES

Spill or Leak Procedures:

Spills should be taken up with suitable absorbent material and placed in containers. Spill areas can be washed with water; collect wash water for

approved disposal. Do not flush to storm sewer or waterway.

For safety and environmental precautions, please review entire Material Safety Data Sheet for necessary information.

### 7. HANDLING AND STORAGE

Storage Temperature:

40° - 100°F

Handling / Storage:

Protect from freezing; keep container sealed when not in use

Ventilation Requirements:

General

Sensitivity to Static Electricity: Sensitivity to Mechanical Impact: No No

# 8. EXPOSURE CONTROL AND PERSONAL PROTECTION

**Conditions Under Which Personal** 

**Protective Equipment Required:** 

Normal work conditions, maintenance / repair.

**Eye Protection Requirements:** 

Wear safety glasses with side shields.

Glove Requirements:

Gloves are not normally required for foreseeable

conditions of use.

**Clothing Requirements:** 

Protective clothing is normally not necessary for

foreseeable conditions of use.

Change / Removal of Clothing:

None required

Wash Requirements:

None

Respirator Requirements:

None required under normal handling conditions.

**Ventilation Requirements:** 

General

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Pure Material or Mixture:

Mixture

Physical Form:

Liquid

Appearance / Physical Description:

White; slight sweet odor

Odor Threshold:

Not Available

pH:

8

**Boiling Point:** 

> 212°F

Melting / Freezing Point:

< 40°F

Solubility in Water:

Miscible

Partition Coefficient (n-octanol/water):

Not Applicable 1.07

Specific Gravity (Water = 1): Bulk Density:

8.9 lb / gal

Dulk Delisity

43% / wt

Volatiles:

43% / WL

Evaporation Rate (Water = 1): Vapor Pressure:

17.5 mm Hg @ 20°C (68°F) 0.62

Vapor Density (Air = 1):

< 6.6% / wt

Volatile Organic Compounds: Autoignition Temperature:

Unknown

Flash Point:

Not Applicable

**Oxidizing Properties:** 

Not Applicable

# Duncan Enterprises Material Safety Data Sheet - Tulip Fashion Glitter Bond

#### 10. STABILITY AND REACTIVITY

Stability:

Stable

Incompatibilities:

Materials that react with water.

NFPA Reactivity Hazard Class:

0 = Insignificant

**Hazardous Decomposition Products:** 

Carbon Monoxide, Carbon Dioxide

Hazardous Polymerization:

Will not occur.

### 11. TOXICOLOGICAL INFORMATION

# Short - Term Effects of Exposure

**Route of Entry** 

Acute Effects - Eye:

Slight, transient

Acute Effects - Skin Contact: No hazard in normal industrial use. Acute Effects - Inhalation:

No hazard in normal industrial use.

Acute Effects - Ingestion:

No hazard in normal industrial use.

Long - Term Effects of Exposure

**Effect of Chronic Exposure:** 

This product should be considered non – hazardous and has no known

chronic effects.

Target Organs:

Not applicable

Carcinogenicity

None

#### 12. ECOLOGICAL INFORMATION

No Applicable Data

### 13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods:

Waste disposal should be in accordance with existing Federal, State,

and Local environmental regulations.

**Empty Container Warnings:** 

Empty containers may contain product residue; follow MSDS and label

warnings even after they have been emptied.

### 14. TRANSPORT INFORMATION

# **U.S. Department of Transportation Information**

**DOT Shipping Name:** 

Adhesive Glues, NOI 4620 Sub. 5

**DOT Hazard Class:** 

Non-hazardous

**DOT Reportable Quantity:** 

None

#### **United Nations Information**

U.N. Number: None

U.N. Class:

None

#### 15. REGULATORY INFORMATION

TSCA:

All components are on the TSCA Inventory

FDA:

21CFR175.105

SARA/Title III:

This product contains no substances at or above the reported threshold under

Section 313, based on available data.



Products bearing the Nontoxic Product Seal are certified in a program of toxicological evaluation by a nationally recognized toxicologist to contain no materials in sufficient quantities to be toxic or injurious to humans or to cause acute or chronic health problems. These products are certified to be labeled in accordance with the voluntary chronic hazard labeling standard ASTM D-4236. In addition, there is no physical hazard as defined within 29 CFR Part 1910.1200(c).

### 16. OTHER INFORMATION

### **Table of Abbreviations**

ACGIH American Conference of Governmental Industrial Hygienists

ANSI American National Standards Institute
ASTM American Society for Testing Materials

°C Degrees Centigrade
CAS Chemical Abstract Service

CERCLA Comprehensive Environmental Response, Compensation and Liability Act

CFR Code of Federal Regulations
CPR Controlled Products Regulations
DOT Department of Transportation
EPA Environmental Protection Agency

°F Degrees Fahrenheit

FDA Food & Drug Administration

Hg Mercury

HMIS Hazardous Materials Identification System
IARC International Agency for Research on Cancer

**LD** Lethal Dose

mg / kg Milligram per kilogram

mm Millimeter

MSDS Material Safety Data Sheet

MSHA Mine Safety and Health Administration

N/A Not Applicable

NFPA National Fire Protection Association

NIOSH National Institute for Occupational Safety and Health

NTP National Toxicology Program

OSHA Occupational Safety and Health Administration

ppm Parts per million

SARA Superfund Amendment and Reauthorization Act

STEL Short-Term Exposure Limit
TSCA Toxic Substances Control Act
TWA Time - Weighted Average

U.N. United Nations

WHMIS Workplace Hazardous Materials Information System

Greater ThanLess Than

# Duncan Enterprises Material Safety Data Sheet - Tulip Fashion Glitter Bond

## 16. OTHER INFORMATION (Continued)

**Creation Date: Revision Date:** 

11/5/07 N/A

**Technical Contact:** 

Frank Peters

Senior R&D Chemist **Duncan Enterprises** 

5673 East Shields Avenue

Fresno, CA 93727 559-291-4444 559-291-9444 (Fax)

## **Disclaimer**

The information given and the recommendations made herein apply to our product(s) alone and not combined with any other product(s). Such are based on our research and on data from other reliable sources and are believed to be accurate. No guarantee of accuracy is made. It is the purchaser's responsibility before using any product to verify this data under their own operating conditions and to determine whether the product is suitable for their purposes.