

SAFETY DATA SHEET

Revision Date 13-Apr-2018

12/4/2018

Version 4

Product identifier

Product Name

118DA ALL PURPOSE SPRAY ADHESIVE 10.5 OZ

Other means of identification

Product Code

82019

Permatex All Purpose

Spray Adhesive # 7651216

Recommended use of the chemical and restrictions on use

Recommended Use Uses advised against

Flammable Aerosol. Adhesive.

No information available

Details of the supplier of the safety data sheet

Manufacturer Address

ITW Permatex 6875 Parkland Blvd. Solon, OH 44139 USA

24-hour emergency phone number

Chem-Tel: 800-255-3924 International Emergency: 00+1+ 813-248-0585

Contract Number: MIS0003453

E-mail address: mail@permatex.com

May Also Be Distributed by:

ITW Permatex Canada 101-2360 Bristol Circle

Oakville, ON Canada L6H 6M5 Telephone: (800) 924-6994

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Reproductive toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Aspiration toxicity	Category 1
Flammable aerosols	Category 1
Gases under pressure	Liquefied gas

Label elements

Emergency Overview

Signal word Danger

Causes skin irritation .

Causes serious eye irritation

Suspected of damaging fertility or the unborn child

May cause drowsiness or dizziness

May cause damage to organs through prolonged or repeated exposure

May be fatal if swallowed and enters airways

Extremely flammable aerosol

Contains gas under pressure; may explode if heated



Appearance White

Physical state Liquid Flammable Aerosol

Odor Solvent

Precautionary Statements - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Wash face, hands and any exposed skin thoroughly after handling

Do not breathe dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Do not spray on an open flame or other ignition source

Pressurized container: Do not pierce or burn, even after use

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

Specific treatment (see supplemental first aid instructions on this label)

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention

If skin irritation occurs: Get medical advice/attention

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

Wash contaminated clothing before reuse

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Do NOT induce vomiting

In case of fire: Use CO2, dry chemical, or foam to extinguish.

Precautionary Statements - Storage

Store locked up

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

- The classification as a carcinogen or mutagen need not apply since it can be shown that the substance contains less than 0.1 % w/w 1,3-butadiene (EINECS No. 203-450-8)

Unknown acute toxicity

12 % of the mixture consists of ingredient(s) of unknown toxicity

#carefolyffolyfffolyfffolyffyr af folgelyffyr (ciriabilayff)

Substance(s)

Chemical Name	CAS No	Weight-%
PETROLEUM GASES, LIQUEFIED,	68476-86-8	30 - 60
SWEETENED		
N-HEXANE	110-54-3	10 - 30
ACETONE	67-64-1	10 - 30
CYCLOHEXANE	110-82-7	1 - 5

Any concentration shown as a range is due to batch variation.

ZJEJRODNOMEKOURES

Description of first aid measures

General advice

Get medical advice/attention if you feel unwell.

Eye contact

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. If eye irritation persists: Get medical

advice/attention.

Skin contact

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin

with water/shower. Wash with soap and water. If symptoms persist, call a physician.

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing. If symptoms persist, call a physician.

Ingestion

IF SWALLOWED:. Call a physician or poison control center immediately. Do NOT induce

vomiting.

Self-protection of the first aider

Ensure that medical personnel are aware of the material(s) involved and take precautions to

protect themselves.

Most important symptoms and effects, both acute and delayed

Symptoms

See section 2 for more information.

Indication of any immediate medical attention and special treatment needed

Note to physicians

Treat symptomatically.

Suitable extinguishing media

Carbon dioxide (CO2), Dry chemical, Foam

Unsuitable extinguishing media

None.

Specific hazards arising from the chemical

Extremely flammable. Contains gas under pressure; may explode if heated. Vapors may travel to source of ignition and flash back.

Explosion data

Sensitivity to Mechanical Impact Sensitivity to Static Discharge None. None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

CESTUE AND EXAMINED PORTION OF THE PROPERTY OF

Personal precautions, protective equipment and emergency procedures

Personal precautions

Use personal protective equipment as required. Avoid breathing vapors or mists. Avoid contact with skin, eyes or clothing. Remove all sources of ignition. Take precautionary measures against static discharges. Contents under pressure. Do not puncture or incinerate cans.

Environmental precautions

Environmental precautions

See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for containment

Prevent further leakage or spillage if safe to do so.

Methods for cleaning up

Eliminate all ignition sources if safe to do so. Ensure adequate ventilation. Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal.

Prevention of secondary hazards

Clean contaminated objects and areas thoroughly observing environmental regulations.

TARETONIC PARTIES AND INCOME.

Precautions for safe handling

Advice on safe handling

Handle in accordance with good industrial hygiene and safety practice. Avoid breathing vapors or mists. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Wash contaminated clothing before reuse. Use personal protective equipment as required. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not puncture or incinerate cans. Contents under pressure.

Conditions for safe storage, including any incompatibilities

Storage Conditions

Store locked up. Do not expose to temperatures exceeding 50 °C/122 °F. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static

electricity).

Incompatible materials

Strong oxidizing agents, Acids

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
N-HEXANE	TWA: 50 ppm	TWA: 500 ppm	IDLH: 1100 ppm
110-54-3	S*	TWA: 1800 mg/m ³	TWA: 50 ppm
		(vacated) TWA: 50 ppm	TWA: 180 mg/m ³
		(vacated) TWA: 180 mg/m ³	
ACETONE	STEL: 500 ppm	TWA: 1000 ppm	IDLH: 2500 ppm
67-64-1	TWA: 250 ppm	TWA: 2400 mg/m ³	TWA: 250 ppm
		(vacated) TWA: 750 ppm	TWA: 590 mg/m ³
		(vacated) TWA: 1800 mg/m³	•
·		(vacated) STEL: 2400 mg/m ³ The	
		acetone STEL does not apply to the	
		cellulose acetate fiber industry. It is	
		in effect for all other sectors	
		(vacated) STEL: 1000 ppm	
CYCLOHEXANE	TWA: 100 ppm	TWA: 300 ppm	IDLH: 1300 ppm
110-82-7		TWA: 1050 mg/m ³	TWA: 300 ppm
	•	(vacated) TWA: 300 ppm	TWA: 1050 mg/m ³
		(vacated) TWA: 1050 mg/m ³	· ·

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

Appropriate engineering controls

Engineering Controls

Showers

Eyewash stations Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear safety glasses with side shields (or goggles).

Skin and body protection

Wear protective natural rubber, nitrile rubber, Neoprene™ or PVC gloves.

Respiratory protection

Use NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as

appropriate.

General Hygiene Considerations

Handle in accordance with good industrial hygiene and safety practice. Regular cleaning of

equipment, work area and clothing is recommended.

UM PLIYASIGALYAND (GHEMIQYAU PROBERTIES

Information on basic physical and chemical properties

Physical state

Appearance

Odor Odor threshold Liquid; Flammable Aerosol

White

Solvent

No information available

Property

Hq

Melting point / freezing point Boiling point / boiling range

Flash point

Values

> 38 °C / >100 °F

Evaporation rate

Flammability (solid, gas)

Flammability Limit in Air

Upper flammability limit: Lower flammability limit:

Vapor pressure Vapor density Relative density

Water solubility Solubility in other solvents

Partition coefficient Autoignition temperature **Decomposition temperature**

Kinematic viscosity Dynamic viscosity **Explosive properties** Oxidizing properties

No information available No information available

< -18 °C / < 0 °F

No information available

No information available No information available No information available

>1 0.73

Negligible

No information available No information available No information available No information available No information available

No information available No information available No information available

Other Information

Softening point Molecular weight VOC Content (%)

Density **Bulk density** No information available No information available

65%

No information available No information available Remarks • Method

Gives a flame projection at full valve opening or flashback at any degree of valve opening

Butyl acetate = 1

Air = 1

OΖ

nden parillingaanderparinga

Reactivity

Stable under normal conditions

Chemical stability

Stable under recommended storage conditions

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Strong oxidizing agents, Acids

Hazardous Decomposition Products

Carbon oxides

Religio X (exe) Elegatora El National Anticon I

Information on likely routes of exposure

Harmful by inhalation. May cause drowsiness or dizziness.

Eye contact

Inhalation

Contact with eyes may cause irritation. May cause redness and tearing of the eyes.

Skin contact

May cause skin irritation and/or dermatitis.

Ingestion

Potential for aspiration if swallowed. Aspiration may cause pulmonary edema and

pneumonitis.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
N-HEXANE	= 25 g/kg (Rat)	= 3000 mg/kg (Rabbit)	= 48000 ppm (Rat) 4 h
110-54-3			<u> </u>
ACETONE	= 5800 mg/kg (Rat)	•	= 50100 mg/m³ (Rat) 8 h
67-64-1			
CYCLOHEXANE	= 12705 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	= 13.9 mg/L (Rat) 4 h
110-82-7			

Information on toxicological effects

Symptoms

No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization

No information available.

Germ cell mutagenicity

No information available.

Carcinogenicity

No information available.

Target Organ Effects

Central nervous system, Eyes, Peripheral Nervous System (PNS), Respiratory system,

Skin

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral)

18153 mg/kg

ATEmix (dermal)

10777 mg/kg 440.9 mg/l

ATEmix (inhalation-dust/mist)
ATEmix (inhalation-vapor)

211200 mg/l

Ecotoxicity

57 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Mobility

No information available.

Chemical Name	Partition coefficient
PETROLEUM GASES, LIQUEFIED, SWEETENED 68476-86-8	<=2.8
ACETONE 67-64-1	-0.24
CYCLOHEXANE 110-82-7	3.44

Other adverse effects

No information available

HEHDRIZONALUKON KIDIERANIONE

Waste treatment methods

Disposal of wastes

This material, as supplied, is a hazardous waste according to federal regulations (40 CFR

261).

Contaminated packaging

Do not reuse container.

US EPA Waste Number

D001

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
N-HEXANE	Toxic
110-54-3	Ignitable
ACETONE	Ignitable
67-64-1	
CYCLOHEXANE	Toxic
110-82-7	Ignitable

ren iranisiadis ilnidermandon

DOT

UN/ID no

1950

Proper shipping name:

Aerosols, Limited Quantity (LQ)

Hazard Class

2.1

Emergency Response Guide

126

Number

IATA

UN/ID no

ID 8000

Proper shipping name:

Consumer commodity

Hazard Class

9

ΟZ

ERG Code

9L

IMDG

UN/ID no

1950

Proper shipping name:

Aerosols, Limited Quantity (LQ)

Hazard Class

EmS-No

F-D, S-U

International Inventories

TSCA Complies DSL/NDSL Complies **EINECS/ELINCS** Complies **ENCS** Not determined **IECSC** Complies Complies **KECL PICCS** Complies **AICS** Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %	
N-HEXANE - 110-54-3	1.0	
CYCLOHEXANE - 110-82-7	1.0	

SARA 311/312 Hazard Categories

Acute health hazard	Yes
Chronic Health Hazard	Yes
Fire hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
CYCLOHEXANE	1000 lb		-	. X
110-82-7			,	

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
N-HEXANE	5000 lb	-	RQ 5000 lb final RQ
110-54-3		•	RQ 2270 kg final RQ
ACETONE	5000 lb	-	RQ 5000 lb final RQ

67-64-1			RQ 2270 kg final RQ
CYCLOHEXANE	1000 lb	- " - " - " - " - " - " - " - " - " - "	RQ 1000 lb final RQ
110-82-7			RQ 454 kg final RQ

US State Regulations

California Proposition 65

WARNING: This product contains chemicals known to the state of California to cause birth defects or other reproductive harm **U.S. State Right-to-Know Regulations**

Chemical Name	New Jersey	Massachusetts	Pennsylvania
ACETONE	X	X	X
67-64-1			
N-HEXANE	X	X	X
110-54-3			
CYCLOHEXANE	X	X	X
110-82-7	·		

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

WHMIS Hazard Class

A Compressed gases, B5 - Flammable aerosol, D2B - Toxic materials

36.0THERINEORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION.

NFPA HMIS Health hazards 2 Health hazards 2 Flammability 4 Flammability 4 Instability 0

Physical hazards 0

Personal protection B

NFPA (National Fire Protection Association)
HMIS (Hazardous Material Information System)

Revision Date

13-Apr-2018

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet