Valvoline	Page: 1
SAFETY DATA SHEET	Revision Date: 09/22/2017
	Print Date: 1/17/2018
	SDS Number: 000000273516
Valvoline™ FULL SYNTHETIC MODERN ENGINE SAE 5W-30 Motor Oil	Version: 1.0
™ Trademark, Valvoline or its subsidiaries, registered in various countries	
882228	

Napa Full synthetic motor oil

29 CFR 1910.1200 (OSHA HazCom 2012)

**SECTION 1. PRODUCT AND COMPANY IDENTIFICATION** 

54-30

**Product identifier** 

Trade name

Valvoline™ FULL SYNTHETIC MODERN ENGINE SAE

5W-30 Motor Oil

™ Trademark, Valvoline or its subsidiaries, registered in

various countries

Relevant identified uses of the substance or mixture and uses advised against

Recommended use

: Motor Oil

Details of the supplier of the safety data sheet

Valvoline LLC 100 Valvoline Way Lexington, KY 40509

United States of America (USA) 1-800-TEAMVAL (1-800-8326-825) Emergency telephone number

1-800-VALVOLINE (1-800-825-8654)

**Regulatory Information Number** 1-800-TEAMVAL (1-800-8326-825)

**Product Information** 

1-800-TEAMVAL (1-800-8326-825)

# **SECTION 2. HAZARDS IDENTIFICATION**

#### **GHS Classification**

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

#### **GHS label elements**

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

#### Other hazards

None known.

# **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture

: Mixture

Chemical nature

: Defatter

**Hazardous components** 

Chemical name CAS-No. Classification Concentration (%)

<b>Valvoline</b>	Page: 2
SAFETY DATA SHEET	Revision Date: 09/22/2017
	Print Date: 1/17/2018
	SDS Number: 000000273516
Valvoline™ FULL SYNTHETIC MODERN ENGINE SAE 5W-30 Motor Oil	Version: 1.0
™ Trademark, Valvoline or its subsidiaries, registered in various countries	·
882228	

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC	64742-65-0	Asp. Tox. 1; H304	5.9299
CATALYTIC DE WAXED HEAVY PARAFFINIC OIL (PETROLEUM)	64742-70-7	Asp. Tox. 1; H304	1.0699
DISTILLATES (PETROLEUM), SOLVENT-REFINED LIGHT PA	64741-89-5	Asp. Tox. 1; H304	1.0699
Distillates (Petroleum), Hydrotreated Heavy Paraffinic	64742-54-7	Asp. Tox. 1; H304	1.0699

#### **SECTION 4. FIRST AID MEASURES**

General advice

: No hazards which require special first aid measures.

If inhaled

: If breathed in, move person into fresh air.

If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact

: First aid is not normally required. However, it is

recommended that exposed areas be cleaned by washing

with soap and water.

In case of eye contact

: Remove contact lenses.

Protect unharmed eye.

If swallowed

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

Most important symptoms and effects, both acute and delayed

: Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary

abnormalities.

Valvoline	Page: 3
SAFETY DATA SHEET	Revision Date: 09/22/2017
	Print Date: 1/17/2018
	SDS Number: 000000273516
Valvoline™ FULL SYNTHETIC MODERN ENGINE SAE 5W-30 Motor Oil	Version: 1.0
™ Trademark, Valvoline or its subsidiaries, registered in various countries	
882228	

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through

the skin may include:

acne

stomach or intestinal upset (nausea, vomiting, diarrhea)

irritation (nose, throat, airways)

Notes to physician

: No hazards which require special first aid measures.

#### **SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media

: Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Water spray

Foam

Carbon dioxide (CO2)

Dry chemical

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: carbon dioxide and carbon monoxide

Hydrocarbons Aldehydes Sulphur oxides

Specific extinguishing

methods

Product is compatible with standard fire-fighting agents.

Further information

: Standard procedure for chemical fires.

Special protective equipment

for firefighters

: In the event of fire, wear self-contained breathing apparatus.

#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures : Persons not wearing protective equipment should be excluded

from area of spill until clean-up has been completed.

**Environmental precautions** 

: Prevent further leakage or spillage if safe to do so.

Methods and materials for

: Soak up with inert absorbent material (e.g. sand, silica gel,

acid hinder universal hinder sewdust

Valvoline	Page: 4
SAFETY DATA SHEET	Revision Date: 09/22/2017
	Print Date: 1/17/2018
	SDS Number: 000000273516
Valvoline™ FULL SYNTHETIC MODERN ENGINE SAE 5W-30  Motor Oil  ™ Trademark, Valvoline or its subsidiaries, registered in various countries	Version: 1.0
882228	

Keep in suitable, closed containers for disposal.

Other information

: Comply with all applicable federal, state, and local regulations.

### **SECTION 7. HANDLING AND STORAGE**

Advice on safe handling

: Smoking, eating and drinking should be prohibited in the

application area.

For personal protection see section 8.

Materials to avoid

: No materials to be especially mentioned.

# SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
CATALYTIC DE WAXED HEAVY PARAFFINIC OIL (PETROLEUM)	64742-70-7	TWA	5 mg/m3 Mist	OSHA Z-1
	-	TWA	5 mg/m3 Mist	OSHA P0
		TWA	5 mg/m3 Mist	NIOSH REL
		ST	10 mg/m3 Mist	NIOSH REL
		PEL	5 mg/m3 particulate	CAL PEL
DISTILLATES (PETROLEUM), SOLVENT-REFINED LIGHT PA	64741-89-5	TWA	5 mg/m3 Mist	OSHA Z-1
		TWA	5 mg/m3 Inhalable fraction	ACGIH
		TWA	5 mg/m3 Mist	OSHA P0
		TWA	5 mg/m3 Mist	NIOSH REL
		ST	10 mg/m3 Mist	NIOSH REL
		PEL	5 mg/m3 particulate	CAL PEL
Distillates (Petroleum).	64742-54-7	TWA	5 ma/m3	OSHA 7-1

<b>Valvoline</b>	Page: 5
SAFETY DATA SHEET	Revision Date: 09/22/2017
	Print Date: 1/17/2018
	SDS Number: 000000273516
Valvoline™ FULL SYNTHETIC MODERN ENGINE SAE 5W-30 Motor Oil	Version: 1.0
™ Trademark, Valvoline or its subsidiaries, registered in various countries	
882228	

Hydrotreated Heavy Paraffinic		Mist	
	TWA	5 mg/m3 Inhalable fraction	ACGIH
	TWA	5 mg/m3 Mist	OSHA P0
	TWA	5 mg/m3 Mist	NIOSH REL
	ST	10 mg/m3 Mist	NIOSH REL
	PEL	5 mg/m3 particulate	CAL PEL

Hazardous components without workplace control parameters

Components	CAS-No.
DISTILLATES (PETROLEUM),	64742-65-0
SOLVENT-DEWAXED HEAVY	
PARAFFINIC	

**Engineering measures** 

: General room ventilation should be adequate for normal conditions of use. However, if unusual operating conditions exist, provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Respiratory protection

No personal respiratory protective equipment normally

required.

Eye protection

Not required under normal conditions of use. Wear splash-

proof safety goggles if material could be misted or splashed

into eyes.

Skin and body protection

Wear as appropriate:

Safety shoes

Wear resistant gloves (consult your safety equipment

supplier).

Hygiene measures

: General industrial hygiene practice.

# **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Physical state

: liquid

Odour

: No data available

<b>Valvoline</b>	Page: 6
SAFETY DATA SHEET	Revision Date: 09/22/2017
	Print Date: 1/17/2018
	SDS Number: 000000273516
Valvoline™ FULL SYNTHETIC MODERN ENGINE SAE 5W-30 Motor Oil	Version: 1.0
™ Trademark, Valvoline or its subsidiaries, registered in various countries 882228	

**Odour Threshold** 

: No data available

pΗ

: No data available

Melting point/freezing point

: No data available

Boiling point/boiling range

No data available

Flash point

> 390 °F / > 199 °C

Method: Cleveland open cup

Evaporation rate

: No data available

Flammability (solid, gas)

No data available

Upper explosion limit

No data available

Lower explosion limit

No data available

Vapour pressure

: No data available

Relative vapour density

: No data available

Relative density

: No data available

Density

: 0.850 g/cm3

Solubility(ies)

Water solubility

: No data available

Solubility in other solvents

: No data available

Partition coefficient: n-

octanol/water

: No data available

Thermal decomposition

: No data available

Viscosity

Viscosity, dynamic

: No data available

Viscosity, kinematic

: 55 mm2/s (40 °C)

Oxidizing properties

: No data available

#### **SECTION 10. STABILITY AND REACTIVITY**

Reactivity

No decomposition if stored and applied as directed

Valvoline.	Page: 7
SAFETY DATA SHEET	Revision Date: 09/22/2017
	Print Date: 1/17/2018
	SDS Number: 000000273516
Valvoline™ FULL SYNTHETIC MODERN ENGINE SAE 5W-30 Motor Oil	Version: 1.0
™ Trademark, Valvoline or its subsidiaries, registered in various countries	
882228	4

Chemical stability

: Stable under recommended storage conditions.

Possibility of hazardous

reactions

: Product will not undergo hazardous polymerization.

Conditions to avoid

: excessive heat

Incompatible materials

: Strong oxidizing agents

Hazardous decomposition

products

Aldehydes

carbon dioxide and carbon monoxide

Hydrocarbons Sulphur oxides

#### **SECTION 11. TOXICOLOGICAL INFORMATION**

Information on likely routes of : Inhalation

exposure

Skin contact

Eye Contact Ingestion

#### **Acute toxicity**

Not classified based on available information.

# Components:

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:

Acute oral toxicity

: LD50 (Rat): > 5,000 mg/kg

Acute dermal toxicity

: LD50 (Rabbit): > 5,000 mg/kg

### CATALYTIC DE WAXED HEAVY PARAFFINIC OIL (PETROLEUM):

Acute oral toxicity

: LD50 (Rat): > 2,000 mg/kg

Assessment: Not classified as acutely toxic by ingestion under

Remarks: Information given is based on data obtained from

similar substances.

Acute dermal toxicity

: LD50 (Rabbit): > 2,000 mg/kg

Assessment: Not classified as acutely toxic by dermal

absorption under GHS.

Remarks: Information given is based on data obtained from

similar substances.

Valvoline	Page: 8
SAFETY DATA SHEET	Revision Date: 09/22/2017
	Print Date: 1/17/2018
	SDS Number: 000000273516
Valvoline™ FULL SYNTHETIC MODERN ENGINE SAE 5W-30 Motor Oil	Version: 1.0
™ Trademark, Valvoline or its subsidiaries, registered in various countries	
882228	

Acute oral toxicity

: LD50 (Rat): > 15 g/kg

Acute dermal toxicity

: LD50 (Rabbit): > 5 g/kg

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:

Acute oral toxicity

: LD50 (Rat): > 15 g/kg

Acute dermal toxicity

: LD50 (Rabbit): > 5 g/kg

## Skin corrosion/irritation

Not classified based on available information.

#### **Components:**

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:

Result: Slight, transient irritation

CATALYTIC DE WAXED HEAVY PARAFFINIC OIL (PETROLEUM):

Result: Slight, transient irritation

DISTILLATES (PETROLEUM), SOLVENT-REFINED LIGHT PA:

Result: Slight, transient irritation

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:

Result: Slight, transient irritation

#### Serious eye damage/eye irritation

Not classified based on available information.

#### Product:

Remarks: Unlikely to cause eye irritation or injury.

#### Components:

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:

Result: Slight, transient irritation

# CATALYTIC DE WAXED HEAVY PARAFFINIC OIL (PETROLEUM):

Result: Slight, transient irritation

### DISTILLATES (PETROLEUM), SOLVENT-REFINED LIGHT PA:

Result: Slight, transient irritation

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:

Result: No eye irritation

## Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Valvoline	Page: 9		
SAFETY DATA SHEET	Revision Date: 09/22/2017		
	Print Date: 1/17/2018		
	SDS Number: 000000273516		
Valvoline™ FULL SYNTHETIC MODERN ENGINE SAE 5W-30 Motor Oil	Version: 1.0		
™ Trademark, Valvoline or its subsidiaries, registered in various countries 882228			

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

**Aspiration toxicity** 

Not classified based on available information.

Components:

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:

May be fatal if swallowed and enters airways.

CATALYTIC DE WAXED HEAVY PARAFFINIC OIL (PETROLEUM):

May be fatal if swallowed and enters airways.

DISTILLATES (PETROLEUM), SOLVENT-REFINED LIGHT PA:

May be fatal if swallowed and enters airways.

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:

May be fatal if swallowed and enters airways.

#### **Further information**

**Product:** 

Remarks: No data available

Carcinogenicity:

**IARC** 

No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

**OSHA** 

No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by OSHA.

**NTP** 

No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

# **SECTION 12. ECOLOGICAL INFORMATION**

### **Ecotoxicity**

#### **Product:**

**Ecotoxicology Assessment** 

Acute aquatic toxicity

: Not classified based on available information.

Chronic aquatic toxicity

Not classified based on available information

Valvoline.	Page: 10
SAFETY DATA SHEET	Revision Date: 09/22/2017
	Print Date: 1/17/2018
	SDS Number: 000000273516
Valvoline™ FULL SYNTHETIC MODERN ENGINE SAE 5W-30 Motor Oil ™ Trademark, Valvoline or its subsidiaries, registered in various countries 882228	Version: 1.0

### Components:

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:

Toxicity to fish

: LL50 (Fish): > 100 mg/l

Exposure time: 96 h

aquatic invertebrates

Toxicity to daphnia and other : EL50 (Aquatic invertebrates): > 10,000 mg/l

Exposure time: 48 h

Toxicity to algae

: EL50 (Algae, algal mat (Algae)): > 100 mg/l

Exposure time: 72 h

Toxicity to fish (Chronic

toxicity)

: NOEC (Fish): 10 mg/l

Toxicity to daphnia and other

aquatic invertebrates (Chronic toxicity)

: NOEC (Aquatic invertebrates): 10 mg/l

# Persistence and degradability

No data available

**Bioaccumulative potential** 

No data available Mobility in soil No data available

Other adverse effects

No data available

**Product:** 

Additional ecological

information

: No data available

#### **SECTION 13. DISPOSAL CONSIDERATIONS**

#### Disposal methods

General advice

: Dispose of in accordance with all applicable local, state and

federal regulations.

Contaminated packaging

: Empty remaining contents.

### **SECTION 14. TRANSPORT INFORMATION**

International transport regulations REGULATION

Valvoline	Page: 11
SAFETY DATA SHEET	Revision Date: 09/22/2017
	Print Date: 1/17/2018
	SDS Number: 000000273516
Valvoline™ FULL SYNTHETIC MODERN ENGINE SAE 5W-30 Motor Oil	Version: 1.0
Trademark, Valvoline or its subsidiaries, registered in various countries 882228	

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.
11.0 DOT DO		_l			LID. WII.
U.S. DOT - RO	Not dangerous goods				
	Not dangerous goods			· · · · · · · · · · · · · · · · · · ·	
PED DAIL O			<del></del>		<del></del>
FR_RAIL_C	Not dangerous goods				
	Hot dangerous goods				
LC DOT INI A	ND WATERWAYS				
I.S. DOT - INLA	Not dangerous goods				
	The daily or odd goods		•		
DG ROAD C				- W	•
DG_ROAD_C	Not dangerous goods				
	dangorodo goodo				
DC DAIL C	TO FIRE THE EXCEPTION WHITE WHITE HERE IN THE STATE OF TH		distance of the		, this is now a distribution Mail on South Green and a second of the contract
DG_RAIL_C	Not dangerous goods	<del></del>			
	ivot dangerous goods		*		
DO INIME O					
DG_INWT_C	Not dangerous goods		·		····
	Not dangerous goods				
HERNATIONAL	Not dangerous goods	ODS		***	
	Not dangerous goods			<del></del>	
ITEDNIATION				·	
HERNATIONAL	AIR TRANSPORT ASSOCIATI Not dangerous goods	ON - CARGO			
	Not dangerous goods				
ITERNATIONAL	AIR TRANSPORT ASSOCIATI	ON - PASSEN	GER		
	Not dangerous goods				
X_DG	Not dongorous assets		W- A	· · · · · · · · · · · · · · · · · · ·	
	Not dangerous goods	· · · · · · · · · · · · · · · · · · ·			·

Valvoline	Page: 12
SAFETY DATA SHEET	Revision Date: 09/22/2017
	Print Date: 1/17/2018
	SDS Number: 000000273516
Valvoline™ FULL SYNTHETIC MODERN ENGINE SAE 5W-30 Motor Oil ™ Trademark, Valvoline or its subsidiaries, registered in various countries 882228	Version: 1.0

Marine pollutant	 no	

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

# **SECTION 15. REGULATORY INFORMATION**

EPCRA - Emergency Planning and Community Right-to-Know Act CERCLA Reportable Quantity

Gomponents CAS-No. Component RQ Calculated product RQ. (lbs) (lbs)

ETHYLENEDIAMINE 107-15-3 5000 \*

SARA 304 Extremely Hazardous Substances Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
ETHYLENEDIAMINE	107-15-3	5000	*

<sup>\*:</sup> Calculated RQ exceeds reasonably attainable upper limit.

SARA 311/312 Hazards

: No SARA Hazards

**SARA 313** 

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

California Prop 65

Proposition 65 warnings are not required for this product based on the results of a risk assessment.

The components of this product are reported in the following inventories:

DSL

: All components of this product are on the Canadian DSL

AICS

: On the inventory, or in compliance with the inventory

**ENCS** 

: Not in compliance with the inventory

KECI

: On the inventory, or in compliance with the inventory

**PICCS** 

: Not in compliance with the inventory

**IECSC** 

: On the inventory, or in compliance with the inventory

TSCA

on the inventory, or in compliance with the lifter

. . . . .

: On TSCA Inventory

**Inventories** 

<sup>\*:</sup> Calculated RQ exceeds reasonably attainable upper limit.


Valvoline	Page: 13
SAFETY DATA SHEET	Revision Date: 09/22/2017
	Print Date: 1/17/2018
	SDS Number: 000000273516
Valvoline™ FULL SYNTHETIC MODERN ENGINE SAE 5W-30 Motor Oil	Version: 1.0
™ Trademark, Valvoline or its subsidiaries, registered in various countries 882228	

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

### **SECTION 16. OTHER INFORMATION**

#### **Further information**

Revision Date: 09/22/2017



# NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIB

#### **Full text of H-Statements**

H304

May be fatal if swallowed and enters airways.

Sources of key data used to compile the Safety Data Sheet Valvoline internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).

Valvoline	Page: 14
SAFETY DATA SHEET	Revision Date: 09/22/2017
	Print Date: 1/17/2018
	SDS Number: 000000273516
Valvoline™ FULL SYNTHETIC MODERN ENGINE SAE 5W-30 Motor Oil	Version: 1.0
™ Trademark, Valvoline or its subsidiaries, registered in various countries	·
882228	

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data

ACGIH: American Conference of Industrial Hygienists

BEI: Biological Exposure Index

CAS: Chemical Abstracts Service (Division of the American Chemical Society).

CMR: Carcinogenic, Mutagenic or Toxic for Reproduction

FG: Food grade

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement: Hazard Statement

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization

ICAO-TI (ICAO): Technical Instructions by the "International Civil Aviation Organization"

IMDG: International Maritime Code for Dangerous Goods

ISO: International Organization for Standardization

logPow: octanol-water partition coefficient

LCxx: Lethal Concentration, for xx percent of test population

LDxx: Lethal Dose, for xx percent of test population. ICxx: Inhibitory Concentration for xx of a substance

Ecxx: Effective Concentration of xx N.O.S.: Not Otherwise Specified

OECD: Organization for Economic Co-operation and Development

**OEL**: Occupational Exposure Limit P-Statement : Precautionary Statement

PBT: Persistent, Bioaccumulative and Toxic

PPE: Personal Protective Equipment STEL: Short-term exposure limit STOT: Specific Target Organ Toxicity

TLV: Threshold Limit Value TWA: Time-weighted average

vPvB: Very Persistent and Very Bioaccumulative

WEL: Workplace Exposure Level

CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act

DOT: Department of Transportation

FIFRA: Federal Insecticide, Fungicide, and Rodenticide Act HMIRC: Hazardous Materials Information Review Commission

HMIS: Hazardous Materials Identification System NFPA: National Fire Protection Association

NIOSH: National Institute for Occupational Safety and Health OSHA: Occupational Safety and Health Administration

PMRA: Health Canada Pest Management Regulatory Agency

RTK: Right to Know

WHMIS: Workplace Hazardous Materials Information System